


AD-A085 990

NAVAL AIR ENGINEERING CENTER LAKEHURST NJ GROUND SUPP--ETC F/G 10/2  
APPLICATION OF A MICROCOMPUTER TO A MOBILE ELECTRIC POWER PLANT--ETC(U)  
MAY 80 R F O'DONNELL  
NAEC-92-139


UNCLASSIFIED

NL

1 of 4  
AD-A085 990



08599



MICROCOPY RESOLUTION TEST CHART  
NBS 1963-A

**LEVEL**



LAKEHURST, N.J.  
08733

**NAVAL AIR ENGINEERING CENTER**

REPORT NAEC-92-139

**APPLICATION OF A MICROCOMPUTER  
TO A MOBILE ELECTRIC POWER PLANT**

Handling & Servicing/Armament Division  
Ground Support Equipment Department  
Naval Air Engineering Center  
Lakehurst, New Jersey 08733

22 MAY 1980

**DTIC  
ELECTE**  
JUN 27 1980

Final Report for Period July 1975 to September 1979  
AIRTASK A3400000/051B/6F41461400, WU 32

APPROVED FOR PUBLIC RELEASE:  
DISTRIBUTION UNLIMITED

THIS DOCUMENT IS BEST QUALITY PRACTICABLE.  
THE COPY FURNISHED TO DDC CONTAINED A  
SIGNIFICANT NUMBER OF PAGES WHICH DO NOT  
REPRODUCE LEGIBLY.

Prepared for  
Commander, Naval Air Systems Command  
AIR-340E  
Washington, DC 20361

DDC FILE COPY

ADA 085990

80 6 26 041

APPLICATION OF A MICROCOMPUTER  
TO A MOBILE ELECTRIC POWER PLANT

Prepared by: Richard F. O'Donnell  
Richard F. O'Donnell  
Advanced Technology Section (92724)  
Armament Handling and Requirements Branch

Reviewed by: J. J. Connor  
J. J. Connor  
Head, Handling and Servicing/  
Armament Division (927)

Approved by: F. E. Evans  
F. E. Evans  
Ground Support Equipment Superintendent (92A)

**NOTICE**

Reproduction of this document in any form by other than naval activities is not authorized except by special approval of the Secretary of the Navy or the Chief of Naval Operations as appropriate.

The following espionage notice can be disregarded unless this document is plainly marked CONFIDENTIAL or SECRET.

This document contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C., Sections 793 and 794. The transmission or the revelation of its contents in any manner to an unauthorized person is prohibited by law.



## **DISCLAIMER NOTICE**

**THIS DOCUMENT IS BEST QUALITY  
PRACTICABLE. THE COPY FURNISHED  
TO DTIC CONTAINED A SIGNIFICANT  
NUMBER OF PAGES WHICH DO NOT  
REPRODUCE LEGIBLY.**

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NAEC-92-139	2. GOVT ACCESSION NO. AD-A085990	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) APPLICATION OF A MICROCOMPUTER TO A MOBILE ELECTRIC POWER PLANT.		5. TYPE OF REPORT & PERIOD COVERED FINAL REPORT. Jul 1975-Sep 1979 PERFORMING ORG. REPORT NUMBER NAEC-92-139
7. AUTHOR(s) Richard F. O'Donnell		6. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Air Engineering Center Ground Support Equipment Department (Code 92724) Lakehurst, NJ 08733		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS A3400000/051B/6F4I46I400, W.U. 32
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Air Systems Command AIR-340E Washington, DC 20361		12. REPORT DATE 28 May 1980
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 280
15. DISTRIBUTION STATEMENT (of this Report) Approved For Public Release; Distribution Unlimited.		16. SECURITY CLASS. (of this report) UNCLASSIFIED
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		18a. DECLASSIFICATION/DOWNGRADING SCHEDULE
19. SUPPLEMENTARY NOTES		
20. KEY WORDS (Continue on reverse side if necessary and identify by block number) MICROCOMPUTER MIL-STD-704C AC GENERATOR VOLTAGE MOBILE POWER PLANT FREQUENCY used		
21. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report contains information relevant to a generator control system to be utilized in a new DOD Mobile Electric Power Plant (MEP354). An initial study revealed that a microcomputer control strategy was the most suitable system to use for this particular application. A breadboard system was built and tested to see if the controlled power complies with the applicable standard for ground power, MIL-STD-704C. Results obtained indicate that the microcomputer control system will regulate voltage and frequency to the extent called out in the aforementioned military standard.		

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE  
1 JAN 73 S/N 0102-LF-014-6601


UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

405917

Jm

UNCLASSIFIED  
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED  
SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

## SUMMARY

A. GENERAL. The military standard pertaining to the quality of power generated by mobile electric ground support equipment presents rigid guidelines to be met. A control system is needed which will meet the goals of this standard with the least parts and costs, while maintaining a very high degree of reliability and maintainability. This report reveals why a microcomputer control system is appropriate and how such a system actually performed in a breadboard situation.

B. PROCEDURES AND RESULTS

1. A previous endeavor in the exploratory development area produced a generator that would conform to MIL-STD-704C (NAVAIRENGCEN report number NAEC-92-125). The Franklin Institute Research Laboratories in Philadelphia, Pennsylvania, under contract to NAVAIRENGCEN, completed a study to ascertain the optimum control method for an auxiliary power unit alternator. The report issued, which is included in its entirety as Appendix A, revealed that a microcomputer control system displays the most favorable characteristics of the various systems addressed.

2. A breadboard design of a microcomputer control system was built and tested for conformance to MIL-STD-704C. Results, as displayed graphically in Appendix D, indicate that a microcomputer control system will regulate the electrical characteristics of the particular generator used, as required in MIL-STD-704C. It is recommended that a microcomputer control scheme as exemplified in the report be included in MEP 354.

Accession For	
NTIS GMAI	<input checked="" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unannounced	
Justification	
By	
Distribution	
Availability Codes	
Dist	Avail and/or special
A	23 AP.

This page left blank  
intentionally.

## TABLE OF CONTENTS

<u>Section</u>	<u>Subject</u>	<u>Page</u>
	SUMMARY.....	1
I	INTRODUCTION.....	5
II	BACKGROUND.....	6
III	OBJECTIVES.....	7
IV	APPROACH.....	7
V	SYSTEM DESCRIPTION.....	7
VI	DISCUSSION OF RESULTS.....	8
VII	CONCLUSIONS AND RECOMMENDATIONS.....	9
	APPENDICES	
	A. FEASIBILITY STUDY OF OPTIMUM CONTROL METHODS FOR AUXILIARY POWER UNIT ALTERNATOR.....	12
	B. SYSTEM SOFTWARE.....	215
	C. SYSTEM HARDWARE.....	245
	D. VOLTAGE AND FREQUENCY REGULATION RESULTS.....	271

NAEC-92-139

This page left blank  
intentionally.

## I. INTRODUCTION

The performance of electrical and electronic equipment is largely dependent on the quality of power supplied to it. AC devices will perform satisfactorily if the input power is of the specified amplitude and frequency with a limited amount of tolerable distortion. It is essential that these devices receive the expected quality of power. Degradation of performance, abbreviation of service life, inefficient operation, and heating problems all are related to the application of improper input power, whether under steady state or transient operating conditions.

The current military standard which defines the electrical power requirements supplied to the utilization equipment aboard aircraft is MIL-STD-704C. Due to its stringent requirements, the ground support equipment community recognized a need to develop new Mobile Electric Power Plants (MEPPs) which would be able to supply the specified power to aircraft during ground maintenance and preflight checks. MEP 354 is the DOD designation for the new MEPP which will replace two older units, the NC-8A and the NC-2A. This report documents the investigation that led to the selection and testing of a generator control system.



## II. BACKGROUND

The Fleet's need for a quality of power as defined in MIL-STD-704C is the driving force behind an effort to build a new Mobile Electric Power Plant, MEP 354. A previous study was made to obtain a generator that was most likely to comply with the new standard. A DOD 30KW diesel-driven generator was obtained due to its favorable electro-mechanical characteristics and availability. A computer program was written to calculate the expected electrical parameters of this generator set. Verification of the computer results was completed through a comprehensive test program as delineated in the appropriate military standard test directive, MIL-STD-705B.

Design changes stemming from the above tests were incorporated in the generator to achieve a generator that complies with MIL-STD-704C.

A later study, which is enclosed as Appendix A, indicated that a standard microcomputer control system would be the most suitable control system for the generator set. The decision was based on several parameters including, ability to meet the voltage regulation requirements, development costs, hardware costs, and operational costs. Based on this conclusion, a standard microcomputer board was obtained (Intel 80/10) and a breadboard control system was set up and tested. The goal of this report is to indicate that such a system works very well. The voltage and frequency characteristics obtained by the breadboard microcomputer system met both the steady-state and transient requirements of MIL-STD-704C.

### III. OBJECTIVES

The objective of this effort was to obtain a generator control system which would regulate a generator's output characteristics and meet the new standard for aircraft/ground support power, MIL-STD-704C. Desirable attributes of the control system are simplicity (in terms of the fewest number of parts), reliability, maintainability, and low cost (both initial and life cycle).

### IV. APPROACH

Once it was determined that a microcomputer control system exhibited the best characteristics for our application, a standard microcomputer board was obtained. Control algorithms for both voltage and frequency were drawn up. From these algorithms a detailed machine language program was written. Next, the necessary hardware to support the computer program was designed and built into a breadboard system. Finally, the polished system was tested for conformance to MIL-STD-704C.

### V. SYSTEM DESCRIPTION

The control algorithms and the theory behind them, software flowcharts, and the actual program listing are included as Appendix B. The supporting hardware, built around an Intel 8080 microprocessor on an 80/10 microcomputer board, is enclosed as Appendix C.

## VI. DISCUSSION OF RESULTS

Appendix D gives vivid evidence of the performance of the microcomputer control system for both voltage and frequency. With the diesel-generator set's battery voltage applied to the field and an external resistor of 1.5 ohms placed in series with the field, the voltage regulation characteristics met the transient and steady-state requirements of MIL-STD-704C. Using a 4-cylinder Hercules-White engine and a 15KW Electric Machine generator, a 15 KW, 0.8 power factor load was used to determine the regulator response. Figure D-1 illustrates that the voltage does get back within the steady-state limits in the required time span.

Utilizing the same engine and generator with a Woodward electrohydraulic governor, the frequency response was tested again with a 15KW, 0.8 power factor load (rated load). Figure D-2 displays the frequency control system's response. The frequency stabilizes within the steady-state limits in 2.25 seconds. Clearly, this is well within the allowable 10 seconds from removal or application of load.

It is therefore concluded that the chosen microcomputer control system did effectively regulate the DOD engine-generator set's voltage and frequency response to comply with the specifications of MIL-STD-704C.

## VII. CONCLUSIONS AND RECOMMENDATIONS

This program consisted of a comparative study of possible control systems, algorithm and computer program writing, breadboard building and testing, and an evaluation of the final system. Results, depicted graphically in Appendix D and discussed previously, indicated that a microcomputer control system, when used in conjunction with the particular DOD diesel-driven generator set, meets the requirements of MIL-STD-704C.

It is recommended that a microcomputer system be included in the total MEP 354 development package as the AC voltage and frequency control system. It is further recommended that a Woodward type of electrohydraulic governor system be employed on the diesel engine.

A microcomputer is a versatile and powerful tool. The Intel 8080 microprocessor performed very well as the core of the control system. Nevertheless, it has ample capacity to control or monitor other functions besides AC voltage and frequency. Control of DC voltage for a transformer rectifier unit and monitoring of key parameters such as over/under voltage, excessive current draw, oil pressure, water temperature, and other functions could very well be performed by the 8080. At the onset of this program the 8080 was at the vanguard of the industry. However, the electronics industry is progressing at a very rapid rate, particularly in the digital field. Current microprocessors are more powerful and faster, and have a larger supply of peripheral packages to support them than those which existed a few years ago. It would prove worthwhile to incorporate the most advantageous and well-supported microprocessor in MEP 354.

NAEC-92-139

This page left blank  
intentionally.

## APPENDICES

<u>APPENDIX</u>	<u>TITLE</u>	<u>PAGE</u>
A	FEASIBILITY STUDY OF OPTIMUM CONTROL METHODS FOR AUXILIARY POWER UNIT ALTERNATOR. . .	12
B	SYSTEM SOFTWARE. . . . .	215
C	SYSTEM HARDWARE. . . . .	245
D	VOLTAGE AND FREQUENCY REGULATION RESULTS . . . .	271

APPENDIX A

FEASIBILITY STUDY OF OPTIMUM CONTROL METHODS  
FOR AUXILIARY POWER UNIT ALTERNATOR

Prepared by:  
The Franklin Institute Research Laboratories  
Philadelphia, Pennsylvania  
Contract No. N68335-75-C-1346  
August, 1976

## SUMMARY

The objective of the study was the selection of a design strategy for a motor generator controller. The first step was to establish specific design goals. These goals included compliance with MIL-STD-704B, MIL-D-8512 and MIL-T-21200L. The next step was the analysis of the equipment to be controlled--alternators and diesel engines.

Once the goals and restrictions were established, the study of various system design strategies was begun. The major area of investigation was in design techniques to achieve the required voltage regulation. These techniques were divided into three major categories: analog, digital and hybrid. Several methods in each category were evaluated; many through computer simulation. The investigation determined that methods in all three categories could meet the regulation goals.

Having established the feasibility of meeting the voltage regulation goals, the selection of the best strategy to meet the overall goals of the motor generator was made. This selection was based on many factors including: development costs, hardware costs and operational costs. The main conclusion was that the motor generator controller should be based around a standard microcomputer using a saturating control type of regulation.



## CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>
	SUMMARY . . . . .	13
1	DESIGN GOALS. . . . .	18
	1.1 Regulation . . . . .	18
	1.2 Environmental Goals. . . . .	20
	1.3 Operational Goals. . . . .	20
2	ANALYSIS OF ALTERNATORS . . . . .	23
	2.1 Field Winding. . . . .	23
	2.2 Regulation . . . . .	24
	2.3 Exciter System . . . . .	24
	2.4 Non-Linear or Saturation Considerations. . . . .	24
3	ANALYSIS OF DIESEL ENGINE . . . . .	27
	3.1 Rotating Inertia . . . . .	27
	3.2 Torque Versus Fuel Flow. . . . .	27
	3.3 Throttle Control . . . . .	27
4	SYSTEM DESIGN STRATEGIES. . . . .	30
	4.1 Literature Search and Review . . . . .	30
	4.2 Analog Method of Control . . . . .	30
	4.2.1 Compensation Selection. . . . .	39
	4.2.2 Analysis of Speed Regulation System . . . . .	47
	4.2.3 Analysis of Voltage Regulation System . . . . .	47
	4.3 Digital Methods . . . . .	52
	4.3.1 Test Bed for Digital and Hybrid Techniques. . . . .	52
	4.3.2 NAVAIR Technique. . . . .	55
	4.3.3 NAVAIR Design Analysis. . . . .	60

## CONTENTS (Continued)

<u>Section</u>	<u>Title</u>	<u>Page</u>
4.3.4	Bang-Bang . . . . .	66
4.3.5	Analysis of Bang-Bang Technique . . . . .	67
4.3.6	Multi-Level Bang-Bang . . . . .	69
4.3.7	Analysis of Multi-Level Bang-Bang Techniques. . . . .	69
4.3.8	Direction Sensitive Multi-Level Bang-Bang	72
4.3.9	Analysis of Direction Sensitive Multi- Level Bang-Bang . . . . .	74
4.3.10	Digital Simulation of Analog Designs. . .	74
4.3.11	Digital Simulation of Analog Designs. . .	74
4.4	Hybrid Methods . . . . .	76
4.4.1	Analysis of Hybrid Methods. . . . .	77
4.5	Monitor and Diagnostic System. . . . .	77
4.5.1	Monitor System. . . . .	77
4.5.2	Diagnostics . . . . .	79
4.5.3	Analysis of Monitoring and Diagnostic Methods . . . . .	81
5	CONCLUSIONS . . . . .	85
6	RECOMMENDATIONS . . . . .	86
APPENDIX A	- Determination of Constants and Development of Transfer Characteristics . . . . .	87
APPENDIX B	- Computerized Literature Searches on the Subject of Regulation Design . . . . .	111
APPENDIX C	- Assembly Language Program to Implement Bang-Bang Regulation Techniques. . . . .	204
APPENDIX D	- Study of Effect of Lower Main Field Time Constants. . . . .	210

## ILLUSTRATIONS

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
1-1	Envelope of AC Voltage Surge . . . . .	19
1-2	Temperature/Altitude Requirements for Motor Generator Controller. . . . .	21
2-1	Alternator Block Diagram . . . . .	26
3-1	Diesel Engine Block Diagram. . . . .	29
4-1	General Block Diagram of the Microcomputer Based Monitoring and Diagnostic System. . . . .	31
4-2	Alternator and Diesel Engine Block Diagram . . . . .	33
4-3	AC-APU Analog Computer Program . . . . .	36
4-4	AC-APU Analog Computer Program . . . . .	37
4-5	Alternator 10% Inherent Regulation . . . . .	38
4-6	AC-APU Analog Computer Program . . . . .	40
4-7	Alternator 10% Inherent Regulation . . . . .	41
4-8	Alternator 15% Inherent Regulation . . . . .	42
4-9	Alternator 15% Inherent Regulation . . . . .	43
4-10	Open Loop Transfer Characteristic - With and Without Compensation. . . . .	44
4-11	Alternator and Voltage Regulator Open Loop to Closed Loop Transfer. . . . .	45
4-12	Closed Loop Transfer Characteristic - With and Without Compensation. . . . .	46
4-13	Alternator and Voltage Regulator Open Loop to Closed Loop Transfer With Lead at 3.34 HZ and Lag at 13.7 HZ. . . . .	48
4-14	AC-APU Analog Computer Program . . . . .	49
4-15	Speed Regulator with Integrator. . . . .	50
4-16	PSG with Vertical Return Spring and Electric Speed Setting Motor . . . . .	51
4-17	Power Dissipation in Exciter Field Control . . . . .	53
4-18	Block Diagram of Digital Computer Controller . . . . .	54
4-19a	Basic Flow Chart of Bang-Bang Control. . . . .	56
4-19b	Basic Flow Chart of Bang-Bang Control (cont) . . . . .	57
4-20	AC-APU Analog Computer Program . . . . .	58
4-21	Bi Directional Comparator Control. . . . .	59
4-22	AC-APU Computer Program. . . . .	61
4-23	Uni-Directional Comparator Control . . . . .	62
4-24	AC-APU Analog Computer Program . . . . .	63
4-25	Bi-Directional Comparator with Compensation #1 . . . . .	64
4-26	Bi-Directional Comparator with Compensation #2 . . . . .	65
4-27	An Example of $V_{out}$ Oscillations Occurring with Bang-Bang Control . . . . .	68

## ILLUSTRATIONS (Continued)

<u>Figure No.</u>	<u>Title</u>	<u>Page</u>
4-28	An Example of a Look-Up Table for Multi-Level Bang-Bang Control . . . . .	70
4-29	An Example of Multi-Level Bang-Bang Control . . . . .	71
4-30	An Example of a Look-Up Table for the Direction Sensitive Multi-Level Bang-Bang Control . . . . .	73
4-31	An Example of Direction Sensitive Multi-Level Bang-Bang Control . . . . .	75
4-32	Operator's Display. . . . .	78
4-33	Evaluation Chart of Diagnostic and Monitoring Systems. . . . .	82

## 1. DESIGN GOALS

The general goal of this study was the selection of the optimum design strategy for a motor generator (AC-APU) controller. The controller must meet all specifications and standards for use with motor generator sets rated from 15 KW to 100 KW.

Specifically, the motor generator controller must meet the following military standards and specifications:

MIL-STD-704B	Military Standard, Aircraft Electric Power Characteristics
MIL-D-8512	Military Specification, Design; Special Support Equipment
MIL-T-21200L	Gen. Spec. for Test Equip. for Use with Electronic and Electrical Equipment

This section is a discussion of the AC-APU design goals as they relate to regulation, environment, and general operation. The goals were derived by FIRL from the referenced military standards and specifications, and from discussions with Naval Air Engineering Center personnel.

### 1.1 REGULATION

The voltage and frequency of the AC-APU must be regulated to the required standards set forth in MIL-STD-704B. These standards require that the voltage not exceed the time envelope profile shown in Figure 1-1, and that the frequency remain within 1.25% except during load transient conditions. These goals are attainable only through use of servo systems in which a reference standard is compared to the variables to be controlled (voltage and frequency) and as a result the error is amplified to a level that will correct the variables. The amount of amplification required is a function of the allowable error. This can be expressed as:




Figure 1-1. Envelope of AC Voltage Surge

$$E = e_r - e_v$$

$$e_v = EG = (e_r - e_v) G$$

$$\frac{e_v}{e_r} = \frac{G}{1 + G}$$

For 1% regulation:

$$\frac{99}{100} = \frac{G}{1 + G}$$

$$G = 99$$

## 1.2 ENVIRONMENTAL GOALS

A summary of the environmental requirements for the motor generator controller follows.

Temperature altitude - See Figure 1-2.

Humidity - Up to 100% humidity, condensing on and in equipment in operating and non-operational modes.

Vibration - Must be capable of withstanding a logarithmic sweep of 5 to 55 to 5 Hertz (sinewave) in 15 minutes at the following amplitudes:

<u>Frequency Hertz</u>	<u>Double Amplitude</u>
5 to 15	.06 in.
15 to 25	.04 in.
25 to 55	.02 in.

Shock - Must be capable of withstanding 18 shocks of 15g.

General - Must operate effectively under the following conditions: sand, dust, salt, snow, rain, ice.

- Must be mildew resistant
- Must be usable by a person wearing heavy arctic clothing
- Must be shielded against radiated interference.

## 1.3 OPERATIONAL GOALS

MIL-STD-704B states the specifications of the controller in terms of voltage regulation, frequency regulation, etc. However, a major goal

## TEMPERATURE/ALTITUDE

Operating			Non-Operating	
Temperature Extremes °C		Altitude	Temperature Extremes °C	Altitude Maximum
Continuous	Intermittant 20 Min.			
-54 to +55	+71	0 to 10,000 ft. (30.0 to 20.6 in Hg.	-62 to +85	50,000 ft. (3.4 in. Hg)

Figure 1-2. Temperature/Altitude Requirements for Motor Generator Controller

of this study was to insure that the AC-APU will be easy to operate and repair. Therefore, the complete controller will not only control but monitor and diagnose as well.

The regulator portion should:

- Meet all applicable standards and specifications
- Be of simple design
- Be adjustable over a range of output voltage

The goals of the monitor function are as follows:

- The following parameters should be continuously monitored:
  - voltage
  - current
  - frequency
  - speed
  - oil pressure
  - fuel level
  - coolant temperature
- These parameters should be presented to the operator on demand and the appropriate parameters should be automatically



presented when abnormal operation is detected.

- The presentation of information to the operator should be simple to understand. Where possible, this information is to be presented in "GO/NO GO" format.
- Operator actions required to obtain monitored information should be simple.
- The number of displays should be minimized.
- All necessary displays should be located centrally.

The goals of the diagnostic function are as follows:

- The diagnostics should act in conjunction with the monitoring function to detect and control abnormal conditions. Abnormal conditions include:
  - over/under voltage
  - over/under frequency
  - over current
  - over temperature
  - low fuel level
  - low oil pressure
  - low oil level
  - low coolant level
- Ideally, the diagnostics should detect not only absolute faults (e.g. overcurrent) but potential faults (e.g. sharp rise in temperature).
- The diagnostics should minimize operator involvement and be completely automatic.
- The diagnostics should permit total check out of the motor generator set and controller. Ideally, the diagnostics should pin point any faulty electrical or mechanical components and be performed while the AC-APU is in operation.
- Any non-automatic diagnostics should be easy to use.
- Ideally, the total diagnostic feature should be self-contained in the motor generator controller. However, a separate peripheral device to perform detailed diagnostics may be considered if cost, size and operation factors are beneficial.

## 2. ANALYSIS OF ALTERNATORS

The closed loop system to regulate voltage and frequency of an alternator requires that the characteristics of the alternator be known in terms of time variable expressions. The alternator consists of a field winding used to provide rotor flux and a stator winding that is cut by these lines of flux to provide a sinusoidal voltage whose frequency is determined by the number of pairs of poles and rotor speed. Since each item is critical to the successful design of the control system for the alternator, each was examined separately.

### 2.1 FIELD WINDING

The field winding has a time variable expression related to the inductance and resistance of the winding. Since current is related to the field flux, the transfer characteristic is desired between current and applied voltage.

$$E = IR + L \frac{dI}{dt}$$

Using the Laplace transform  $S$  for  $d/dt$

$$E = IR + SIL$$

$$\frac{I}{E} = \frac{1}{R + SL}$$

The real term in the denominator is  $R$  and when the imaginary term ( $SL$ ) is equal to  $R$ , the phase angle will be  $45^\circ$  and the amplitude will decrease to .707 of the D.C. amplitude. The relation of  $(L/R)$  is known as the time constant of the system and appears at a frequency determined by

$$f = \frac{1}{2\pi (L/R)}$$

## 2.2 REGULATION

If the alternator had no inherent regulation due to load, there would be no need for the development of a regulator. Unfortunately, every alternator has inherent regulation due to the effective impedance that appears between the generated voltage and the terminal voltage. The amount of regulation varies with machine design and is a measure of decrease in terminal voltage when full load current is drawn from the alternator. The specific design considered in the analog computer simulation has a regulation that is calculated to be between 8 and 10 per cent from no load to full load.

## 2.3 EXCITER SYSTEM

The field excitation can be derived from a static source such as battery or A.C. rectified. The exciter must provide a D.C. power sufficient to fully saturate the field. Field excitation can also be obtained by use of a generator on the same shaft as the alternator. Some designs use D.C. generators with brushes to pick off the D.C. power which is to be delivered to the field. More recent exciter designs use brushless types of exciters which have no parts that will wear. Such designs therefore are nearly maintenance free. The penalty to be paid for such a design is the effect of an additional time constant that makes the control loop more difficult to stabilize.

## 2.4 NON-LINEAR OR SATURATION CONSIDERATIONS

The relation of field current to flux developed in the air gap of the alternator is fairly linear over a portion of the operating range. Normally the operating point is placed just beyond the knee of the curve so that when higher flux is needed to overcome the inherent regulation characteristics, the ratio of current to flux is not the same as found under no-load conditions. Since the non-linear transfer characteristic of the field is in the control loop, the loop gain is not constant but varies with load current. At no load the gain is higher than at full load.

Each of these characteristics have been determined in general form so that any alternator design can be simulated by this technique. Parameters have been determined for a specific alternator for this study and the derivation of the parameters are included in Appendix A.

The block diagram representing the alternator is shown in Figure 2-1.  $E_{ex}$  is the exciter input voltage. The gain and dynamics of the exciter are represented by  $K_{ex}/R_{ex} (L_{ex}/R_{ex} S + 1)$  and the output voltage  $E_f$  is the voltage delivered to the main field winding. The dynamics of the main field are represented by  $1/R_f (L_f/R_f S + 1)$  with the gain  $K_f$  and an output in terms of flux appearing in the alternator air gap.

The voltage gain constant  $K_e$  multiplied by rotor speed  $S\theta_G$  will develop the generated voltage which through the internal impedance of the rotor represented by the regulating characteristic  $R_l/(R_G + R_l)$  will produce the terminal voltage  $E_l$ .

The terminal voltage multiplied by the conductance of the load  $1/R_l$  will produce the load current  $I_l$ . The load current multiplied by the torque constant  $K_T$  and scaled by the shaft spring constant, the combination of which is multiplied by the flux  $\phi$  will produce the generator torque  $T_G$ .




Figure 2-1. Alternator Block Diagram

### 3. ANALYSIS OF DIESEL ENGINE

The application of a diesel engine to drive an alternator requires far better speed control than that required for a D.C. generator. Since frequency is directly related to shaft speed, the shaft speed should be kept constant regardless of load conditions. As in the analysis of the alternator the closed loop system to regulate speed required that the characteristics of the diesel be known in terms of time variable expressions. Since each item is critical to the successful design of the governor for the engine, they are discussed separately.

#### 3.1 ROTATING INERTIA

The rotating inertia of the system consists of the diesel engine inertia coupled by shaft to the alternator inertia. The shaft has an angular spring rate. The inertia will develop a force due to angular acceleration or rate of change of shaft velocity. The shaft angular spring rate combined with the inertia of the engine and the alternator have a natural frequency that is determined by  $\sqrt{\frac{K}{J}}$ .

#### 3.2 TORQUE VERSUS FUEL FLOW

The fuel flow system versus developed torque is fairly constant regardless of shaft speed. For the analog computer simulation, it has been considered constant.

#### 3.3 THROTTLE CONTROL

The flow of fuel into the engine must be controlled and in order to maintain constant speed, the throttle opening must be controlled by the error between the speed reference and the actual shaft speed. The time variable element in the throttle system is the moving valve piece. The valve piece has inertia, damping and, in most cases, a spring to return

it to the closed position. Valves that are operated by electrical force coils have a time constant due to the inductance and resistance of the coil.

Each of these characteristics have been determined in general form so that any diesel engine design can be simulated. For this study, parameters have been determined for a specific engine and the derivation of the parameters is included in the appendix.

The block diagram representing the diesel engine is shown in Figure 3-1. The input voltage to the flow control valve is shown as  $E_Y$ . This voltage through the coil dynamics  $1/R_S(L_S R_S S + 1)$  and the mechanical dynamics of the valve represented by  $1/[J_T/K_S S^2 + K_D/K_S S + 1]$  with a gain of  $K K_{SY}$  will produce a valve displacement represented by  $X_T$ . The valve displacement will provide flow of fuel to the diesel engine and a torque  $T_D$  will be developed in proportion to the engine gain  $K_1$ . The resultant torque applied to the shaft coupling diesel engine to alternator rotor is derived from the developed torque  $T_D$  minus the torque due to change of shaft speed through the dynamics of  $K_D(J_D/K_S S + 1)$ . The dynamics of the shaft are represented by  $1/K_S(J_D/K_S S^2 + K_D/K_S S + 1)$ . The resultant torque from the shaft when summed with the alternator torque  $T_G$  will accelerate the alternator inertia and overcome friction and windage described in the block with gain and dynamics of  $K_S/K_D (J_G/K_D S + 1)$  and an output of shaft speed  $S\theta_G$ .




Figure 3-1. Diesel Engine Block Diagram



## 4. SYSTEM DESIGN STRATEGIES

This section describes the various system design strategies considered for the motor/generator controller and the analysis of calculations and test results.

In order to maintain a reference point, the discussion of the voltage regulator hardware and design trade-offs assumes that a microcomputer will be used for the monitoring and diagnostic functions. A general block diagram of the monitoring and diagnostic system is presented in Figure 4-1. The block diagram is discussed in detail in Section 4.5.3.

### 4.1 LITERATURE SEARCH AND REVIEW

A computerized literature search was performed to aid in the selection of regulator design strategies. The search retrieved information from three data bases:

- Engineering Index
- Institute of Electrical Engineers (IEE)
- Information Service of Mechanic Engineering (ISMEC)

The results of the computer search are presented as Appendix B.

A review of the data obtained from the computer search and from other sources led to the selection of several regulation methods; these fall into the general categories - digital, analog and hybrid.

### 4.2 ANALOG METHOD OF CONTROL

The analog method of load voltage control from an alternator requires the use of continuous current. The amplitude of the current must vary in order to control the alternator field. The error voltage, that is the difference between reference voltage and load voltage, is a continuous voltage varying in amplitude. It is amplified to provide the necessary




Figure 4.1. General Block Diagram of the Microcomputer Based Monitoring and Diagnostic System

field current needed to hold the load voltage to the required level. The most accurate system for this type of control is a type 1 system. This differs from a type zero system in that a type zero system has an error that is dependent upon loop gain. A type 1 system has an integration so that under static conditions the error is zero.

The complete system of the diesel engine drive, governor, alternator and voltage regulator have been simulated for the analog system. The general form block diagram is shown in Figure 4-2. The description of the symbols and the derivation of their numerical values are given in Appendix A.

Referring to Figure 4-2, the shaft speed of the alternator  $S\theta_G$  is the controlled function that is desired to be constant. The speed as compared to the reference  $S\theta_V$  will produce an error  $e_D$  that may be a mechanical or electrical signal used to drive the throttle valve the distance  $X_T$ . Throttle displacement will produce fuel flow which through the gain constant  $K_1$  of the diesel engine will produce an output torque of  $T_D$ . This torque will drive the combined inertia of the alternator ( $J_G$ ) and diesel engine ( $J_D$ ) through the shaft spring constant ( $K_S$ ). Since friction and windage ( $K_D$ ) are present some torque will be required even at constant shaft speed and zero electrical load.

The alternator loop has a load voltage ( $E_L$ ) compared to a reference voltage ( $E_r$ ) to provide an error ( $e$ ) as an input to the voltage regulator. The voltage regulator will drive the exciter field which in turn will drive the main field of the alternator. The field flux ( $\phi$ ) developed by the main field excitation will generate a voltage ( $E_g$ ) that is a product of shaft speed ( $S\theta_G$ ) and field flux ( $\phi$ ) through a gain constant ( $K_e$ ). The load voltage ( $E_L$ ) will adjust in level in proportion to the load current by virtue of the alternator inherent regulation characteristic.

The load current ( $I_L$ ) multiplied by the field flux ( $\phi$ ) will produce a torque  $\left( \frac{K_T I_L \phi}{K_S} \right)$  that will subtract from the shaft torque delivered



to the alternator inertia thus slowing down the shaft speed.

From this block diagram and the constants derived in the appendix, the analog computer simulation was developed as shown in Figure 4-3. In Figure 4-3 the block designated as governor contains the electronic equivalent of the dynamics of the solenoid operated flow control valve to supply fuel flow to the engine. The input is an electronic voltage  $S\theta_Y/100$  which when compared with the tachometer voltage representative of the shaft speed  $S\theta_G/100$  will produce the error voltage necessary to produce the input to the diesel engine.

The input to the diesel engine has a non-symmetrical torque limit in which the acceleration torque is twice that of the deceleration. The dynamics of the shaft stiffness and diesel engine inertia are included in the block marked diesel engine. The block marked alternator has the torque input to the alternator dynamics including rotor inertia. Multipliers are used to generate developed torque from load current and field flux and shaft speed multiplied by field flux to develop generated voltage  $E_G/10$ . A feedback path in the amplifier used to convert  $E_G/10$  to  $E_L/10$  establishes alternator regulation due to load. A second amplifier with a bias input is provided to facilitate a larger scale voltage of the load voltage as designated by  $\Delta E_L/2$ . Regulation and dynamics of the alternator can be more accurately determined using this means of off-set or bias level cancelling. The exciter input shown in the exciter block comes from a voltage regulator that has an input from  $E_L$  and provides gain and compensation to stabilize the loop. The exciter block contains the gain and dynamics of the exciter used to drive the main field.

Of the many runs that were made, those recorded for the 10% and 15% inherent regulation with and without the compensation needed to bring the transient within the allowable limits of the MIL-STD-704B are discussed in the following paragraphs.

The alternator with 10% inherent regulation is shown in Figure 4-4 with a voltage regulator system of nominal control characteristics. The characteristics include compensating networks that are in the AC voltage regulator design shown in Figure 1-12 of the NAVAIR 19-45-19 report. Using this as a starting point, a voltage regulation characteristic as recorded in Figure 4-5 was obtained. The load current  $I_L/2$  is equivalent to full load at unity power factor. The initial drop in load voltage due to inherent regulation is observed in the trace of  $-\Delta E_L/2$ . Close study shows that when load is applied the frequency of ringing is lower than when load is removed and the first overshoot is of lesser amplitude.

The alternator shaft speed  $S\theta_G/100$  equivalent to 209 rad/sec or 2000 rpm shows a decrease in speed when load is applied. Since this is a type zero regulator, the speed will not return to the initial or unloaded speed since some error must exist and is directly related to loop gain. The torque shows an increase when load is applied as recorded in T/50. Since the characteristics of the diesel engine are approximated for this simulation, the levels have not been calibrated precisely.

The selected loop gain produces a system response that falls just outside the allowable parameters. The natural frequency of the underdamped voltage wave measures to be 0.09 sec/cycle or 11.1 Hz. Since the system has a damping characteristic of close to 0.1 and it is desired to maintain approximately the same speed of response, a compensating network in the forward loop of the voltage regulator was added. This is in the form of a lead lag network with the lead term set for 3.35 Hz and the lag at 13.7 Hz thus producing positive phase shift in the range of 11 Hz. The schematic




Figure 4-3. AC-APU Analog Computer Program





Figure 4-4. AC-APU Analog Computer Program



# NO FORWARD LOOP COMPENSATION



$$\frac{T_D}{50}$$

$$\frac{56}{100}$$

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-5. Alternator 10% Inherent Regulation

for this system is shown in Figure 4-6. The results of this compensation with adjustment of loop gain for optimum performance is shown in Figure 4-7. The system performance exhibits much greater damping and fits well within the allowable limits.

The same system characteristics as shown in Figures 4-4 and 4-6 have been used for the alternator with a 15% inherent regulation. Figure 4-8 is for the uncompensated system where the amplitude of regulation is much larger than that for the 10% design. Similar damping characteristics are observed. The compensation network does help in this design but would have to be modified to provide optimum performance. The compensated response is shown in Figure 4-9 and has identical compensation to that shown in Figure 4-6.

#### 4.2.1 Compensation Selection

The linear analysis of the alternator and voltage regulator shown in Figure 4-4 has been calculated and plotted in Figure 4-10 with gain recorded as  $M_1$  and phase shift as  $\theta$ . In order to fit within the time profile of the transient response, the bandwidth of response must be in the order of 10 Hz or higher. This requires that the open loop gain of the system should be at least 57 db/S. Plotting the phase and gain characteristics of the open loop transfer on the Nichols chart shown in Figure 4-11, the characteristics of the closed loop response are obtained. This response is plotted in Figure 4-12 as closed loop nominal amplitude ( $M_1$ ) versus frequency. The system has a definite characteristic of low damping as evidenced by the 4.5 db peak around 16 Hz. Since the phase shift shown in Figure 4-10 for  $\theta_1$  is nearly constant at  $140^\circ$  from 1 Hz to 10 Hz, this peak would be of the same amplitude for gains between 37 db/S and 57 db/S. The frequency of the peak would vary from 1.6 Hz to 16 Hz depending upon gain.

The approach used for compensation is to add positive phase shift to bring the phase angle back to 120 degrees or less at around 10 Hz. A compensation network with the lead and lag separated by a ratio of 4:1 will provide a maximum leading phase shift of 37 degrees when the lead is at a lower frequency than the lag. This characteristic has been included in Figure 4-10 as  $M_2$  and  $\theta_2$  when incorporated with the alternator and voltage regulator characteristic of  $M_1$ . The phase and gain plotted on the Nichols chart of Figure 4-13 provides the open loop to closed loop response for the





Figure 4-6. AC-APU Analog Computer Program

# WITH FORWARD LOOP COMPENSATION



$$\frac{T_D}{50}$$


$$\frac{50V}{100}$$

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-7. Alternator 10% Inherent Regulation  
41 (A-30 or A-203)

# NO FORWARD LOOP COMPENSATION



$$\frac{T_D}{50}$$

$$\frac{50V}{100}$$

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-8. Alternator 15% Inherent Regulation

## WITH FORWARD LOOP COMPENSATION




Figure 4-9. Alternator 15% Inherent Regulation




Figure 4-10. Open Loop Transfer Characteristic - With and Without Compensation




Figure 4-11. Alternator and Voltage Regulator  
Open Loop to Closed Loop  
Transfer.






Figure 4-12. Closed Loop Transfer Characteristic,  
With and Without Compensation

compensated system. The closed loop response is plotted in Figure 4-12 recorded as  $M_2$  for magnitude versus frequency. The system has a characteristic of critical damping and a bandwidth that is flat to 20 Hz.

The analog computer runs that include non-linearities are found in 4-5 to compare with  $M_1$  and in 4-7 to compare to  $M_2$ .

During the course of the study an investigation was made to determine the effect of different generator field time constants. It was found that increasing the time constant by a factor of 3 had a minimal effect on system performance when compensation networks were used. Close to the same bandwidth could be achieved using linear system analysis. The characteristics of the open and closed loop frequency response for this system are shown in Appendix D.

#### 4.2.2 Analysis of Speed Regulation System

Most diesel engine governors are of the type zero system as illustrated in each of the analog computer programs. The best system for maintaining frequency control is a type one system. This system has been simulated on the analog computer as shown in Figure 4-14. An integrator has been added to make the governor a type one system. Considerable compensation is necessary to stabilize the speed control loop. Performance of this circuit is shown in Figure 4-15. It will be noted that under full load conditions the speed returns to no load speed after the transient period. No attempt was made at this time to optimize the control characteristic of the governor system with the integrator in the loop.

Such a system is commercially available from the Woodward Governor Company and is described in their Bulletin 37013, PSG Governor. A picture of this type of governor is shown in Figure 4-16 where the electric drive motor is the integrator between error voltage and throttle position.

#### 4.2.3. Analysis of Voltage Regulation System

The strictly analog system is theoretically the best system as far as bandwidth of response since there is continuous signal with which to operate. Linear analysis techniques and compensation networks are easily calculated and fabricated.

A disadvantage is encountered when large currents such as field or exciter currents are controlled by analog methods. In the specific case




Figure 4-13. Alternator and Voltage Regulator Open Loop to Closed Loop Transfer With Lead at 3.34 Hz Lag at 13.7 Hz




Figure 4-14. AC-APU Analog Computer Program




Figure 4-15. Speed Regulator with Integrator




Fig. 1. Speed Setting Motor with Vertical Return Spring and Electrically  
Controlled Setting Motor.

51 (A-40 or A-203)

being studied, the exciter field is powered from a 28V DC source. Current must be regulated from zero to 3.3 amperes for an output voltage of 120V rms. The resistance of the field is 2.35 ohms thus making a maximum current capability of  $28/2.35 = 11.9$  amperes. In Figure 4-17 we have plotted load current to the exciter versus power dissipated in the series element. At the no load operating point, the power to be dissipated in heat is equal to:

$$P_D = [28 - I_{ex}(2.35)] I_{ex}$$

$$P_D = (28 - 7.755) 3.3$$

$$P_D = 66.8 \text{ watts}$$

#### 4.3 DIGITAL METHODS

The basic regulation methods selected for study were the NAVAIR Design, bang-bang, multi-level bang-bang, direction sensitive multi-level bang-bang and the digital simulation of analog designs. The actual implementation of many of the digital techniques provided great insights into the problems and advantages of the various techniques. However, none of the methods were developed to an optimal state.

##### 4.3.1 Test Bed for Digital and Hybrid Techniques

The digital and hybrid regulation techniques were tested in real time through the use of the combination of the digital and hybrid computers. The bang-bang techniques were programmed into a PACER 100 digital computer via analog to digital (A/D) and digital to analog (D/A) converters. The PACER was used as a regulator for the analog computer motor generator simulation. A block diagram of the system is presented as Figure 4-18.

The PACER provides a conservative comparison to existing microcomputer systems in that:

- A. Its cycle time (1  $\mu$ s) is fairly typical of microcomputer systems, and is, in fact, slower than many current microcomputer systems. For example, the XECON SMC360 has a typical instruction cycle time of 120 nanoseconds.




Figure 4-17. Power Dissipation in Exciter Field Control






Figure 4-18. Block Diagram of Digital Computer Controller

- B. While the PACER is basically a 16-bit machine, its A/D and D/A are 8-bit devices. Thus, all data manipulation is handled in bytes of 8 bits--the same as most microcomputers.
- C. The PACER instruction set contains 84 basic instructions, fewer than most microprocessors. For example, the Digital Equipment Corporation's KD11F microprocessor uses 400 basic instructions.

The PACER assembly language program for the general bang-bang techniques is presented as Appendix C. A basic flow chart of the program is presented as Figure 4-19a. This flow chart represents the multi-level bang-bang (to be described in Section 4.3.4) with provisions for switching in a parallel regulator when the output voltage is within programmed limits. Variations of this basic flow chart and of the program are used to perform the different bang-bang techniques.

#### 4.3.2 NAVAIR TECHNIQUE

The first digital method to be considered is that of a comparator operating on the integrated error output of the voltage regulator system. This is similar to the system described in the NAVAIR report 19-45-19, Figure 1-13, AC Voltage Regulator, Schematic Diagram. In this system the voltage sensed is 3-phase half wave rectified. A lead network in the voltage feedback to the summing junction provides the ripple frequency to turn the comparator on and off. Since the analog computer simulation is a D.C. equivalent of the A.C. voltage, the ripple frequency will not be present and the on-off cycle is, therefore, dependent upon the control loop time constant. This is verified in the several runs made for this system on the analog computer with various compensating networks.

The first digital control technique is shown in Figure 4-20. The driving pulses are from full positive to full negative thus forcing the exciter input in either direction. This is somewhat similar to using a diode around the exciter field to force the field to collapse at a high rate. The performance of this system is shown in Figure 4-21 where the adjustable gain has been set to provide optimum results. The response does have a switching rate of about 28 Hz with a peak to peak amplitude of 2.5V. This is within the allowable voltage band for transient operations.




Figure 4-19a. Basic Flow Chart of Bang-Bang Control




Figure 4-19b. Basic Flow Chart of Bang-Bang Control (Continued)





Figure 4-20. AC-APU Analog Computer Program



$$\frac{T_D}{50}$$

$$\frac{50_G}{100}$$

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-21. B1 Directional Comparator Control

The same system was simulated with the exception that a single direction of driving current pulse was permitted in the exciter field. This circuit is shown in Figure 4-22 where the diode  $D_1$  has been added. The performance characteristic is shown in Figure 4-23 where it is evident that the voltage regulation is outside the allowable range during transient but just fits within the range during constant load. The switching rate is about 14 Hz which agrees with the anticipated response being twice the time period due to only unidirectional pulse modulation of the exciter current.

A higher loop gain would permit faster operation of the comparator circuit and decrease the load voltage excursion. The high frequency range of the system was increased by adding a lead compensation between the comparator and the exciter field input. In actual hardware this can be incorporated in the base of the transistor used to drive the field current. This circuit is shown in Figure 4-24. The performance of the circuit is shown for two values of capacitance  $C_1$  with optimum gain settings. Figure 4-25 is the response when  $C_1 = .047 \mu\text{F}$ . Pulse modulation is evident in the recording of the exciter input voltage. The response is too slow and the transient falls outside the allowable limits. The constant load condition shows a clean and steady voltage level. A compromise is reached when  $C_1 = .01 \mu\text{F}$  and the gain adjusted for optimum performance as recorded in Figure 4-26. The switching rate is approximately 42.5 Hz and the response does fall within the constant load and transient envelope of performance requirement. The amplitude of load voltage ripple is approximately 1.2 volts peak to peak.

#### 4.3.3 NAVAIR Design Analysis

In the NAVAIR system, a comparator is used to pulse width modulate the current delivered to the exciter field. This system has considerably lower losses since the series element is either fully saturated or completely cut off. The power dissipation is limited to the rise and fall time versus the repetition rate. As an approximation if the rise time is 10 microseconds and the repetition rate 1000 Hz, then the heat dissipation








Figure 4-23. Uni-Directional Comparator Control





Figure 4-24. AC-APU Analog Computer Program

$$C_1 = .047 \mu F$$




EXCITER  
INPUT

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-25. Bi-Directional Comparator with Compensation #1.

$$C_1 = .01 \mu F$$



EXCITER  
INPUT

$$-\frac{\Delta E_L}{2}$$

$$\frac{I_L}{2}$$

Figure 4-26. B1 Directional Comparator with Compensation #2

would be in the range of:

$$P'_D = \left( \frac{2 \times 10 \times 10^{-6}}{10^{-3}} \right) 80 \times .636 = 1.018 \text{ watts}$$

This is a considerable reduction in the heat dissipation problem.

The switching rate of the comparator is dependent upon either ripple frequency of the load voltage or the system time constants. For the AC application the ripple can be obtained from the rectified load voltage as in the design shown in the NAVAIR report 19-45-19, Figure 1-13.

#### 4.3.4 Bang-Bang

A bang-bang controller operates by monitoring the output voltage of the motor generator set and depending on the value of the voltage calls for either maximum or minimum field current. This is similar to the NAVAIR design. For example, if the output voltage should be equal to 10 volts but is actually equal to a value above 10 volts, the controller will reduce the voltage by setting the field current to the minimum. If the output falls below 10 volts, the controller responds by setting the field current to the maximum level. In this way the controller switches on or off in an attempt to maintain a constant output voltage level.

The rate of this on-off switching is a function of current demands and the switching level of the controller. If for example, a sudden current demand is placed on the motor generator, the voltage will tend to fall, and the controller will respond by holding the field current at maximum until the voltage recovers. The chief advantage is that, in the optimum design, the recovery time is minimized because the field current is maximized.

The switching level of the controller is the level at which the controller recognizes that the voltage is too high or too low. Normally, the off level is  $V + h$  and the on level is  $V - h$ , where  $V$  is the desired output and  $h$  is a small preset voltage level. This is also known as hysteresis. The smaller the  $h$ , the faster the controller will respond to variations in  $V$  by switching the field current.

In the computer program the bang-bang system was implemented by using one break point (output voltage was either above or below the reference) and two control words (the field current was switched between full on and full off). The program was also modified so that the parallel regulator was never switched in; thus, the pure bang-bang effect was obtained.

#### 4.3.5 Analysis of Bang-Bang Technique

The major problem with the pure bang-bang system as implemented was oscillation of the regulator's output voltage. The bang-bang decision (to switch from high field current to low field current) was based on the relationship of the output voltage to the reference voltage. When the output voltage was greater than the reference voltage, the field current control was set to the low value; when output was less than the reference, the field current control was set to the higher value. However, the momentum of the output voltage is such that about .05 seconds, after the bang-bang level has been applied, is required to reverse direction. Figure 4-27 presents an example of the oscillation. This effect may be eliminated or minimized by a number of methods. One such method is to optimize the gain of the control signal to the field current. This would reduce the time to reverse the momentum of the voltage and thus reduce the amplitude of the oscillation.

The bang-bang scheme could be performed by a microcomputer in a time sharing mode with the display and diagnostic routines. It is estimated (based on the PACER) that a computer could perform the diagnostic and display routines and still make bang-bang decisions at speeds in excess of 1 KHz.

The hardware required, in addition to that already assumed for display and diagnostics, would be as little as the dedication of one digital output line for the control signal, dedication of one A/D multiplexer channel for reading to regulator output voltage, use of approximately 100 words of memory, and the addition of a field current driver circuit. In actual hardware dollars this would be about \$100.




Figure 4-27. An Example of  $V_{out}$  Oscillations Occurring with Bang-Bang Control.

#### 4.3.6 Multi-Level Bang-Bang

Multi-level bang-bang (MLBB) operates in a manner similar to pure bang-bang except the controller does not simply turn the field current on or off. The controller sets the field current to a level dependent on the difference between the actual output voltage and the desired output voltage. The chief advantage of this method is that, optimally, it combines the fast recovery of bang-bang with the smooth operation of a linear circuit.

The control can be described as a look-up table. Given the output voltage, the table indicates the field current setting for best regulation. An example of a look up table is presented as Figure 4-28. Referring to the figure, if the desired output voltage was 10 and the actual voltage was 18 volts, the field current would be turned off; if the output voltage was 1, the field current would be turned completely on. The operation as described so far is identical to pure bang-bang. However, if the output voltage were 7.5, the field current would be set to 60% of full scale; a reading of 16V will result in a field current setting of 10% of full scale, etc. Since a digital computer is programmable, any voltage breakpoint and field current value could be assigned and modified without effecting the hardware. Ideally, the optimum values would be selected for the regulator.

In the computer program, the multilevel bang-bang system was implemented as described--through the use of a look-up list. The computer stored a list of breakpoints. These breakpoints represented zones above and below the reference voltage. Each breakpoint or zone had a corresponding control word. The control word represented the desired field current to be supplied when the output voltage was within the zone.

#### 4.3.7 Analysis of Multi-level Bang-Bang Techniques

A reduction in the amplitude of the output voltage oscillation was achieved by switching from pure bang-bang control to the multilevel bang-bang (see Figure 4-29).

Most of the hardware required for MLBB is identical to that used in pure bang-bang, the major exception being the field current driver. In the



OUTPUT VOLTAGE RANGE*	FIELD CURRENT % OF FULL ON
20 TO 17.0	0
16.9 TO 14.0	10
13.9 TO 12.0	40
11.9 TO 9.0	50
8.9 TO 7.0	60
6.9 TO 4.0	90
3.9 TO 0.0	100

\* IN THIS EXAMPLE, 10 VOLTS IS THE DESIRED  
OUTPUT VOLTAGE.

Figure 4-28. An Example of a Look-Up Table for  
Multi-Level Bang-Bang Control




Figure 4-29. An Example of Multi-Level Bang-Bang Control

bang-bang case the driver can be a single saturating switch; however, in multiple bang-bang the driver can be either a non-saturating driver or an adjustable gain saturating driver. The non-saturating driver would be less complex but also less efficient (more heat) than the adjustable gain saturating driver.

The hardware cost of the saturating driver would be about \$60 compared to about \$30 for the non-saturating driver. The other hardware addition would be a requirement for about 200 more words of memory. The estimated hardware cost of adding the MLBB with a saturating field current driver is \$150 (about \$50 more than the bang-bang controller). MLBB would not demand significantly more computer time than bang-bang. Therefore, the controlling rate could still be in excess of 1 KHz.

#### 4.3.8 Direction Sensitive Multi-Level Bang-Bang

Direction sensitive multi-level bang-bang (DSMLBB) is yet a further extension of the basic bang-bang scheme. DSMLBB is similar to MLBB in that the control is dependent on the difference between the desired and actual output voltage. However, DSMLBB takes past events into consideration by adding direction of the output voltage as a control parameter.

Continuing the example of a look up list, Figure 4-30 shows a list for DSMLBB. Notice that the selection of field current depends on the direction of the output voltage. For example, if the voltage were sitting at 10V when a load was placed on the line, the voltage would tend to drop or go down. If the voltage dropped to 5 volts, the controller would try to recover by calling for full field current (100%). If the voltage began to rise, to say 5.1 volts, the field current selection would be made from the "up" column and would be 90%. As the voltage further recovered (8 volts) the control would be selected from the charts "up" column.

Thus when the load is changed and the actual voltage is moving away from the desired voltage, the control reacts quickly and applies a decisive counter control; however, as the voltage begins to approach the desired value, the control is such as to allow the voltage to recover with minimum overshoot. Ideally, this system will rapidly control load transients with

OUTPUT VOLTAGE* ZONE	FIELD CURRENT % OF FULL ON	
	DIRECTION OF VOLTAGE	
	UP	DOWN
20 TO 17.0	0	0
16.9 TO 14.0	0	10
13.9 TO 12.0	10	40
11.9 TO 9.0	45	55
8.9 TO 7.0	60	90
6.9 TO 4.0	90	100
3.9 TO 0.0	100	100

\* IN THIS EXAMPLE, 10 VOLTS IS THE  
DESIRED OUTPUT VOLTAGE.

Figure 4-30. An Example of a Look-Up Table for the  
Direction Sensitive Multi-Level Bang-  
Bang Control.

a minimum overshoot.

The computer program to implement the DSMLBB scheme was an extension to the MLBB program. A subroutine was added to determine, at each occurrence of reading the output voltage, if the output voltage had changed directions (output voltage derivative zero crossing). If the direction had not changed control word for the zone would be read as in the MLBB program. However, if the direction of the output voltage has changed, the control word would be selected from another list.

#### 4.3.9 Analysis of Direction Sensitive Multi-Level Bang-Bang

The MLBB experiments showed (Figure 4-29) that the particular design required over 300 ms to regulate after application of 100% load. DSMLBB was implemented in an attempt to reduce the settling time. Figure 4-31 presents a DSMLBB run in which the settling time was reduced to below 200 ms.

The only hardware difference between MLBB and DSMLBB is the addition of about 100 words of memory in the latter case. This comes to a hardware cost difference of about \$10. The computer time requirements remain essentially unchanged.

#### 4.3.10 Digital Simulation of Analog Designs

The digital simulation of an analog design consists basically of solving a differential equation in real time. The equation can be written from an existing analog design. The chief advantage of this method is that the regulation scheme can be modified in software without changing any hardware. This advantage may aid in creating a controller with a single hardware design but with versatility to control various AC-APUs.

#### 4.3.11 Digital Simulation of Analog Designs

Any analog regulator circuit that can be built can be simulated by the digital computer, by solving the circuit equations. The only real questions in the current case are: Can the computer solve the equation in real time and if yes, does the computer have enough time to perform the diagnostic




Figure 4-31. An Example of Direction Sensitive Multi-Level Bang-Bang Control

and monitoring functions? To answer these questions the analog regulator of Section 4.2 was studied. Based on this circuit, the PACER instruction times, and solution of the convolution integral at 100 samples, the controlling function could be updated at a rate of approximately 500 Hz and still maintain the monitor and diagnostic functions.

The additional hardware (over that required for the basic monitoring and diagnostic system) would be similar to that required for the MLBB circuit except that approximately 1500 words of additional memory would be needed. The total additional cost would be about \$360.

#### 4.4 HYBRID METHODS

Hybrid regulation is the combination of analog and digital regulation schemes. This study combined the analog methods described in Section 4.2 with the bang-bang and multiple level bang-bang schemes presented in Section 4.3.

Under steady state conditions the regulation would be provided by the analog regulator. However, under transient conditions, the digital regulator would provide control. Such a system provides smooth operation, fast regulation and efficient use of hardware. The smooth operation is provided through the use of the analog techniques. The fast regulation is provided through the use of the bang-bang techniques. Because the digital system is used only on demand in transient situations, the same digital hardware could conceivably be time shared with the monitor display and diagnostic functions.

Subroutine D of the flow chart in Figure 4.19b presents the method used for switching from the digital control to a supplementary parallel controller such as an analog regulator. When the system is in steady state (output voltage within a programmed envelope), the supplementary regulator is in control. When a transient occurs, the digital system is switched into control.

#### 4.4.1 Analysis of Hybrid Methods

The hybrid techniques are any combination of digital or analog techniques. Ideally, a hybrid technique has the advantages of the individual techniques but none of the disadvantages. Our study has not disproved this; however, we have discovered that hybrid techniques have a particular, although probably minor, problem - that of successfully switching from one technique to another. For example, in one simulation the combination of an analog technique with the bang-bang method would latch in the bang-bang mode. In this particular instance, once the system was placed into bang-bang mode, the analog system was permitted to drift freely; as a result the analog controller was never ready to resume control. This was corrected by forcing the analog regulator to follow the system in the bang-bang mode even though the analog regulator was not actually being used by the system.

#### 4.5 MONITOR AND DIAGNOSTIC SYSTEM

Referring to Figure 4.1, the general microcomputer based controller will consist of: a microcomputer with a variety of digital and analog input/output devices. The analog inputs will include parameters to be monitored (current, frequency, voltage, oil level, etc.) and the diagnostic test points. Analog outputs will include field current control and other system controls. Digital inputs will include inputs from the operators console as well as diagnostic digital inputs. Digital outputs will include commands to the control circuits and control panel (e.g. alphanumeric display and indicator lamps).

##### 4.5.1 Monitor System

The ideal monitoring system as described in Section 1.3 (Design Goals) was studied and a strategy was developed for its implementation.

An operator's display that fits the needs of the monitor design goals is presented in Figure 4-32. It consists of an alphanumeric display and several lighted key switches.






Figure 4-32. Operator's Display

The alphanumeric display is used to present quantitative operating instructions and information. The instructions would guide the operator in the use of the motor generator set and the diagnostic procedures. The quantitative information available for display would include the following:

- Voltage
- Current
- Frequency
- Speed
- Oil Temperature
- Oil Pressure
- Oil Level
- Fuel Level
- Coolant Temperature
- Coolant Level

Under normal conditions, the operator could command the system to display one or more of the parameters on the alphanumeric display. Under fault or near-fault conditions, the display would automatically present the parameters of interest along with any pertinent instructions for the operator (see Section 4.5.2 Diagnostics).

The key switches would have two purposes: To enter operator commands and to present the current status of the various parameters. For example, by pushing the voltage key, the value of the voltage will be presented on the alphanumeric display. If the voltage were within limits the voltage key switch would be green. If the voltage were beyond specified limits, the key switch would blink red. The key switches would also be capable of presenting warnings; for example, if the oil temperature suddenly changed although did not rise beyond the specified limits, the oil temp key switch would turn red. The operator could obtain more information by pressing the key switch. Pertinent information would be presented on the alphanumeric display.

#### 4.5.2 Diagnostics

The exact method of detecting faults must be deferred until the hardware design has been finalized. However, a general strategy has been developed. As described in the design goals, the diagnostics will be of two

types: operating and non-operating.

The operating diagnostics will continuously check the following parameters:

- Voltage
- Current
- Frequency
- Speed
- Oil Temperature
- Oil Pressure
- Oil Level
- Fuel Level
- Coolant Temperature
- Coolant Level, and
- Hardware

These are the same parameters presented on the key switch display. When the parameters are within specified limits, the diagnostic routine will set the key switch lamps to green. If any parameters go outside the specified limits, the key switch will turn red and the appropriate instructions will be presented to the operator. For example, if the fuel level is approaching empty, the fuel level lamp will turn red and the alphanumeric display may read "ADD FUEL". If any parameter goes beyond the specifications and into a state in which damage could occur, the key switch blinks red and the system takes appropriate action to eliminate the unsafe condition. For example, if the oil temperature were too high the system would automatically shut down.

These parameters can be combined to form a fault tree to aid in diagnosing specific faults. For example, by themselves, a rise in oil temperature and a change in oil level may not be faults; however, the simultaneous occurrence of the two may indicate an oil leak. This information could be passed on to the operator (condition red). If the situation worsens, the system may automatically shut down (condition blinking red). The change from red to blinking red may also be a function of time. For example, if the red condition lasts longer than  $t$  time, the condition is changed to blinking red.

The hardware function will continuously test various key hardware components. If a fault is detected appropriate action will be taken

automatically (e.g. shut down) and the alphanumeric display will indicate the location of the fault.


The diagnostics discussed thus far are performed while the system is actually in operation. If possible all the diagnostics should be incorporated into the operating system. However, complete diagnostics may actually require that the system be non-operating. For example, if the system contained digital read/write memory the best test is to write patterns into the memory and to compare what is read with what is written. This cannot easily be performed with the system in operation. Similarly, with analog portions of the system perhaps the system may best be checked by feeding the circuits known inputs which cannot be inserted during normal operation.

#### 4.5.3 Analysis of Monitoring and Diagnostic Methods

The regulation schemes were evaluated based on the assumption that a microcomputer would exist in the controller for the monitoring and diagnostic functions. However, the functions as described in Sections 4.5.1 and 4.5.2 could also be accomplished through the use of discrete analog or digital design; or through the use of a minicomputer. The microcomputer could either be a purchased system (such as the Intel 80/100 single board computer) or a specially designed system based on a standard microprocessor family (such as the Intel 8080 family). The distinction between a minicomputer and a microcomputer is a fine one. The definition used in this study is that a minicomputer is closer to a general purpose computer and is therefore more user-oriented than a microcomputer. An example of a minicomputer is a PDP8. Figure 4.33 is a chart of the relative merits of each method.

The categories compared are: development costs; hardware costs; operational costs; flexibility; size and speed. These are considered as they fit the particular problem of controlling a motor generator.

The development costs for a minicomputer are the lowest, while the costs of the development of a custom microcomputer are the highest. As



	Discrete Design	Minicomputer	Standard Microcomputer	Custom Microcomputer
Development Costs	3	1	2	4
Hardware Costs	4	2	1	3
Operational Costs	3	2	1	4
Flexibility	4	2	1	3
Size and Weight	3	4	2	1
Speed	1	3	3	2
Average	3.6	2.8	2	3.4

Key: 1 = is best

4 = is worst

Figure 4-33. Evaluation Chart of Diagnostic and Monitoring Systems.

stated previously, a minicomputer is normally oriented towards the programmer and, therefore, the programming costs are minimized. Also the majority of the hardware design is standard. A commercial microcomputer system is very similar to a minicomputer except that the programming task may be higher because the system is hardware not software oriented.

The lowest hardware cost is expected to be a commercial microcomputer because a minimum system can be assembled from standard parts. The most expensive is expected to be the discrete design because of a greater number of parts and the largest construction costs.

Operational costs include training of operators and maintenance personnel; costs of maintenance and inventory. It is believed that a commercial microcomputer will have the lowest operational costs mainly because the hardware will consist largely of standard, inexpensive circuit boards or modules. The most expensive is expected to be the custom microcomputer. While the components of the custom microcomputer are standard, the basic configuration will be non-standard and, therefore, special maintenance procedures will need to be developed.

The standard microcomputer is believed to have the greatest flexibility in that it can be modified at a minimum cost while a discrete design will be the highest cost. For example, if requirements change for any part of the controller a standard microcomputer may compensate via software, or if software alone will not satisfy the requirement standard components from the microcomputer family can often be used. In a discrete design, however, hardware must always be changed and the changes are rarely minor.

Because a custom microcomputer is designed with the minimum parts, it will most likely be the smallest and lightest system. Analysis of the speed at which the regulator could operate shows that 300 Hz is acceptable if the monitor and display function can also be performed. In this case, all the systems are acceptable; however, the discrete design because it will be most likely perform most of the functions in parallel will be the fastest.

NAEC-92-139

An unweighted average of the values presented in the chart indicates that the ranking should be as follows (best system first):

- Standard microcomputer
- Minicomputer
- Custom microcomputer
- Discrete design

## 5. CONCLUSIONS

The following conclusions have been drawn from this study:

1. Simulation of voltage regulation techniques has shown that either analog or digital methods can meet the regulation requirements of MIL-STD-704B. While the only digital method that actually fell within the specification during simulation was the NAVAIR bang-bang technique, the other digital techniques showed the flexibility of a computer based regulator. The simulations lead to the conclusions that the techniques can be optimized to meet the voltage regulation specification.
2. Digital techniques have the advantage over analog techniques. This is mainly due to the minimization of heat generation.
3. The best design method for meeting the diagnostic and monitoring goals is one based on standard microcomputers.
4. A microcomputer can perform all of the control tasks: regulation, diagnostic and monitoring.



## 6. RECOMMENDATIONS

The following recommendations are suggested as a result of this study:

1. The design of the AC-PAU controller should be based on a microcomputer system.
2. Saturating control should be the general technique of regulation.
3. The next phase of the program should be optimization of regulator design and the hardware implementation of the controller.

# I

생물

COMPUTED BY J. STONE	DATE 2/11/76	PAGE
CHECKED BY	DATE	
TITLE AC-APU		PROJECT C4258-06

## LIST OF SYMBOLS

$T_D$  = DIESEL ENGINE DEVELOPED TORQUE

$J_D$  = DIESEL ENGINE INERTIA

$\Theta_D$  = DIESEL ENGINE SHAFT POSITION

$K_S$  = SHAFT SPRING RATE

$J_G$  = GENERATOR INERTIA

$\Theta_G$  = GENERATOR SHAFT POSITION

$K_T$  = GENERATOR TORQUE CONSTANT

$\phi$  = GENERATOR FIELD FLUX

$I_L$  = LOAD CURRENT

$K_D$  = FRICTION DAMPING ON ROTATING SHAFT

$S$  = LAPLACE TRANSFORM ( $d/dt$ )

$L_S$  = STATOR } SYNCHRONOUS REACTANCE  
 $R_S$  = STATOR }

$L_L$  = LOAD INDUCTANCE

$R_L$  = LOAD RESISTANCE

$K_e$  = GENERATOR CONSTANT

$E_G$  = GENERATED VOLTAGE

$E_L$  = LINE VOLTAGE

$K_f$  = GENERATOR FIELD GAIN CONSTANT

$L_f$  = " " " " INDUCTANCE

$R_f$  = " " " " RESISTANCE

COMPUTED BY <b>J. STONE</b>	DATE
CHECKED BY	DATE

NAEC-92-139
PAGE
PROJECT <b>C4258-06</b>

TITLE <b>AC APU</b>
------------------------

$L_{ex}$  = EXCITER INDUCTANCE  
 $R_{ex}$  = " RESISTANCE  
 $R_s$  = SPEED REGULATOR SOLENOID RESISTANCE  
 $L_s$  = " " " INDUCTANCE  
 $X_T$  = " " THROTTLE POSITION  
 $K_{sr}$  = " " " RETURN SPRING  
 $J_T$  = " " " INERTIA  
 $K_D$  = " " " DAMPING  
 $K_i$  = GAIN TRANSFER OF  $T_D/X_T$

COMPUTED BY J. STONIS	DATE	PAGE
CHECKED BY	DATE	PROJECT
TITLE		

## DEVELOPMENT OF EQUATIONS

$$1) T = (J_D s^2 + K_D s) \theta_D = (\theta_D - \theta_G) K_S = (J_G s^2 + K_T I \phi s) \theta_G$$

$$K_S \theta_D = (J_G s^2 + K_T I \phi s) \theta_G + K_S \theta_G$$

$$2) \theta_D = \left[ \left( \frac{J_G}{K_S} s^2 + \frac{K_T I \phi}{K_S} s \right) + 1 \right] \theta_G$$

SUBSTITUTING IN 1)

$$3) T = (J_D s^2 + K_D s) \left[ \left( \frac{J_G}{K_S} s^2 + \frac{K_T I \phi}{K_S} s \right) + 1 \right] \theta_G$$

$$4) \frac{s \theta_G}{T} = \frac{1}{K_D \left( \frac{J_D}{K_D} s + 1 \right) \left[ \frac{J_G}{K_S} s^2 + \frac{K_T I \phi}{K_S} s + 1 \right]}$$

SINCE  $I$  &  $\phi$  WILL BE VARIABLES


WE MUST BRING THESE OUT.

$$5) T - J_G s^2 \theta_G = K_T I \phi s \theta_G$$

THIS IS BASIC AND DOES NOT INCLUDE DEFL. CHARACTERISTICS.

COMPUTED BY J. STONE	DATE		NAEC-92-139
CHECKED BY	DATE		PAGE
TITLE		PROJECT	

THIS CAN BE IN A FEEDBACK FORM



CHECKING THE LOOP WE HAVE

$$6) \quad \frac{S \theta_G}{T} = \frac{\frac{1}{K_T I \phi}}{1 + \frac{1}{K_T I \phi} (J_G S)} = \frac{1}{K_T I \phi + J_G S}$$

$$7) \quad \frac{S \theta_G}{T} = \frac{1}{K_T I \phi \left( \frac{J_G}{K_T I \phi} S + 1 \right)}$$

EXPANDING WE FIND

$$T = J_G S^2 \theta_G + K_T I \phi S \theta_G$$

THIS CHECKS WITH 5)

ALL DIGITAL CHARACTERISTICS MUST BE INCLUDED.

AD-A085 990


NAVAL AIR ENGINEERING CENTER LAKEHURST NJ GROUND SUPP--ETC F/6 10/2  
APPLICATION OF A MICROCOMPUTER TO A MOBILE ELECTRIC POWER PLANT--ETC(U)  
MAY 80 R F O'DONNELL  
NAEC-92-139

UNCLASSIFIED


NL

2 of 4

AD-A085 990



08599



MICROCOPY RESOLUTION TEST CHART  
NBS 1963-A



COMPUTED BY <b>J. STONE</b>	DATE		PAGE
CHECKED BY	DATE		PROJECT
TITLE			

8) FROM 1)

$$T = (J_D S^2 + K_D S) \Theta_D = (\Theta_D - \Theta_G) K_S$$

$$J_D S^2 \Theta_D + K_D S \Theta_D = K_S \Theta_D - K_S \Theta_G$$

EXPANDING 3)

$$9) \frac{T}{\Theta_G} = \frac{J_D J_G}{K_S} S^4 + \frac{J_D K_T I \phi}{K_S} S^3 + J_D S^2 + \frac{J_G K_D}{K_S} S + \frac{K_D K_T I \phi^2}{K_S} S + K_D S$$


$$\frac{T}{S \Theta_G} = \frac{J_D J_G}{K_S} S^3 + \frac{J_G K_D}{K_S} S^2 + J_D S + K_D + K_T I \phi S \left[ \frac{J_D}{K_S} S + \frac{K_D}{K_S} \right]$$

$$10) \frac{T}{S \Theta_G} = K_D \left[ \frac{J_D J_G}{K_D K_S} S^3 + \frac{J_G}{K_S} S^2 + \frac{J_D}{K_D} S + 1 \right] + \frac{K_D K_T I \phi}{K_S} S \left[ \frac{J_D}{K_D} S + 1 \right]$$

$$11) T - K_D \left[ \frac{J_D J_G}{K_D K_S} S^3 + \frac{J_G}{K_S} S^2 + \frac{J_D}{K_D} S + 1 \right] S \Theta_G = \frac{K_D K_T I \phi}{K_S} S \left[ \frac{J_D}{K_D} S + 1 \right] S \Theta_G$$

IN FEED BACK FORM THIS IS:-

COMPUTED BY J. STONE	DATE		PAGE
CHECKED BY	DATE		PROJECT
TITLE			



CHECKING THE LOOP WE HAVE :-

$$12) \quad \frac{S\theta_G}{T} = \frac{\frac{K_s}{S(K_T I\phi)(J_D S + K_D)}}{1 + \frac{K_s}{S(K_T I\phi)(J_D S + K_D)} \left( \frac{J_D J_G}{K_s} S^3 + \frac{J_G K_D}{K_s} S^2 + J_D S + K_D \right)}$$

$$13) \quad \frac{S\theta_G}{T} = \frac{K_s}{S K_T I\phi (J_D S + K_D) + \left[ \frac{J_D J_G}{K_s} S^3 + \frac{J_G K_D}{K_s} S^2 + K_s J_D S + K_s K_D \right]}$$

$$14) \quad \frac{S\theta_G}{T} = \frac{1}{\left[ \frac{J_D J_G}{K_s} S^3 + \left( \frac{J_D K_T I\phi + J_G K_D}{K_s} \right) S^2 + \left( \frac{K_T I\phi K_D}{K_s} + J_D \right) S + K_D \right]}$$

COMPUTED BY J. STONE	DATE		PAGE
CHECKED BY	DATE		PROJECT
TITLE			


THIS REDUCES TO

$$15) \frac{T}{s\phi} = \frac{J_D J_G}{K_S} s^3 + \frac{J_G K_b}{K_S} s^2 + J_D s + \frac{J_D K_T I \phi}{K_S} s^2 + \frac{K_b K_T I \phi}{K_S} s + K_b$$

$$16) \frac{T}{s\phi} = K_D \left[ \frac{J_D J_G}{K_D K_S} s^3 + \frac{J_G}{K_S} s^2 + \frac{J_D}{K_D} s + 1 \right] + K_T I \phi \left[ \frac{J_D}{K_S} s^2 + \frac{K_b}{K_S} s \right]$$


THIS CHECKS WITH 10)

17) THE TRANSFER CHARACTERISTIC OF THE ALTERNATOR FIELD IS



$$T_f = \frac{L_f}{R_f}$$

18) THE TRANSFER CHARACTERISTIC OF THE EXCITER IS



$$T_{ex} = \frac{L_{ex}}{R_{ex}}$$

COMPUTED BY J. STONE	DATE		HAEC-92-139
CHECKED BY	DATE		PAGE
TITLE			PROJECT

19) THE ALTERNATOR INHERENT REGULATION IS EXPRESSED AS:-

$$E_L = E_G - I_L R_s$$

20)  $I_L = \frac{E_L}{R_L}$

21)  $\frac{E_L}{E_G} = \frac{R_L}{R_L + R_s}$

22)  $\frac{I_L}{E_G} = \frac{1}{R_s \left( \frac{L_s}{R_s} s + 1 \right)}$

COMPUTED BY J. STONE	DATE 6/7/76	PAGE
CHECKED BY	DATE	PROJECT C4258-06
TITLE DETERMINATION OF CONSTANTS FOR AC-APU		

1860 LB IN.

 $T_{D1}$  = DIESEL ENGINE DEVELOPED TORQUE

930 LB IN.

 $T_{D2}$  = DIESEL ENGINE TORQUE DUE TO COMPRESSION12.763 LB-IN-SEC<sup>2</sup> $J_D$  = DIESEL ENGINE INERTIA $\theta_D$  = DIESEL ENGINE SHAFT POSITION $82.14 \times 10^6$  LB-IN/RAD $K_S$  = SHAFT SPRING RATE12.37 LB-IN-SEC<sup>2</sup> $J_G$  = GENERATOR INERTIA $\theta_G$  = GENERATOR SHAFT POSITION $1.572 \times 10^3$  LB-IN/A/LINE/KT = GENERATOR TORQUE CONSTANT $10.95 \times 10^3$  LINES/IN<sup>2</sup>  $\Phi$  = GENERATOR FIELD FLUX

83.27 A

 $I_A$  = FULL LOAD CURRENT

.1369 LB-IN-SEC

 $K_D$  = FRICTION DAMPING ON ROTATING SHAFT $S$  = LAPLACE TRANSFORM (d/dt) $L_s$   
 $R_s$ 

} EFFECTIVE GENERATOR IMPEDANCE

 $L_L$   
 $R_L$ 

} LOAD IMPEDANCE

 $.091 \times 10^{-3}$  V/rad/sec/line/in<sup>2</sup> $K_e$  = GENERATOR CONSTANT

208V

 $E_G$  = GENERATED VOLTAGE $E_L$  = LOAD VOLTAGE385.84 line/in<sup>2</sup>/VOLT $K_f$  = GENERATOR FIELD GAIN CONSTANT

.2295 H

 $L_f$  = GENERATOR FIELD INDUCTANCE1.72  $\Omega$  $R_f$  = GENERATOR FIELD RESISTANCE

COMPUTED BY J. STONE	DATE		PAGE
CHECKED BY	DATE		PROJECT C4258-06
TITLE			

 $.46 H$  $L_{ex} = \text{EXCITER INDUCTANCE}$  $2.4 \Omega$  $R_{ex} = \text{RESISTANCE}$  $3.46 V/V$  $K_{ex} = \text{VOLTAGE GAIN}$

COMPUTED BY J. STONE	DATE 6/7/76		PAGE
CHECKED BY	DATE		PROJECT C4258-00
TITLE			

# 1) DIESEL ENGINE

HERCULES D-298-ER (76 HP)

RATED FOR 219 LB-FT. @ 2000 rpm.

BSFC = .392 LB/BHP HR

#/HR = .392 x 83.5 = 32.73 LB/HR.

THE ENGINE LOAD IS DETERMINED BY -

30 KW 1.00 P.F. 88.5% EFF

SHAFT LOAD =  $\frac{30}{1 \times .885} = 33.9 \text{ KW}$ ,  $\frac{33.9}{.746} = 45.44 \text{ HP}$

$T_G = \frac{45.44 \times 550 \text{ FT-LB/SEC}}{209.3 \text{ RAD/SEC}} = 119.41 \text{ LB-FT.}$

F&W LOSSES [PAGE G-03, (183)] = 596.1 W

TOTAL LOSSES [PAGE G-03, (247)] = 3871 W

% F&W LOSSES  $\frac{596.1 \times 100}{30000} = 1.99\% = 2.376 \text{ LB-FT.}$

FOR THE INITIAL RUNS THE TORQUE  
LIMIT WAS SET FOR 130% OF 119.41  
OR 155 LB-FT X 1860 LB-IN.

COMPUTED BY J. STONE		DATE 6/7/76	PAGE
CHECKED BY		DATE	
TITLE			PROJECT C4258-06

THE DECELERATION TORQUE IS DEVELOPED FROM THE KNOWN COMPRESSION RATIO OF THE ENGINE.

FOR THE WHITE ENGINE #DX-1678

COMPRESSION RATIO = 17.5:1


AIR INTAKE = 14.5 PSI

INCREASE IS  $(17.5)(14.5) - 14.5 = 239.5$  PSI

STROKE = 4.5"  $r = 2.25$ "

BORE = 3.75"  $A = \frac{\pi D^2}{4} = .785(14.05) = 11.02 \text{ in}^2$

$T_D @ 2000 \text{ rpm} = 154 \times 12 = 1850 \text{ LB IN.}$



$$\frac{P_c}{P} = \frac{h_0 - r(1 - \cos \theta)}{h_0}$$



COMPUTED BY J. STONE	DATE 6/7/66		PAGE
CHECKED BY	DATE		PROJECT C4258-06
TITLE			

$$T_{D_2} = F r \sin \theta$$

$$F = \left[ \frac{P_1}{P_0} (147) - 147 \right] A$$

$$F = 162 \left[ \frac{P_1}{P_0} - 1 \right]$$

$$\therefore T_{D_2} = 364.5 \left[ \frac{P_1}{P_0} - 1 \right] \sin \theta$$

$\theta$	$\frac{P_1}{P_0}$	F	$T_D$
0°	1.0	0	0
30°	1.068	11	12.4 LB IN
60°	1.308	49.9	97.3
90°	1.99	160	360
120°	3.3	372	725
150°	8.25	1338	1505
180°	17.1	2610	0

USING AN AVERAGE VALUE WE  
HAVE  $.636 \times 1505 = 957$  LB IN

FOR SIMULATION USE A RATIO OF 2:1  
FOR DEVELOPED TORQUE TO COMPRESSOR TORQUE

COMPUTED BY J. STONER	DATE 6/1/64		PAGE
CHECKED BY	DATE		PROJECT C425806
TITLE			

DIESEL ENGINE INERTIA ( $J_D$ )  
HERCULES MODEL D-298-ER

MASSSES: -

$$.036 + .235 + .143 + .21 + .21 + .143 + .236 + 11.76$$

$$\text{TOTAL} = 12.763 \text{ LB. IN. SEC}^2$$

SHAFT SPRING RATE ( $K_S$ )

$$K_S = 82.94 \times 10^6 \text{ LB IN/RAD.}$$

GENERATOR INERTIA ( $J_G$ )

30 KW 400 HZ

MASSSES: -

$$12.03 + .34$$

$$\text{TOTAL} = 12.37 \text{ LB. IN SEC}^2$$

2) GENERATOR TORQUE CONSTANT ( $K_T$ )

$$K_T = \frac{T_G}{I_p \phi} = \frac{119.41}{83.27 (10.95 \times 10^3)} = .131 \times 10^{-3} \frac{\text{LB IN}}{\text{A/FLUX}}$$

$$K_T = 1.572 \times 10^{-3} \text{ LB IN/A/LINE OF FLUX}$$

COMPUTED BY J. STONE	DATE 6/7/76		PAGE
CHECKED BY	DATE		PROJECT C4258-06
TITLE			

3) FRICTION DAMPING ON ROTATING SHAFT  
F+W LOSSES (SEE PAGE 2)

$$F+W = 2.376 \text{ LB FT.}$$

$$K_D = \frac{2.376 \text{ LB FT}}{209.3 \text{ RAD/SEC}} = .0114 \frac{\text{LB FT SEC}}{\text{RAD}}$$

$$K_D = .1369 \frac{\text{LB IN SEC}}{\text{RAD}}$$

4) GENERATOR CONSTANT ( $K_e$ )

$$E_G = 208 \text{ VOLTS}$$

$$SOG = \frac{2000 \text{ rev}}{\text{min}} \times \frac{\text{min}}{60 \text{ sec}} \times \frac{2\pi \text{ rad}}{\text{rev}} = 209.3 \text{ rad/sec}$$

$$K_e = \frac{E_G}{SOG \phi} = \frac{208}{(209.3)(10.95 \times 10^3)}$$

$$K_e = .091 \times 10^{-3} \text{ V/rad/sec/line/in}^2$$

COMPUTED BY J. STONER	DATE 6/7/76		PAGE
CHECKED BY	DATE		PROJECT C4258-16
TITLE			

# 5) GENERATOR FIELD CONSTANT, ( $K_f$ )

$$K_f = \frac{\Phi}{E_f}$$

FROM FIELD SATURATION CURVE

$$E_a = 416V$$


$$I_f = 16.5A$$

$$R_f = 1.72 \Omega$$

$$E_f = 16.5 \times 1.72 = 28.38 V$$

$$\therefore K_f = \frac{10.95 \times 10^3}{28.38} = 385.84 \text{ lines/in}^2/\text{Volt}$$

GENERATOR SATURATION



COMPUTED BY J. STONE	DATE 6/7/76		PAGE
CHECKED BY	DATE		PROJECT C4258-06
TITLE			

SIMULATION OF SATURATION BY  
2 BREAKS. (FROM GEN. CURVE 37.5KVA 400HZ)

1ST SLOPE

$$\frac{478}{405} \times 386 = \underline{456} \text{ LINES/IN}^2/\text{V}$$

BREAK @ 330V

$$\phi = \frac{330}{416} \times 10.95 \times 10^3 = 8.7 \times 10^3 \text{ LINES/IN}^2$$

2nd SLOPE

$$\left( \text{FOR } 386 \text{ LINES/IN}^2/\text{V} = \frac{192}{8 \times 1.72} = 14.32 \text{ V/V} \right)$$

$$\frac{122}{8 \times 1.72} = 8.86 \text{ V/V}$$

$$\frac{8.86}{14.32} \times 386 = \underline{239} \text{ LINES/IN}^2/\text{V}$$

BREAK @ 455V

$$\phi = \frac{455}{416} \times 10.95 \times 10^3 = 12 \times 10^3 \text{ LINES/IN}^2$$

3rd SLOPE


$$\frac{87}{16 \times 1.72} = 3.16 \text{ V/V}$$

$$\frac{3.16}{14.32} \times 386 = \underline{85.2} \text{ LINES/IN}^2/\text{V}$$

COMPUTED BY J. STANLEY	DATE 6/1/78		PAGE
CHECKED BY	DATE		PROJECT C4258-06
TITLE			

## 6) GOVERNOR FOR DIESEL ENGINE

ELECTRICAL INPUT TO GOVERNOR  
WILL CAUSE THROTTLE VALVE  
TO MOVE A DESIRED AMOUNT.



TRANSFER CHAR. OF SOLENOID

$$F_s = NI = J s^2 x_T + K_D x_T + K_S x_T$$

$$E = I (R_s + s L_s)$$

$$\frac{I}{E} = \frac{1}{R_s \left( \frac{L_s}{R_s} s + 1 \right)}$$

$$\frac{NI}{E} = \frac{N}{R_s \left( \frac{L_s}{R_s} s + 1 \right)} = \frac{F_s}{E}$$

$$\therefore \frac{x_T}{NI} = \frac{1}{K_s \left( \frac{J}{K_s} s^2 + \frac{K_D}{K_s} s + 1 \right)}$$

COMPUTED BY J. STONE	DATE 6/7/76	PAGE
CHECKED BY	DATE	PROJECT C 4258-06
TITLE		

## ENGINE TORQUE

$$T_D = PA$$

$$Q = A(SX_P)$$

$$\frac{Q}{A} = SX_P$$

$$SX_P = KSO_D$$

$$A = \frac{Q}{KSO_D}$$

$$\therefore T_D = P\left(\frac{Q}{KSO_D}\right)$$

FROM INFORMATION ON WHITE DIESEL  
ENGINE MODEL D-2300 WE FIND  
A RELATION OF TORQUE VS LBS. OF  
FUEL / HR AT SPECIFIC SHAFT SPEEDS.  
FOR OUR SIMULATION WE WILL USE  
A CONSTANT. THE ACTUAL RELATION IS:-

$$\text{SINCE } Q = K_T X_T$$

$$T_D = \frac{P}{K} \left( \frac{K_T X_T}{SO_D} \right)$$

$$\frac{T_D}{X_T} = \frac{K'}{SO_D}$$

COMPUTED BY J. STONE	DATE 6/7/76		PAGE
CHECKED BY	DATE		PROJECT C4256-06
TITLE			

FROM LUCAS (MARCH 10, 1976)  
ARTICLE OF GOVERNING OF OIL  
ENGINES PAGE 23, THE CONTROL  
ROD OPENING VARIES FROM  
2-8 mm.

FOR FULL OPEN THROTTLE WE  
WILL USE

$$X_T = \frac{.8 \text{ cm}}{2.54 \text{ cm}} \text{ in} = .315 \text{ in.}$$

THE ENGINE CONSTANT ( $K_1$ )  
WILL BE EXPRESSED AS.

$$K_1 = \frac{T_D}{X_T} = \frac{119.41}{.315} \left( \frac{12 \text{ in}}{\text{ft}} \right)$$

$$K_1 = 4550 \frac{\text{LB. IN.}}{\text{IN.}}$$

ASSUME A COIL POWER LEVEL = 30W

$$I = \frac{30 \text{ W}}{28 \text{ V}} = 1.07 \text{ A}$$

$$R_s = \frac{28}{1.07} = 26.13 \Omega$$



NAEC-92-139

COMPUTED BY J. STONE	DATE 6/1/76		PAGE
CHECKED BY	DATE		PROJECT C-4258-06
TITLE			


ALSO ASSUME A TIME CONSTANT  
OF  $\tau = .015$

$$\tau = \frac{L_s}{R_s} = .015 = \frac{L_s}{26.13}$$

$$L_s = .392 \text{ H}$$

COMPUTED BY	DATE		PAGE
CHECKED BY	DATE		PROJECT
TITLE			


# SIMULATION OF ALTERNATOR FIELD SATURATION



NAEC-92-139

COMPUTED BY <b>J. STONE</b>	DATE		PAGE
CHECKED BY	DATE		PROJECT <b>C4258-06</b>
TITLE			

EFFECT OF TORQUE LIMIT  
ON SIMULATION OF  
DIESEL ENGINE  
START UP AND SHUT DOWN

 $T_D$  $\frac{SOG}{100}$

COMPUTERIZED LITERATURE SEARCHES  
ON THE SUBJECT OF REGULATION DESIGN

NARC-92-139

User 244 Date:03/25/76 Time:06:00:44 File: 8

Set Items Description

1	878	ELECTRIC MACHINERY
2	560	ELECTRIC GENERATORS
3	11	ELECTRIC MOTOR GENERATOR SETS
4	1417	1-3/OR
5	2932	CONTROL SYSTEMS
6	0	BANG BANG
7	15083	DIGITAL
8	419	PREDICTIVE
9	3416	PROPORTIONAL
10	0	SAMPLED DATA
11	18699	7-10/OR
12	1	4 AND 5 AND 11
13	8	4 AND 5
14	21	COMPUTER SYSTEMS
15	0	4 AND 14
16	741	COMPUTER SYSTEMS, DIGITAL
17	0	4 AND 16

Print 13/5/1-8

Search Time: 15.42 Pts.: 8 Descs.: 9

ID NO.- EI750850836 550836

SELECTION OF OPTIMAL PARAMETERS FOR AN AUTOMATIC GENERATION CONTROL SYSTEM.

Ramanamurti, M.; Kibe, A. V.

Indian Inst of Technol, Kanpur

DESCRIPTORS- \*CONTROL SYSTEMS, ELECTRIC GENERATORS, (MATHEMATICAL TECHNIQUES, Linearization),

CARD ALERT- 731, 705, 921

CODEN- JEELAC SOURCE- J Inst Eng (India) Electr Eng Div v 55 pt EL 3 Feb 1975 p 129-133

The system provides proper input signals to each area controller to minimize the deviations in frequency and tie line power due to any sudden disturbance in the system by loss of generation or load variation. Concept of minimum settling time to obtain optimum gains for the controller inputs is used. The system sensitivity for different parameters is also investigated. 4 refs.

ID NO.- EI750637327 537327

THYRISTOR PULSE-FREQUENCY CONTROL SYSTEMS FOR ELECTRICAL MACHINES.

Lifanov, S. V.; Morgovskiy, Yu. Ya.

DESCRIPTORS- (\*ELECTRIC MACHINERY, \*Control Systems), PULSE TIME MODULATION,

CARD ALERT- 705, 716, 731

CODEN- SAUCRZ SOURCE- Sov Autom Control v 7 n 5 Sep-Oct 1974 p 62-66

Discussed are pulse-frequency control systems for electrical machines, using thyristor pulse shapers, intended for speed regulation of dc motors and control of synchronous generator voltages. It is shown that by using pulse-frequency modulation instead of pulsewidth modulation, it is possible to reduce the commutation losses and simplify the instrumentation. The problem of determining the parameters of a modulator that minimizes the commutation losses is examined. 8 refs.

ID NO.- EI750208798 508798

OR USTROICHIVOSTI KOMBINIROVANNYKH SISTEM AVTOMATICHESKOGO REGULIROVANIYA ELEKTRICHESKIKH MASHIN. \$left bracket\$ Stability of Combined Control Systems of Electric Machines \$right bracket\$ .

Iekakh, M. N.

DESCRIPTORS- (\*ELECTRIC MACHINERY, \*Control Systems), (CONTROL SYSTEMS, Invariance), SYSTEM STABILITY,

CARD ALERT- 705, 731

CODEN- ELKTAQ SOURCE- Elektrotehnika n 11 Nov 1974 p 39-43

It is shown that automatic control by dependent disturbances in the class of systems designed in accordance with the combined principle of control results in a change in the characteristic equation and, consequently, in the dynamic properties of the system. In Russian.

ID NO.- EI741169341 469341

USTROISTVO DLYA KONTROL'YA SOSTOYANIYA SISTEMY NEPOSREDSTVENNOGO VODYANOGO OKHLAZHDENIYA OBROTNI STATORA SINKHRONNYKH GENERATOROV. \$left bracket\$ Device for Controlling the State of the System of Direct Cooling by Water of the Synchronous Generator Stator Winding \$right bracket\$ .

Vainshtein, R. A.; Getmanov, V. T.; Chikunov, A. G.

Tomsk Polytech Inst in. S. M. Kirov, USSR

DESCRIPTORS- (\*ELECTRIC GENERATORS, \*Protection), (ELECTRIC MACHINERY, Cooling), CONTROL SYSTEMS,

CARD ALERT- 701, 705, 731

CODEN- IVZEAY SOURCE- Izv Vyssh Uchebn Zaved, Energ n 7 Jul 1974 p 9-12

The necessity for and the usefulness of technical development of devices permitting control of the state of the system of cooling of stator windings of synchronous generators, with direct cooling by water, is demonstrated. Problems of development of a device of this kind utilizing electric values with the frequency of 25 Hz are set forth. This device is to be introduced into the primary circuit of the generator to implement failure-proof protection against short-circuiting to the ground. In Russian.

ID NO.- EI741061916 461916

O KLASSIFIKATSII ELEKTRICHESKIH MASHIN DLYA SISTEM AVTOMATICHESKOGO UPRAVLENIYA. \$left bracket\$ Classification of Electric Machines for Automatic Control Systems \$right bracket\$ .

Batovrin, A. A.; Titov, N. P.

DESCRIPTORS- (\*ELECTRIC MACHINERY, \*Control), CONTROL SYSTEMS, (INFORMATION SCIENCE, Classification),

CARD ALERT- 705, 731, 901

CODEN- IVUEA9 SOURCE- Izv Vyssh Uchebn Zaved, Elektromekh n 5 May 1974 p 539-546

Problems of classification of electric machines working in automatic control systems are considered. Division of all machines into power and information machines is proposed. A classification table is given of the main elements of automatic control systems with their transfer and transition functions. Each element is exemplified in the table by one or more types of electric machines. In Russian.

ID NO.- EI740313337 413337

DAS DONAUKRAFTWERK OTTENSCHHEIM-WILHERING. \$left bracket\$ Ottensheim-Wilhering Hydroelectric Power Plant on the Danube \$right bracket\$ .

Anon

DESCRIPTORS- (\*HYDROELECTRIC POWER PLANTS, \*Austria), (HYDRAULIC TURBINES, Tubular), (ELECTRIC GENERATORS, Hydroelectric), (RIVER BASIN PROJECTS, Austria), CONTROL SYSTEMS, ELECTRIC POWER SYSTEMS,

CARD ALERT- 402, 441, 611, 632, 706, 731

CODEN- OBZORC SOURCE- OZE Oesterr Z Elektr v 26 n 10 Oct 1973 p 397-542

The entire issue of the journal is devoted to the new hydroelectric power plant on the Danube in Austria which is to be put into service at the end of 1973. This is the fourth multipurpose project built in Austria, utilizing water resources of the Danube. The total of 25 articles is divided into 6 sections. The first section contains a general article about the turbine types at Austrian hydroelectric power plants and on special problems of the new Kaplan tubular turbine, and an article comparing the present project with its immediate predecessor. The second section (10 articles) deals with general planning and construction work with a detailed article on the project, on the tubular turbine, etc. The third section (7 articles) dealing with mechanical engineering and electrical engineering work describes the turbine unit, turbine controllers, power generation equipment, high voltage equipment, control equipment, etc. The fourth part (2 articles) describes the hydraulic steel structures, such as locks. The fifth part (3 articles) deals with maintenance and management problems. The last part contains the most important factual data about the plant and its construction. In German.

ID NO.- EI740312291 412291

ISSLEDOVANIIE TSIFROVOI SISTEMY AVTOMATICHESKOGO REGULIROVANIYA NAPRYAZHENIYA GENERATORA. \$left bracket\$ Investigation of a Digital System of Automatic Control of Generator Voltage \$right bracket\$ .

Serkov, V. I.; Solov'ev, V. N.

DESCRIPTORS- (\*ELECTRIC GENERATORS, \*Control Systems), (CONTROL, ELECTRIC VARIABLES, Voltage), CONTROL SYSTEMS, DIGITAL,

CARD ALERT- 731, 706, 715, 705, 701

CODEN- IVUEA9 SOURCE- Izv Vyssh Uchebn Zaved, Elektromekh n 9 Sep 1973 p 966-970

A digital controller is proposed for maintaining generator voltage. On the basis of a proposed diagram of stability and quality, constructed in the space of the coefficients of the characteristic equation of a closed system, parameters are selected for the algorithm of a digital computer. Recommendations are given for meeting various technical requirements with respect to the control system of generator voltage. In Russian.



ID NO.- EI730101275 301275

## POWER SYSTEM GENERATOR STABILITY USING STATE SPACE TECHNIQUES.

Webb, A. J.; Sheard, G.

The Electricity Commission of New South Wales, Sydney

DESCRIPTORS- (\*ELECTRIC GENERATORS, \*Control), CONTROL SYSTEMS,

CARD ALERT- 705, 731

CODEN- PRAUA6 SOURCE- Proc Inst Radio Electron Eng, Australia v 33  
n 5 May 1972 p 182-186

The stable operation of the generators in a large electric power system can be substantially improved by using supplementary signals in addition to terminal voltage as feedback information to the generators' automatic excitation regulators. The selection and conditioning of available signals has been investigated by applying linear state space techniques to the generators and their excitation systems and stability and damping assessed by examination of the eigenvalues of the state matrix. 14 refs.

User 244 Date:03/25/76 Time:06:35:09 File:13

Set	Items	Description
1	3	ELECTRIC MACHINERY
2	213	ELECTRIC GENERATORS
3	0	ELECTRIC MOTOR GENERATOR SETS
4	216	3-OR
5	2112	CONTROL SYSTEMS
6	7	BANG BANG
7	21600	DIGITAL
8	235	PREDICTIVE
9	932	PROPORTIONAL
10	26	SAMPLED DATA
11	22690	6-10/OR
12	0	4 AND 5 AND 11
13	2	4 AND 5
14	1	4AND 11
15	261	COMPUTER SYSTEMS
16	0	4AND15
17	0	VOLTAGE
18	6396	SPEED
19	38	RPM
20	6423	17-19/OR
21	12633	VOLTAGE
22	18714	20 OR 21
23	1263	REGULATOR
24	125	GOVERNOR
25	54765	CONTROL
26	55173	23-25/OR
27	857	ENGINE
28	4807	GENERATOR
29	19	ROTATING MACHINERY
30	39	ALTERNATING CURRENT
31	5679	27-30/OR
32	8881	SWITCHING
33	1	PROPORTIONAL BAND
34	8882	32 OR33
35	9810	6 OR 9 OR 34
36	286	22 AND 26 AND 31
37	14	35 AND 36
38	36	22 AND 31 AND 35
39	41580	COMPUTER
40	21600	DIGITAL
41	238	MICROPROCESSOR
42	0	MICRO PROCESSOR
43	1150	MINICOMPUTER
44	1	MICRO(W) PROCESSOR
45	6688	30-44/OR
46	809	31AND45
47	2407	34AND45AND35
48	28	31AND45AND35
49	975	27OR29OR30
50	116	45AND45

859736 C7604562

AN APPLICATION IN ENGINE TESTING  
LOWRES, E.J. ; GEC-ELLIOTT PROCESS AUTOMATION, BOREHAMWOOD,  
ENGLAND

MINICOMPUTER FORUM 585-600 1975

11-13 FEB. 1975 LONDON, ENGLAND

PUBL: ONLINE OXBRIDGE, MIDDX., ENGLAND

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, INTERNAL  
COMBUSTION ENGINES

IDENTIFIERS: ENGINE TESTING, AUTOMATION EQUIPMENT, MINICOMPUTER,  
SOFTWARE PACKAGE CONRAD, INTERNAL COMBUSTION ENGINE TESTING, QUALITY  
CONTROL

SECTION CLASS CODES: C8847

UNIFIED CLASS CODES: WHENAD

THE TESTING OF INTERNAL COMBUSTION ENGINES IN MANY WAYS LENDS ITSELF  
TO AUTOMATION BUT IT HAS BEEN FOUND THAT STANDARD MINI COMPUTER  
:AUTOMATION: PACKAGES FALL SHORT IN THIS APPLICATION. THE PAPER  
DESCRIBES THE BASIC REQUIREMENTS OF THE AUTOMATION EQUIPMENT AND  
ILLUSTRATES THESE BY GIVING AN EXAMPLE OF A TYPICAL TEST PERFORMED ON  
AN ENGINE. THE APPLICATION OF A MINICOMPUTER TO PERFORM THESE  
FUNDAMENTAL REQUIREMENTS HAS LED TO THE DEVELOPMENT OF A SOFTWARE  
PACKAGE CONRAD. IT IS SHOWN HOW CONRAD MEETS THE PRIME REQUIREMENTS,  
PROVIDING THE ENGINEER WITH A FACILITY BY WHICH HE CAN MAKE BASIC  
CHANGES TO THE WAY IN WHICH AN ENGINE IS TESTED WITHOUT RESORTING TO  
USING A PROGRAMMER

859721 B7606229, C7604547

THE MEASUREMENT OF AVERAGE INDICATOR DIAGRAMS BY A MINICOMPUTER  
AIDED DATA ACQUISITION SYSTEM

KONTANI, K. ; MECH. ENGG. LAB., AGENCY OF INDUSTRIAL SCI. AND  
TECHNOL., IGUSA SUGINAMI-KU, TOKYO, JAPAN

J. MECH. ENG. LAB. (JAPAN) VOL.29, NO.3 92-108 MAY 1975  
CODEN: KGKSBL

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, DATA ACQUISITION  
, INTERNAL COMBUSTION ENGINES

IDENTIFIERS: AVERAGE INDICATOR DIAGRAMS, MINICOMPUTER AIDED DATA  
ACQUISITION SYSTEM, CONTINUOUS ENGINE CYCLES, IGNITION TIMING, PRECISE  
MEASUREMENT

SECTION CLASS CODES: C8847, B4270, C7660

UNIFIED CLASS CODES: WHENAD, BECRAX

LANGUAGE: JAPANESE

THE SYSTEM YIELDS A MEAN PRESSURE TRACE FOR A CERTAIN NUMBER OF  
CONTINUOUS ENGINE CYCLES AND, AT THE SAME TIME, RECORDS THE MAXIMUM  
PRESSURE, THE MAXIMUM RATE OF PRESSURE RISE AND THE IGNITION TIMING OF  
EACH CYCLE, THUS ACCOMPLISHING A PRECISE MEASUREMENT OF AN INDICATOR  
DIAGRAM. THE DETAILED DESCRIPTION OF THE METHOD AS WELL AS THE  
DISCUSSION OF THE PROBLEMS ACCOMPANYING THE AVERAGING TREATMENT ARE  
SHOWN (4 REFS)

858815 B7607584, C7603563

DRIVING SIMULATOR FOR FAST TRAINS

CARMINATI, E.

TECNOL. ELETTR. (ITALY) NO.6 72-7 JUNE 1975

DESCRIPTORS: RAILWAYS, SIMULATION, TRAINING, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: FAST TRAINS, ENGINE CONTROLS, SIGNAL VISUALISATION, NOISE SIMULATION, DRIVING SIMULATOR, COMPUTER CONTROL

SECTION CLASS CODES: B5620, B1220, C7872, C7600, C8846

UNIFIED CLASS CODES: TKBAAR, ADCAAP, VHBKAK, VKZAAS, WHEKAS

LANGUAGE: ITALIAN

TRAINING FOR DRIVERS OF TRAINS OF 200 KM/H REQUIRES EXPERIENCE SUPPLEMENTED BY PRACTICE IN A SIMULATOR AS IN THE TRAINING OF AIR-PILOTS. A SIMULATOR MADE BY E. MARRELLI CO. FOR THE ITALIAN RAILWAYS IS DESCRIBED; IT PROVIDES FOR DRIVING IN DAY AND NIGHT CONDITIONS, ENGINE CONTROLS AND SAFETY MATTERS, SIGNAL VISUALISATION AND NOISE SIMULATION, DATA GENERATION, SUPERVISION AND RECORDING OF DRIVER PERFORMANCE. THE SIMULATOR IS CONTROLLED BY A PDP/8/E COMPUTER

858548 C7603265

CONTROL SYSTEM OF THE ANALOGUE-DIGITAL-ANALOGUE TYPE WITH A DIGITAL COMPUTER HAVING MULTIPLE FUNCTIONS FOR AN AUTOMATIC VEHICLE

RIVIERE, J.-P., BERTUOL, B., LEICHLER, C.

PATENT NO.: USA 3906207 ASSIGNEES: REGIE NAT. USINES RENAULT, AUTOMOBILES PEUGEOT FILED: 10 MAY 1973

ORIGINAL PATENT APPL. NO.: FRANCE 72.16823

PRIORITY DATE: 10 MAY 1972

16 SEPT. 1975

DESCRIPTORS: AUTOMOBILES, ENGINES, DIGITAL CONTROL, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, ANALOGUE-DIGITAL CONVERSION, DIGITAL-ANALOGUE CONVERSION

IDENTIFIERS: DIGITAL COMPUTER, MULTIPLE FUNCTIONS, AUTOMATIC VEHICLE, 10 BINARY DIGITS, A/D/A CONTROL SYSTEM, ENGINE CONTROL

SECTION CLASS CODES: C7851, C8846

UNIFIED CLASS CODES: VMKCAD, WHEKAS

ENGINE CONTROL SIGNALS ARE CALCULATED BY A UNIT CAPABLE OF MULTIPLYING AND ADDING TWO NUMBERS OF UP TO 10 BINARY DIGITS AND STORING THE SUM IN A READ-WRITE MEMORY

858408 A7607515, B7606350, C7603100  
 DIGITAL QUARTZ TRANSDUCERS FOR ABSOLUTE PRESSURE MEASUREMENTS  
 PAROS, J.M. ; PAROSCI. INC., REDMOND, WA, USA  
 WASHBURN, B.  
 ; ISA  
 STD BOOK NO.: 0 87664 261 X  
 PROCEEDINGS OF THE 21ST INTERNATIONAL INSTRUMENTATION SYMPOSIUM  
 435-42 1975  
 19-21 MAY 1975 ISA PHILADELPHIA, PA., USA  
 PUBL: ISA PITTSBURGH, PA., USA  
 DESCRIPTORS: PRESSURE TRANSDUCERS, PRESSURE MEASUREMENT  
 IDENTIFIERS: ABSOLUTE PRESSURE MEASUREMENTS, QUARTZ CRYSTAL SENSING  
 ELEMENT, OCEANOGRAPHY, METEOROLOGY, JET ENGINE TESTING, PROPULSION  
 CONTROL SYSTEMS, AIR DATA COMPUTERS, LABORATORY PRESSURE STANDARDS,  
 DIGITAL QUARTZ TRANSDUCERS  
 SECTION CLASS CODES: B4449, C7449, B4250, C7630, A0630  
 UNIFIED CLASS CODES: BKETAH, BECHAA, BGGAAV  
 THE CONSTRUCTION, OPERATION, AND PERFORMANCE OF A SERIES OF ABSOLUTE  
 PRESSURE TRANSDUCERS WHICH EMPLOY A SPECIAL QUARTZ CRYSTAL SENSING  
 ELEMENT ARE DESCRIBED. THE RESONANT FREQUENCY OF THE QUARTZ CRYSTAL  
 VARIES WITH PRESSURE INDUCED STRESS AND THE ULTRA-HIGH VACUUM IN WHICH  
 THE RESONATOR OPERATES IS USED AS THE ABSOLUTE PRESSURE REFERENCE.  
 BECAUSE OF THEIR DIGITAL-TYPE OUTPUT, HIGH ACCURACY, LOW POWER  
 CONSUMPTION, AND INSENSITIVITY TO ENVIRONMENTAL ERRORS, THESE  
 INSTRUMENTS HAVE BEEN USED SUCCESSFULLY IN SUCH DIVERSE FIELDS AS  
 OCEANOGRAPHY, METEOROLOGY, JET ENGINE TESTING PROPULSION CONTROL  
 SYSTEMS, AIR DATA COMPUTERS, AND LABORATORY PRESSURE STANDARDS (3  
 REFS)

847735 C7602019  
 DIGITAL COMPUTING TECHNIQUES IN THE MANUFACTURE AND OPERATION OF  
 ENGINE MANAGEMENT SYSTEMS  
 DAVIES, R.J. ; LUCAS AEROSPACE LTD., SOLIHULL, ENGLAND  
 AERONAUT. J. (GB) VOL.79, NO.776 349-53 AUG. 1975 CODEN:  
 AENJAK  
 DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE ENGINES,  
 AUTOMATIC TESTING, MANUFACTURING ADMINISTRATIVE DATA PROCESSING  
 IDENTIFIERS: ENGINE MANAGEMENT SYSTEMS, DIGITAL TECHNIQUES, ENGINE  
 CONTROL, STORE INFORMATION, SELF TEST PROGRAMMES, INTERNAL FAULT  
 DIAGNOSIS  
 SECTION CLASS CODES: C8849, C7875, C8670  
 UNIFIED CLASS CODES: WHEZAN, VHRMAY, WKKAAN  
 INTRODUCES THE DIGITAL TECHNIQUES IN ENGINE CONTROL LEADING TO MANY  
 ADVANTAGES. THE ABILITY OF DIGITAL SYSTEMS TO STORE INFORMATION MEANS  
 THAT CALIBRATION AND TEST PROGRAMMES CAN BE PERFORMED USING  
 INFORMATION DERIVED FROM THE EARLY STAGES OF PRODUCTION. WIDE RANGING  
 SELF TEST PROGRAMMES CAN ALSO BE INCLUDED, AS CAN DIAGNOSIS OF  
 INTERNAL FAULTS

847731 C7602015

COMPUTER AIDED DESIGN OF THE EXHAUST OF A TURBOCHARGED DIESEL ENGINE  
LEDGER, J.D. ; INST. OF SCI. AND TECHNOL., UNIV. OF MANCHESTER,  
MANCHESTER, ENGLAND

STD BOOK NO.: 0 903796 06 6

INTERACTIVE SYSTEMS 171-81 1975

SEPT. 1975 LONDON, ENGLAND

PUBL: ONLINE UXBRIDGE, MIDDX., ENGLAND

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, MECHANICAL ENGINEERING,  
COMPUTER-AIDED DESIGN

IDENTIFIERS: TURBOCHARGED DIESEL ENGINE, COMPRESSIBLE GAS FLOWS,  
EXHAUST PIPE, DISPLAY FACILITIES, BOUNDARY CONDITIONS, DESIGN  
FACILITIES, FINAL PROGRAM SUITE, CHANGES IN ENGINE, TURBOCHARGER  
PARAMETERS, FLOW EQUATIONS, MULTI PIPE EXHAUST SYSTEMS, CAD

SECTION CLASS CODES: C8847

UNIFIED CLASS CODES: WHENAD

DEVELOPMENT OF A DESIGN SUITE FOR STUDYING THE UNSTEADY,  
COMPRESSIBLE GAS FLOWS IN THE EXHAUST PIPE OF A TURBOCHARGED DIESEL  
ENGINE IS DISCUSSED. INTERACTION AND DISPLAY FACILITIES WHICH COULD  
GREATLY ASSIST THE ENGINE DESIGNER ARE INCORPORATED. FOLLOWING A  
REVIEW OF THE METHOD OF SOLUTION EMPLOYED AND THE BOUNDARY CONDITIONS  
RELEVANT TO THIS APPLICATION, DETAILS OF THE INTERACTION AND DESIGN  
FACILITIES AND THE STRUCTURE OF THE FINAL PROGRAM SUITE ARE PRESENTED.  
EXAMPLES OF THE USE OF THE SUITE FOR STUDYING CHANGES IN ENGINE,  
EXHAUST PIPE AND TURBOCHARGER PARAMETERS ARE GIVEN FOR TWO ENGINES. AN  
EXTENSION TO THE DESIGN SUITE IS BRIEFLY DISCUSSED IN WHICH AN  
ALTERNATIVE METHOD OF SOLUTION OF THE FLOW EQUATIONS IS INCORPORATED  
AS AN ADDITIONAL MODULE. FINALLY, RECOMMENDATIONS ARE MADE FOR FURTHER  
EXTENDING THE DESIGN FACILITIES TO ACCOMMODATE COMPLEX MULTI PIPE  
EXHAUST SYSTEMS, AS THE USE OF COMPUTER-AIDED DESIGN TECHNIQUES WOULD  
SHOW EVEN GREATER BENEFIT TO THE ENGINE DESIGNER FOR SUCH SYSTEMS (8  
REFS)

847579 A7600290, C7601842

MULTIELEMENT ANALYSIS VIA COMPUTER-CONTROLLED RAPID-SCAN ATOMIC FLUORESCENCE SPECTROMETER WITH A CONTINUUM SOURCE

JOHNSON, D.J., PLANKEY, P.W., WINEFORDNER, J.D. ; DEPT. OF CHEM., UNIV. OF FLORIDA, GAINESVILLE, FL, USA

ANAL. CHEM. (USA) VOL.47, NO.11 1739-43 SEPT. 1975 CODEN: ANCHAN

DESCRIPTORS: SPECTROCHEMICAL ANALYSIS, SPECTROMETER COMPONENTS AND ACCESSORIES, SPECTROCHEMICAL ANALYSIS, SPECTROSCOPY APPLICATIONS OF COMPUTERS

IDENTIFIERS: CONTINUUM SOURCE, TRACE WEAR METALS, JET ENGINE LUBRICATING OILS, AG, AU, CD, CR, CO, CU, FE, IN, HG, MN, NI, PB, PD, PT, SN, SR, TL, ZN, AL, BE, MO, TI, V, DETECTION LIMITS, COMPUTER CONTROLLED RAPID SCAN SLEWD SCAN ATOMIC FLUORESCENCE SPECTROMETER, MULTIELEMENT ANALYSIS, EIMAC XE ARC EXCITATION SOURCE, ACETYLENE FLAME, DETECTION LIMIT, ANALYTICAL CURVE, JET ENGINE LUBRICATING OIL, AIR FORCE AVERAGE TRACE METAL CONTENT VALUES

SECTION CLASS CODES: A0695, A0693, C8816

UNIFIED CLASS CODES: BGZMGP, BGZGAZ, WHCKAC

A VERSATILE, SIMPLE, RELATIVELY INEXPENSIVE COMPUTER-CONTROLLED, SLEWD-SCAN SPECTROMETER WITH A SINGLE EIMAC XENON ARC EXCITATION SOURCE, AND AN ACETYLENE (AIR OR N/SUB 2/O) FLAME IS DESCRIBED AND USED FOR MULTIELEMENT ANALYSIS OF TRACE WEAR METALS IN JET ENGINE LUBRICATING OILS. ANALYTICAL FIGURES OF MERIT OBTAINED FOR 18 ELEMENTS (AG, AU, CD, CR, CO, CU, FE, IN, HG, MN, NI, PB, PD, PT, SN, SR, TL, ZN) MEASURED WITH A SEPARATED AIR/ACETYLENE FLAME AND THE EIMAC SOURCE AND FOR 5 ELEMENTS (AL, BE, MO, TI, AND V) WITH A SEPARATED N/SUB 2/O/ACETYLENE FLAME AND THE SAME EIMAC SOURCE ARE LISTED. THE DETECTION LIMITS OBTAINED ARE COMPARABLE TO THE BEST VALUES OBTAINED BY FLAME ATOMIC ABSORPTION SPECTROMETRY WITH SINGLE ELEMENT HOLLOW CATHODE LAMPS (7 REFS)

846519 C7600747

SENSING AND INPUT SYSTEM FOR COMPUTER CONTROL OF IC ENGINE

PATENT NO.: UK 1400614 ASSIGNEES: RENAULT AND PEUGEOT FILED:  
13 JUNE 1972

ORIGINAL PATENT APPL. NO.: FRANCE 71.21514

PRIORITY DATE: 14 JUN 1971

16 JULY 1975

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, ANGULAR VELOCITY  
MEASUREMENT, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, ELECTRIC  
SENSING DEVICES, SIGNAL PROCESSINGIDENTIFIERS: COMPUTER CONTROL, INTERNAL COMBUSTION ENGINE, TOOTHED  
RING, FLYWHEEL, PULSE TRAIN, ENGINE SPEED, SENSORS, ANGULAR POSITION,  
CRANKSHAFT, SIGNAL PROCESSING CIRCUITRY

SECTION CLASS CODES: C7851, C8846, C7441, C7442

UNIFIED CLASS CODES: VHKCAD, WHEKAS, BKECAB, BKEEAM

THE SYSTEM IS OPERATIVE WITH AN INTERNAL COMBUSTION ENGINE HAVING A  
TOOTHED RING MOUNTED ON THE FLYWHEEL FOR ENGAGEMENT BY THE PINION OF A  
STARTER MOTOR. A FIRST SENSOR IS RESPONSIVE TO THE PASSAGE OF THE  
TEETH TO PRODUCE A FIRST PULSE TRAIN, HAVING A FREQUENCY RELATED TO  
THE ENGINE SPEED. SECOND AND THIRD SENSORS ARE RESPONSIVE TO COACTING  
ELEMENTS MOUNTED ON THE FLYWHEEL. THESE ELEMENTS ARE DISPOSED IN  
PRE-DETERMINED ANGULAR RELATIONSHIPS WITH THE ENGINE CRANKS ETC. AND  
PRODUCE SIGNALS REPRESENTING THE ANGULAR POSITION OF THE CRANKSHAFT  
ETC. AT GIVEN INSTANTS, THE SIGNALS FROM EACH OF THE SENSORS BEING FED  
INTO SIGNAL PROCESSING CIRCUITRY

835469 B7543875, C7528449

APPARATUS FOR DETERMINING THE GROSS THRUST OF A JET ENGINE

PLETT, E.G.

PATENT NO.: USA 3886790 ASSIGNEES: CONTROL DATA CANADA LTD  
FILED: 18 MARCH 1974

ORIGINAL PATENT APPL. NO.: CANADA 169738

PRIORITY DATE: 27 APR 1973

3 JUNE 1975

DESCRIPTORS: AEROSPACE ENGINES, GAS TURBINES, PRESSURE MEASUREMENT,  
AEROSPACE APPLICATIONS OF COMPUTERSIDENTIFIERS: GROSS THRUST, JET ENGINE, NOZZLE TOTAL PRESSURE,  
DIFFUSER, STATIC PRESSURES, NOZZLE ENTRANCE, COMPUTER

SECTION CLASS CODES: C8849, C7851, B4720

UNIFIED CLASS CODES: WHEZAN, VHKCAD, ZLEAAZ

THE APPARATUS COMPUTES THE NOZZLE TOTAL PRESSURE FROM MEASUREMENTS  
OF THE TOTAL PRESSURE IN THE DIFFUSER AND OF THE STATIC PRESSURES AT  
THE NOZZLE ENTRANCE AND ON THE UPSTREAM SIDE OF THE DIFFUSER



B35458 B7540413, C7528438

COMPUTERIZED DIAGNOSTIC TESTER AT HAND

OHARA, J.P., ASHTON, D.N., KRAHER, L.L. ; DETROIT EDISON CO.,  
DETROIT, MI, USAELECTR. WORLD (USA) VOL.184, NO.3 36-50 1 AUG. 1975 CODEN:  
ELWOA3DESCRIPTORS: AUTOMOBILES, MAINTENANCE ENGINEERING, COMPUTER-AIDED  
ANALYSIS, AUTOMATIC TEST EQUIPMENTIDENTIFIERS: ENGINE, AUTOMOBILES, TRUCKS, MAINTENANCE, COMPUTERISED  
DIAGNOSTIC TESTER

SECTION CLASS CODES: B1263, B5620, C8849

UNIFIED CLASS CODES: ADGDAL, TREEAR, WNRZAN

A NEW, COMPUTER-RUN ENGINE DIAGNOSTIC SYSTEM THAT TELLS WHAT TO FIX, AND HAS THE POTENTIAL TO ELIMINATE COSTLY, TIME-CONSUMING TRIAL-AND-ERROR REPAIRS OF AUTOMOBILES AND TRUCKS, IS CURRENTLY BEING EVALUATED BY CONSOLIDATED EDISON CO. IN A CONCERTED EFFORT TO MINIMIZE FLEET-MAINTENANCE COSTS WHILE OPTIMIZING FUEL USAGE. THE TESTER, DEVELOPED BY HAMILTON TEST SYSTEMS (HTS), A SUBSIDIARY OF UNITED TECHNOLOGIES CORP, AUTOMATICALLY CHECKS ELECTRICAL, EXHAUST EMISSION, AND OTHER ENGINE CONDITIONS, DETERMINES WHAT IS WRONG, AND DECIDES WHAT PARTS HAVE TO BE REPAIRED, ADJUSTED, OR REPLACED. ITS COMPUTER THEN ISSUES A PRINTOUT, WHICH PROVIDES ALL THIS INFORMATION BOTH TO THE MECHANIC AND TO FLEET MANAGEMENT

833711 C7526451

MODELLING ENGINE STATIC STRUCTURES WITH CONICAL SHELL FINITE  
ELEMENTSKIEB, R.P. ; AERONAUTICAL SYSTEMS DIV., WRIGHT-PATTERSON AIR  
FORCE BASE, OH, USA

J. AIRCR. (USA) VOL.12, NO.4 230-3 APRIL 1975 CODEN: JAIKAM

DESCRIPTORS: FINITE ELEMENT ANALYSIS, AEROSPACE ENGINES, MODELLING,  
AEROSPACE APPLICATIONS OF COMPUTERSIDENTIFIERS: ENGINE STATIC STRUCTURES, CONICAL SHELL FINITE ELEMENTS  
, NONSYMMETRIC LOADING, COMPUTER TIME, AZMUTHAL COORDINATE, STRESS,  
NONSYMMETRIC DISPLACEMENT, FOURIER SERIES, STANDARD PLATE MODEL,  
STANDARD BEAM MODEL, MODELLING

SECTION CLASS CODES: C6420, C8849, C8200

UNIFIED CLASS CODES: VCEAAX, WNEZAN, DLTAAB

THE CONICAL SHELL ELEMENT WITH NONSYMMETRIC LOADING AND DISPLACEMENT CAPABILITIES HAS EXCELLENT POSSIBILITIES FOR APPLICATION TO ENGINE STATIC STRUCTURES. THE MAJOR BENEFIT WOULD BE A DRAMATIC REDUCTION IN COMPUTER TIME AS COMPARED WITH A PLATE MODEL, HOWEVER, A SEVERE LIMITATION IS THE INABILITY TO COMBINE THIS ELEMENT WITH ANY OTHER ELEMENT TYPES. A TECHNIQUE IS SHOWN THAT CAN BE USED TO BYPASS THIS ELEMENT COMPATIBILITY PROBLEM. THE INHERENT DIFFICULTY LIES IN THE DEGREE-OF-FREEDOM PECULIARITIES OF THE CONICAL SHELL ELEMENT. THE NONSYMMETRIC MOTION OF THIS ELEMENT IS ACCOMPLISHED BY EXPANDING EACH DEGREE OF FREEDOM IN A FOURIER SERIES WITH RESPECT TO THE AZMUTHAL COORDINATE. THE TECHNIQUE PRESENTED SUMS THIS FOURIER SERIES FOR EACH DEGREE OF FREEDOM AND CONNECTS IT TO THE APPROPRIATE DEGREE OF FREEDOM FOR THE NONSHELL PORTIONS OF THE STRUCTURE BY USING FUNCTIONAL CONSTRAINTS. THE METHODS USED TO MAKE THE ELEMENTS COMPATIBLE AND THE COMPUTER TIME, DISPLACEMENT, AND STRESS COMPARISONS WITH STANDARD PLATE AND BEAM MODELS WILL BE SHOWN (3 REFS)

821950 C7525494

NUMERICALLY-EXPERIMENTAL STUDY ON THE COMBUSTION AND PERFORMANCE OF A SPARK-IGNITION ENGINE. 4 CYCLE ENGINE

HATTA, K., SANO, T. ; INST. OF SPACE AND AERONAUTICAL SCI., UNIV. TOKYO, TOKYO, JAPAN

BULL. INST. SPACE AND AERONAUT. SCI. UNIV. TOKYO A (JAPAN) VOL.10, NO.4A 715-54 OCT. 1974 CODEN: TDOHAD

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, AIR POLLUTION, SIMULATION, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: SPARK IGNITION ENGINE, ATMOSPHERIC POLLUTANT NO, COMBUSTION PROCESS, FLAME PROPAGATION, SIMULATION MODEL, N-OCTANE, NUMERICAL EXPERIMENTAL STUDY, FOUR CYCLE ENGINE, DIGITAL COMPUTER ANALYSIS

SECTION CLASS CODES: C8847

UNIFIED CLASS CODES: WHEHAD

LANGUAGE: JAPANESE

DIGITAL COMPUTER ANALYSIS OF THE PERFORMANCE OF A SPARK IGNITION ENGINE AND THE SUBSEQUENT FORMATION OF THE ATMOSPHERIC POLLUTANT NO PRESENTS A BETTER UNDERSTANDING OF THE COMBUSTION PROCESS BASED ON THE ONE-DIMENSIONAL THEORY OF FLAME PROPAGATION UNDER THE HEAT EXCHANGING BETWEEN WALLS AND GAS IN THE CYLINDER. BECAUSE OF MAJOR INTEREST IN THE COMBUSTION PROCESS FOR THE PRESENTATION OF A NUMERICAL SIMULATION MODEL, THE GAS EXCHANGE PROCESS IS SIMPLY ASSUMED TO BE OF THE IDEALIZED INDICATOR DIAGRAM. AS THE FUEL, N-OCTANE AND AS THE COMPONENTS OF THE BURNED GAS, ELEVEN SPECIES, CO, CO/SUB 2/, H, H/SUB 2/, H/SUB 2/O, N, N/SUB 2/, NO, O, O/SUB 2/ AND OH ARE CONSIDERED TO BE IN CHEMICAL EQUILIBRIUM EXCEPT FOR NO WHOSE FORMATION IS PREDICTED BY ZELDOVICH MECHANISM (4 REFS)

820772 C7524130

CONTROL SYSTEM FOR INTERNAL COMBUSTION ENGINE

PATENT NO.: UK 1395027 ASSIGNERS: CHANTIERS ATLANTIQUES FILED: 12 APRIL 1972

ORIGINAL PATENT APPL. NO.: FRANCE 13341

PRIORITY DATE: 15 APR 1971

21 MAY 1975

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: INTERNAL COMBUSTION ENGINE, CONTROL MEMBERS, CRANKSHAFT, COMPUTER, CONTROL INSTRUCTION, REFERENCE POSITION, ENGINE SPEED, VALVES, FUEL INJECTION PUMPS, ENGINE LOAD, ENGINE TEMPERATURE

SECTION CLASS CODES: C7851, C8846

UNIFIED CLASS CODES: VHKAD, WHEKAS

THE SYSTEM ACTS ON THE MOTIONS OF CONTROL MEMBERS WHOSE DISPLACEMENTS ARE A FUNCTION OF ROTATION OF THE ENGINE CRANKSHAFT. THE CONTROL IS EFFECTED THROUGH A COMPUTER, WITH SIGNALS REPRESENTING CONTROL INSTRUCTION AND THE ANGULAR POSITION OF THE CRANKSHAFT RELATIVE TO A REFERENCE POSITION, AND PREVAILING CONDITIONS IN THE ENGINE. THESE CONDITIONS INCLUDE ENGINE SPEED, LOAD AND ENGINE TEMPERATURE; THE CONTROL SIGNALS FROM THE COMPUTER ACT ON THE INLET AND EXHAUST VALVES AND FUEL INJECTION PUMPS

810343 B7535772, C7522632

GAS EXCHANGE CALCULATIONS: TURBINE AND ENGINE VALVE BOUNDARY CONDITIONS. APPLICATIONS AND CORRELATIONS WITH ENGINE TPST DATA

BULATY, T. ; BBC AKTIENGESSELLSCHAFT BROWN, BOVERI CIE, BADEN, SWITZERLAND

INT. J. MECH. SCI. (GB) VOL.17, NO.5 325-37 MAY 1975 CODEN: IMSCAW

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, BOUNDARY-VALUE PROBLEMS, GAS TURBINES, VALVES

IDENTIFIERS: GAS EXCHANGE CALCULATIONS, ENGINE VALVE, BOUNDARY CONDITIONS, ENGINE TEST DATA, COMPUTER PROGRAMS, THERMODYNAMIC MODEL, TURBOCHARGER TURBINE, MATHEMATICAL REPRESENTATION, TIMING

SECTION CLASS CODES: C8847, B5244, C7851

UNIFIED CLASS CODES: WHEHAD, TEGEAT, VMKCAD

WHEN INVESTIGATING THE COMBINED OPERATION OF INTERNAL COMBUSTION ENGINES AND TURBOCHARGERS, COMPUTER PROGRAMS ARE USED TO CALCULATE THE GAS EXCHANGE PROCESS, FOR WHICH ASSUMPTIONS OF VARYING COMPLEXITY ARE MADE. APART FROM A THERMODYNAMIC MODEL FOR THE CYLINDERS AND PIPING, SUCH PROGRAMS REQUIRE BOUNDARY CONDITIONS FOR THE SYSTEM OF EXHAUST PIPING, I.E. APPROPRIATE DESCRIPTIONS OF THE TURBOCHARGER TURBINE AND THE ENGINE VALVE SYSTEM. THE MATHEMATICAL REPRESENTATION OF THE CHARACTERISTICS OF THE TURBOCHARGER TURBINES AND THE ENGINE VALVES ARE COVERED. GENERAL RULES ARE DERIVED FOR THE CHOICE OF SUITABLE TIMING FOR TURBOCHARGED FOUR-STROKE ENGINES, BASED ON THE COMPUTED OPTIMIZATION OF THE VALVE TIMING, AND BY CORRELATING EXPERIMENTAL RESULTS AND THE CHARACTERISTIC VALUES OF THE VALVES (12 REFS)

785175 C7516497

DIGITAL INTEGRATED CONTROL OF A MACH 2.5 MIXED-COMPRESSION SUPERSONIC INLET AND AN AUGMENTED MIXED-FLOW TURBOPAN ENGINE

BATTERTON, P.G., ARPASI, D.J., BAUMBICK, R.J.

REPORT NO.: NASA-TN-X-3075 ISSUED BY: NASA, CLEVELAND, OHIO, USA OCT. 1974

DESCRIPTORS: AEROSPACE ENGINES, DIGITAL CONTROL, AEROSPACE CONTROL

IDENTIFIERS: MACH 2.5, MIXED COMPRESSION SUPERSONIC INLET, MIXED FLOW TURBOPAN ENGINE, DIGITAL CONTROL, AEROSPACE ENGINES, DIGITAL INTEGRATED CONTROL

SECTION CLASS CODES: C7875

UNIFIED CLASS CODES: VHRMAY

AVAILABILITY: NTIS SPRINGFIELD, VA. 22151, USA

A DIGITALLY IMPLEMENTED INTEGRATED INLET-ENGINE CONTROL SYSTEM WAS DESIGNED AND TESTED ON A MIXED-COMPRESSION, AXISYMMETRIC, MACH 2.5 SUPERSONIC INLET WITH 45 PERCENT INTERNAL SUPERSONIC AREA CONTRACTION AND A TP30-P-3 AUGMENTED TURBOPAN ENGINE. THE CONTROL MATCHED ENGINE AIRFLOW TO AVAILABLE INLET AIRFLOW. BY MONITORING INLET TERMINAL SHOCK POSITION AND OVER-BOARD BYPASS DOOR COMMAND, THE CONTROL ADJUSTED ENGINE SPEED SO THAT IN STEADY STATE, THE SHOCK WOULD BE AT THE DESIRED LOCATION AND THE OVERBOARD BYPASS DOORS WOULD BE CLOSED. DURING ENGINE-INDUCED TRANSIENTS, SUCH AS AUGMENTOR LIGHT-OFF AND CUTOFF, THE INLET OPERATING POINT WAS MOMENTARILY CHANGED TO A MORE SUPERCRITICAL POINT TO MINIMIZE UNSTARTS. THE DIGITAL CONTROL ALSO PROVIDED AUTOMATIC INLET RESTART. A VARIABLE INLET THROAT RURED CONTROL BASED ON THROAT MACH NUMBER, PROVIDED ADDITIONAL INLET STABILITY MARGIN

784536 C7515757

THE DEVELOPMENT OF A COMPUTER MODEL FOR PREDICTION OF THE US TRUCK AND BUS POPULATION, FUEL USAGE, AND AIR POLLUTION CONTRIBUTION  
TINGLEY, D.S., JOHNSON, J.H. ; MICHIGAN TECHNOL. UNIV., USA

VOGT, W.G., HICKLE, H.H.

MODELLING AND SIMULATION, VOL.4 53-8 1973

23-24 APRIL 1973 PITTSBURGH, PA., USA

PUBL: ISA PITTSBURGH, PA., USA

DESCRIPTORS: TRANSPORTATION, ROAD VEHICLES, AIR POLLUTION, SIMULATION

IDENTIFIERS: TRANSPORTATION, SIMULATION, COMPUTER MODEL, TRUCK, BUS POPULATION, FUEL USAGE, AIR POLLUTION CONTRIBUTION, VEHICLE PRODUCTION PROJECTIONS, ENGINE, VEHICLE WEIGHT, 1932 TO THE YEAR 2000, DIESEL, GASOLINE

SECTION CLASS CODES: C6420, C7871

UNIFIED CLASS CODES: VCEAAX, VHRCAZ

USING NEW VEHICLE PRODUCTION PROJECTIONS, THE MODEL COMPUTES TRUCKS IN THE POPULATION BY TYPE OF ENGINE (GASOLINE OR DIESEL), GROSS VEHICLE WEIGHT AND BY AGE. FROM THESE DATA IT CALCULATES THE RESPECTIVE CO, HC, NO/SUB X/, CO/SUB 2/ AND PARTICULATE MATTER EMISSIONS AND THE FUEL USAGE BY VARIOUS VEHICLES. THE MODEL COVERS THE TIME PERIOD FROM 1932 TO THE YEAR 2000. VARIOUS PUBLISHED POPULATION, FUEL USAGE, SCRAPPAGE, AND SALES DATA ARE USED TO VERIFY THE ACCURACY OF THE MODEL. THE MODEL IS DEVELOPED TO THE POINT OF ITS VERIFICATION. CONCLUSIONS ABOUT THE AIR POLLUTION AND FUEL USAGE OF DIESEL AND GASOLINE POWERED TRUCKS ARE DRAWN FROM THE MODEL RESULTS (10 REFS)

772877 C7514820

THE INFLUENCE OF AVIONIC SYSTEM REQUIREMENT ON AIRBORNE COMPUTER DESIGN

SHEPHERD, J.T. ; MARCONI-ELLIOTT AVIONIC SYSTEMS LTD., ROCHESTER, ENGLAND

; AGARD

AGARD CONFERENCE PROCEEDINGS NO.149 ON REAL TIME COMPUTER BASED SYSTEMS 28/1-21 1974

27-31 MAY 1974 AGARD ATHENS, GREECE

PUBL: AGARD NEUILLY SUR SPINE, FRANCE

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, SPECIAL PURPOSE COMPUTERS

IDENTIFIERS: AUTOPILOTS SYSTEMS, AVIONIC SYSTEM REQUIREMENT, AIRBORNE COMPUTER DESIGN, CONSTRAINTS, SYSTEM PERFORMANCE REQUIREMENTS, AIRCRAFT OPERATIONAL ECONOMIC ENVIRONMENT, AIR DATA SYSTEMS, FLIGHT DIRECTOR SYSTEMS, HEAD UP, WEAPON DELIVERY SYSTEMS, NAVIGATION SYSTEMS, CENTRAL MANAGEMENT SYSTEMS, ENGINE CONTROL SYSTEMS

SECTION CLASS CODES: C8849, C9840

UNIFIED CLASS CODES: WHEZAN, XREAAZ

THIS PAPER EXAMINES THE CONSTRAINTS IMPOSED UPON THE AIRBORNE COMPUTER DESIGNER BY THE SYSTEM PERFORMANCE REQUIREMENTS AND THE AIRCRAFT OPERATIONAL ECONOMIC ENVIRONMENT. IN ORDER TO EXAMINE THESE REQUIREMENTS A NUMBER OF TYPICAL SYSTEMS ARE CONSIDERED

771969 F7522914, C7513821

THYRISTOR DRIVE SYSTEM FOR A TESTING STAND OF AIRCRAFT ENGINE FUEL SYSTEMS

LASTOWIECKI, J., DUSZCZYK, K. ; POLITECHNIKA WARSZAWSKA, POLAND  
PRZEGŁ. ELEKTROTECH. (POLAND) VOL.51, NO.1 11-13 JAN. 1975  
CODEN: PZELAL

DESCRIPTORS: THYRISTOR APPLICATIONS, ELECTRIC DRIVES, AUTOMATIC TEST EQUIPMENT, AIRCRAFT, AEROSPACE CONTROL, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: OPTIMAL CONTROLLER SETTING, DIRECT CURRENT DRIVE SYSTEM, AEROSPACE CONTROL, AUTOMATIC TEST EQUIPMENT, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, THYRISTOR DRIVE SYSTEM, TESTING STAND, AIRCRAFT ENGINE FUEL SYSTEMS, ELECTRONIC REGULATORS, COMPUTER CONTROLLED 30 KW MOTOR

SECTION CLASS CODES: C7875, C8846, C7856, B5620

UNIFIED CLASS CODES: VPRMAY, WHEKAS, VMKKAR, TKEAAR

LANGUAGE: POLISH

A METHOD OF DESIGNING A DRIVING SYSTEM FOR A TESTING STAND OF AIRCRAFT ENGINE FUEL SYSTEMS IS DISCUSSED. THE RELATIONSHIPS FOR AN OPTIMUM CHOICE OF THE SETTINGS OF ELECTRONIC REGULATORS ARE GIVEN. THE RESULTS OF TESTS ON A D.C. DRIVE SYSTEM WITH A COMPUTER CONTROLLED 30 KW MOTOR IS DISCUSSED (3 REFS)

771954 B7522915, C7513806

COMPUTERS ON MERCHANT SHIPS. II

POLET, T.W., POLET, T.W., JR.

POLYTECH. TIJDSCHR. ELEKTROTECH. ELEKTRON. (NETHERLANDS) VOL.30, NO.5 149-55 5 MARCH 1975 CODEN: PTEEBR

DESCRIPTORS: SHIPS, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, RADIONAVIGATION, COMMUNICATIONS APPLICATIONS OF COMPUTERS, PROCESS COMPUTERS

IDENTIFIERS: ONLINE OPERATION, OFF LINE OPERATION, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, RADIONAVIGATION, COMMUNICATIONS APPLICATIONS OF COMPUTERS, MERCHANT SHIPS, PROCESS CONTROL COMPUTERS, ENGINE CONTROL AND MAINTENANCE, SHIPBOARD TRIALS, COLLISION PREVENTION COMPUTER AIDED SYSTEMS, INTEGRATED NAVIGATION SYSTEMS, SOURCES OF ERRORS

SECTION CLASS CODES: B5620, C7874, C8846, C8842, B3660, C7850

UNIFIED CLASS CODES: TKEAAR, VMKKAM, WHEKAS, WHEEAO, PGKAAZ, VMKAAS

LANGUAGE: DUTCH

FOR PT.I SEE IBID., VOL.30, NO.4, P.103 (1975). THE FUNCTION OF ON-LINE AND OFF-LINE PROCESS CONTROL COMPUTERS IS ILLUSTRATED BY BLOCK DIAGRAMS. IT IS SUGGESTED THAT THE APPLICATION OF COMPUTERS TO ENGINE CONTROL AND MAINTENANCE IS EASIER THAN THEIR APPLICATION TO NAVIGATION PROBLEMS. SOME SHIPBOARD TRIALS HAVE SHOWN UP POSSIBLE SOURCES OF ERRORS. AS THE MOST USEFUL NAVIGATION AIDS, THE COLLISION PREVENTION COMPUTER AIDED SYSTEMS ARE CONSIDERED. THE USE OF INTEGRATED NAVIGATION SYSTEMS IS INCREASING

758985 C7512019

COMPUTER PROGRAM TO PREDICT THE GAS EXCHANGE PROCESS OF A DIESEL ENGINE

HALLAM, A.J., COTTAM, S. ; RUSTON PAXMAN DIESELS LTD., LINCOLN, ENGLAND

COMPUT. AIDED DES. (GB) VOL.7, NO.2 83-8 APRIL 1975 CODEN: CAIDA5

DESCRIPTORS: COMPUTER-AIDED DESIGN, INTERNAL COMBUSTION ENGINES, ENGINEERING APPLICATIONS OF COMPUTERS, THERMODYNAMICS

IDENTIFIERS: INTERNAL COMBUSTION ENGINES, COMPUTER AIDED DESIGN, COMPUTER PROGRAM, PREDICT, GAS EXCHANGE PROCESS, DIESEL ENGINE, THERMODYNAMIC PERFORMANCE, DATA PREPARATION

SECTION CLASS CODES: C8847

UNIFIED CLASS CODES: WHEHAD

RUSTON PAXMAN DIESELS LTD HAS MADE MUCH USE OF COMPUTER PROGRAMS IN THE DEVELOPMENT OF DIESEL ENGINES, IN PARTICULAR FOR THE PREDICTION OF THERMODYNAMIC PERFORMANCE. THE ORIGINAL PROGRAM FOR THIS PURPOSE HAS UNDERGONE CONSIDERABLE CHANGE, BOTH TO IMPROVE THE ACCURACY AND EXTEND THE APPLICATION. THESE CHANGES HAVE RESULTED IN THE PROGRAM BECOMING UNNECESSARILY COMPLICATED FOR THE DESIGNER TO USE. BY RETURNING TO FIRST PRINCIPLES A NEW PROGRAM HAS BEEN WRITTEN THAT IS CONSIDERABLY MORE VERSATILE THAN THE OLD ONE, AND WHICH IS FAR SIMPLER TO USE BECAUSE DATA PREPARATION IS NOW GOVERNED SOLELY BY THE COMPLEXITY OF THE PROBLEM BEING TACKLED. THIS PROGRAM IS DESCRIBED (7 REFS)

745056 E7513864

HOW UNCONVENTIONAL STIRLING ENGINES CAN HELP CONSERVE ENERGY

MARTINI, W.R., WHITE, M.A., DESTESSE, J.G. ; MCDONNELL DOUGLAS CORP., RICHLAND, WASH., USA

; ASME, IEEE, ET AL

9TH INTERSOCIETY ENERGY CONVERSION ENGINEERING CONFERENCE PROCEEDINGS 1092-9 1974

26-30 AUG. 1974 ASME, IEEE, ET AL SAN FRANCISCO, CALIF., USA

PUBL: ASME NEW YORK, USA

DESCRIPTORS: HEAT ENGINES

IDENTIFIERS: SINGLE VALVE CONTROL, DOUBLE STIRLING ENGINE CHILLER, STIRLING ENGINES, FREE POWER PISTON, FREE DISPLACER, DRIED ORGANIC MATTER, COMPUTER SIMULATIONS, ENGINE TESTS, SELF STARTING, DIRECT HYDRAULIC POWER, VEHICLES, MECHANICAL POWER CONCEPT, THERMALLY REGENERATIVE BRAKING, DESIGN CONCEPT, FLAT PLATE SOLAR COLLECTOR, BUILDINGS

SECTION CLASS CODES: B5240

UNIFIED CLASS CODES: TEGAAX

UNCONVENTIONAL STIRLING ENGINES, WITH EITHER A FREE POWER PISTON OR FREE DISPLACER, CAN EFFICIENTLY USE A WIDE VARIETY OF FUELS, INCLUDING DRIED ORGANIC MATTER, A MAJOR UNUSED FUEL RESOURCE. BOTH COMPUTER SIMULATIONS AND ENGINE TESTS HAVE DEMONSTRATED SELF STARTING AND SINGLE-VALVE CONTROL OF AN ENGINE PRODUCING HYDRAULIC POWER FROM HEAT WITHOUT INTERVENING SHAFT POWER. DIRECT HYDRAULIC POWER FOR VEHICLES IS EVALUATED AS IS A MECHANICAL POWER CONCEPT PARTICULARLY ATTRACTIVE BECAUSE OF THERMALLY REGENERATIVE BRAKING. FINALLY, A DESIGN CONCEPT WHICH CAN USE 200 DEGREEST HEAT FROM A FLAT PLATE SOLAR COLLECTOR OR HIGHER TEMPERATURE COMBUSTION HEAT SOURCES TO MORE EFFICIENTLY PRODUCE HEATING AND COOLING FOR BUILDINGS THAN IS NOW POSSIBLE (4 REFS)

735401 C7506296

APPLICATION OF FUZZY ALGORITHMS FOR CONTROL OF SIMPLE DYNAMIC PLANT  
HAMDANI, B.R. ; QUEEN MARY COLL., LONDON, ENGLAND  
PROC. INST. ELECTR. ENG. (GB) VOL. 121 NO. 12 1585-8 DEC. 1974  
CODEN: PEEZAH

DESCRIPTORS: HEAT ENGINES, CONTROL SYSTEMS, DIRECT DIGITAL CONTROL,  
CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: LABORATORY BUILT STEAM ENGINE, APPLICATION OF FUZZY  
ALGORITHMS, CONTROL OF SIMPLE DYNAMIC PLANT, CONTROLLER

SECTION CLASS CODES: C7851, C8846

UNIFIED CLASS CODES: VMKCAD, WHEKAS

THE PAPER DESCRIBES A SCHEME IN WHICH A FUZZY ALGORITHM IS USED TO  
CONTROL PLANT, IN THIS CASE, A LABORATORY-BUILT STEAM ENGINE. THE  
ALGORITHM IS IMPLEMENTED AS AN INTERPRETER OF A SET OF RULES EXPRESSED  
AS FUZZY CONDITIONAL STATEMENTS. THIS IMPLEMENTATION ON A DIGITAL  
COMPUTER IS USED ON-LINE, TO CONTROL THE PLANT. THE MERIT OF SUCH A  
CONTROLLER IS DISCUSSED IN THE LIGHT OF THE RESULTS OBTAINED

732554 R7508079

DIGITAL DWELL ANGLE ENCODER

SHAKIB, J. ; IBM, NEW YORK, USA

IBM TECH. DISCLOSURE BULL. (USA) VOL. 27, NO. 5 1280-1 OCT. 1974  
CODEN: IBMTAA

DESCRIPTORS: COUNTING CIRCUITS, ELECTRIC IGNITION

IDENTIFIERS: DIGITAL DWELL ANGLE ENCODER, DWELL ANGLE, IGNITION  
SYSTEM, LOGICALLY GATING CLOCK PULSES, COUNTING CIRCUITS, AUTOMATED  
DATA ACQUISITION, DIAGNOSTICS OF AUTOMOBILE ENGINE PERFORMANCE

SECTION CLASS CODES: B1830, B5620, B1870

UNIFIED CLASS CODES: ETGAAT, TKEAAR, ETNAAP

THE DWELL ANGLE OF THE POINTS OF AN IGNITION SYSTEM FOR AN INTERNAL  
COMBUSTION ENGINE IS DIGITIZED BY LOGICALLY GATING CLOCK PULSES INTO  
COUNTING CIRCUITS. THE APPARATUS IS PARTICULARLY USEFUL FOR PROVIDING  
A DIRECT READOUT DIGITAL RESULT OR INPUT DATA TO A COMPUTER, AND IS  
PARTICULARLY WELL SUITED FOR AUTOMATED DATA ACQUISITION AND  
DIAGNOSTICS OF AUTOMOBILE ENGINE PERFORMANCE

727295 C7505344

A SIMILARITY PARAMETER FOR SCALING DYNAMIC INLET DISTORTION

MOORE, M.T. ; GENERAL ELECTRIC CO., CINCINNATI, OHIO, USA

TRANS. ASME SER. B (USA) VOL. 96, NO. 3 795-800 AUG. 1974  
CODEN: JEVIA8

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE ENGINES

IDENTIFIERS: METHOD D PARAMETER, SIMILARITY PARAMETER, DYNAMIC INLET  
DISTORTION, ANALOGUE AND DIGITAL ANALYSES, METHOD D DISTORTION  
METHODOLOGY, ANALOGUE FILTERING, DIGITAL AVERAGING, TURBINE ENGINE  
PERFORMANCE

SECTION CLASS CODES: C8849

UNIFIED CLASS CODES: WHEZAN

DESCRIBES THE ANALOGUE FILTER BANDWIDTH AND DIGITAL AVERAGE TIME OF  
THE TIME-DEPENDENT PRESSURE DATA PRIOR TO COMPUTATION OF THE METHOD D  
PARAMETERS. ANALOGUE FILTERING AND DIGITAL AVERAGING ARE SHOWN TO BE  
EQUIVALENT UNDER CERTAIN CONDITIONS AND CONSISTENT SELECTION CAN BE  
MADE FOR COMPARISON OF TRENDS IN INLET DYNAMIC DISTORTION BETWEEN  
INLETS OF DIFFERENT TYPES AND SIZES

727276 C7505324

PROSPECTS FOR ADVANCED COMPUTER ROLES IN MARINE ENGINE MONITORING  
WILLIAMS, V.P.

SPERRY TECHNOL. (USA) VOL. 2 NO. 2 34-5 1974 CODEN: SPTYBV

DESCRIPTORS: MARINE SYSTEMS, NAVAL ENGINEERING, ENGINEERING  
APPLICATIONS OF COMPUTERS

IDENTIFIERS: ALARM SCANNING TECHNIQUE, DIGITAL COMPUTER, DATA  
PROCESSING, MARINE ENGINE MONITORING, AUTOMATED SYSTEM, WARNING SYSTEM  
, PREDICTIVE MAINTENANCE SYSTEM, PROGRAMMING MATHEMATICAL MODELS,  
SAFETY CONTROL SYSTEMS

SECTION CLASS CODES: C8847, C8846, C8849

UNIFIED CLASS CODES: WHEHAD, WHEKAS, WHEZAN

REVIEWS THE APPLICATIONS OF COMPUTERS IN MARINE ENGINE MONITORING  
WHICH INCLUDE AUTOMATED SYSTEM, WARNING SYSTEM, PREDICTIVE MAINTENANCE  
SYSTEM, PROGRAMMING MATHEMATICAL MODELS, AND SAFETY CONTROL SYSTEMS

726729 B7504833, C7504672

ADJUSTABLE COUNTER FOR THE CONTROL OF A DIESEL ENGINE TEST PROGRAMME  
GRYGAS, U., HOTTOWITZ, R. ; TECH. HOCHSCHULE OTTO VON GUERICKE  
MAGDEBURG, GERMANY

WISS. Z. TECH. HOCHSCH. OTTO VON GUERICKE MAGDER. (GERMANY) VOL.  
18 NO. 3 311-15 1974 CODEN: WCGMAI

DESCRIPTORS: COUNTERS, COUNTER ACCESSORIES, ELECTRIC CONTROL  
EQUIPMENT, INTERNAL COMBUSTION ENGINES, AUTOMATIC TEST EQUIPMENT,  
MACHINE TESTING

IDENTIFIERS: ADJUSTABLE COUNTER, ANALOGUE TO DIGITAL CONVERTOR,  
CONTROL, DIESEL ENGINE, TEST PROGRAMME, TEST BED, TECHNICAL UNIVERSITY  
OF MAGDEBURG, FUEL INJECTION, CAMERA FILM TRANSPORT, OSCILLOSCOPE  
CAMERA, COMBUSTION PRESSURE, PHOTOELECTRIC PULSES, CRANKSHAFT,  
CAMSHAFT, LOGIC SYSTEM, MIXTURE FORMATION, COMBUSTION PROCESSES

SECTION CLASS CODES: C7896, C7682, B1269

UNIFIED CLASS CODES: VHZRAY, VKMCAV, ADGMAB

LANGUAGE: GERMAN

DESCRIBES A TEST BED AT THE TECHNICAL UNIVERSITY OF MAGDEBURG TO  
STUDY THE MIXTURE FORMATION AND COMBUSTION PROCESSES ON A ONE-CYLINDER  
DIESEL ENGINE. AN ADJUSTABLE COUNTER UNIT CONTROLS THE SWITCHING  
INSTANTS OF FUEL INJECTION, CAMERA FILM TRANSPORT, OSCILLOSCOPE CAMERA  
AND ANALOGUE-TO-DIGITAL CONVERTER OF COMBUSTION PRESSURE. THE COUNTER  
IS GOVERNED BY PHOTO ELECTRIC PULSES FROM THE CRANKSHAFT, CAMSHAFT AND  
DEAD CENTRE POSITION. THE COUNTER ACTIVATES THE MEASURING INSTRUMENTS  
DURING A PRESCRIBED WORK PERIOD OF THE ENGINE, ENABLING DIRECT  
COMPARISON OF DIFFERENT MEASURED QUANTITIES. THE ORGANIZATION OF THE  
MEASUREMENT PROGRAMME IS DISCUSSED AND THE LOGIC SYSTEM AND  
CONSTRUCTION OF THE COUNTER ARE DESCRIBED



722527 B7506913, C7503292

SMALL TRANSFORMER DESIGN BY COMPUTER

PALMER, M.D.

REPORT NO.: RAE-TR-73155 ISSUED BY: ROYAL AIRCRAFT ESTABL.,  
FARNBOROUGH, ENGLAND

FEB. 1974

DESCRIPTORS: POWER TRANSFORMERS, ELECTRICAL ENGINEERING APPLICATIONS  
OF COMPUTERS, ION ENGINES, AEROSPACE APPLICATIONS OF COMPUTERS,  
COMPUTER-AIDED DESIGNIDENTIFIERS: POWER TRANSFORMER DESIGN, COMPUTER AIDED DESIGN,  
AEROSPACE PROPULSION, ION ENGINE SUPPLY, AEROSPACE APPLICATIONS OF  
COMPUTERS, IMPROVEMENTS IN EFFICIENCY, REDUCTION IN MASS

SECTION CLASS CODES: B4760, B5350, C8849, C8841

UNIFIED CLASS CODES: ZLKAAH, TGKAAT, WHEZAN, WHECAF

AVAILABILITY: NTIS, SPRINGFIELD, VA. 22151, USA

A COMPUTER PROGRAM WAS WRITTEN TO INVESTIGATE TRANSFORMER DESIGN FOR  
AN ION MOLAR APPLICATION UNDER CONDITIONS COMPATIBLE WITH THE OTHER  
CIRCUIT ELEMENTS WITH THE AIM OF OBTAINING IMPROVEMENTS IN EFFICIENCY  
AND REDUCTION IN MASS. TRANSFORMERS PRODUCED FROM THE RESULTING  
DESIGNS FEATURED EFFICIENCIES IN EXCESS OF 98PERCENT AND MASSES SOME  
25PERCENT LESS THAN THEIR PREDECESSORS

717924 B7503984, C7503268

MEASUREMENT OF INDICATED MEAN EFFECTIVE PRESSURE OF A RECIPROCATING  
ENGINE WITH A MINICOMPUTER

SHINOYAMA, F., YANAGIHARA, S.

J. MECH. ENG. LAB. (JAPAN) VOL.28, NO.1 17-20 JAN. 1974  
CODEN: JGKSBLDESCRIPTORS: INTERNAL COMBUSTION ENGINES, ENGINEERING APPLICATIONS  
OF COMPUTERS, PRESSURE MEASUREMENTIDENTIFIERS: ENGINEERING APPLICATION OF COMPUTERS, INTERNAL  
COMBUSTION ENGINES, MEASUREMENT OF INDICATED MEAN EFFECTIVE PRESSURE,  
RECIPROCATING ENGINE, MINICOMPUTER, STROKE SIGNAL GENERATOR, TWO  
STROKE GASOLINE ENGINE

SECTION CLASS CODES: C8847, B4449, C7449

UNIFIED CLASS CODES: WHEMAD, BKETAH

LANGUAGE: JAPANPSE

DESCRIBES THE METHOD WHICH HAS BEEN DEVELOPED TO REDUCE THE  
INDICATED MEAN EFFECTIVE PRESSURE (I.M.E.P.) OF EACH CYCLE AND A  
CONTINUOUS 1000 CYCLES, BY USING A MINICOMPUTER AND STROKE SIGNAL  
GENERATOR. THE STROKE IS DIVIDED INTO TWENTY PARTS HAVING THE SAME  
VOLUME AND THE REPRESENTATIVE CYLINDER PRESSURE DETECTED BY A  
PRECISION PRESSURE PICK-UP IS SAMPLED WITH THE COMPUTER AT THE  
MID-POINT OF EACH DIVIDED STROKE. IN THE DIGITAL COMPUTER THE PRESSURE  
SIGNALS ARE PROCESSED IN REAL TIME (ON LINE) AND I.M.E.P. AND THE  
OTHER VALUES OF EACH CYCLE ARE MEMORIZED. THE METHOD WAS APPLIED TO A  
TWO STROKE GASOLINE ENGINE AND THE RESULTS WERE COMPARED WITH ENGINE  
DYNAMOMETER TORQUE (2 REFS)

708959 B7501614, C7501314

## PREDICTION OF PRESSURE AND FLOW TRANSIENTS IN A GASEOUS BIPROPELLANT REACTION CONTROL ROCKET ENGINE

HARKOWSKY, J.J. ; AMERICAN ELECTRIC POWER SERVICE CORP., NEW YORK  
COMPUT. AND FLUIDS (GB) VOL. 2 NO. 2 195-61 AUG. 1974 CODEN:

CFPLBI

DESCRIPTORS: ROCKETS, COMBUSTION, CONTROL SYSTEMS, COMPUTER-AIDED ANALYSIS, AEROSPACE APPLICATIONS OF COMPUTERS

IDENTIFIERS: UPSTREAM WEIGHTED DIFFERENCING SCHEMES, MASS TRANSFER, PRESSURE TRANSIENTS,  $H/SUB\ 2/+0/SUB\ 2/$  REACTION, CONTINUITY EQUATIONS, FLOW TRANSIENTS, GASEOUS BIPROPELLANT REACTION CONTROL ROCKET ENGINE, VALVES, MANIFOLDS, INJECTORS, FEEDLINE, MANIFOLD VOLUME, IBM 360/65, COMBUSTION LAG TIME, PORTMAN IV

SECTION CLASS CODES: B4710, C8849, C7875

UNIFIED CLASS CODES: ZLCAAJ, WMEZAN, VHRMAY

AN ANALYTIC MODEL IS DEVELOPED TO PREDICT PRESSURE AND FLOW TRANSIENTS IN A GASEOUS HYDROGEN-OXYGEN REACTION CONTROL ROCKET ENGINE FEED SYSTEM. THE ONE-DIMENSIONAL EQUATIONS OF MOMENTUM AND CONTINUITY ARE REDUCED BY THE METHOD OF CHARACTERISTICS FROM PARTIAL DERIVATIVES TO A SET OF TOTAL DERIVATIVES WHICH DESCRIBE THE STATE PROPERTIES ALONG THE FEEDLINE. SYSTEM COMPONENTS, E.G. VALVES, MANIFOLDS AND INJECTORS ARE REPRESENTED BY PSEUDO STEADY-STATE RELATIONS AT DISCRETE JUNCTIONS IN THE SYSTEM. SOLUTIONS WERE EFFECTED BY A PORTMAN IV PROGRAM ON AN IBM 360/65. THE RESULTS INDICATE THE RELATIVE EFFECT OF MANIFOLD VOLUME, COMBUSTION LAG TIME, FEEDLINE PRESSURE FLUCTUATIONS, PROPELLANT TEMPERATURE, AND FEEDLINE LENGTH ON THE CHAMBER PRESSURE TRANSIENT. THE ANALYTICAL COMBUSTION MODEL IS VERIFIED BY GOOD CORRELATION BETWEEN PREDICTED AND OBSERVED CHAMBER PRESSURE TRANSIENTS (15 REFS)

708920 C7501275

## COMPUTER-AIDED DESIGN OF THERMALLY LOADED AXISYMMETRIC DIESEL ENGINE COMPONENTS

TOMLINSON, G.R., LEONARD, R., HENSHALL, S.H. ; MANCHESTER POLYTECH., ENGLAND

COMPUT. AIDED DES. (GB) VOL. 6 NO. 3 132-5 JULY 1974 CODEN: CAIDA5

DESCRIPTORS: COMPUTER AIDED DESIGN, FINITE ELEMENT ANALYSIS, STRESS ANALYSIS, INTERNAL COMBUSTION ENGINES

IDENTIFIERS: THERMALLY LOADED AXISYMMETRIC DIESEL ENGINE COMPONENTS, FINITE ELEMENT METHODS, DESIGN, PISTON CROWNS, CYLINDER LINERS, EXHAUST VALVES, PISTON RING GROOVE DISTORTION, EXHAUST VALVE TEMPERATURES, LINER STRESSES

SECTION CLASS CODES: C8847

UNIFIED CLASS CODES: WHEHAD

DESCRIBES THE USE OF FINITE ELEMENT METHODS FOR THE DESIGN OF PISTON CROWNS CYLINDER LINERS AND EXHAUST VALVES AND IT IS SHOWN THAT A MARKED CORRELATION EXISTS BETWEEN PREDICTED AND MEASURED RESULTS. PRINCIPAL FACTORS SUCH AS PISTON RING GROOVE DISTORTION EXHAUST VALVE TEMPERATURE AND LINER STRESSES CAN BE RELIABLY EVALUATED AT REASONABLE COST (8 REFS)

701431 C7424923

## DIGITAL SIMULATION OF STATIONARY GAUSSIAN LOADS

KANEMATSU, H., WASH, W.A. ; UNIV. MASSACHUSETTS, AMHERST, USA

; POLISH ACAD. SCI. ET AL

ZAGADNIENIA DRGAN NIELINIOWYCH (POLAND) 247-65 1974 CODEN:

ZDNIAD

CONF: 6TH INTERNATIONAL CONFERENCE ON NONLINEAR OSCILLATIONS 29  
AUG. - 4 SEPT. 1972 POLISH ACAD. SCI. ET AL POZNAN, POLAND

DESCRIPTORS: RANDOM NUMBER GENERATION, SIMULATION, RANDOM PROCESSES

IDENTIFIERS: DIGITAL SIMULATION, STATIONARY GAUSSIAN LOADS, FILTERED  
WHITE NOISE RANDOM PROCESS, LINEAR FILTER, JET ENGINE SOUND PRESSURES,  
BOUNDARY LAYER PRESSURE FLUCTUATIONS, GUST LOADINGS, ATMOSPHERIC  
TURBULENCE

SECTION CLASS CODES: C8890, C8812

UNIFIED CLASS CODES: WMZAAP, WMCBA

LANGUAGE: ENGLISH

THIS STUDY IS CONCERNED WITH A DIGITAL SIMULATION TECHNIQUE FOR  
REPRESENTING A NON-WHITE STATIONARY GAUSSIAN RANDOM PROCESS. A  
FILTERED WHITE NOISE RANDOM PROCESS IS OBTAINED BY PASSING AN  
APPROXIMATE WHITE NOISE RANDOM PROCESS THROUGH A LINEAR FILTER. AS  
APPLICATIONS, JET ENGINE SOUND PRESSURES, BOUNDARY LAYER PRESSURE  
FLUCTUATIONS, AND GUST LOADINGS IN ATMOSPHERIC TURBULENCE ARE  
SIMULATED BY USING VARIOUS TYPES OF FIRST AND SECOND ORDER LINEAR  
FILTERS (10 REFS)

693717 C7422473

## DIGITAL ENGINE CONTROL SYSTEM FOR FUEL-INJECTION AND IGNITION TIMING

BREINESSER, P., KUZNIA, CH. ; SIEMENS AG MUNCHEN, GERMANY

; CONVENTION OF NAT. SOC. ELECTRICAL ENGRS. WESTERN EUROPE, IEEE

EUROPEAN CONFERENCE ON ELECTROTECHNICS. EUROCON :74 DIGEST.

(EXTENDED ABSTRACTS ONLY) B5-12/2PP. 1974

22-26 APRIL 1974 CONVENTION OF NAT. SOC. ELECTRICAL ENGRS. WESTERN  
EUROPE, IEEE AMSTERDAM, NETHERLANDS

PUBL: ROYAL INSTN. ENGRS., NETHERLANDS THE HAGUE, NETHERLANDS

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, CONTROL ENGINEERING  
APPLICATIONS OF COMPUTERS, AUTOMOBILES, FUEL, IGNITION, DIGITAL  
CONTROL, TABLE LOOKUPIDENTIFIERS: AUTOMOTIVE APPLICATIONS, DIGITAL COMPUTERIZED SYSTEM,  
IGNITION TIMING, TABLE LOOKUP, INTERPOLATION, THROTTLE ANGLE, ENGINE  
SPEED, FUEL INJECTION CONTROL

SECTION CLASS CODES: C7851, C8846, C8440, C7871

UNIFIED CLASS CODES: VMKAD, WMEKAS, WGEAAJ, VNRCA7

A DIGITAL COMPUTERIZED SYSTEM FOR THE ACCURATE CONTROL OF THE  
FUEL-TO-AIR RATIO AND THE IGNITION TIMING HAS BEEN DEVELOPED.  
EXPERIMENTS SHOWED A CONSIDERABLE REDUCTION OF EXHAUST EMISSIONS AND  
FUEL CONSUMPTION. TO GENERATE THE CONTROL SIGNALS, A TABLE LOOKUP  
TECHNIQUE WITH INTERPOLATION IS USED. THE TWO PARAMETERS WHICH DEFINE  
THE OPERATING CONDITION OF THE ENGINE, NAMELY THE THROTTLE ANGLE AND  
THE ENGINE SPEED, ARE USED FOR TABLE ENTRANCE

683813 B7435293, C7421849

RB199 RELATED SUB-SYSTEMS AND ASSOCIATED COMPONENTS

AIRC. ENG. (GB) VOL.46, NO.5 9-10, 13-16 MAY 1974 CODEN: AIENAP

DESCRIPTORS: AEROSPACE PROPULSION, AEROSPACE ENGINES, AIRCRAFT, CLOSED LOOP SYSTEMS, AEROSPACE CONTROL, AEROSPACE APPLICATIONS OF COMPUTERS, HEAT EXCHANGERS, AEROSPACE INSTRUMENTATION, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: MRCA, RB199 ENGINE, DIGITAL AIR INTAKE CONTROLLER, FUEL COOLED OIL COOLER, AIR COOLED FUEL COOLER, FUEL SYSTEM PRESSURE REDUCING VALVES, HIGH ENERGY IGNITION UNIT, TURBINE BLADE PYROMETER AMPLIFIER, NORD-MICRO GMBH, HAWKER SIDDELEY DYNAMICS, MAGNETI MARELLI, AIR INTAKE ANTI/DEICING SYSTEM, INTEGRATED PUMP AND CONTROL SYSTEM, AUXILIARY POWER UNIT, GEARBOX CONTROL UNIT, PRECOOLER OUTLET TEMPERATURE CONTROL, WATER EXTRACTOR, VARIABLE GEOMETRY AIR INDUCTION, AERODYNAMICALLY CLOSED LOOP

SECTION CLASS CODES: B4740, C8846, C8849, C7875

UNIFIED CLASS CODES: ZLGAAP, WHEKAS, WHEZAN, VHRMAY

DESCRIBES FEATURES OF THE MRCA RELATED TO THE RB199 ENGINE, INCLUDING: DIGITAL AIR INTAKE CONTROLLER, AIR INTAKE ANTI-ICE SYSTEM, FUEL COOLED OIL COOLER, AIR COOLED FUEL COOLER, FUEL SYSTEM PRESSURE REDUCING VALVES, HIGH ENERGY IGNITION UNIT AND THE TURBINE BLADE PYROMETER AMPLIFIER. FIRMS PARTICIPATING IN THESE DEVELOPMENTS INCLUDE NORD-MICRO GMBH, HAWKER SIDDELEY DYNAMICS AND MAGNETI MARELLI

674355 C7419467

AN EXPERIMENTAL INVESTIGATION INTO DUPLEX DIGITAL CONTROL OF AN ENGINE WITH REHEAT

EVANS, J.P.O., HELPS, K.A.

; AGARD

AGARD CONFERENCE PROCEEDINGS NO. 137 ON ADVANCES IN CONTROL SYSTEMS 16/1-14 1974

24-26 SEPT. 1973 AGARD GRILLO, NORWAY

PUBL: AGARD NEUILLY SUR SPINNE

DESCRIPTORS: AEROSPACE ENGINES, AEROSPACE CONTROL, DIRECT DIGITAL CONTROL, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, AEROSPACE APPLICATIONS OF COMPUTERS

IDENTIFIERS: DUPLEX DIGITAL CONTROL, ENGINE WITH REHEAT, CROSS MONITORING COMPUTERS, HYDROMECHANICAL BACK UP SYSTEM

SECTION CLASS CODES: C7875, C8846, C8849

UNIFIED CLASS CODES: VHRMAY, WHEKAS, WHEZAN

DESCRIBES AN EXPERIMENTAL INVESTIGATION INVOLVING THE CONTROL OF A P.S. 50 ENGINE BY A PAIR OF CROSS-MONITORING COMPUTERS WITH A HYDROMECHANICAL BACK-UP SYSTEM. THE CONTROLLER WAS DEVELOPED JOINTLY BY SMITHS INDUSTRIES LIMITED, AND DOWTY FUEL SYSTEMS LIMITED, AND WAS COMMISSIONED AND RUN IN LATE 1972 AT THE D.F.S. TEST BED AT STAVERTON, ENGLAND. THE P.S. 50 IS A SINGLE SPOOL ENGINE WITH MULTI-MANIFOLD REHEAT

662848 R7427801, C7416947

A : SPEEDY: APPROACH TO DIGITAL FREQUENCY METERING  
CREASEY, D.ELECTRON. EQUIP. NEWS (GB) VOL. 15, NO. 11 64-5 APRIL-MAY  
19. TEGE TRS A O OLL7 O CODEN: BEQNAWDESCRIPTORS: FREQUENCY METERS, INTERNAL COMBUSTION ENGINES, GAS  
TURBINES, TACHOMETERS, DIGITAL INSTRUMENTATIONIDENTIFIERS: INTERNAL COMBUSTION ENGINES, AIRCRAFT TURBINE ENGINES,  
PERFORMANCE ADJUSTMENT, GAS TURBINE ENGINES, ENGINE DEVELOPMENT,  
DIGITAL FREQUENCY METERING

SECTION CLASS CODES: B4424, B4442, B5240, B4270, C7660

UNIFIED CLASS CODES: BKCKAZ, BKKEAM, TEGAAX, BECRAX

DISCUSSES APPLICATION TO INTERNAL COMBUSTION ENGINES AND AIRCRAFT  
TURBINE ENGINES FOR PERFORMANCE ADJUSTMENT

641129 A7439135, C7412723

NOISE MEASUREMENT ON A V-6 DIESEL ENGINE

CHUNG, J.Y., CROCKER, M.J., HAMILTON, J.P. ; PURDUE UNIV., WEST  
LAFAYETTE, IND., USA

TREE, D.R.

; INST. NOISE CONTROL ENGNG

1973 NATIONAL CONFERENCE ON NOISE CONTROL ENGINEERING 86-91 1973  
15-17 OCT. 1973 INST. NOISE CONTROL ENGNG WASHINGTON, D.C., USA

PUBL: INST. NOISE CONTROL ENGNG. POUGHKEEPSIE, N.Y., USA

DESCRIPTORS: NOISE ABATEMENT, ACOUSTIC NOISE, INTERNAL COMBUSTION  
ENGINES, FOURIER ANALYSIS, ACOUSTIC INTENSITY MEASUREMENTIDENTIFIERS: NOISE SPECTRA, DIGITAL FOURIER ANALYSER, STRUCTURAL  
ATTENUATION, DIESEL ENGINE NOISE, VEE 6 DIESEL ENGINE

SECTION CLASS CODES: A9890, C7455

UNIFIED CLASS CODES: ZCZAFZ, VGEZAP

THE MEASUREMENTS OF THE NOISE SPECTRA WHICH ARE SHOWN IN THIS PAPER  
HAVE BEEN MADE BY MEANS OF A DIGITAL FOURIER ANALYSER. THE MAIN  
PURPOSE OF THE PAPER IS TO DISCUSS THE STRUCTURAL ATTENUATION OF THE  
DIESEL ENGINE NOISE

618181 D7412495, C7408932

BEAM DIAGNOSTICS OF THE RIT 10-ENGINE

ALTENBURG, W., GRISEL, J. ; GIESSEN UNIV., GERMANY

; IEE, UKAEA

STD BOOK NO.: 0 85296119 7

CONFERENCE ON ELECTRIC PROPULSION OF SPACE VEHICLES 48-52 1973

10-12 APRIL 1973 IEE, UKAEA ABINGDON, BERKS., ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: ION ENGINES, ION BEAMS, AEROSPACE ENGINES,  
COMPUTER-AIDED ANALYSIS, AEROSPACE APPLICATIONS OF COMPUTERS, DATA  
REDUCTION AND ANALYSIS, ELECTRIC PROPULSION

IDENTIFIERS: RIT 10 ENGINE, ION THRUSTERS, BEAM DIAGNOSTICS, ANGULAR  
DISTRIBUTION, ENERGY, CHARGE SPECTRUM, DIVERGENCE EFFICIENCY, THRUST  
VECTOR DEVIATION, INTEGRATED BEAM CURRENT

SECTION CLASS CODES: B4760, C8849

UNIFIED CLASS CODES: ZLKAAM, WHEZAN

TO DETERMINE THE BEAM DATA OF RIT 10- THRUSTERS, E.G. THE ANGULAR  
DISTRIBUTION, ENERGY CHARGE SPECTRUM, THE DIVERGENCE EFFICIENCY, AN  
EVENTUAL THRUST VECTOR DEVIATION AS WELL AS THE INTEGRATED BEAM  
CURRENT, A SPECIAL BEAM DIAGNOSTIC APPARATUS HAS BEEN BUILT UP IN THE  
PUMPING FACILITY :P 6000:. BY USING DIFFERENT MOVABLE PROBES WHICH ARE  
DRIVEN BY THREE ELECTRIC MOTORS, THE BEAM REGION UP TO 1 M DISTANCE  
FROM THE THRUSTER EXIT CAN BE SCANNED CONTINUOUSLY. THE DATA PICKED UP  
BY THE PROBE (ABOUT 30000 FOR EACH PROFILE) ARE FED TO A DIGITAL  
COMPUTER (HONEYWELL H 316) WHICH PLOTS THE PROFILE CARDS AND PRINTS  
THE ABOVE MENTIONED PERFORMANCE DATA. FIRST EXPERIMENTAL RESULTS ARE  
GIVEN (4 REFS)

618174 C7408925

ENGINE DATA LOGGED FASTER BY COMPUTER

SYSTEMS (GB) VOL.1, NO.2 22-3 OCT. 1973

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, DATA ACQUISITION,  
ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: INTERNAL COMBUSTION ENGINE, PERFORMANCE, DATA  
ACQUISITION SYSTEM, COMPUTER

SECTION CLASS CODES: C8849

UNIFIED CLASS CODES: WHEZAN

THE NEED FOR AUTOMATION IN MONITORING INTERNAL COMBUSTION ENGINE  
PERFORMANCE HAS BEEN RECOGNISED BY MANY ORGANISATIONS INCLUDING THE  
SOUTHWEST RESEARCH INSTITUTE, TEXAS, WHERE PROJECTS INVOLVE THE  
EVALUATION OF DIESEL AND PETROL ENGINES FOR FUEL ECONOMY, LUBRICATION  
PERFORMANCE, OCTANE REQUIREMENTS, HYDROCARBON EMISSION ETC. RECENTLY  
THE SINGLE-CYLINDER CATERPILLAR ENGINE LABORATORY THAT CAN MONITOR 50  
ENGINES SIMULTANEOUSLY HAS BEEN AUTOMATED WITH A HEWLETT-PACKARD  
SENSOR-BASED DATA ACQUISITION SYSTEM

606088 B7405160, C7406042

A COMPUTER-CONTROLLED ENGINE TEST CELL FOR ENGINEERING EXPERIMENTS  
RILLINGS, J.H., CREPS, W.D., VORA, L.S. ; GENERAL MOTORS RES.  
LABS., WARREN, MICH., USA

PROC. IEEE (USA) VOL.61, NO.11 1622-6 NOV. 1973 CODEN:  
IEEPAD

DESCRIPTORS: AUTOMATIC TEST EQUIPMENT, AUTOMOBILES, INTERNAL  
COMBUSTION ENGINES, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS,  
ENGINEERING APPLICATIONS OF COMPUTERS, DATA ACQUISITION, DATA  
REDUCTION AND ANALYSIS, COMPUTER-AIDED ANALYSIS

IDENTIFIERS: AUTOMOTIVE ENGINES, DATA ACQUISITION, COMPUTER  
CONTROLLED ENGINE TEST CELL

SECTION CLASS CODES: B7269, C8849, C7851

UNIFIED CLASS CODES: ADGMAR, WMEZAN, VMKCAD

A COMPUTER-CONTROLLED ENGINE TEST CELL WAS DEVELOPED FOR CONDUCTING  
COMPLEX TRANSIENT EXPERIMENTS WITH AUTOMOTIVE ENGINES. THE TEST CELL  
USES A MINICOMPUTER WITH A 16000-WORD 16-B CORE MEMORY TO PERFORM DATA  
ACQUISITION AND CLOSED-LOOP CONTROL OF THE ENGINE AND DYNAMOMETER. A  
TABLE-DRIVEN REAL-TIME CONTROL PROGRAM IS USED TO DUPLICATE THE  
EFFECTS OF VEHICLE, TRANSMISSION, AND ROAD ON ENGINE OPERATION.  
REFERENCE DATA AND ACQUIRED DATA ARE EXCHANGED OVER A HIGH-SPEED  
COMMUNICATIONS CHANNEL BETWEEN THE MINICOMPUTER AND A CENTRALIZED DATA  
ACQUISITION COMPUTER (DAC) SYSTEM. DATA CAN BE PLOTTED AGAINST TIME OR  
CROSS-PLOTTED AGAINST OTHER PARAMETERS ON A GRAPHIC CATHODE-RAY-TUBE  
DISPLAY PERIPHERAL TO THE MINICOMPUTER. THE USER CAN INTERACT WITH THE  
SYSTEM TO CHANGE PARAMETERS DURING THE RUNNING OF AN EXPERIMENT (2  
REFS)

585981 C7401117

SOLUTION IMPROVEMENT IN COMPUTERIZED STRUCTURAL ANALYSIS SIMULATION  
 PITTS, G.N., BATHMAN, R. ; CENTRAL TEXAS COLL., KILLEEN, USA  
 ; ISA, ET AL

STD BOOK NO.: 1

PROCEEDINGS OF THE 1973 SUMMER COMPUTATION SIMULATION CONFERENCE  
 476-8 1973

13-19 JULY 1973 ISA, ET AL MONTREAL, QUEBEC, CANADA

PUBL: SIMULATION COUNCIL LA JOLLA, CALIF., USA

DESCRIPTORS: AEROSPACE SIMULATION, AEROSPACE APPLICATIONS OF  
 COMPUTERS, AEROSPACE ENGINES, COMPUTER AIDED ANALYSIS, NUMERICAL  
 ANALYSIS

IDENTIFIERS: STRUCTURAL ANALYSIS, SIMULATION, AIRCRAFT, ROCKET,  
 ENGINE

SECTION CLASS CODES: C8849, C8200

UNIFIED CLASS CODES: WHEZAN, DLTAAB

WITH THE STATE OF THE ART IN AIRCRAFT AND ROCKET ENGINE DESIGN  
 REACHING AN UNPRECEDENTED HEIGHT, STRUCTURAL ANALYSIS HAS BECOME AN  
 EXTREMELY DIFFICULT TASK. THE ENGINEER IS FACED WITH THE COMPLEX  
 PROBLEM OF AN ENGINE OPERATING AT VERY HIGH TEMPERATURE WITH  
 EXCEPTIONALLY LARGE STRESSES AND STRAINS. SINCE MANY STRUCTURAL  
 PROBLEMS CAN BE SIMULATED WITH SYSTEMS OF NONLINEAR SIMULTANEOUS  
 EQUATIONS, MUCH TIME AND EFFORT HAS BEEN SPENT ON DEVELOPING VARIOUS  
 METHODS TO SOLVE THESE SYSTEMS. THE SOLUTION METHOD PRESENTED IN THIS  
 PAPER IS A COMBINATION AND MODIFICATION OF METHODS WHICH RESULTS IN A  
 SIGNIFICANT DECREASE IN SOLUTION COST AND EXECUTION TIME. THE PROPOSED  
 METHOD IS CHARACTERIZED BY RAPID CONVERGENCE AND LESS CRITICAL INITIAL  
 APPROXIMATIONS (4 REFS)

585971 C7401103

SIMULATION OF THERMODYNAMIC PROCESS OF A DIESEL ENGINE ON A SMALL  
 DIGITAL COMPUTER

OJHA, V.P. ; DIESEL LOCOMOTIVE WORKS, VARANASI, INDIA

J. INST. ENG. (INDIA) MECH. ENG. DIV. VOL.53, PT.116 292-301  
 JULY 1973 CODEN: JEMDAS

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, SIMULATION, THERMODYNAMICS  
 , MODELLING, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: SIMULATION, THERMODYNAMIC PROCESS, DIESEL ENGINE, SMALL  
 DIGITAL COMPUTER, MATHEMATICAL MODEL

SECTION CLASS CODES: C8849

UNIFIED CLASS CODES: WHEZAN

THIS PAPER DISCUSSES A MATHEMATICAL MODEL FOR SIMULATING THE  
 THERMODYNAMIC PROCESS OF A DIESEL ENGINE. THE MODEL HAS BEEN USED TO  
 PREDICT THE PERFORMANCE OF 251B, 16 CYLINDER DIESEL ENGINES BEING  
 MANUFACTURED AT THE DIESEL LOCOMOTIVE WORKS VARANASI. SOME OF THE  
 CHARACTERISTICS LIKE HEAT RELEASE PATTERN, HEAT TRANSFER COEFFICIENTS  
 AND EFFICIENCIES OF TURBO COMPONENTS WERE EITHER ASSUMED OR OBTAINED  
 FROM THE TEST BED RESULTS. THE EFFICACY OF THIS MODEL IS ILLUSTRATED  
 BY PREDICTING THE PERFORMANCE OF THE SAME ENGINE WORKING AT A  
 DIFFERENT SPEED AND RATING. THIS MODEL IS COMPACT, WHICH ENABLES IT TO  
 BE COMPUTERIZED FOR SMALL COMPUTERS LIKE THE 140 VERSION OF IBM SERIES  
 OF DATA PROCESSING MACHINES WITH A STORAGE CAPACITY OF 12K (11 REFS)



573749 C732354R

THE USE OF A HYBRID COMPUTER IN THE OPTIMIZATION OF GAS TURBINE  
CONTROL PARAMETERS

SARAVANAMUTTOO, H.I.R., MACISAAC, B.D. ; CARLETON UNIV., OTTAWA,  
CANADA

TRANS. ASME SER. A (USA) VOL.95, NO.3 257-64 JULY 1973  
CODEN: JRPOA8

DESCRIPTORS: HYBRID COMPUTER METHODS, CONTROL ENGINEERING  
APPLICATIONS OF COMPUTERS, GAS TURBINES, OPTIMISATION, SIMULATION,  
AUTOMATIC CONTROL

IDENTIFIERS: SINGLE SPOOL, TURBOJET ENGINE, AUTOMATIC CONTROL,  
HYBRID COMPUTER, OPTIMIZATION, GAS TURBINE, CONTROL PARAMETERS,  
SIMULATION, THRUST RESPONSE, ENGINE DYNAMICS

SECTION CLASS CODES: C7851, C8846, C8849

UNIFIED CLASS CODES: VHKAD, WHEKAS, WHEZAN

THE PAPER DISCUSSES THE HYBRID COMPUTER SIMULATION OF A SINGLE-SPOOL  
TURBOJET ENGINE. THE PROBLEM IS APPROACHED FROM THE VIEWPOINT OF  
ENGINEERING THERMODYNAMICS, USING THE NORMAL COMPRESSOR AND TURBINE  
CHARACTERISTICS. THIS WAS FOUND TO YIELD AN EXTREMELY FLEXIBLE  
SIMULATION CAPABLE OF OPERATION OVER THE ENTIRE RUNNING RANGE. THE  
SIMULATION WAS USED TO INVESTIGATE METHODS OF IMPROVING THE THRUST  
RESPONSE AND IT WAS FOUND THAT A DETAILED INSIGHT INTO THE ENGINE  
DYNAMICS PERMITTED A SIGNIFICANT IMPROVEMENT IN THRUST RESPONSE (6  
REFS)

564358 C7322595

PROCESSING ENGINE TEST DATA USING SPEED

WARMAN, E.A., SCOTT, S.W.

; IEE, ET AL

STD BOOK NO.: 0 85296114 6

CONFERENCE ON THE USE OF DIGITAL COMPUTERS IN MEASUREMENT 94-8  
1973

24-27 SEPT. 1973 IEE, ET AL YORK, ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, ENGINEERING APPLICATIONS  
OF COMPUTERS, MACHINE TESTING, COMPUTER AIDED ANALYSIS

IDENTIFIERS: PROCESSING, ENGINE, TEST DATA, SPEED, COMPUTERS

SECTION CLASS CODES: C8849

UNIFIED CLASS CODES: WHEZAN

SPEED: A SYSTEM FOR PROCESSING EXPERIMENTAL ENGINE DATA IS A SYSTEM  
OF HARDWARE AND SOFTWARE BEING DEVELOPED BASICALLY FOR THE OFF LINE  
PROCESSING OF MEASUREMENT DATA FROM ENGINES. THE AIM HAS BEEN TO  
CREATE FLEXIBILITY OF USE. A BUILDING BLOCK CONSTRUCTION OF EQUIPMENT  
HAS BEEN EMPLOYED. TO DATE THE EQUIPMENT HAS RESOLVED INTO A PERMANENT  
INSTALLATION IN THE NOISE FACILITY: AND A PORTABLE SYSTEM (2 REFS)

555037 B7333727, C7320776

GUIDELINES IN DESIGNING A DIGITAL DATA ACQUISITION SYSTEM  
WESTWICK, J.F. ; GENERAL MOTORS CORP., INDIANAPOLIS, IND., USA  
ROBERTS, R.R.  
; ISA

STD BOOK NO.: 87664 182 6

PROCEEDINGS OF THE 18TH INTERNATIONAL ISA AEROSPACE INSTRUMENTATION  
SYMPOSIUM, VOL. 18 29-35 1972

15-17 MAY 1972 ISA MIAMI, FLA., USA

PUBL: ISA PITTSBURGH, PA., USA

DESCRIPTORS: DATA ACQUISITION, GAS TURBINES, AEROSPACE TEST  
FACILITIES, REAL-TIME SYSTEMS, ENGINEERING APPLICATIONS OF COMPUTERS  
IDENTIFIERS: DESIGN, SOLID STATE HIGH SPEED COMPUTER HARDWARE,  
AEROSPACE, INDUSTRIAL, GAS TURBINE ENGINE DEVELOPMENT, HIGH SPEED,  
TRANSIENT CONDITIONS, GRAPHIC OUTPUT, REAL TIME OPERATION, DIGITAL  
DATA ACQUISITION SYSTEM

SECTION CLASS CODES: C8849, B4720, B5244

UNIFIED CLASS CODES: WHEZAN, ZLEAAZ, TEGEAT

DIGITAL DATA ACQUISITION SYSTEM DEVELOPMENT AND DESIGN HAS BECOME  
MORE SOPHISTICATED WITH THE AVAILABILITY OF SOLID STATE HIGH SPEED  
COMPUTER HARDWARE AND :REAL-TIME: MONITOR SOFTWARE. THE NEWLY  
INSTALLED SYSTEM AT DETROIT DIESEL ALLISON SUPPORTS AEROSPACE AND  
INDUSTRIAL GAS TURBINE ENGINE DEVELOPMENT TEST PROGRAMS BY PROVIDING  
HIGH SPEED ACQUISITION OF DATA, DISPLAY OF REAL-TIME PERFORMANCE TO  
THE TEST ENGINEER USING THE ACQUIRED DATA, AND QUICK RETURN OF FINAL  
PERFORMANCE RESULTS IN GRAPHIC AND TABULAR FORM. THE SYSTEM IS USED  
ALSO TO RECORD TRANSIENT CONDITIONS OF PERFORMANCE AND PROVIDE GRAPHIC  
OUTPUT OF THESE CONDITIONS FOR ANALYSIS

555002 R7333730, C7320740

DEVELOPMENT OF A DIGITAL CONTROL SYSTEM FOR A SPACECRAFT PROPULSION TEST FACILITY

SHALLEY, R.R. ; NASA, PLUM BROOK STATION, SANDUSKY, OHIO, USA

ROBERTS, R.R.

; ISA

STD BOOK NO.: 87664 182 6

PROCEEDINGS OF THE 18TH INTERNATIONAL ISA AEROSPACE INSTRUMENTATION SYMPOSIUM, VOL. 18 69-72 1972

15-17 MAY 1972 ISA MIAMI, FLA., USA

IUBL: ISA PITTSBURGH, PA., USA

DESCRIPTORS: AEROSPACE PROPULSION, AEROSPACE TEST FACILITIES, CONTROL SYSTEMS, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: CONTROL SYSTEM, SPACECRAFT PROPULSION TEST FACILITY, DIGITAL COMPUTER CONTROL, ABORT SYSTEM, ROCKET ENGINE TESTING, STRUCTURE TESTING, WIND TUNNEL TESTS, CONTROL FUNCTION UPDATING, CONTINUOUS ABORT MONITORING, SOFTWARE, SHORT DURATION TESTS, HARDWARE

SECTION CLASS CODES: B4720, C8846, C7875

UNIFIED CLASS CODES: ZLEAAZ, WMEKAS, VHRMAY

A DIGITAL COMPUTER CONTROL AND ABORT SYSTEM WHICH IS USED AT NASA-LEWIS RESEARCH CENTER'S PLUM BROOK TEST FACILITIES IS DESCRIBED. THE SYSTEM WAS DESIGNED BY NASA PERSONNEL TO CONTROL TEST OPERATIONS SUCH AS ROCKET ENGINE TESTING, STRUCTURE TESTING, AND WIND TUNNEL TESTS. BECAUSE OF THE NATURE OF SPACECRAFT SYSTEM TESTING, PARTICULARLY ROCKET ENGINE TESTING, THE UNIQUE FEATURES OF THE SYSTEM ARE, CONTROL FUNCTION UPDATING AT A 20 MILLISECOND RATE, CONTINUOUS ABORT MONITORING AND A SOFTWARE SYSTEM DESIGNED FOR SHORT DURATION TESTS RATHER THAN CONTINUOUS ON-LINE CONTROL. TO ACCOMPLISH THESE SYSTEM REQUIREMENTS, SPECIAL HARDWARE WAS DESIGNED

555001 B7333728, C7320739

SUPERVISORY COMPUTER CONTROL OF JET ENGINE DUAL COMPRESSOR TESTS  
 GOODWIN, W., SELLERCK, F.G., WATERMAN, A. ; UNITED AIRCRAFT CORP.,  
 EAST HARTFORD, CONN., USA

ROBERTS, R.R.

; ISA

STD BOOK NO.: 87664 782 6

PROCEEDINGS OF THE 18TH INTERNATIONAL ISA AEROSPACE INSTRUMENTATION  
 SYMPOSIUM, VOL. 18 37-47 1972

15-17 MAY 1972 ISA MIAMI, FLA., USA

PUBL: ISA PITTSBURGH, PA., USA

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE TEST  
 FACILITIES, AEROSPACE ENGINES, CONTROL ENGINEERING APPLICATIONS OF  
 COMPUTERS, CONTROL SYSTEMS, COMPRESSORS

IDENTIFIERS: SUPERVISORY COMPUTER CONTROL, JET ENGINE DUAL  
 COMPRESSOR, DIGITAL COMPUTER CONTROLLED, TESTING, COAXIAL GAS TURBINE,  
 OPERATING PARAMETERS, AERODYNAMIC CONDITIONS, RELIABILITY, FLEXIBILITY  
 , SYSTEM DESIGN

SECTION CLASS CODES: B4720, C8846, C7851

UNIFIED CLASS CODES: ZLEAAZ, WHEKAS, VHKCAD

DIGITAL COMPUTER CONTROLLED TESTING OF SEPARATELY DRIVEN COAXIAL GAS  
 TURBINE LOW PRESSURE AND HIGH PRESSURE COMPRESSORS, REFERRED TO AS  
 :DUAL COMPRESSOR TESTING,: HAS BEEN IMPLEMENTED SUCCESSFULLY. THE  
 SUPERVISORY CONTROL SYSTEM MEASURES, COMPUTES, AND CONTROLS DUAL  
 COMPRESSOR OPERATING PARAMETERS, MAINTAINING DESIRED AERODYNAMIC  
 CONDITIONS DURING TESTS. THIS ACHIEVED BY COMPUTER CONTROL OF TWO GAS  
 TURBINE DRIVE ENGINES OF 18000 HP AND 35000 HP, AND SIX FAST-ACTING  
 CONTROL VALVES, RANGING UP TO SIX FEET IN DIAMETER. RELIABILITY AND  
 FLEXIBILITY WERE EMPHASIZED IN THE SYSTEM DESIGN

546160 C7318686

AN ENGINE TEST LANGUAGE FOR COMPUTER CONTROL OF ENGINE TESTS

WARMAN, E.A.

; IEE, ET AL

STD BOOK NO.: 0 85296111 1

CONFERENCE ON SOFTWARE FOR CONTROL 137-44 1973

17-19 JULY 1973 IEE, ET AL WARWICK, ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: AUTOMATIC TESTING, HEAT ENGINES, CONTROL ENGINEERING  
 APPLICATIONS OF COMPUTERS, PROBLEM-ORIENTED LANGUAGES

IDENTIFIERS: ENGINE TEST LANGUAGE, COMPUTER CONTROL, ENGINE TESTS,  
 GET L

SECTION CLASS CODES: C8314, C7851, C8846

UNIFIED CLASS CODES: WECEAR, VHKCAD, WHEKAS

A RESEARCH INVESTIGATION INTO THE POSSIBLE LEVELS OF AUTOMATION AND  
 COMPUTER INVOLVEMENT IN ENGINE TESTING INDICATED IT WOULD BE DESIRABLE  
 TO DEVELOP A PROGRAMMING LANGUAGE FOR DESCRIBING ENGINE TESTING  
 SEQUENCES. WORK SUBSEQUENT TO THIS INVESTIGATION IS NOW CONCERNED WITH  
 EXPANDING THIS LANGUAGE TO ALLOW IT TO DEAL WITH ANY PROCESS  
 SEQUENCING SITUATION (5 REFS)

526710 C7315029

THE SCIENTIFIC AND TECHNOLOGICAL INFORMATION SYSTEM OF THE KARL LIBKNECHT WORKS AT MAGDEBURG

KARSTEN, E. ; VER SCHWERNASCHINENBAU :KARL LIBKNECHT:, MAGDEBURG, GERMANY

INFORMATIK (GERMANY) VOL.20, NO.1 12-14 1973 CODEN: IIDWAN

DESCRIPTORS: INFORMATION DISSEMINATION, INFORMATION CENTRES, INFORMATION USE, INFORMATION RETRIEVAL SYSTEMS, MINICOMPUTERS

IDENTIFIERS: SCIENTIFIC AND TECHNOLOGICAL INFORMATION SYSTEM, EAST GERMAN DEMOCRATIC REPUBLIC, INFORMATION CENTRE, MINI COMPUTER, DATA BANK, DIESEL ENGINE CHARACTERISTICS, INFORMATION DISSEMINATION

SECTION CLASS CODES: C8580, C8520

UNIFIED CLASS CODES: ZTRAAR, ZTEAAH

LANGUAGE: GERMAN

THIS FACTORY IN THE EAST GERMAN DEMOCRATIC REPUBLIC PRODUCES DIESEL ENGINES AND OTHER HEAVY INDUSTRIAL EQUIPMENT, ALSO FOR THE PETROLEUM INDUSTRY. THE INFORMATION CENTRE AT THE WORKS USES A MINI COMPUTER FOR BUILDING UP A DATA BANK OF DIESEL ENGINE CHARACTERISTICS. VARIOUS PUBLICATIONS DISSEMINATE USEFUL INFORMATION (ON DIESEL ENGINES AND RELATED SUBJECTS) TO WIDER CIRCLES. THE CENTRE COOPERATES WITH ITS POLISH AND RUSSIAN COUNTERPARTS AND FORMS A CONSTITUENT PART OF THE STATE-CONTROLLED SCIENTIFIC AND TECHNOLOGICAL INFORMATION SYSTEM OF THE EAST GERMAN REPUBLIC

525758 C7313966

COLLOQUIUM DIGEST ON COMPUTER STRUCTURES FOR ARTIFICIAL INTELLIGENCE ; IEE, IERE

1973

11 MAY 1973 IEE, IERE LONDON, ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: ARTIFICIAL INTELLIGENCE, BOILERS, COMPUTER APPLICATIONS, CONTROLLERS, LEARNING SYSTEMS

IDENTIFIERS: COMPUTER STRUCTURES, ARTIFICIAL INTELLIGENCE, COMPUTATIONAL PROBLEMS, LEARNING NETS, MINERVA AND ASTRA LEARNING SYSTEMS, OBJECT MOTION SIMULATION, HUMAN CONTROLLERS, ADAPTIVE CONTROLLERS, STEAM ENGINE BOILER SYSTEM, NEURON PLASTIC CHANGE MODELS

SECTION CLASS CODES: C6440, C8890

UNIFIED CLASS CODES: VCKAAR, WMZAAP

THE FOLLOWING TOPICS WERE DEALT WITH: HUMAN AND AUTOMATIC ADAPTIVE CONTROLLERS, COMPUTATIONAL PROBLEMS, DYNAMIC DIGITAL LEARNING NETS, MINERVA AND ASTRA LEARNING SYSTEMS, ITERATIVE ARRAYS FOR OBJECT MOTION SIMULATION, MODELS OF PLASTIC CHANGE IN NEURONS, AND APPLICATIONS TO STEAM ENGINE-BOILER SYSTEM. 9 PAPERS WERE PRESENTED, OF WHICH ALL ARE PUBLISHED IN FULL IN THE PRESENT PROCEEDINGS

518935 C7312556

## ELECTRONIC FUEL INJECTION SYSTEM

GORDON, C.C., MCGAVIC, J.P.

PATENT NO.: USA 3702601 ASSIGNEES: GENERAL MOTORS CORP. FILED:  
11 JUNE 1971

ORIGINAL PATENT APPL. NO.: USA 152088

14 NOV. 1972

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, DIGITAL CONTROL, FLOW CONTROL

IDENTIFIERS: ELECTRONIC FUEL INJECTION SYSTEM, INTERNAL COMBUSTION ENGINE, FUEL INJECTORS, TIMING SIGNALS, SYNCHRONIZATION, MAGNITUDE PERMUTATIONS, PULSE TRAIN, CONTROL PULSES, ENGINE CYCLE

SECTION CLASS CODES: C7851, C7453

UNIFIED CLASS CODES: VMKAD, VGEVAS

AN INTERNAL COMBUSTION ENGINE INCLUDES A GROUP OF EIGHT FUEL INJECTORS FOR APPLYING FUEL TO THE ENGINE. A SET OF FOUR TIMING SIGNALS DEVELOPED IN SYNCHRONIZATION WITH ENGINE OPERATION COLLECTIVELY CONTAIN EIGHT MAGNITUDE PERMUTATIONS PER ENGINE CYCLE. THE OCCURRENCE OF EACH OF THE MAGNITUDE PERMUTATIONS DEFINES THE START OF INJECTION FOR A CORRESPONDING ONE OF THE FUEL INJECTORS. THE SET OF TIMING SIGNALS IS COMBINED TO FORM A PAIR OF TIMING SIGNALS WHICH ARE COMBINED TO FORM A SINGLE TIMING SIGNAL CONTAINING ALL OF THE MAGNITUDE PERMUTATIONS. A SINGLE PULSE TRAIN DEVELOPED IN SYNCHRONIZATION WITH THE SINGLE TIMING SIGNAL CONTAINS EIGHT CONTROL PULSES PER ENGINE CYCLE. THE LENGTH OF EACH OF THE CONTROL PULSES DEFINES THE PERIOD OF INJECTION FOR A CORRESPONDING ONE OF THE FUEL INJECTORS IN TIME COMPRESSED NONOVERLAPPING RELATIONSHIP. THE SINGLE PULSE TRAIN IS SEPARATED BY THE SINGLE TIMING SIGNALS TO FORM A PAIR OF PULSE TRAINS WHICH ARE SEPARATED BY THE PAIR OF TIMING SIGNALS TO FORM A SET OF FOUR PULSE TRAINS COLLECTIVELY CONTAINING ALL OF THE CONTROL PULSES. THE LENGTH OF THE CONTROL PULSES IN THE SET OF PULSE TRAINS IS EXTENDED TO DEFINE THE PERIOD OF INJECTION FOR THE FUEL INJECTORS IN TIME EXPANDED OVERLAPPING RELATIONSHIP. LASTLY, THE SET OF PULSE TRAINS IS SEPARATED BY THE SET OF TIMING SIGNALS TO FORM A SERIES OF EIGHT PULSE TRAINS EACH CONTAINING CONTROL PULSES WHICH ARE APPLIED TO ENERGIZE A CORRESPONDING ONE OF THE GROUP OF EIGHT FUEL INJECTORS

509024 B7318684, C7310722

A COMPUTER SYSTEM FOR PROCESS CONTROL AND PREDICTIVE MAINTENANCE OF A DIESEL ENGINE ON A SEAGOING VESSEL

DRAGER, K.H., LILAND, H. ; DET NORSKE VERITAS, OSLO, NORWAY

; INSTRUMENT SOC. AMERICA

STD BOOK NO.: 87664 190 9

PROCEEDINGS OF THE 27TH ANNUAL ISA CONFERENCE 502/12PP. 1972

9-12 OCT. 1972 INSTRUMENT SOC. AMERICA NEW YORK, USA

PUBL: INSTRUMENT SOC. AMERICA PITTSBURGH, PA., USA

DESCRIPTORS: MAINTENANCE ENGINEERING, INTERNAL COMBUSTION ENGINES, PROCESS CONTROL, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, SHIPS

IDENTIFIERS: COMPUTER SYSTEM, PROCESS CONTROL, DIESEL ENGINE, SEAGOING VESSEL, SENSORS, RING CONDITION, COMBUSTION, OPTIMAL MAINTENANCE, COMPUTER HARDWARE, SOFTWARE SYSTEM, RELIABILITY, HEAT SYSTEMS, TRANSPORTATION, MARINE SYSTEMS

SECTION CLASS CODES: B5246, B1263, C7874, C7851, C8846

UNIFIED CLASS CODES: TEGGAE, ADGDAL, VHRKAM, VMKAD, WHEKAS

THIS PAPER DESCRIBES A COMPUTER SYSTEM INSTALLED ONBOARD A LARGE NORWEGIAN TANKER FOR PROCESS CONTROL AND PREDICTIVE MAINTENANCE OF THE PROPULSION MACHINERY; A SULZER DIESEL ENGINE (4 REFS)

499678 B7315460, C7308672

VIRGULE VARIABLE-GEOMETRY WHEELED TELEOPERATOR

VERTUT, J., GUILAUD, J.-P., DERRIE, G., GERMOND, J.-C., RICHE, P. ; COM. ENERGIE ATOMIQUE, SACLAY, FRANCE

PARMAKES, R.

; AMERICAN NUCLEAR SOC

PROCEEDINGS OF THE 20TH CONFERENCE ON REMOTE SYSTEMS TECHNOLOGY 303-9 1972

19-21 SEPT. 1972 AMERICAN NUCLEAR SOC IDAHO FALLS, IDAHO, USA

PUBL: AMERICAN NUCLEAR SOC. HINSDALE, ILL., USA

DESCRIPTORS: ROAD VEHICLES, TELECONTROL EQUIPMENT, DRIVES

IDENTIFIERS: TV CAMERAS, DIGITAL COMMUNICATIONS LINK, MA22 MASTER SLAVE MANIPULATORS, VARIABLE GEOMETRY WHEELED TELEOPERATOR, VIRGULE, RADIO CONTROLLED RESCUE VEHICLE, BATTERY POWERED FOR SHORT TERM OPERATIONS, PETROL ENGINE DRIVEN FOR LONG TERM OPERATIONS

SECTION CLASS CODES: B5620, C7871, C7640

UNIFIED CLASS CODES: TKEAR, VMCAZ, VKGAAN

VIRGULE IS A FRENCH ACRONYM REFERRING TO A RADIO-CONTROLLED RESCUE VEHICLE CAPABLE OF OPERATING OVER ROUGH TERRAIN EITHER INDOORS OR OUTDOORS. THE TELEOPERATOR IS EQUIPPED WITH AT LEAST TWO TV CAMERAS AND ONE PAIR OF MA22 MASTER-SLAVE MANIPULATORS, EACH CAPABLE OF EXERTING 12-KG FORCES IN ANY DIRECTION, AND OF LIFTING UP TO 30 KG IN CERTAIN POSITIONS. THE FOUR-WHEELED VEHICLE HAS MORE FLEXIBILITY THAN A TRACK VEHICLE. IT CAN MOVE IN A STRAIGHT LINE IN ANY DIRECTION (REFERRED TO ITS OWN AXIS) AND CAN STEER ABOUT ANY CENTER OF ROTATION, CONTROLLED BY A SINGLE CONTROL HANDLE WITH THREE DEGREES-OF-FREEDOM. WHEN THE VEHICLE IS MOVING, ONLY ONE ARM CAN BE OPERATED. A 24-CHANNEL DIGITAL COMMUNICATIONS LINK IS USED FOR CONTROL, AND ANOTHER ONE FOR FEEDBACK. THESE LINKS MAY BE RADIO OR COAXIAL CABLE. BATTERIES PROVIDE SHORT-TERM AUTONOMOUS OPERATION; POWER MAINS (INDOORS) OR A GASOLINE-ENGINE-DRIVEN GENERATOR (OUTDOORS) ARE USED FOR LONG OPERATION (8 REFS)

489569 B7311094, C7306088

DIGITAL ROTATION SPEED MEASUREMENT FOR INTERNAL-COMBUSTION ENGINES  
LOSFL, M.E.

MESS. AND PRUEF. (GERMANY) VOL.8, NO.9 539-41 SEPT. 1972

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, FREQUENCY MEASUREMENT,  
DIGITAL CIRCUITS, ANGULAR VELOCITY MEASUREMENTIDENTIFIERS: DIGITAL MEASUREMENT, INTERNAL COMBUSTION ENGINE,  
IGNITION PULSE, ROTATION SPEED MEASUREMENT, IGNITION IMPULSE FREQUENCY  
, IGNITION IMPULSE INTERVAL

SECTION CLASS CODES: B5246, B4455, C7455, B1870

UNIFIED CLASS CODES: TEGGAE, BKEZAK, ETNAAP

LANGUAGE: GERMAN

FOR THE DIGITAL MEASUREMENT OF THE ROTATION SPEED OF AN INTERNAL  
COMBUSTION ENGINE, THE IGNITION PULSE IS GENERALLY USED. TWO SOLUTIONS  
ARE DEALT WITH: DETERMINING THE IGNITION-IMPULSE-FREQUENCY AND  
DETERMINING THE IGNITION-IMPULSE-INTERVAL. BOTH SCHEMES ARE DESCRIBED

488746 B7311423, C7304089

PROCESS COMPUTER CONTROLS RETARDER AND HUMP SHUNTING ENGINE  
HETZ, K.DTSCH. EISENBAHNTECH. (GERMANY) VOL.20, NO.11 490-4 NOV. 1972  
CODEN: DEPTANDESCRIPTORS: LOCOMOTIVES, CONTROL ENGINEERING APPLICATIONS OF  
COMPUTERS, BRAKES, PROCESS CONTROLIDENTIFIERS: RETARDER, HUMP SHUNTING ENGINE, EFFICIENCY, HUMP,  
PROCESS COMPUTER CONTROL

SECTION CLASS CODES: B5620, C7872, C8846, C8849

UNIFIED CLASS CODES: TKEAAR, VMREAK, WMPKAS, WMPZAN

LANGUAGE: GERMAN

THE EFFICIENCY OF A HUMP IS DECISIVELY DETERMINED BY THE TIMES OF  
LOSS AND SHUNTING SPEED. AN INSTALLATION AT THE GOODS STATION OF HALLE  
IS PRESENTED WHERE THE EFFICIENCY WAS INCREASED BY 5.5 PER CENT UNDER  
EXPERIMENTAL CONDITIONS



488701 R7311364, C7303952

MODIFICATION OF A FUEL-CELL ENGINE FOR CONTROL BY A DIGITAL COMPUTER  
HAGEDORN, N.H.

REPORT NO.: NASA-TM-X-2575 ISSUED BY: NASA, CLEVELAND, OHIO, USA  
JUNE 1972

DESCRIPTORS: FUEL CELLS, CONTROL ENGINEERING APPLICATIONS OF  
COMPUTERS, ELECTRICAL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: DIGITAL COMPUTER, SOLENOID VALVES, TRANSDUCERS, LIMIT  
SWITCHES, LOAD, ELECTROLYTE CONCENTRATION, SYSTEM SHUTDOWN, FUEL CELL  
ENGINE, DIRECT ENERGY CONVERSION

SECTION CLASS CODES: B5416, C7856, C8841, C8846

UNIFIED CLASS CODES: EVCGAH, VMKKAR, WMECAE, WMEKAS

AVAILABILITY: NTIS, SPRINGFIELD, VA. 22151, USA

A MANUALLY OPERATED FUEL-CELL SYSTEM WAS MODIFIED TO BE MONITORED  
AND CONTROLLED BY A DIGITAL COMPUTER. THE PURPOSE WAS TO HAVE A TEST  
ITEM WITH WHICH TO STUDY POSSIBLE SYSTEM-COMPUTER INTERFACE PROBLEMS.  
THE MODIFICATION CONSISTED OF INSTALLING SOLENOID VALVES, CIRCUITRY,  
TRANSDUCERS, AND LIMIT SWITCHES ON THE SYSTEM. THESE MODIFICATIONS  
PERMIT COMPUTER CONTROL OF LOAD CURRENT, REACTANT PURGE, WATER  
REMOVAL, AND ELECTROLYTE CONCENTRATION AND COMPUTER INITIATION OF  
SYSTEM SHUTDOWN

480219 B7307008, C7304913

WASTE GAS UTILISATION IN MARINE ENGINE INSTALLATIONS

BPHLORADSKY, E.-J.

FRENNST.-WAERME-KRAFT (BWK) (GERMANY) VOL. 24, NO. 11 411-15  
NOV. 1972 CODEN: PRWKAY

DESCRIPTORS: BOILERS, STEAM PLANTS, MARINE SYSTEMS, COMPUTER-AIDED  
DESIGN, SHIPS

IDENTIFIERS: COMPUTER PROGRAMMES, LOAD DEPENDENT BEHAVIOUR, WASTE  
GAS UTILISATION, MARINE ENGINE INSTALLATIONS, OPERATIONAL EFFICIENCY,  
THERMAL ENERGY, STEAM TURBINE, TURBOGENERATOR, DESIGN, WASTE GAS  
BOILER PLANTS

SECTION CLASS CODES: F5242, C8841

UNIFIED CLASS CODES: TEGCAR, WMECAE

LANGUAGE: GERMAN

WASTE HEAT BOILER PLANTS APPEAR PARTICULARLY SUITABLE TO IMPROVE THE  
TOTAL OPERATIONAL EFFICIENCY. PART OF THE THERMAL ENERGY OF THE ENGINE  
WASTE GASES CAN BE TRANSMITTED IN A WASTE HEAT BOILER TO A WORKING  
MEDIUM WHICH FLOWS THROUGH A SEPARATE CYCLE, FOR INSTANCE THE STEAM  
TURBINE OF A TURBOGENERATOR. COMPUTER PROGRAMS FOR FULL AND PART-LOAD  
CONDITIONS HAVE BEEN DEVELOPED FOR THE DESIGN OF WASTE GAS BOILER  
PLANTS. WASTE HEAT BOILERS FOR TWO ENGINE INSTALLATIONS HAVE BEEN  
DESIGNED TAKING CERTAIN RESTRICTIONS INTO CONSIDERATION, AND THEIR  
LOAD-DEPENDENT BEHAVIOUR PREDICTED, BASED ON CALCULATED RESULTS (13  
REFS)

479246 C730391P

## COMPUTER CONTROLLED ENGINE TESTING

TAYLOR, J.C. ; LONDON COLL. PRINTING, ENGLAND

; IEE, INST. MECH. ENGRS

COLLOQUIUM DIGEST ON CONTROL APPLICATIONS OF MINI-COMPUTERS  
5/1-6PP. 1972

13 DEC. 1972 IEE, INST. MECH. ENGRS LONDON, ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: HEAT ENGINES, AUTOMATIC TESTING, CONTROL ENGINEERING  
APPLICATIONS OF COMPUTERSIDENTIFIERS: COMPUTER CONTROLLED, ENGINE TESTING, TEST BEDS, SPC 16,  
PETROL ENGINES, DIESEL ENGINES

SECTION CLASS CODES: C7851, C8846, C8849

UNIFIED CLASS CODES: VMKAD, WMEKAS, WMEZAN

DESCRIBES TWO ENGINE TEST BEDS THAT HAVE BEEN BUILT AND FULLY  
INSTRUMENTED FOR COMPUTER CONTROL. THE TWO TEST BEDS ARE CONTROLLED  
LOCALLY WITH ANALOGUE 3-TERM CONTROLLERS IN EACH CONTROL LOOP. THE  
SET-POINT INPUTS TO THE CONTROLLERS CAN BE SWITCHED SO THAT EITHER  
LOCAL MANUAL CONTROL OR CONTROL FROM ANALOGUE OUTPUT FROM A DIGITAL  
COMPUTER IS POSSIBLE. THE TWO BEDS ARE LINKED TO A GENERAL AUTOMATION  
SPC 16 DIGITAL COMPUTER VIA AN INTERFACE

466783 C7302327

GENERALIZED SIMULATION TECHNIQUE FOR TURBOJET ENGINE SYSTEM ANALYSIS  
SELDNER, K., MIHALOEW, J.R., BLAHA, R.J.REPORT NO.: NASA-TN-D-6610 ISSUED BY: NASA, CLEVELAND, OHIO, USA  
FEB. 1972DESCRIPTORS: HEAT ENGINES, AEROSPACE APPLICATIONS OF COMPUTERS,  
ANALOGUE COMPUTER METHODS, SIMULATION, COMPUTER-AIDED ANALYSISIDENTIFIERS: GENERALIZED SIMULATION TECHNIQUE, TURBOJET ENGINE  
SYSTEM ANALYSIS, PROPULSION SYSTEM DYNAMICS, CONTROLS RESEARCH,  
SCHEMATIC MODEL, BASIC CONSERVATION EQUATIONS, PERFORMANCE  
CHARACTERISTICS, NONLINEAR ANALOGUE SIMULATION, ANALOGUE COMPUTER

SECTION CLASS CODES: C8849, C9980

UNIFIED CLASS CODES: WMEZAN, XTMAAH

AVAILABILITY: NTIS, SPRINGFIELD, VA. 22151, USA

A NONLINEAR ANALOG SIMULATION OF A TURBOJET ENGINE WAS DEVELOPED.  
THE PURPOSE OF THE STUDY WAS TO ESTABLISH SIMULATION TECHNIQUES  
APPLICABLE TO PROPULSION SYSTEM DYNAMICS AND CONTROLS RESEARCH. A  
SCHEMATIC MODEL WAS DERIVED FROM A PHYSICAL DESCRIPTION OF A J85-13  
TURBOJET ENGINE. BASIC CONSERVATION EQUATIONS WERE APPLIED TO EACH  
COMPONENT ALONG WITH THEIR INDIVIDUAL PERFORMANCE CHARACTERISTICS TO  
DERIVE A MATHEMATICAL REPRESENTATION. THE SIMULATION WAS MECHANIZED ON  
AN ANALOG COMPUTER. THE SIMULATION WAS VERIFIED IN BOTH STEADY-STATE  
AND DYNAMIC MODES BY COMPARING ANALYTICAL RESULTS WITH EXPERIMENTAL  
DATA OBTAINED FROM TESTS PERFORMED AT THE LEWIS RESEARCH CENTER WITH A  
J85-13 ENGINE. IN ADDITION, COMPARISON WAS ALSO MADE WITH PERFORMANCE  
DATA OBTAINED FROM THE ENGINE MANUFACTURER. THE COMPARISONS  
ESTABLISHED THE VALIDITY OF THE SIMULATION TECHNIQUE

466776 B7303350, C7302320

EXPERIMENTAL VERIFICATION OF A DIGITAL COMPUTER SIMULATION METHOD FOR PREDICTING GAS TURBINE DYNAMIC BEHAVIOUR

PAWKE, A.J., SARAVANAMUTTOO, H.I.H., HOLMES, M. ; GAS COUNCIL ENGNG. RES. STATION, NEWCASTLE UPON TYNE, ENGLAND

PROC. INST. MECH. ENG. (GB) VOL.186, PT.27 323-9 1972 CODEN: PINLAA

DESCRIPTORS: GAS TURBINES, TRANSIENT RESPONSE, SIMULATION, ENGINEERING APPLICATIONS OF COMPUTERS, MECHANICAL ENGINEERING

IDENTIFIERS: EXPERIMENTAL VERIFICATION, DIGITAL COMPUTER SIMULATION METHOD, GAS TURBINE, DYNAMIC BEHAVIOUR, MATHEMATICAL MODEL, TRANSIENT RESPONSE, TEST RESULTS, TWIN SPOOL GAS TURBINE ENGINE

SECTION CLASS CODES: B5244, C8849

UNIFIED CLASS CODES: TEGPAT, WMEZAN

A MATHEMATICAL MODEL WHICH SIMULATES THE TRANSIENT RESPONSE OF A TWIN-SPOOL GAS TURBINE ENGINE ON A GENERAL PURPOSE DIGITAL COMPUTER IS DESCRIBED TOGETHER WITH TEST RESULTS VERIFYING THE SIMULATION (5 REFS)

466770 C7302312

COMPUTER DIAGNOSIS OF THE VW

KAMINSKI, R.K.

INSTRUM. TECHNOL. (USA) VOL. 19, NO. 9 60-2 SEPT. 1972 CODEN: IRTCA4

DESCRIPTORS: SPECIAL PURPOSE COMPUTERS, VEHICLES, AUTOMATIC TEST EQUIPMENT, COMPUTER ARCHITECTURE, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: SPECIAL PURPOSE COMPUTER, COMPUTER DIAGNOSIS, ENGINE, HARDWARE, TEST PROCEDURES, IGNITION PERFORMANCE, ENGINE COMPRESSION

SECTION CLASS CODES: C8849, C9840

UNIFIED CLASS CODES: WMEZAN, XREAAP

SINCE MID-1971, ALL VOLKSWAGENS HAVE BEEN EQUIPPED FOR A UNIQUE VW COMPUTER DIAGNOSIS, MORE THAN 60 SEPARATE CHECKS TO DETERMINE THE CONDITION OF A CAR HAVE BEEN MADE. EACH OF THESE VWS CONTAIN SENSORS AND WIRING WHICH ARE CONNECTED TO A SOCKET IN THE ENGINE COMPARTMENT. AT THE DEALER'S SERVICE CENTER, AN UMBILICAL CORD WILL TIE THE VW TO A SPECIAL-PURPOSE COMPUTER AND THE APPROXIMATELY 21-MINUTE CHECKOUT WILL BEGIN. SYSTEM HARDWARE AND TEST PROCEDURES ARE EXPLAINED IN THIS ARTICLE (3 REFS)

466769 H7302803, C7302311

DESIGNING DIGITAL DATA ACQUISITION SYSTEMS

WESTWICK, J.E.

INSTRUM. TECHNOL. (USA) VOL. 19, NO. 9 45-9 SEPT. 1972

CODEN: IRTCA4

DESCRIPTORS: COMPUTER GRAPHICS, DATA ACQUISITION, AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE ENGINES, AEROSPACE TEST FACILITIES, GAS TURBINES, TESTING

IDENTIFIERS: DESIGNING, DIGITAL DATA ACQUISITION SYSTEMS, COMPUTER HARDWARE, AEROSPACE, INDUSTRIAL GAS TURBINE ENGINE DEVELOPMENT, HIGH SPEED, DISPLAY, TEST ENGINEER, GRAPHIC, TABULAR FORM, REAL TIME PERFORMANCE, REAL TIME MONITOR SOFTWARE, SOLID STATE HARDWARE

SECTION CLASS CODES: C8849, C8440, R4740

UNIFIED CLASS CODES: WHEZAN, WGEAAJ, ZLGAAP

DIGITAL DATA ACQUISITION SYSTEM DEVELOPMENT AND DESIGN HAVE BECOME MORE SOPHISTICATED WITH THE AVAILABILITY OF SOLID-STATE COMPUTER HARDWARE AND REAL-TIME MONITOR SOFTWARE. A NEW SYSTEM, BASED ON DESIGN GUIDELINES REVIEWED IN THIS ARTICLE, AT GM'S DETROIT DIESEL ALLISON DIVISION SUPPORTS AEROSPACE AND INDUSTRIAL GAS TURBINE ENGINE DEVELOPMENT PROGRAMS. THE COMPUTER-BASED SYSTEM PROVIDES HIGH SPEED ACQUISITION OF DATA, DISPLAY OF REAL-TIME PERFORMANCE TO THE TEST ENGINEER AND QUICK RETURN OF FINAL PERFORMANCE RESULTS IN GRAPHIC AND TABULAR FORM

466713 C7302255

SOLUTION OF DYNAMICS OF INDIRECT CONTROL OF SHIP-PROPULSION SETS ON AN ANALOGUE COMPUTER APPLIED TO THE CKD TYPE 6L 525 II PV MARINE ENGINE

SUBRI, M.

CZECH. HEAVY IND. (CZECHOSLOVAKIA) NO.1 18-25 1972 CODEN: CZHIAR

DESCRIPTORS: STABILITY, NON-LINEAR SYSTEMS, CONTROLLERS, ANALOGUE COMPUTER METHODS, MARINE SYSTEMS, HEAT SYSTEMS, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: ANALOGUE COMPUTER, MARINE ENGINE, DIESEL ENGINE, CONTROL SYSTEMS, PROPORTIONAL PLUS INTEGRAL, CONTROLLER, PROPELLER, GENERATOR, CENTRIFUGAL GOVERNOR, DISTRIBUTION GEAR WITH SLIDE VALVE, SERVOPISTON, ELASTIC FEEDBACK, DROOP, SHIP PROPULSION SETS, HARMONIC DISTURBANCES, LOAD STEP CHANGES, CONSTANT SPEED STABILISER

SECTION CLASS CODES: C8846, C9980, C6620, C6690

UNIFIED CLASS CODES: WHEKAS, XTMAAH, VEEAAW, VEVAAC

FOR RELIABLE AND SAFE OPERATION OF SHIP-PROBLEM SETS WITH DIESEL ENGINES, THE BEHAVIOUR OF THESE SETS AS CONTROL SYSTEMS MUST BE KNOWN IN ADVANCE. THE EXISTING METHODS DO NOT ENABLE THE PROPERTIES OF THESE SETS TO BE DETERMINED WITH ADEQUATE ACCURACY AND THE TESTS TO BE CONDUCTED ON FINISHED SETS LEAVING THE FACTORY. AN ANALOGUE COMPUTER SOLUTION TO THIS NONLINEAR PROBLEM IS OFFERED. A PROPORTIONAL PLUS INTEGRAL CONTROLLER IS USED IN A SYSTEM OF DIESEL ENGINE, GEAR BOX AND PROPELLER OR GENERATOR. THE BEHAVIOUR WAS STUDIED FOR STORMY WEATHER CONDITIONS

465706 B7302810, C7301131

## NERVA FLIGHT ENGINE CONTROL SYSTEM DESIGN

NORMAN, H.H., PARZIALF, E.A., SALUJA, J.K., SCHENZ, R.F., JR. ;  
WESTINGHOUSE ELECTRIC CORP., SACRAMENTO, CALIF., USA

NUCL. TECHNOL. (USA) VOL.15, NO.3 447-54 1972 CODEN: NUTYBB

DESCRIPTORS: AEROSPACE PROPULSION, AUTOMATIC CONTROL APPLICATIONS,  
NUCLEAR POWER, NUCLEAR SYSTEMS, AEROSPACE CONTROLIDENTIFIERS: NERVA FLIGHT ENGINE CONTROL SYSTEM DESIGN, NUCLEAR  
ROCKET ENGINE, MULTILoop CLASSICAL CONTROLS DESIGN APPROACH, HIGH  
DEGREE OF COUPLING, MULTIVARIABLE NATURE, SYSTEM MODEL LINEARIZATION,  
SYSTEM SIMPLIFICATION, QUADRATIC OPTIMAL CONTROL DESIGN, TRANSIENT  
PERFORMANCE, DIGITAL IMPLEMENTATION

SECTION CLASS CODES: C7854, B4760

UNIFIED CLASS CODES: VMKGAA, ZLKAAH

MODERN CONTROL SYSTEM THEORY HAS BEEN APPLIED TO THE DESIGN OF THE  
CONTROL SYSTEM FOR THE NERVA NUCLEAR ROCKET ENGINE. MULTILoop  
CLASSICAL CONTROLS DESIGN APPROACH HAS BEEN USED PREVIOUSLY IN THE  
ENGINE TEST PROGRAM. THE CONFIGURATION AND OPERATION OF THE ENGINE  
SYSTEM WITH THE RESULTING HIGH DEGREE OF COUPLING AND THE  
MULTIVARIABLE NATURE OF THE SYSTEM ESTABLISHES A NEED FOR MODERN  
CONTROL TECHNIQUES WITH CONSIDERABLE ADVANTAGES OVER CLASSICAL  
METHODS. THE DESIGN PROCEDURE CONSISTS OF SYSTEM MODEL LINEARIZATION,  
SYSTEM SIMPLIFICATION, AND THE QUADRATIC OPTIMAL CONTROL DESIGN.  
TRANSIENT PERFORMANCE RESULTS HAVE BEEN OBTAINED FROM DIGITAL  
IMPLEMENTATION OF THE CONTROL SYSTEM

465689 C7301114

DIGITAL CONTROL OF AN INTERNAL COMBUSTION ENGINE: THE INTERFACE  
DESIGN PROCESSNICHOLS, J.A., ALLAN, J.J., III ; MCDONNELL DOUGLAS CORP.,  
HUNTINGTON BEACH, CALIF., USA

; US DEPT. COMMERCE, IEEE

PROCEEDINGS OF THE TECHNICAL CONFERENCE : ISLANDS OF APPLICATION:  
157-65 1972

8-13 JUNE 1972 US DEPT. COMMERCE, IEEE TOKYO, JAPAN

PUBL: IEEE NEW YORK, USA

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, DIGITAL CONTROL

IDENTIFIERS: DIGITAL CONTROL, INTERNAL COMBUSTION ENGINE, INTERFACE  
DESIGN PROCESS, POWER OUTPUT, FUEL CONSUMPTION, OPERATING TEMPERATURES  
, EXHAUST EMISSIONS

SECTION CLASS CODES: C7851, C8846, C8849

UNIFIED CLASS CODES: VMRCAD, VMKAS, VMKZAN

A DIGITALLY CONTROLLED TEST BED FOR INTERNAL COMBUSTION ENGINES HAS  
BEEN BUILT AND TESTED. THE PURPOSE OF THE WORK, HOWEVER, WAS TO  
EXAMINE THE INTERFACE DESIGN PROCESS. THE INTERFACE DESIGN PROCESS IS  
DEVELOPED IN GENERIC AND THEN SPECIFIC TERMS. THE DEVELOPMENT OF THE  
IC ENGINE TEST BED FACILITY IS THEN DESCRIBED AS AN EXAMPLE OF THE  
METHOD. SPECIFIC RESULTS ARE GIVEN FOR THE PARTICULAR APPLICATION, AND  
THE GENERAL APPROACH IS EVALUATED (1 REFS)

465649 C7301074

THEORETICAL DESIGN OF AN ADAPTIVE CONTROLLER FOR AN I.C. ENGINE

GILL, R.P., HARLAND, G.P., SCHWARZENBACH, J.

CONTR. AND INSTRUM. (GB) VOL.4, NO.9 50-3 OCT. 1972 CODEN:

CTLIAM

DESCRIPTORS: HEAT ENGINES, ANALOGUE COMPUTER METHODS, ADAPTIVE CONTROL

IDENTIFIERS: ANALOGUE COMPUTER, THEORETICAL DESIGN, ADAPTIVE CONTROLLER, INTERNAL COMBUSTION ENGINE, SPEED CONTROL

SECTION CLASS CODES: C7851, C6660, C9980, C8846

UNIFIED CLASS CODES: VMKCAD, VENAAG, XTAAH, WHEKAS

AN I.C. ENGINE-SPEED CONTROL SYSTEM HAS BEEN INVESTIGATED THEORETICALLY ON AN ANALOGUE COMPUTER TO DETERMINE THE DEGREE OF IMPROVEMENT IN EXISTING SPEED-CONTROL SYSTEMS THAT CAN BE OBTAINED BY USING ADAPTIVE TECHNIQUES (3 REFS)

465648 C7301073

COMPUTER CONTROL FOR IC ENGINES DEVELOPMENT

BLOXHAM, R.D., JONES, T.P., MURGATROYD, W., WING, R.D.

PART. MECH. ENG. (GB) VOL.9, NO.9 58-61 OCT. 1972 CODEN:

CHMGAF

DESCRIPTORS: HEAT ENGINES, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: INTERNAL COMBUSTION ENGINES, REAL TIME COMPUTING, COMPUTER CONTROL, DEVELOPMENT, OPTIMUM EQUIPMENT, PROGRAMMING, TEST FACILITY, ENVIRONMENTAL STUDIES, CYCLIC FLUCTUATIONS, PERKINS PRODUCTION DIESEL ENGINE

SECTION CLASS CODES: C7851, C8846, C8849

UNIFIED CLASS CODES: VMKCAD, WHEKAS, WHEZAN

DEVELOPMENT OF THE OPTIMUM EQUIPMENT AND PROGRAMMING NECESSARY FOR A VERSATILE COMPUTER-CONTROLLED IC ENGINES TEST FACILITY HAS BEEN CARRIED OUT IN THE MECHANICAL ENGINEERING DEPARTMENT AT IMPERIAL COLLEGE, LONDON. ENVIRONMENTAL STUDIES OF A WIDELY VARYING NATURE HAVE BEEN THE PRIMARY OBJECTIVE AND THE FACILITY HAS ENORMOUS POTENTIAL FOR GENERAL ENGINE RESEARCH PARTICULARLY IN THE DEVELOPMENT STAGES OF PRODUCTION ENGINES. THE OVERALL PERFORMANCE OF THIS PROTOTYPE ALL-DIGITAL CONTROL AND ANALYSIS SYSTEM HAS ALREADY SHOWN TIME SAVINGS OF 10:1 IN PRE-PRODUCTION TESTING FOR ONE MOTOR MANUFACTURER. THE GENERAL AIMS OF THE PROJECT ARE TWOFOLD: (I) TO DEMONSTRATE THE USE OF COMPUTERS IN ENGINE DEVELOPMENT; (II) TO PROVIDE THE BASIC FACILITIES REQUIRED FOR SOPHISTICATED EXPERIMENTS ASSOCIATED WITH ENGINES RESEARCH AND TO DEMONSTRATE THE POTENTIAL OF REAL-TIME COMPUTING IN THIS CONNECTION. THE FIRST DEMONSTRATION OF THIS KIND, RELATED TO CYCLIC FLUCTUATIONS ON A PERKINS PRODUCTION DIESEL ENGINE, IS DESCRIBED

455590 C7225377

A FLUIDIC SENSOR FOR CLOSED LOOP ENGINE ACCELERATION CONTROL

WETZEL, A.J., ARNETT, S.E., HIGH, R.

FLUID. Q. (USA) VOL.4, NO.2 68-79 APRIL 1972 CODEN: FLOUA2

DESCRIPTORS: HEAT ENGINES, ACCELERATION CONTROL, FLUIDICS, NONELECTRIC SENSING DEVICES, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: FLUIDIC SENSOR, CLOSED LOOP, ENGINE ACCELERATION CONTROL, HYBRID CONTROLLER, COMPUTER, FUEL CONTROL, TURBO GAS GENERATOR ENGINES

SECTION CLASS CODES: C7551, C7322, C7422, C8825

AN ANALYTICAL AND DEMONSTRATION PROGRAM WAS CONDUCTED TO EVALUATE THE APPLICABILITY OF A UNIQUE ACCELERATION PARAMETER FOR TURBO-GAS GENERATOR ENGINES. THIS PARAMETER IS THE ENGINE AIRFLOW GENERALIZED TO THE COMPRESSOR DISCHARGE STATION. CONTROL-ENGINE TESTS WERE CONDUCTED USING A HYBRID CONTROL SYSTEM AND A J85-GE-7 ENGINE. THE HYBRID CONTROLLER CONSISTED OF FLUIDIC AND ELECTRONIC SENSORS, THE APAPL IBM 1800 COMPUTER AND AN ELECTROHYDROMECHANICAL FUEL CONTROL. IN THIS PAPER THE FINDINGS OF THE PROGRAM, WITH PARTICULAR EMPHASIS ON THE FEATURES OF A FLUIDIC SENSOR WHICH WAS USED TO MEASURE THE PARAMETER, AND THE CONTROL PROGRAMMING FLEXIBILITY AVAILABLE WITH THE IBM 1800 ARE DISCUSSED

447278 C7224258

REMOTE TEST SITE COMPUTATION OF COMPLEX ENGINE INLET DYNAMIC PARAMETERS USING AN ANALOG COMPUTER

SMITH, E.L., FLEETWOOD, P.M. ; MCDONNELL AIRCRAFT CO., ST. LOUIS, MO., USA

ISA TRANS. (USA) VOL.11, NO.1 56-64 1972 CODEN: ISATAZ

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, REAL TIME SYSTEMS, ANALOGUE COMPUTER METHODS, HEAT ENGINES

IDENTIFIERS: REAL TIME COMPUTATION, DISPLAY, ANALOGUE COMPUTER, REMOTE TEST SITE COMPUTATION, COMPLEX ENGINE INLET DYNAMIC PARAMETERS, DYNAMIC PRESSURE DATA SIGNALS, INTEGRATED CIRCUIT OPERATIONAL AMPLIFIERS, PRATT AND WHITNEY ENGINE PARAMETERS, HARDWARE, COMPUTATIONAL CIRCUITRY, FLAGGING PULSES, DIGITIZATION, COMPUTER ANALYSIS

SECTION CLASS CODES: C8829, C9950

A SYSTEM TO PROVIDE REAL-TIME COMPUTATION AND DISPLAY OF COMPLEX ENGINE INLET DISTORTION PARAMETERS, COMPUTED FROM A LARGE NUMBER OF DYNAMIC PRESSURE DATA SIGNALS, WAS SUCCESSFULLY IMPLEMENTED USING INTEGRATED CIRCUIT OPERATIONAL AMPLIFIERS AS THE PRIMARY ANALOGUE COMPUTATIONAL ELEMENTS. PRATT AND WHITNEY ENGINE PARAMETERS ARE SHOWN AND HARDWARE DIAGRAMS OF THE COMPUTATIONAL CIRCUITRY ARE EXPLAINED. ALSO SHOWN IS HOW THE SYSTEM PROVIDED FLAGGING PULSES TO THE RAW DATA TAPES FOR SUBSEQUENT DIGITIZATION AND COMPUTER ANALYSIS OF WORST CASE DATA, WITH RESULTANT IMPROVEMENT IN TEST DATA AT SIGNIFICANT SAVINGS IN TIME AND MONEY (4 REFS)

446709 C7223638

THE VIBRATION OF ENGINE CRANKSHAFTS-A PAST NUMERICAL SOLUTION  
 CRAVEN, A.H., HOLMES, R. ; UNIV. SUSSEX, BRIGHTON, ENGLAND

INT. J. NUMER. METH. ENG. (GB) VOL. 5, NO. 1 17-24 SEPT.-OCT.  
 1972 CODEN: IJNMBH

DESCRIPTORS: NUMERICAL METHODS, PHYSICS

IDENTIFIERS: VIBRATION, ENGINE CRANKSHAFTS, PAST NUMERICAL SOLUTION,  
 DYNAMICAL EQUATIONS, MOTION, CLEARANCE TOLERANCE, BEARING, MINIMUM  
 FILM THICKNESS, CLEARANCE TOLERANCE, COMPUTER TIME

SECTION CLASS CODES: C8240

THIS PAPER DESCRIBES A VERY PAST NUMERICAL METHOD FOR SOLVING THE  
 FULL DYNAMICAL EQUATIONS GOVERNING THE MOTION OF THE CRANKSHAFT AND,  
 AS AN EXAMPLE, THE METHOD IS USED TO CALCULATE THE EFFECT OF CLEARANCE  
 TOLERANCE ON THE PERFORMANCE OF A TYPICAL BEARING. IT WAS FOUND THAT  
 THE MINIMUM FILM THICKNESS IS NOT GREATLY AFFECTED BY THE CLEARANCE  
 TOLERANCE, SUGGESTING THAT A FAIR DEGREE OF VARIATION OF CLEARANCE CAN  
 BE ALLOWED (3 REFS)

436915 C7222538

TURBINE TORQUE COMPUTER

PATENT NO.: UK 1266262 ASSIGNEES: BENDIX CORP. FILED: 20 MARCH  
 1970

ORIGINAL PATENT APPL. NO.: USA 810668

PRIORITY DATE: 26 MAR 1969

8 MARCH 1972

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, TURBINES, TORQUE  
 MEASUREMENT, AEROSPACE APPLICATIONS OF COMPUTERS, SPECIAL PURPOSE  
 COMPUTERS

IDENTIFIERS: TURBINE TORQUE COMPUTER, HELICOPTERS, RESERVE  
 CAPABILITY, STATIC PRESSURE, AMBIENT TEMPERATURE SIGNALS, ADJUSTMENT  
 DEVICE, ENGINE CHARACTERISTICS, COMPENSATE

SECTION CLASS CODES: C9650, C8829

A TURBINE TORQUE COMPUTER IS DISCLOSED FOR HELICOPTERS. IT COMPUTES  
 THE RESERVE CAPABILITY OF THE TURBINE BY OPERATING ON STATIC PRESSURE  
 AND AMBIENT TEMPERATURE SIGNALS, TO PRODUCE A SIGNAL CORRESPONDING TO  
 RATED TORQUE AT THAT PRESSURE AND TEMPERATURE. OPERATING ON THIS  
 SIGNAL AND A SIGNAL CORRESPONDING TO THE TORQUE OUTPUT OF THE TURBINE,  
 IT PRODUCES A SIGNAL CORRESPONDING TO PERCENTAGE MAXIMUM RATED TORQUE  
 BEING PRODUCED BY THE ENGINE. PREFERABLY A SUBNORMAL ADJUSTMENT DEVICE  
 IS CONNECTED BETWEEN THE TWO PARTS OF THE COMPUTER FOR ADJUSTING THE  
 RATED TORQUE SIGNAL TO COMPENSATE FOR SUB-NORMAL ENGINE  
 CHARACTERISTICS



436519 A7258940, C7222131

AN ANALYSIS OF EACH ENGINE CYCLE USING A DIGITAL ELECTRONIC COMPUTER  
HIGASHINO, I., YOSHIMURA, K. ; OSAKA CITY UNIV., JAPAN

MEM. PAC. ENG. OSAKA CITY UNIV. (JAPAN) VOL.12 25-37 DEC. 1971

CODEN: MPEOAR

DESCRIPTORS: COMBUSTION, COMPUTER APPLICATIONS, HEAT ENGINES,  
ENGINEERING APPLICATIONS OF COMPUTERS, ANALOGUE-DIGITAL CONVERSIONIDENTIFIERS: A/D CONVERTORS, DIGITAL ELECTRONIC COMPUTER, DIGITAL  
DATA PROCESSING DEVICE, INSTANTANEOUS CHARACTERISTIC VALUES,  
COMBUSTION, CYLINDER PRESSURE, INTERNAL COMBUSTION ENGINE, GAS  
CONDITION, POWER UP, EXHAUST GAS CLEANING, CYCLE SIMULATION, ANALOGUE  
DATA RECORDER

SECTION CLASS CODES: A0400, C8829, A0240

THE COMBUSTION IN A CYLINDER OF AN INTERNAL COMBUSTION ENGINE IS COMPLETED IN A VERY SHORT TIME, AND ALSO VARIOUSLY INFLUENCED BY MANY FACTORS. IN VIEW OF THE FACT THAT COMBUSTION CHANGES CYCLE TO CYCLE, IT IS VERY DIFFICULT IN TECHNIQUE TO KNOW THE GAS CONDITION IN A CYLINDER DIRECTLY. BUT IT IS ESSENTIALLY NECESSARY TO ANALYZE AND ESTIMATE A COMBUSTION CONDITION CYCLE TO CYCLE IN ORDER TO SOLVE THE PROBLEM OF POWER UP OR EXHAUST GAS CLEANING. IN OTHER HAND, FOR ANALYZING A COMBUSTION CONDITION, PROCEDURE OF CYCLE SIMULATION IS USED. IN THIS CASE, IT IS NOT EASY TO ESTIMATE HEAT RELEASE RATE OF A PRE-MIXTURE ENGINE IN COMPARISON WITH A FUEL INJECTION ENGINE. IN THIS PAPER, IN ORDER TO ANALYZE AND ESTIMATE A COMBUSTION, THE PRESSURE VALUE IN A CYLINDER, WHICH CAN BE MEASURED RELATIVELY EASILY AS AN INSTANTANEOUS VALUE, IS MEASURED WITH USE OF AN ANALOGUE DATA RECORDER AND ITS DATA IS TRANSFORMED TO DIGITAL DATA BY A-D CONVERTOR. AFTER THIS PROCEDURE BY USING A DIGITAL ELECTRONIC COMPUTER AND THIS DIGITAL PRESSURE DATA, SOME CHARACTERISTIC VALUES OF COMBUSTION ARE CALCULATED AT EACH POINT OF A SMALL CRANK ANGLE INTERVAL, FOR EXAMPLE, THE POLYTROPIC EXPONENT, THE RATE OF PRESSURE INCREASE, THE RATE OF CYLINDER VOLUME CHANGE, THE GAS TEMPERATURE, THE SPECIFIC HEAT RATIO AND THE RATE OF GAS HEATING. AND THEN THE MEAN EFFECTIVE PRESSURE AND THE TOTAL HEAT RELEASE ARE CALCULATED (5 REFS)

435441 C7220939

ENGINE SPEED AND CLUTCH SYNCHRONIZING CONTROLS INCLUDING TRANSMISSION CONTROLS

NUMAZAWA, A., ITO, O.

PATENT NO.: USA 3645366 ASSIGNEES: NIPPONDENSO, K.K. FILED: 1 JUNE 1970

ORIGINAL PATENT APPL. NO.: JAPAN 44/43885

PRIORITY DATE: 3 JUN 1969

29 FEB. 1972

DESCRIPTORS: SPEED CONTROL, ROAD TRAFFIC, LOGIC CIRCUITS, DIGITAL CIRCUITS, CLUTCHES

IDENTIFIERS: ENGINE SPEED AND CLUTCH SYNCHRONIZING CONTROL, TRANSMISSION CONTROLS, ELECTRONIC CONTROL SYSTEM, GEAR SHIFTS, SYNCHRONOUS CLUTCH SHAFT SPEEDS, PRESIFT PREDICTIVE COMPUTER, DIGITAL LOGIC CIRCUITRY

SECTION CLASS CODES: C7461, C7322

AN ELECTRONIC CONTROL SYSTEM FOR A CLUTCH LOCATED BETWEEN AN ENGINE AND A VARIABLE RATIO TRANSMISSION INCLUDES MEANS TO DETECT THE SPEED OF THE INPUT AND OUTPUT CLUTCH SHAFTS, AND TO CONTROL THE ENGINE SPEED BEFORE DURING GEAR SHIFTS SO THAT THE CLUTCH WILL ENGAGE AT SYNCHRONOUS CLUTCH SHAFT SPEEDS. A SPECIAL PRESIFT PREDICTIVE COMPUTER MEANS IS USED IN COMBINATION WITH SPECIAL DIGITAL LOGIC CIRCUITRY TO INSURE RELIABLE AND OPTIMUM OPERATION

435322 C7220814

FLUIDIC GOVERNOR SYSTEM

PATENT NO.: UK 1266415 ASSIGNEES: BENDIX CORP. FILED: 7 MARCH 1969

ORIGINAL PATENT APPL. NO.: USA 712976

PRIORITY DATE: 14 MAR 1968

8 MARCH 1972

DESCRIPTORS: SPEED CONTROL, FLUIDICS, DIGITAL CIRCUITS, CONTROLLERS

IDENTIFIERS: FLUIDIC GOVERNOR SYSTEM, CONTROLLING, FLUID PULSE GENERATORS, TRAIN PULSES, ENGINE SPEED, FLUIDIC CIRCUITRY, FLUID PULSE ERROR SIGNAL, FREQUENCY

SECTION CLASS CODES: C7322, C7410

DISCLOSES A SYSTEM FOR CONTROLLING THE SPEED OF AN ENGINE. IT EMPLOYS FLUID PULSE GENERATORS PRODUCING PULSES, HAVING A FREQUENCY REPRESENTING THE SPEED OF THE ENGINE, AND FURTHER TRAIN PULSES FOR REPRESENTING A DESIRED ENGINE SPEED VALUE. THE PULSE TRAINS ARE FED TO FLUIDIC CIRCUITRY PRODUCING A FLUID PULSE ERROR SIGNAL HAVING A FREQUENCY WHICH VARIES WITH THE ERROR SIGNAL AND WHICH CONTROL THE ENGINE TO REDUCE THE ERROR

424526 C7219772

PRACTICAL APPLICATION OF COMPUTERS TO AUTOMOTIVE ENGINE BEARING DESIGN

SPIKES, R.H., PIRAUULT, J.P.

END ENG. MATER. AND DES. (GB) VOL.15, NO.6 493-6 JUNE 1972

CODEN: EMADA3

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, COMPUTER-AIDED DESIGN

IDENTIFIERS: COMPUTERS, AUTOMOTIVE ENGINE BEARING DESIGN, LUBRICATION, HYDRODYNAMIC PERFORMANCE OF THE OIL, BIG END BEARING

SECTION CLASS CODES: C8829

DESCRIBES HOW THE COMPUTER MAY BE USED IN CALCULATIONS CONCERNING THE LUBRICATION SYSTEM AND HYDRODYNAMIC PERFORMANCE OF THE OIL IN A BIG END BEARING (7 REFS)

424278 A7248636, B7225961, C7219502

PROCEEDINGS OF THE 17TH INTERNATIONAL ISA AEROSPACE INSTRUMENTATION SYMPOSIUM

; INSTRUMENT SOC. AMERICA

STD BOOK NO.: 87664 154 0

1971

10-12 MAY 1971 INSTRUMENT SOC. AMERICA LAS VEGAS, NEV., USA

PUBL: INSTRUMENT SOC. AMERICA PITTSBURGH, PA., USA

DESCRIPTORS: SPACE VEHICLES INSTRUMENTATION, COMPUTER APPLICATIONS, AEROSPACE INSTRUMENTATION, AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE

IDENTIFIERS: AEROSPACE INSTRUMENTATION, ENVIRONMENTAL INSTRUMENTATION, AEROSPACE COMPUTER APPLICATIONS, ENGINE TESTING, OPTICAL INSTRUMENTATION, WIND TUNNEL, TELEMETRY, SURFACE VEHICLE INSTRUMENTATION, DATA PROCESSING, DISPLAY, MEASUREMENT TECHNIQUES, IN FLIGHT INSTRUMENTATION

SECTION CLASS CODES: A2050, B3620, C8812

THE FOLLOWING TOPICS WERE DEALT WITH: ENVIRONMENTAL INSTRUMENTATION; AEROSPACE COMPUTER APPLICATIONS; IN-FLIGHT INSTRUMENTATION; ENGINE TESTING; OPTICAL INSTRUMENTATION; WIND TUNNEL; TELEMETRY; SURFACE VEHICLE INSTRUMENTATION; DATA PROCESSING AND DISPLAY; ADVANCES IN MEASUREMENT TECHNIQUES AND DEVICES. INDIVIDUAL PAPERS WITHIN THE SUBJECT SCOPE OF THIS JOURNAL WILL BE ABSTRACTED IN THIS OR A SUBSEQUENT ISSUE

421274 1723009\*

DIGITAL DATA REDUCTION METHODS FOR AIRCRAFT ENGINE NOISE ANALYSIS  
MCNEILL, H. ; RENSSELAER POLYTECH. INST. CONNECTICUT, HARTFORD,  
USA

SOUND AND VIBR. (USA) VOL.6, NO.4 26-9 APRIL 1972 CODEN:  
SOVIAJ

DESCRIPTORS: ACOUSTIC NOISE, SONIC MEASUREMENTS  
IDENTIFIERS: DIGITAL DATA REDUCTION METHODS, AIRCRAFT ENGINE NOISE  
ANALYSIS, ANALOGUE ELECTRONIC ANALYSERS, ANALYSIS TIME, FAN NOISE  
SPECTRUM

SECTION CLASS CODES: B3810

DIGITAL DATA REDUCTION METHODS FOR ANALYZING AIRCRAFT ENGINE NOISE  
CHARACTERISTICS ARE DISCUSSED. THE APPROACH IS SUPERIOR TO THOSE  
EMPLOYING ANALOG ELECTRONIC ANALYZERS BECAUSE OF REDUCED ANALYSIS  
TIME, LOWER COST, AND IMPROVED INFORMATION EXCHANGE RESULTING FROM THE  
ANALYTICAL TECHNIQUE STANDARDIZATION THAT IS POSSIBLE. ANALYSIS OF A  
FAN NOISE SPECTRUM EXEMPLIFIES APPLICATION OF THE DIGITAL DATA  
REDUCTION METHOD (2 REFS)

410013 C7217153

COMPUTER AIDED DESIGN OF CONTROL AND GAS EXCHANGE IN INTERNAL  
COMBUSTION ENGINE IN DIALOGUE MADE WITH A VIDEO DISPLAY

PAPEZ, S.L., BABISCH, H.J.

SYRBE, M.

; INTERKAMA

STD BOOK NO.: 3 486 33571 5

INTERKAMA 5TH INTERNATIONAL CONGRESS WITH EXHIBITION FOR INSTRUMENTS  
AND AUTOMATION 161-2 1971

14-21 OCT 1971 INTERKAMA DUSSELDORF, GERMANY

PUBL: E. OLDENBURG VERLAG MUNICH, GERMANY

DESCRIPTORS: COMPUTER AIDED DESIGN, HEAT ENGINES, ENGINEERING  
APPLICATIONS OF COMPUTERS, DISPLAY SYSTEMS, MAN-MACHINE SYSTEMS

IDENTIFIERS: FOUR STROKE ENGINE, MAN MACHINE DIALOGUE, COMPUTER  
AIDED DESIGN, CONTROL AND GAS EXCHANGE, INTERNAL COMBUSTION, ENGINE  
CONTROL, OPTIMIZATION, VIDEO DISPLAY

SECTION CLASS CODES: C8829, C7551, C8825

LANGUAGE: GERMAN

THE PUTTING INTO EFFECT OF THE DEMANDS MADE ON THE DESIGNER OF  
ENGINES DEPENDS ON MANY PARAMETERS. AN OPTIMUM SOLUTION CAN ONLY BE  
FOUND IN CONNECTION WITH EXPERIMENTS. THIS IN TURN DEMANDS TIME AND  
MONEY. IN ORDER TO FACILITATE FINDING THE SOLUTION, TWO PROGRAMS WERE  
SET UP WITH WHICH ENGINE CONTROL AND GAS EXCHANGE OF THE FOUR-STROKE  
ENGINE IS OPTIMIZED BY MEANS OF A VIDEO DISPLAY CONNECTED WITH THE  
COMPUTER. THE MAN-MACHINE DIALOGUE IS SHOWN IN DETAIL ON THE BASIS OF  
DATA OPTIMIZATION (4 REFS)

409794 A7248636, B7225961, C7216905

## PROCEEDINGS OF THE 17TH INTERNATIONAL ISA AEROSPACE INSTRUMENTATION SYMPOSIUM

; INSTRUMENT SOC. AMERICA

STD BOOK NO.: 87664 154 0

1971

10-12 MAY 1971 INSTRUMENT SOC. AMERICA LAS VEGAS, NEV., USA

PUBL: INSTRUMENT SOC. AMERICA PITTSBURGH, PA., USA

DESCRIPTORS: SPACE VEHICLES INSTRUMENTATION, COMPUTER APPLICATIONS, AEROSPACE INSTRUMENTATION, AEROSPACE APPLICATIONS OF COMPUTERS, AEROSPACE

IDENTIFIERS: AEROSPACE INSTRUMENTATION, ENVIRONMENTAL INSTRUMENTATION, AEROSPACE COMPUTER APPLICATIONS, ENGINE TESTING, OPTICAL INSTRUMENTATION, WIND TUNNEL, TELEMETRY, SURFACE VEHICLE INSTRUMENTATION, DATA PROCESSING, DISPLAY, MEASUREMENT TECHNIQUES, IN FLIGHT INSTRUMENTATION

SECTION CLASS CODES: A2050, B3620, C8812

THE FOLLOWING TOPICS WERE DEALT WITH: ENVIRONMENTAL INSTRUMENTATION; AEROSPACE COMPUTER APPLICATIONS; IN-FLIGHT INSTRUMENTATION; ENGINE TESTING; OPTICAL INSTRUMENTATION; WIND TUNNEL; TELEMETRY; SURFACE VEHICLE INSTRUMENTATION; DATA PROCESSING AND DISPLAY; ADVANCES IN MEASUREMENT TECHNIQUES AND DEVICES. INDIVIDUAL PAPERS WITHIN THE SUBJECT SCOPE OF THIS JOURNAL WILL BE ABSTRACTED IN THIS OR A SUBSEQUENT ISSUE

396731 C7213411

AIRCRAFT JET ENGINE FUEL CONTROL

PATENT NO.: DE 1256666 ASSIGNEES: BODENSEWERK GERATE-TECHNIK GMBH FILED: 19 MARCH 1970

ORIGINAL PATENT APPL. NO.: GERMANY P1920002.3

PRIORITY DATE: 19 APR 1969

15 DEC. 1971

DESCRIPTORS: HEAT SYSTEMS, TURBINES, FLOW CONTROL, TEMPERATURE CONTROL, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, AIRCRAFT, AEROSPACE APPLICATIONS OF COMPUTERS

IDENTIFIERS: AIRCRAFT JET ENGINE FUEL CONTROL, THROTTLE LEVER, :TRIMMING: LEVER, ADJUSTING, FUEL SUPPLY, REGULATE TURBINE GAS TEMPERATURE, COMPUTER, ENGINE OPERATING CONDITIONS, AIRCRAFT ALTITUDE DEVIATIONS

SECTION CLASS CODES: C7551, C7323, C8825, C7326

DISCLOSES A FUEL CONTROL SYSTEM UTILISING A MAIN THROTTLE LEVER, ALSO A :TRIMMING: LEVER FOR ADJUSTING THE FUEL SUPPLY TO REGULATE TURBINE GAS TEMPERATURE. THE OPTIMUM TEMPERATURE OR TRIMMING LEVER SETTING IS DETERMINED BY A COMPUTER ACCOUNTING FOR ENGINE OPERATING CONDITIONS AND AIRCRAFT ALTITUDE DEVIATIONS FROM THE OPTIMUM, BEING INDICATED BY LAMPS, ETC

385127 C7211409

ENGINE FUEL CONTROL

PATENT NO.: UK 1258392 ASSIGNEES: ROLLS-ROYCE LTD. FILED: 23 DEC. 1968

ORIGINAL PATENT APPL. NO.: UK 59029/67

PRIORITY DATE: 29 DEC 1967

30 DEC. 1971

DESCRIPTORS: AIRCRAFT, AEROSPACE CONTROL, AEROSPACE APPLICATIONS OF COMPUTERS, CLOSED LOOP SYSTEMS, MINIMIZATION, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: ENGINE FUEL CONTROL, COMPUTER, MINIMISING, FUEL REQUIREMENT, AIRCRAFT, CLOSED LOOP SYSTEM

SECTION CLASS CODES: C7575, C8829, C8825

DESCRIBES A SYSTEM USING A COMPUTER ETC., FOR MINIMISING TOTAL FUEL REQUIREMENT OF ENGINES LOCATED TOWARDS OPPOSITE SIDES OF AN AIRCRAFT ETC. COURSE DIRECTION AND SPEED ARE MAINTAINED BY A CLOSED-LOOP SYSTEM ADAPTED FOR VARYING RESPECTIVE ENGINE FUEL SUPPLIES IN OPPOSITE SENSES TO OBTAIN MAXIMUM OVERALL EFFICIENCY ETC., AS INDICATED BY ACCELERATION OF THE AIRCRAFT, PARTICULARLY IN A CASE WHERE THE ENGINE EFFICIENCIES ARE DIFFERENT

375770 C7210355

THE CDC STAR-100 A LARGE SCALE NETWORK ORIENTED COMPUTER SYSTEM

HOLLAND, S.A., PURCELL, C.D. ; CONTROL DATA CORP., MINNEAPOLIS, MINN., USA

; IEEE

5TH ANNUAL 1971 IEEE INTERNATIONAL COMPUTER SOCIETY CONFERENCE ON HARDWARE, SOFTWARE, FIRMWARE AND TRADE-OFFS (DIGESTS) 55-6 1971

22-24 SEP 1971 IEEE BOSTON, MASS., USA

PUBL: IEEE NEW YORK, USA

DESCRIPTORS: GENERAL PURPOSE COMPUTERS

IDENTIFIERS: CDC STAR 100, NETWORK ORIENTED COMPUTER SYSTEM, COMPUTER SYSTEM, COMPUTING ENGINE, DISTRIBUTED NETWORK, ARCHITECTURAL

SECTION CLASS CODES: C9610

AN EXTREMELY LARGE AND POWERFUL COMPUTER SYSTEM HAS BEEN DEVELOPED BY CONTROL DATA CORPORATION (THE STAR-100) FOR THE USE AS A LARGE COMPUTING ENGINE AT THE CENTER OF A DISTRIBUTED NETWORK OF OTHER COMPUTING SYSTEMS. THIS PAPER OUTLINES SOME OF THE SALIENT FEATURES OF THE STAR-100 SYSTEM AS WELL AS SOME CONSIDERATIONS FOR THE USE OF THIS SYSTEM IN ITS INTENDED ENVIRONMENT

364901 C7207316

## RECENT DEVELOPMENT OF SHIPBOARD SUPER-AUTOMATION

IMAMURA, H.

JARU (JAPAN) VOL.4, NO.4 38-48 1971

DESCRIPTORS: MARINE SYSTEMS, CONTROL ENGINEERING APPLICATION OF COMPUTERS

IDENTIFIERS: GENERAL PURPOSE OFFICER OR CREW PLAN, AUTOMATIC NAVIGATION SYSTEMS, ENGINE PLANT CONTROL SYSTEM, SHIPBOARD AUTOMATION, ELECTRONIC COMPUTER

SECTION CLASS CODES: C7574, C8825

STUDIES OF SHIPBOARD AUTOMATION BEGAN IN JAPAN AHEAD OF THE REST OF THE WORLD, AND 10 YEARS AGO THE WORLD'S FIRST AUTOMATED SHIP, THE :KINKASAN MARU: WAS COMPLETED. SINCE THEN, TECHNOLOGICAL IMPROVEMENTS HAVE BEEN MADE ON SHIPBOARD AUTOMATION. THE :SEIKO MARU: THAT COULD SUCCEED IN THE DEVELOPMENT OF HIGHLY CENTRALIZED CONTROL SYSTEM OF A SHIP WAS COMPLETED IN 1970 AS THE FIRST SUPER-AUTOMATED SHIP IN THE WORLD, BY TAKING FULL ADVANTAGES OF ELECTRONIC COMPUTER ON BOARD. IT IS BELIEVED THAT THE FRUITFUL RESULTS OBTAINED FROM THE TECHNICAL INNOVATION WILL BE WIDELY REFLECTED UPON THREE OBJECTIVES I.E., THE MECHANIZATION OF HUMAN TASKS ON BOARD SHIP, THE IMPROVEMENT OF SHIP SAFETY, AND ECONOMICAL OPERATION OF SHIPBOARD WORKS WHICH UNDOUBTEDLY WILL BRING ABOUT THE PROSPERITY OF THE FUTURE SHIPPING CIRCLES

364832 C7207245

## MACE APPLIED TO TWO CLOSED LOOP CONTROL DDC SYSTEMS

ST. JOHNSTON, A.D., ST. JOHNSTON, A.

INSTRUM. PRACT. (GB) VOL, 26 NO. 1 36-9 JAN. 1972 CODEN: INPAAI

DESCRIPTORS: SUPERVISORY AND EXECUTIVE PROGRAMS, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, CLOSED LOOP SYSTEMS, DIRECT DIGITAL CONTROL

IDENTIFIERS: MACE, CLOSED LOOP, DDC SYSTEMS, MASTER CONTROL EXECUTIVE, CHEMICAL PLANT, INTERNAL COMBUSTION ENGINE

SECTION CLASS CODES: C7563, C8825, C8829, C8370

DESCRIBES THE APPLICATION OF A MASTER CONTROL EXECUTIVE TO THE CONTROL SYSTEMS OF A CHEMICAL PLANT AND THAT OF AN INTERNAL COMBUSTION ENGINE TEST BED. BOTH SYSTEMS BEING D.D.C

355027 C7205722

## HISTORY AND APPLICATIONS OF COMPUTERS

ALLEN, M.W.

KARBOWIAK, A.P., HURY, R.M.

STD BOOK NO.: 0 471 45853 8

INFORMATION, COMPUTERS, MACHINES, AND MAN 51-7 1971

PUBL: WILEY LONDON, ENGLAND

DESCRIPTORS: DIGITAL COMPUTERS, ANALOGUE COMPUTERS

IDENTIFIERS: ANALOGUE AND DIGITAL COMPUTERS, SLIDE RULE, HISTORY OF COMPUTERS, ARITHOMETER, JACQUARD LOOM PUNCHED CARD SYSTEM, DIFFERENCE ENGINE, ENIAC, EDVAC, APPLICATIONS OF COMPUTERS

SECTION CLASS CODES: C8000, C8800

346618 C7204938

REQUIREMENTS FOR DIGITAL COMPUTER SIMULATION OF GAS TURBINE  
PROPULSION SYSTEM PERFORMANCE PHASE 1: STEADY-STATE AND TRANSIENT  
ENGINE PERFORMANCE SIMULATION. FINAL REPORT, 15 JUL. 1969-30 JUN. 1970

HUTCHESON, L., ARMSTRONG, W.C., COOPER, G.B.

REPORT NO.: AEDC-TR-71-24 ISSUED BY: ARO INC., ARNOLD AIR FORCE  
STATION, TENN., USA

USGRDR NO.: AD-720803

CONTRACT NO.: F40600-71-C-0002

MARCH 1971

DESCRIPTORS: SIMULATION, HEAT ENGINES, TURBINES, ENGINEERING  
APPLICATIONS OF COMPUTERS

IDENTIFIERS: STEADY STATE PERFORMANCES, OFF LINE RESULTS, ON LINE  
RESULTS, DIGITAL COMPUTER SIMULATION, GAS TURBINE ENGINE, TRANSIENT  
PERFORMANCE, CORE MEMORY SIZE, THROUGHPUT TIMES, PROGRAMS, DISPLAY  
REQUIREMENTS, DYNAMIC COMPRESSOR MATHEMATICAL MODELS

SECTION CLASS CODES: C9940

AVAILABILITY: NTIS, SPRINGFIELD, VA. 22151, USA

PRESENT AND NEAR-FUTURE REQUIREMENTS FOR THE ADDITION OF DIGITAL  
COMPUTER SIMULATION OF GAS TURBINE ENGINE STEADY-STATE AND TRANSIENT  
PERFORMANCE TO THE PRESENT ENGINE TEST FACILITY AND PROPULSION WIND  
TUNNEL FACILITY DIGITAL DATA CAPABILITY WERE DETERMINED BASED ON  
INFORMATION AND GUIDANCE PROVIDED BY THE AIR FORCE AERO PROPULSION  
LABORATORY AND VARIOUS GAS TURBINE ENGINE MANUFACTURERS. DURING PHASE  
I OF THIS STUDY, DIGITAL COMPUTER HIGH-SPEED CORE MEMORY SIZE AND  
THROUGHPUT TIMES WERE DETERMINED AND ARE PRESENTED FOR SEVERAL MODERN  
STEADY- STATE AND TRANSIENT MATHEMATICAL MODEL SIMULATION PROGRAMS.  
DISPLAY REQUIREMENTS WERE ALSO DETERMINED AND ARE PRESENTED FOR FULL  
UTILIZATION OF THE MATHEMATICAL MODEL RESULTS, OFF-LINE AND ON-LINE  
SOME PRELIMINARY RESULTS ON DYNAMIC COMPRESSOR MATHEMATICAL MODELS ARE  
DISCUSSED

346189 C7204504

ANALOGUE INVESTIGATION OF THE INERTIA-COUPLED FREE-PISTON ENGINE

MOORE, A. : NAT. ENGN. LAB., EAST KILBRIDE, GLASGOW, SCOTLAND

PROC. INST. MECH. ENG. (GB) VOL. 185, NO. 53 725-32 1970-1

CODEN: PIMLAA

DESCRIPTORS: MECHANICAL ENGINEERING, ENGINEERING APPLICATIONS OF  
COMPUTERS, ANALOGUE COMPUTER METHODS

IDENTIFIERS: INERTIA COUPLED FREE PISTON ENGINE, ANALOGUE  
INVESTIGATION, EQUATIONS OF MOTION, ENGINE OF PRACTICAL DIMENSIONS,  
TORQUE MULTIPLY, OVERALL MECHANICAL EFFICIENCY

SECTION CLASS CODES: C8829, C9950

AN ENGINE IS DESCRIBED IN WHICH A FREE PISTON IS LOCATED INSIDE A  
CYLINDER ASSEMBLY WHICH IS ALSO ALLOWED FREEDOM OF MOVEMENT IN THE  
AXIAL DIRECTION. POWER IS TAKEN FROM THE UNIT BY COUPLING THE PISTONS  
TO A HIGH SPEED STATIC PUMP DIRECTLY INTO THE CYLINDER ASSEMBLY. THE  
EQUATIONS OF MOTION FOR THE DEVICE ARE PRESENTED IN NON-DIMENSIONAL  
FORM AND SOLVED WITH THE AID OF AN ANALOGUE COMPUTER. RESULTS ARE  
PRESENTED FOR AN ENGINE OF PRACTICAL DIMENSIONS AND THE INHERENT  
RELATIONSHIP OF THE TORQUE TO TORQUE MULTIPLY IS CONFIRMED. ESTIMATES OF  
OVERALL MECHANICAL EFFICIENCY ARE INCLUDED



336232 B7102663, C7201

AUTOMATIC TEST SYSTEM FOR JET ENGINE ACCESSORIES

COWLEY, R.T. ; RCA, BURLINGTON, MASS., USA

; IEEE, REGION 6, WEMA

PAPERS PRESENTED AT THE WESTERN ELECTRONIC SHOW AND CONVENTION  
21/4 SEP. 1971

24-27 AUG 1971 IEEE, REGION 6, WEMA SAN FRANCISCO, CALIF., USA

PUBL: WESTERN PERIODICALS CO. NORTH HOLLYWOOD, CALIF., USA

DESCRIPTORS: AUTOMATIC TEST EQUIPMENT, AEROSPACE TEST FACILITIES,  
COMPUTER APPLICATIONS, AEROSPACE APPLICATIONS OF COMPUTERS, AUTOMATIC  
TESTINGIDENTIFIERS: AUTOMATIC TEST SYSTEM, JET ENGINE ACCESSORIES, DESIGN,  
MULTISTATION HARDWARE/COMPUTER-SOFTWARE SYSTEM, CONTROL, INFORMATION  
PROCESSING PROBLEMS, AEROSPACE TEST FACILITIES, AEROSPACE APPLICATIONS  
OF COMPUTERS, REAL TIME DATA ACQUISITION, AUTOMATIC CALIBRATION,  
AUTOMATIC TESTING

SECTION CLASS CODES: B3610, C8829

THE DESIGN AND DEVELOPMENT OF A MULTISTATION  
HARDWARE/COMPUTER-SOFTWARE SYSTEM HAS BEEN UNDERTAKEN TO AUTOMATE THE  
CALIBRATION, TEST AND MAINTENANCE OF MECHANICAL ASSEMBLIES. THE SYSTEM  
ATSJEA (AUTOMATIC TEST SYSTEM FOR JET ENGINE ACCESSORIES), HAS BEEN  
DESIGNED AND FABRICATED USING COMMERCIAL COMPONENTS. IT WILL HANDLE A  
WIDE RANGE OF REAL-TIME DATA ACQUISITION, CONTROL AND INFORMATION  
PROCESSING PROBLEMS. THE FIRST APPLICATION IS TO CALIBRATE AND TEST  
JET ENGINE FUEL CONTROLS. THIS PAPER PRESENTS THE SYSTEM REQUIREMENTS  
AND HARDWARE/COMPUTER-SOFTWARE IMPLEMENTATION THAT WAS APPLIED TO  
ACHIEVE THE SYSTEM PERFORMANCE GOALS

323668 C7124250

A GRAPHICS TECHNIQUE FOR THE DESIGN OF MULTIVARIABLE SYSTEMS  
PALLSIDE, P., SERAJI, H. : UNIV. CAMBRIDGE, ENGLAND

; IEE

STD BOOK NO.: 0 85296045 X

4TH UKAC CONTROL CONVENTION ON MULTIVARIABLE CONTROL SYSTEM DESIGN  
AND APPLICATIONS 87-92 1971

1-3 SEP 1971 IEE MANCHESTER, ENGLAND

PUBL: IEE LONDON, ENGLAND

DESCRIPTORS: MULTIVARIABLE CONTROL SYSTEMS, COMPUTER AIDED DESIGN,  
TURBINES

IDENTIFIERS: MULTIVARIABLE CONTROL SYSTEMS, DESIGN BY STATE FEEDBACK,  
DESIGN BY OUTPUT FEEDBACK, COMPUTER AIDED DESIGN, LINEAR TIME  
INVARIANT MULTIVARIABLE FEEDBACK SYSTEMS, FREQUENCY DOMAIN RESULTS,  
GAS TURBINE ENGINE CONTROL, INTERACTIVE GRAPHICS TECHNIQUE, DESIGN,  
STATE OR OUTPUT FEEDBACK, INCOMPLETE STATE FEEDBACK

SECTION CLASS CODES: C8825

A NEW INTERACTIVE GRAPHICS TECHNIQUE FOR THE DESIGN OF LINEAR,  
TIME-INVARIANT MULTIVARIABLE FEEDBACK SYSTEMS WITH ANY NUMBER OF  
INPUTS, STATES AND OUTPUTS IS DESCRIBED. THE METHOD IS BASED ON A  
NUMBER OF RECENT FREQUENCY-DOMAIN RESULTS FOR FEEDBACK DESIGN TO  
ACHIEVE DESIRED CLOSED-LOOP POLE POSITIONS. THESE ARE FAIRLY GENERAL  
AND PRACTICAL IN THAT THEY ALLOW THE DESIGNER TO EMPLOY EITHER STATE  
OR OUTPUT FEEDBACK, AND COVER THE CASE OF INCOMPLETE STATE FEEDBACK  
WHERE NOT ALL THE STATES ARE ACCESSIBLE AND OF OUTPUT FEEDBACK WHERE  
THERE ARE FEWER OUTPUTS THAN STATES. IN ADDITION THE DESIGNER CAN  
SPECIFY THE RELATIVE TIGHTNESS OF THE FEEDBACK TO EACH INPUT AND TREAT  
THE CASE OF FEEDBACK TO ONLY SOME INPUTS, INCOMPLETE INPUT FEEDBACK.  
THE METHOD IS BASED ON A PROGRAM MVSD IN WHICH THE DESIGNER POSITIONS  
THE CLOSED-LOOP POLES ON THE CRT DISPLAY BY MEANS OF A LIGHT-PEN. A  
BRIEF DESCRIPTION IS GIVEN FIRST OF THE THEORETICAL RESULTS FOLLOWED  
BY A DESCRIPTION OF THE INTERACTIVE PROCEDURE AND FINALLY A DESIGN  
STUDY IS MADE OF A 2-INPUT, 2-OUTPUT, 4TH ORDER GAS-TURBINE ENGINE  
CONTROL PROBLEM USING THE TECHNIQUE

322953 A7174439, B7138586, C7123514

PROCEEDINGS OF THE NATIONAL AEROSPACE ELECTRONICS CONFERENCE 1971  
; IEEE, DAYTON SECTION, IEEE, AEROSPACE AND ELECTRONICS GROUP  
1971

17-19 MAY 1971 IEEE, DAYTON SECTION, IEEE, AEROSPACE AND  
ELECTRONICS GROUP DAYTON, OHIO, USA

PUBL: IEEE NEW YORK, USA

DESCRIPTORS: SPACE RESEARCH, AERODYNAMICS, NOISE ACOUSTIC,  
CALCULATING APPARATUS, BIOPHYSICS, AEROSPACE, AIRCRAFT, ACOUSTIC NOISE  
, COMPUTER APPLICATIONS, AIRCRAFT COMMUNICATION, POWER SYSTEMS,  
NAVIGATION, COMPUTER ARCHITECTURE, COMMUNICATIONS SYSTEMS DATA,

IDENTIFIERS: JET ENGINE, NOISE ABATEMENT, ENVIRONMENTAL SENSORS,  
WAKE TURBULENCE, AVIONIC COMMUNICATIONS, RADIO, VISUAL, SATELLITE,  
RECONNAISSANCE, NAVIGATION, SECONDARY POWER SYSTEMS, COMPUTER SYSTEMS,  
TIME FREQUENCY CONCEPTS, MICROELECTRONICS, BIOCYBERNETICS

SECTION CLASS CODES: A2050, B3600, C7576, B2634

THE FOLLOWING TOPICS WERE DEALT WITH: JET ENGINE NOISE ABATEMENT,  
ENVIRONMENTAL SENSORS; AIRCRAFT WAKE TURBULENCE; AVIONIC  
COMMUNICATIONS, RADIO, VISUAL, AND SATELLITE SYSTEM; AIRBORNE  
RECONNAISSANCE, PHOTOGRAPHIC AND RADIONETRIC; NAVIGATION SYSTEMS;  
SECONDARY POWERS SYSTEMS FOR AIRCRAFT; COMPUTER SYSTEMS; TIME  
FREQUENCY CONCEPTS FOR AEROSPACE UTILISATION; MICROELECTRONICS AND  
DEVICES; BIOCYBERNETICS. THERE WERE 90 PARTICIPANTS FROM 2 COUNTRIES  
59 PAPERS WERE PRESENTED, OF WHICH 44 ARE PUBLISHED IN FULL IN THE  
PRESENT PROCEEDINGS, AND 4 AS ABSTRACTS ONLY. INDIVIDUAL PAPERS WITHIN  
THE SUBJECT SCOPE OF THIS JOURNAL WILL BE ABSTRACTED IN THIS OR A  
SUBSEQUENT ISSUE

322586 C7123140

DIRECT HYBRID CONTROL OF AN ENGINE USING ADAPTIVE LOGIC, ADAPTIVE PROGRAMMING AND SELF-ORGANISING STORAGE

CARTER, G.A., MANDANI, R.H., EVANS, P.J. : QUEEN MARY COLL., LONDON, ENGLAND

: IPR

STD BOOK NO.: 0 85296045 X

4TH UKAC CONTROL CONVENTION ON MULTIVARIABLE CONTROL SYSTEM DESIGN AND APPLICATIONS 93-7 1971

1-3 SEP 1971 IPR MANCHESTER, ENGLAND

PUBL: IRE LONDON, ENGLAND

DESCRIPTORS: HEAT ENGINES, SIMULATION, HYBRID COMPUTER METHODS, SELF ORGANIZING STORAGE, LOGIC CIRCUITS, PROGRAMMING, MULTIVARIABLE CONTROL SYSTEM

IDENTIFIERS: DIRECT HYBRID CONTROL, HYBRID COMPUTER SIMULATION, MULTIVARIABLE CONTROL SYSTEMS, SELF ORGANISING STORAGE, ADAPTIVE PROGRAMMING, SMALL GENERAL PURPOSE DIGITAL COMPUTERS, CONTROL AND SUPERVISORY ROLE, :HEURISTIC: METHODS, SMALL MODEL STEAM ENGINE, :EXTERNAL: COMPARATOR CIRCUITS, ADAPTIVE LOGIC ELEMENTS

SECTION CLASS CODES: C7551, C6120, C9950, C6240

THE MOTIVATION FOR THIS IS THE POSSIBILITY OF USING SMALL GENERAL PURPOSE DIGITAL COMPUTERS OF LOW COST IN A CONTROL AND SUPERVISORY ROLE ON ESSENTIAL PLANT. THE MAIN CONCERNS ARE (A) FLEXIBILITY OF THE PROGRAM SO THAT IT CAN BE USED WITH A WIDE VARIETY OF PLANTS, AND (B) EVENTUAL RELIABILITY AND SIMPLICITY. THIS STUDY REPRESENTS A PRELIMINARY INVESTIGATION INTO THE FEASIBILITY AND EVOLUTION OF SUCH AN APPROACH BASED ON :HEURISTIC: METHODS. THE REQUIRED FLEXIBILITY OF THE PROGRAM IMPLIES THE USE OF ADAPTIVE OR :HEURISTIC: METHODS. HOWEVER, INSTEAD OF IMPLEMENTING ANY KNOWN :LEARNING: SCHEME, THE PROGRAM IN THIS STUDY HAS BEEN EVOLVED STARTING WITH THE SIMPLEST SCHEME IN ORDER TO KEEP ITS COMPLEXITY TO A MINIMUM. SINCE RELIABILITY RATHER THAN ACCURACY IS THE MAIN CONCERN, THE SYSTEM DESCRIBED IS DESIGNED TO DEAL WITH SITUATIONS THAT ARE LIKELY TO OCCUR DURING START UP AND ARE THOSE OCCURRING DUE TO LARGE PERTURBATIONS DURING NORMAL OPERATION

322564 A7175040, B7139711, C7123123

PROCEEDINGS OF THE 1971 INTERSOCIETY ENERGY CONVERSION ENGINEERING CONFERENCE

; SOC. AUTOMOTIVE ENGRS., AMERICAN CHEM. SOC., AMERICAN INST. AERONAUTICS AND ASTRONAUTICS, AMERICAN SOC. MECH. ENGRS., IEEE, AMERICAN INST. CHEM. ENGRS., AMERICAN NUCL. SOC., AMERICAN POWER CONFERENCE, MARINE TECHNOLOGY SOC

1971

3-5 AUG. 1971 SOC. AUTOMOTIVE ENGRS., AMERICAN CHEM. SOC., AMERICAN INST. AERONAUTICS AND ASTRONAUTICS, AMERICAN SOC. MECH. ENGRS., IEEE, AMERICAN INST. CHEM. ENGRS., AMERICAN NUCL. SOC., AMERICAN POWER CONFERENCE, MARINE TECHNOLOGY SOC BOSTON, MASS., USA

PUBL: SOC. AUTOMOTIVE ENGRS. NEW YORK, USA

DESCRIPTORS: ELECTRICITY DIRECT CONVERSION, DIRECT ENERGY CONVERSION, POWER SYSTEMS, HEAT ENGINES

IDENTIFIERS: AUTOMOTIVE, ENGINE, EMISSIONS, ELECTRIC VEHICLE, POWER, SPACE FLIGHT, ENERGY CONVERSION, MEDICAL APPLICATIONS, BIOLOGICAL, ECOLOGICAL, COMPRESSION IGNITION, RADIOISOTOPE THERMOELECTRIC GENERATORS, UNDERWATER, SYSTEMS, METEOROLOGICAL EFFECTS, NUCLEAR, BATTERY, THERMAL, POLLUTION, COMPUTER SIMULATION, STIRLING ENGINES, NOISE, FUSION, HEAT, FOSSIL FUEL

SECTION CLASS CODES: A0535, B4400, C7550, B4110

THE FOLLOWING TOPICS WERE DEALT WITH: FUTURE POWER-GENERATOR METHODS; ADVANCED AUTOMOTIVE ENGINE EMISSIONS; ELECTRIC VEHICLE SYSTEMS; POWER FOR MANNED SPACE FLIGHT; ENERGY CONVERSION SYSTEMS FOR MEDICAL APPLICATIONS; ADVANCED AUTOMOTIVE ENGINES; BIOLOGICAL AND ECOLOGICAL EFFECTS OF EMISSIONS; ADVANCES IN COMPRESSION IGNITION ENGINES; RADIOISOTOPES THERMOELECTRIC GENERATOR FOR ADVANCED MISSIONS; UNDERWATER POWER SYSTEMS; METEOROLOGICAL EFFECTS OF EMISSION; NUCLEAR POWER SYSTEMS; BATTERY DEVELOPMENTS; THERMAL POLLUTION EFFECTS; SMALL STATIONARY POWER SOURCES; CLOSED CYCLE ENGINES; POWER SYSTEMS FOR ADVANCED MISSIONS; SPACE POWER TECHNOLOGY; POWER SYSTEM COMPUTER SIMULATION; STIRLING ENGINES; NOISE POLLUTION; ADVANCES IN FUSION POWER PLANTS; HEAT ENGINE HYBRID AUTOMOTIVE POWER PLANTS; RADIOISOTOPE THERMOELECTRIC GENERATORS TEST AND FLIGHT RESULTS; ADVANCES IN FOSSIL FUEL POWER PLANTS; ADVANCED AUTOMOTIVE ENGINE TECHNOLOGY. 141 PAPERS WERE PRESENTED, OF WHICH ALL ARE PUBLISHED IN FULL IN THE PRESENT PROCEEDINGS. INDIVIDUAL PAPERS WITHIN THE SUBJECT SCOPE OF THIS JOURNAL WILL BE ABSTRACTED IN THIS OR A SUBSEQUENT ISSUE.

320802 A7174988, B7138590

ACOUSTICAL ENGINEERING AT JET TEST SITE

ENVIRON. CONTROL. SAF. MANAGE. (USA) VOL. 142, NO. 1 20-1 JULY 1971

DESCRIPTORS: NOISE/ACOUSTIC, NOISE, AIRCRAFT, AEROSPACE TEST FACILITIES

IDENTIFIERS: JET PLANE ENGINE, TURBOFAN ENGINE, NOISE ATTENUATING EQUIPMENT, ACOUSTICAL ENGINEERING, COMPUTER SYSTEM, SOUND ABSORBING MATERIALS

SECTION CLASS CODES: A0340, B3610

A NEED FOR A VIBRATION PREP CONTROL AND MONITORING CENTRE IS EMPHASISED

301526 C7119937

A GENERALIZED METHOD FOR CALCULATION AND ANALYSIS OF THE ACTUAL ICE CYCLE WITH CONSTANT PRESSURE IN THE SCAVENGING AND EXHAUST CHAMBERS USING A DIGITAL COMPUTER

JANKOV, R. ; UNIV. BEOGRADU, YUGOSLAVIA

TEHNIKA (YUGOSLAVIA) VOL.26, NO.4 701-16 1971 CODEN: TEHNA7

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, NUMERICAL METHODS, HEAT SYSTEMS

IDENTIFIERS: ICE CYCLE, SCAVENGING AND EXHAUST CHAMBERS, DIGITAL COMPUTER, DIESEL ENGINES, VARIABLES PRESSURES, INTERNAL ENERGY, DISSOCIATION AND VARIABILITY OF THE SPECIFIC HEAT, GAS COMPOSITION, NUMERICAL METHOD, SCAVENGING CURVE, STATIONARY MODEL TEST, SCAVENGING PROCESS, BACK FLOW OF GASES, LAWS OF COMBUSTION, HEAT TRANSFER, LEAKAGE LOSSES AND GAS VOLUME INCREASE, DIESEL ENGINE, COMPLEX SIMILARITY LAW

SECTION CLASS CODES: C8829

LANGUAGE: CROATIAN

THE METHOD CAN BE USED FOR TWO- AND FOUR-STROKE PETROL AND DIESEL ENGINES WITH CONSTANT PRESSURE IN SCAVENGING AND EXHAUST CHAMBERS AND ALSO WITH VARIABLE PRESSURES IF THESE ARE KNOWN BY MEASUREMENT. FOR CALCULATION OF THE INTERNAL ENERGY OF THE GASES IN THE CYLINDER, THE DISSOCIATION AND VARIABILITY OF THE SPECIFIC HEAT AS A FUNCTION OF TEMPERATURE AND GAS COMPOSITION WERE TAKEN INTO ACCOUNT. A NUMERICAL METHOD USING THE SCAVENGING CURVE FROM A STATIONARY MODEL TEST WAS DEVELOPED FOR CALCULATION OF THE SCAVENGING PROCESS WITH ALLOWANCE FOR BACK FLOW OF GASES INTO THE SCAVENGING CHAMBER. THE LAWS OF COMBUSTION, HEAT TRANSFER, LEAKAGE LOSSES AND GAS VOLUME INCREASE IN THE CYLINDER DUE TO COMBUSTION IN THE CASE OF THE DIESEL ENGINE WERE ALSO TAKEN INTO ACCOUNT. ALL PARTS OF THE CYCLE ARE DESCRIBED BY THE SAME SYSTEM OF EQUATIONS WHICH ARE TRANSFORMED TO PERMIT APPLICATION OF A COMPLEX SIMILARITY LAW (21 REFS)

301491 C7119902

ON LINE FOR QUICK THINKING

ASHTON, S.

ENGINEER SUPPL. (GB) 22-4 30 JUNE 1971 CODEN: ESRSB6

DESCRIPTORS: PROCESS CONTROL, TABLE-TOP COMPUTERS, ON-LINE OPERATION

IDENTIFIERS: CONTROL SYSTEMS, PROCESS CONTROL, MINI COMPUTER, FLEXIBILITY, SOFTWARE, DATA LOGGING, ENGINE TESTING, PROCESS PLANT MONITORING, GEARBOX TESTING, AXLE TESTING, MECHANICAL HANDLING

SECTION CLASS CODES: C8825

SMALL COMPUTERS HAVE OPENED THE WAY TO ON-LINE CONTROL OF MANY PROCESSES ON THE SHOP FLOOR. THIS PAPER LOOKS AT THE LIKELY APPLICATIONS

300794 C7119173

THE USES OF A REAL TIME COMPUTER IN NUCLEAR ROCKET ENGINE TESTING  
 HENSHALL, J.B. ; UNIV. CALIFORNIA, LOS ALAMOS, USA  
 ; AKASHI SEISAKUSHU LTD., ET AL  
 PROCEEDINGS OF THE 8TH INTERNATIONAL SYMPOSIUM ON SPACE TECHNOLOGY  
 AND SCIENCE 121-30 1969  
 25-30 AUG 1970 AKASHI SEISAKUSHU LTD., ET AL TOKYO, JAPAN  
 PUBL: AGNE PUBLISHING INC. TOKYO, JAPAN  
 DESCRIPTORS: NUCLEAR SYSTEMS, AEROSPACE CONTROL  
 IDENTIFIERS: REAL TIME COMPUTER, NUCLEAR ROCKET ENGINE TESTING,  
 PROPULSION SYSTEM, NUCLEAR ENERGY  
 SECTION CLASS CODES: C7575

A PROGRAM TO DEVELOP A PROPULSION SYSTEM UTILIZING NUCLEAR ENERGY  
 HAS BEEN UNDERWAY FOR TEN YEARS IN THE UNITED STATES. THE PROPULSION  
 UNIT CONSISTS OF A SOLID REACTOR WITH THE NUCLEAR ENERGY TRANSFERRED  
 TO HYDROGEN PROPELLANT. THE LOW MOLECULAR WEIGHT OF HYDROGEN GIVES A  
 SPECIFIC IMPULSE EXCEEDING 800 SEC. IN THE TESTING PROGRAM, THE  
 REACTOR IS OPERATED AT TEMPERATURES AND POWER DENSITIES WHICH ARE  
 CLOSE TO MATERIAL LIMITS. THEREFORE IT BECOMES NECESSARY TO MONITOR,  
 DURING THE TEST, REACTOR AND FACILITY PERFORMANCE. THESE MONITORING  
 FUNCTIONS AND OTHER APPLICATIONS HAVE BEEN SOLVED BY THE USE OF A REAL  
 TIME DIGITAL COMPUTER. IN ADDITION, THE COMPUTER GENERATES THE TIME  
 PROFILES REQUIRED TO START THE REACTOR AND RELATED FACILITY SYSTEMS  
 AND CONTROL THEIR OPERATION DURING THE POWERED PHASE OF THE TEST.  
 FUTURE CONTROL USES CONTEMPLATED FOR THE COMPUTER ARE DISCUSSED

300763 C7119141

COMPUTER CONTROL OF MARINE ENGINES (PROPULSION)  
 SWITZMAN, J.  
 ; SOC. ELECTRONIC AND RADIO TECHNICIANS  
 PROCEEDINGS OF THE SYMPOSIUM ON MARINE ELECTRONICS 109-17 1971  
 9-12 JUL 1971 SOC. ELECTRONIC AND RADIO TECHNICIANS BRISTOL,  
 ENGLAND  
 PUBL: SOC. ELECTRONIC AND RADIO TECHNICIANS LONDON, ENGLAND  
 DESCRIPTORS: MARINE SYSTEMS, TRANSPORTATION, CONTROL ENGINEERING  
 APPLICATIONS OF COMPUTERS  
 IDENTIFIERS: MARINE PROPULSION ENGINES, COMPUTER CONTROL, UNATTENDED  
 ENGINE ROOM OPERATION, EFFECT OF FAILURES, INCREASED RESPONSIBILITY  
 SECTION CLASS CODES: C7574, C8825  
 WORLD WIDE GROWTH OF TRADE AND SHIPPING, TECHNICAL DEVELOPMENTS,  
 SHORTAGE OF SKILLED MANPOWER HAVE LED TO INCREASING INTRODUCTION OF  
 UNATTENDED ENGINE ROOM OPERATION AT SEA AND THE PARALLEL INTRODUCTION  
 OF AUTOMATION TO MAKE THIS POSSIBLE. AT THE SAME TIME THE EFFECT OF  
 FAILURES OF MACHINE OR MAN ARE MUCH MORE SERIOUS IN ALL ASPECTS.  
 REDUCTION IN ENGINE ROOM CREW, LARGER AND MORE COMPLEX MACHINERY,  
 NON-CONTINUOUS ATTENDANCE IN THE ENGINE ROOM PLACE AN EVEN BIGGER  
 RESPONSIBILITY ON THE SHIP'S CREW

290983 C7117423

A HYBRID COMPUTER ANALYSIS OF A NON-STATIONARY PROCESS  
BEAUCHAMP, K.G., THOMASSON, P.G., WILLIAMSON, H.E. ; CRANFIELD  
INST. TECHNOL., ENGLAND  
GLADWELL, G.M.L.  
; UNIV. WATERLOO  
PROCEEDINGS OF THE SYMPOSIUM ON COMPUTER-AIDED ENGINEERING 19-30  
1971

11-13 MAY 1971 UNIV. WATERLOO WATERLOO, ONTARIO, CANADA  
PUBL: UNIV. WATERLOO WATERLOO, ONTARIO, CANADA  
DESCRIPTORS: HYBRID COMPUTER METHODS, AEROSPACE APPLICATIONS OF  
COMPUTERS, TIME-VARYING SYSTEMS, ACOUSTIC NOISE, HEAT SYSTEMS  
IDENTIFIERS: HYBRID COMPUTER ANALYSIS, NONSTATIONARY PROCESS, JET  
ENGINE NOISE, SPECTRAL ANALYSIS, AIRCRAFT NOISE ABATEMENT  
SECTION CLASS CODES: C8829, C9950

THE PROBLEM OF JET AIRCRAFT NOISE IS AN INCREASING ONE AND THE  
DESIGN ENGINEER WILL SOON BE FACED WITH THE TASK OF LIMITING THIS TO  
THE MANDATORY LEGAL REQUIREMENTS GOVERNING THE NOISE RADIATED FROM THE  
AIRCRAFT IN FLIGHT. A NECESSARY PREREQUISITE IS TO UNDERSTAND MORE ABOUT  
THE NATURE OF THIS NOISE. IT IS RELATIVELY EASY TO TAKE SOUND  
MEASUREMENTS FROM AN AIRCRAFT SITUATED ON THE GROUND, BUT SIMILAR  
MEASUREMENTS TAKEN AT GROUND LEVEL FOR AN AIRCRAFT IN FLIGHT PRESENT A  
NUMBER OF DIFFICULTIES DUE TO THE COMPLEX NON-STATIONARY NATURE OF THE  
RADIATED NOISE. THIS PAPER ATTEMPTS TO DESCRIBE A SPECTRAL ANALYSIS  
METHOD BY WHICH THE ENGINEER CAN BE GIVEN A QUANTITATIVE DESCRIPTION  
OF DETECTED NOISE VALUES SO AS TO ENABLE AN ASSESSMENT TO BE MADE OF  
THE EFFECTIVENESS OF HIS PRACTICAL MEASURES IN AIRCRAFT NOISE  
ABATEMENT



290849 C7117280

REMOTF TEST SITE COMPUTATION OF COMPLEX ENGINE INLET DYNAMIC  
PARAMETERS USING AN ANALOG COMPUTERSMITH, E.L., FLEETWOOD, P.H. ; MCDONWELL AIRCRAFT CO., ST. LOUIS,  
MO., USA

; INSTRUMENT SOC. AMERICA

STD BOOK NO.: 87664 141 9

ADVANCES IN INSTRUMENTATION, PROCEEDINGS OF THE 25TH ANNUAL ISA  
CONFERENCE 647/1-9 1970II 26-29 OCT 1970 INSTRUMENT SOC. AMERICA PHILADELPHIA, PA.,  
USA

PUBL: INSTRUMENT SOC. AMERICA PITTSBURGH, PA., USA

DESCRIPTORS: AIRCRAFT

IDENTIFIERS: REMOTF TEST SITE COMPUTATION, ANALOG COMPUTER, COMPLEX  
ENGINE INLET DYNAMIC PARAMETERS, INTEGRATED CIRCUIT OPERATIONAL  
AMPLIFIERS

SECTION CLASS CODES: C8821

A SYSTEM TO PROVIDE REAL TIME COMPUTATION AND DISPLAY OF COMPLEX  
ENGINE INLET DISTORTION PARAMETERS WHICH ARE COMPUTED FROM A LARGE  
NUMBER OF DYNAMIC PRESSURE DATA SIGNALS, WAS SUCCESSFULLY IMPLEMENTED,  
USING INTEGRATED CIRCUIT OPERATIONAL AMPLIFIERS AS THE PRIMARY ANALOG  
COMPUTATIONAL ELEMENTS. PRATT AND WHITNEY ENGINE PARAMETERS IN USE AT  
THE TIME ARE SHOWN AND HARDWARE DIAGRAMS OF THE COMPUTATIONAL  
CIRCUITS ARE EXPLAINED. IT IS SHOWN HOW THE SYSTEM PROVIDED FLAGGING  
PULSES TO THE RAW DATA TAPES FOR SUBSEQUENT DIGITIZATION AND COMPUTER  
ANALYSIS OF :WORST CASE: DATA, WITH RESULTANT IMPROVEMENT IN TEST DATA  
AT SIGNIFICANT SAVINGS IN TIME AND MONEY

290156 C7116550

THE NOEEN PROJECT: OPERATIONAL CONTROL AND AUTOMATION ABOARD SHIP BY COMPUTER

DRAGPR, K.H. ; DET NORSKE VERITAS, OSLO, NORWAY  
 ; NORWEGIAN ASSOC. PROFESSIONAL ENGRS., POLYTECH. ASSOC. NORWEGIAN ASSOC. PROFESSIONAL ENGRS., IEEE, NORWEGIAN SECTION, NORWEGIAN ASSOC. ELECTRIC. ENGRS

ELEKTROTEK. TIDSSKR. (NORWAY) VOL.84, NO.8 54 6 MAY 1971  
 CODEN: ETTOAA

CONF: 24TH MEETING OF RADIOTECHNOLOGY AND ELECTRO-ACOUSTICS (ABSTRACTS ONLY RECEIVED) 18-20 JUN 1971 NORWEGIAN ASSOC. PROFESSIONAL ENGRS., POLYTECH. ASSOC. NORWEGIAN ASSOC. PROFESSIONAL ENGRS., IEEE, NORWEGIAN SECTION, NORWEGIAN ASSOC. ELECTRIC. ENGRS BODO, NORWAY

DESCRIPTORS: MARINE SYSTEMS, ENGINEERING APPLICATIONS OF COMPUTERS, HEAT ENGINES, PRESSURE AND VACUUM MEASUREMENT, TEMPERATURE MEASUREMENT, CONTROL ENGINEERING APPLICATIONS OF COMPUTERS, COMPUTER-AIDED ANALYSIS

IDENTIFIERS: DIESEL ENGINE INFORMATION, PRESSURE MEASUREMENT, TEMPERATURE MEASUREMENT, ENGINE CYLINDERS, COMPUTER INSTALLATION, AUTOMATIC CONTROL, SHIP'S ENGINE ROOM, CRT DISPLAY, FAULT FINDING ROUTINES, COMBUSTION

SECTION CLASS CODES: C7574, C8825, C8829

LANGUAGE: NORWEGIAN

A COMPUTER INSTALLATION USED FOR THE AUTOMATIC CONTROL OF A SHIP'S ENGINE ROOM IS DESCRIBED. TWO MACHINES ARE USED, ONE FOR PERFORMING REAL TIME TASKS, AND THE OTHER FOR DOING BATCH PROCESSING JOBS INITIATED BY EITHER THE FIRST MACHINE OR BY THE OPERATOR. INFORMATION ABOUT THE DIESEL ENGINES IS GIVEN ON A CRT DISPLAY AND FAULT FINDING ROUTINES CAN BE USED. IN PARTICULAR, THE PRESSURE AND TEMPERATURE IN THE ENGINES CYLINDERS DURING COMBUSTION CAN BE MEASURED. THE INSTALLATION IS ARRANGED TO BE EASILY ACCESSIBLE, AND HAS SELF CHECKING FACILITIES. ALL THE CONTROLS AND DISPLAYS ARE ON THE ENGINE ROOM CONTROL DESK, SO THAT CENTRAL COMMAND OF THE ENGINE ROOM IS OBTAINED

289851 C7116222

DIGITAL ENGINE CONTROL

AVIAT. REV. (GB) NO.26 16-17 MAY 1971

DESCRIPTORS: AEROSPACE INSTRUMENTATION, AEROSPACE CONTROL, TURBINES

IDENTIFIERS: ENGINE CONTROL EQUIPMENT, DIGITAL

SECTION CLASS CODES: C7551

289766 C7116131

CZECH PNEUMATIC LOGIC SYSTEM  
FLUID POWER INT. (GB) VOL. 36, NO. 422 43-5, 8 MAY 1971  
CODEN: PLPIAT

DESCRIPTORS: PNEUMATIC EQUIPMENT, LOGIC DEVICES  
IDENTIFIERS: PNEUMATIC LOGIC SYSTEM, PNEULOG, CZECHOSLOVAKIA, MARINE  
ENGINE CONTROL, SWITCHES, ANALOGUE DIGITAL SIGNAL CONVERTERS,  
TRANSDUCERS, PROGRAMMING DEVICES, ELECTROPNEUMATIC CONVERTERS  
SECTION CLASS CODES: C7461, C9240  
PNEUMATIC LOGIC SYSTEMS EMPLOYING MOVING PART ELEMENTS ARE USED  
FAIRLY WIDELY IN EUROPE. THIS ARTICLE DESCRIBES TWO RECENT  
APPLICATIONS OF THE PNEULOG SYSTEM DEVELOPED IN CZECHOSLOVAKIA

264830 B7120531, C7112548

ACCELERATION PERFORMANCE ANALYSIS OF A GAS TURBINE DESTROYER ESCORT  
BODNARUK, A., RUBIS, C.J. ; NAVAL SHIP RES. AND DEV. LAB.,  
ANNAPOLIS, MD., USA

TRANS. ASME SER. A (USA) VOL. 93, NO. 1 49-56 JUNE 1971 CODEN:  
JEPOA8

DESCRIPTORS: GAS TURBINES, COMPUTER APPLICATIONS, ACCELERATION  
MEASUREMENT, ENGINEERING APPLICATIONS OF COMPUTERS, TURBINES,  
COMPUTER-AIDED ANALYSIS

IDENTIFIERS: DYNAMIC ACCELERATION PERFORMANCE ANALYSIS, GAS TURBINE  
ENGINE, SINGLE SCREW DESTROYER ESCORT, REVERSING REDUCTION GEAR,  
DIGITAL COMPUTER ANALYSIS, PROPELLER THRUST, TORQUE COEFFICIENTS, SHIP  
PROPULSION, PROPULSION PLANT PARAMETERS, FUEL SCHEDULED ACCELERATION,  
BASE PLUS BOOST OPERATING MODES, FUEL FLOW RATE CONTROL, FUEL RAMPS,  
TIME BASES, ENGINE OVERTORQUE CONDITIONS, TRANSIENT THRUST

SECTION CLASS CODES: B4240, C8829

THE DYNAMIC ACCELERATION PERFORMANCE OF A SINGLE SCREW DESTROYER  
ESCORT DRIVEN BY TWO FT4A-2 GAS TURBINE ENGINES THROUGH A REVERSING  
REDUCTION GEAR WAS ANALYSED. THE ANALYSIS WAS CARRIED OUT ON A DIGITAL  
COMPUTER USING A NEW METHOD OF A SECOND MODIFIED ADVANCE COEFFICIENT  
TO REPRESENT PROPELLER THRUST AND TORQUE COEFFICIENTS. QUANTITATIVE  
RESULTS FOR ALL THE MAJOR SHIP AND PROPULSION PLANT PARAMETERS ARE  
GIVEN FOR THE SHIP IN A CALM SEA WITH NO TURNING MOTIONS DURING FUEL  
SCHEDULED ACCELERATION IN THE BASE AND BASE-PLUS-BOOST OPERATING  
MODES. CONTROL OF FUEL FLOW RATES USING FUEL RAMPS WITH VARYING TIME  
BASES WAS FOUND TO BE EFFECTIVE IN LIMITING ENGINE OVERTORQUE  
CONDITIONS DURING ACCELERATION. OTHER CONCLUSIONS ON TRANSIENT THRUST,  
ACCELERATION TIME, AND HEAD REACH ARE ALSO PRESENTED

264820 C711253H

METHOD FOR IGNITION SYSTEM TESTING AND SERVICING DECISIONS  
BRINEY, L.S., KAHN, H., LEVITRE, P.J., LINVILLE, T.P., PETERSEN,  
P.G., SKARSHINSKI, L., WIDMER, A.X.

IBM TECH. DISCLOSURE BULL. (USA) VOL.13, NO.10 3185-A MARCH  
1971 CODEN: IBMTAA

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, COMPUTER AIDED  
ANALYSIS

IDENTIFIERS: COMPUTER CONTROLLED AUTOMOBILE DIAGNOSTIC SYSTEM,  
IGNITION SYSTEM TESTING TECHNIQUES, SERVICING DECISION, SPARK PLUGS  
DIAGNOSIS, DISTRIBUTOR CAP, ROTOR, INTERNAL COMBUSTION ENGINE TESTING,  
HIGH VOLTAGE PULSE GENERATION, IGNITION SECONDARY COILS, ANALOGUE  
CIRCUITRY, SPARK PLUG WIRES VOLTAGE DETECTION, SPARK PLUG DISCHARGES,  
SPARK PLUG FIRING POTENTIALS, SPARK LINE LENGTH AND SLOPE, DATA  
SAMPLES COLLECTION

SECTION CLASS CODES: C8829

DESCRIBES A METHOD FOR DIAGNOSIS OF THE SPARK PLUGS, SPARK PLUG  
WIRES, AND DISTRIBUTOR CAP AND ROTOR OF AN INTERNAL COMBUSTION ENGINE  
WITHOUT DISASSEMBLY OR REMOVAL OF COMPONENT PARTS. THE METHOD CAN BE  
IMPLEMENTED WITH A COMPUTER CONTROLLED AUTOMOBILE DIAGNOSTIC SYSTEM. A  
SPECIAL APPARATUS PRODUCES A CONTROLLED HIGH-VOLTAGE PULSE, SIMILAR TO  
THE USUAL PULSE FROM THE IGNITION COIL SECONDARY, WHICH IS FED TO THE  
DISTRIBUTOR. THE SPECIAL APPARATUS ALSO CONTAINS DETECTORS AND OTHER  
ANALOGUE CIRCUITRY USED TO DETECT VOLTAGE ON THE SPARK PLUG WIRES AND  
THE END OF EACH SPARK PLUG DISCHARGE. A COMPUTER COLLECTS DATA SAMPLES  
AND COMPUTES SPARK PLUG FIRING POTENTIAL, SPARK LINE LENGTH, AND SPARK  
LINE SLOPE

246985 C7109087

COMPUTER GRAPHICS APPLICATIONS

GANDERTON, R.A.

COMPUT. AIDED DES. (GB) VOL.2, NO.3 49-60 1970 CODEN: CAIDA5

DESCRIPTORS: COMPUTER GRAPHICS, ENGINEERING APPLICATIONS OF  
COMPUTERS, COMPUTER-AIDED DESIGN, REVIEWS

IDENTIFIERS: COMPUTER GRAPHICS APPLICATIONS, HARD COPY GRAPHICS,  
INTERACTIVE GRAPHICS, DIESEL ENGINE PISTON DESIGN, CONCRETE COLUMN  
DESIGN, BRIDGE DESIGN, RACING ROWING BOATS, MULTISPINDLE DRILLING  
MACHINES, PIERCE AND BLANK TOOLS, CONTROL SYSTEMS, INTEGRATED CIRCUIT  
DESIGN, INFORMATION DISPLAY, PRINTED CIRCUIT BOARD LAYOUT

SECTION CLASS CODES: C8820

CONSIDERS SOME OF THE COMMERCIAL APPLICATIONS OF COMPUTER GRAPHICS.  
THERE ARE BASICALLY TWO FORMS GRAPHICS CAN TAKE-HARDCOPY GRAPHICS,  
I.E. PLOTTERS AND DRAUGHTING MACHINES, AND C.R.T. DISPLAYS. THE FIRST  
TYPE IS NOT TRULY INTERACTIVE, AND IS USED PRIMARILY TO OBTAIN  
HARDCOPY OUTPUT TO THE PROBLEM INVOLVED. THE SECOND TYPE MAY OR MAY  
NOT BE INTERACTIVE, AND THE LATTER CASE IS USED TO EASE OR SPEED UP  
THE MAN-MACHINE INTERFACE AS WELL AS OBTAIN A VISUAL OUTPUT. THE  
APPLICATIONS ARE GROUPED INTO HARDCOPY AND INTERACTIVE C.R.T.  
GRAPHICS. THE LIST IS BY NO MEANS EXHAUSTIVE OF THE WORK CURRENTLY  
BEING CARRIED OUT IN THE UK AND DOES NOT INCLUDE APPLICATIONS FROM  
OUTSIDE THE UK

244153 B7114494

NUCLEAR ROCKET EXPERIMENTAL ENGINE TEST RESULTS  
 DURKEE, W.E., DANERVAL, F.B. : AEROJET NUCLEAR SYSTEMS CO.,  
 SACRAMENTO, CALIF., USA

J. SPACECR. AND ROCKETS (USA) VOL.7, NO.12 1397-402 DEC. 1970

DESCRIPTORS: AEROSPACE PROPULSION, NUCLEAR POWER

IDENTIFIERS: NUCLEAR ROCKET EXPERIMENTAL ENGINE TEST RESULTS,  
 XE-PRIME, COMPUTER SIMULATION, AUTOMATIC TEMPERATURE STARTUPS, HIGH  
 SPECIFIC IMPULSE OPERATION, FULL POWER, PERFORMANCE, THROTTLED  
 PRESSURE

SECTION CLASS CODES: B4620

AN EXTENSIVE SERIES OF TESTS OF A NUCLEAR ROCKET EXPERIMENTAL  
 ENGINE, XE-PRIME, WAS COMPLETED IN 1969. THE MAIN EMPHASIS OF THE  
 SERIES WAS UPON CHARACTERISTICS OF STARTING FROM VARIOUS CONDITIONS  
 AND UPON OPERATION OF THE TEST FACILITY UNDER NUCLEAR FIRING  
 CONDITIONS; HOWEVER, ENGINE PERFORMANCE AT FULL POWER AND THROTTLED  
 PRESSURE WERE ALSO INVESTIGATED. THIS PAPER COMPARES SELECTED STARTUP  
 TEST RESULTS WITH PREDICTIONS MADE BY COMPUTER SIMULATION OF THE TEST  
 SYSTEM, AND IT BRIEFLY DESCRIBES FULL-POWER AND HIGH-SPECIFIC-IMPULSE  
 OPERATION. REPRESENTATIVE STARTUP DATA ARE PRESENTED FOR AUTOMATIC  
 TEMPERATURE STARTUPS PERFORMED WITH INITIAL LEVELS OF 0.1 W AND 2.7  
 MW, INITIAL CORE TEMPERATURES OF APPROXIMATELY 250 DEGREES AND 1250  
 DEGREESR, AND DRUM EXPONENTIAL SET POINTS OF +11 DEGREES AND -8.5  
 DEGREES FROM CRITICAL. THE TEST RESULTS SHOWED THAT STARTUP CAN BE  
 CONTROLLED OVER A WIDE RANGE OF INITIAL CONDITIONS

240555 C7107853

FLIGHT TEST EVALUATION OF AN ADVANCED ON-BOARD JET ENGINE MONITORING  
 SYSTEM

FESER, J.R. : EMERSON ELECTRIC CO., ST. LOUIS, MO., USA

: IEEE, AEROSPACE AND ELECTRONIC SYSTEMS GROUP

RECORD OF THE SYMPOSIUM ON AUTOMATIC SUPPORT SYSTEMS FOR ADVANCED  
 MAINTAINABILITY 58-69 1970

19-21 OCT 1970 IEEE, AEROSPACE AND ELECTRONIC SYSTEMS GROUP ST.  
 LOUIS, MO., USA

PUBL: IEEE NEW YORK, USA

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, REAL-TIME SYSTEMS,  
 AIRCRAFT, AUTOMATIC TESTING

IDENTIFIERS: FLIGHT TEST EVALUATION, JET ENGINE MONITORING SYSTEM,  
 REAL-TIME SYSTEM, INFLIGHT REAL-TIME JET ENGINE HEALTH ANALYSIS,  
 COMPUTER CONTROLLED JET ENGINE MONITORING SYSTEM

SECTION CLASS CODES: C8829

EMERSON ELECTRIC CO. DESIGNED, DEVELOPED AND FLIGHT TESTED ON-BOARD  
 A PAN AMERICAN WORLD AIRWAYS B707-321B AIRCRAFT AN ENGINE PERFORMANCE  
 MONITORING SYSTEM (EPMS). EPMS PROVIDES A MEANS OF DETERMINING THE  
 HEALTH OF THE OPERATING JET ENGINE ON A PROVEN TECHNICAL BASIS RATHER  
 THAN BY PERIODIC INSPECTION BASED ON ENGINE OPERATING TIME (TIME  
 COMPLIANCE). THE SYSTEM IS DESIGNED TO AUTOMATICALLY MONITOR AND  
 ANALYZE IN REAL TIME THE ENGINE PARAMETERS THAT ARE SENSITIVE  
 INDICATORS OF JET ENGINE HEALTH. ENGINE ANOMALIES CAN BE DETECTED (AND  
 ENGINE MAINTENANCE SCHEDULED), TEN TO TWENTY-FOUR HOURS SOONER THAN  
 SYSTEMS UTILIZING ON-BOARD RECORDING AND GROUND PROCESSING (13 REFS)

240182 C7107455

COMPUTER MODELING OF ROCKET ENGINE IGNITION TRANSIENTS

MILLS, T.R., BRENN, B.P.

REPORT NO.: NASA-CR-109865 ISSUED BY: DYNAMIC SCI., IRVINE,  
CALIF., USA

CONTRACT NO.: NAS7-467

MAY 1970

DESCRIPTORS: MODELLING, PROGRAMMING, SPACE VEHICLES

IDENTIFIERS: COMPUTER MODELLING, ROCKET ENGINE IGNITION TRANSIENTS,  
PROGRAMMING, SPACE VEHICLES, TRANSIENT PROPELLANT FLOW,  
PRESSURE/TEMPERATURE HISTORIES, ANALYTICAL TESTS, IGNITION SPIKING,  
FUEL LEADS, CONTROLLED VALVE OPENING SEQUENCES, DIGITAL COMPUTER,  
CHAMBER PRESSURIZATION PROGRAM, STARTING CHARACTERISTICS, MAXIMUM  
PRESSURE PREDICTION, FUEL/OXIDIZER MIXTURE ENVIRONMENT

SECTION CLASS CODES: C8340, C6120

AVAILABILITY: CPSTI, SPRINGFIELD, VA. 22151, USA

A COMPUTER PROGRAM WAS WRITTEN TO DESCRIBE TRANSIENT PROPELLANT FLOW AND THE PRESSURE/TEMPERATURE AND O/F HISTORIES WITH THE CHAMBER PRIOR TO IGNITION. EXPERIMENTAL TESTS WERE PERFORMED WHICH CONFIRMED THE ANALYTICAL FINDINGS. IGNITION SPIKING OCCURRED WITH FUEL LEADS AT LOW FUEL TEMPERATURE, AND EVEN AT HIGH FUEL TEMPERATURES WITH LONG VACUUM LEADS; WHILE SPIKING WAS REDUCED BY CONTROLLED VALVE OPENING SEQUENCES AT NOMINAL TEMPERATURES. THE ANALYTICAL STUDY RESULTED IN A PROPELLANT TRANSIENT FLOW DIGITAL COMPUTER PROGRAM AND A CHAMBER PRESSURIZATION TRANSIENT DIGITAL COMPUTER PROGRAM WHICH WAS USED TO OBTAIN THE ENGINE STARTING CHARACTERISTICS. THE DATA FROM THE PRESSURIZATION PROGRAM IS USED TO PREDICT MAXIMUM PRESSURES POSSIBLE FROM THE TRANSIENT CHAMBER FUEL/OXIDIZER MIXTURE ENVIRONMENT

239401 C7106650

TURBOPROP FUEL CONTROL FOR USE WITH CONTAMINATED OR VARIED FUELS

FREDLAKE, J.J., KECK, M.P., SCHWENT, G.V.

PATENT NO.: USA 3514949 ASSIGNERS: US NAVY FILED: 18 JUNE 1968

ORIGINAL PATENT APPL. NO.: USA 737958

2 JUNE 1970

DESCRIPTORS: HEAT ENGINES, FLOW CONTROL, TURBINES

IDENTIFIERS: FUEL FLOW CONTROL, TURBOPROP ENGINE, ENGINE POWER  
CONTROL SYSTEM, CONSTANT SPEED PROPELLER GOVERNOR, CONTAMINATED OR  
VARIED FUELS, COMPUTER SECTION OF ENGINE POWER CONTROL SYSTEM, ENGINE  
OIL WORKING MEDIA, CORRECT TORQUE, CORRECTED SPEED

SECTION CLASS CODES: C7551, C7326

AN ENGINE POWER CONTROL SYSTEM FOR A TURBO-PROP ENGINE EQUIPPED WITH A CONSTANT SPEED PROPELLER GOVERNOR IS PROVIDED WITH MEANS TO MANIPULATE FUEL FLOW IN RESPONSE TO THE CORRECT TORQUE AND CORRECTED SPEED OF THE ENGINE. THE COMPUTER SECTION OF THE ENGINE POWER CONTROL SYSTEM USES ENGINE OIL AS THE WORKING MEDIA. THESE FEATURES ENABLE CONTAMINATED FUEL, OR FUELS OF VARYING QUALITY TO BE USED, WITHOUT REQUIRING FILTRATION OR COMPENSATING ADJUSTMENTS TO THE CONTROL SYSTEM

239290 C7106538

FLUIDIC DIGITAL CONTROL APPARATUS HAVING MULTI-PHASE CONTROL FREQUENCY

EASTMAN, J.M.

PATENT NO.: USA 3532081 ASSIGNERS: BENDIX CORP. FILED: 14 MARCH 1968

ORIGINAL PATENT APPL. NO.: USA 712976

6 OCT. 1970

DESCRIPTORS: FLUIDICS, DIGITAL CONTROL

IDENTIFIERS: DIGITAL CONTROL, FLUIDIC, MULTIPHASE, CONTROL FREQUENCY, ENGINE GOVERNOR, PULSE GENERATOR, SPEED ERROR, BEAT FREQUENCY

SECTION CLASS CODES: C7463

REFERS TO AN ENGINE GOVERNOR APPARATUS HAVING A REFERENCE SPEED VARIABLE FREQUENCY FLUID PULSE GENERATOR AND AN ENGINE SPEED VARIABLE FREQUENCY FLUID PULSE GENERATOR, ONE OF WHICH GENERATES A FOUR PHASE FLUID PULSE OUTPUT AGAINST WHICH THE OTHER FLUID PULSE GENERATOR OUTPUT IS COMPARED. THE REFERENCE SPEED AND ENGINE SPEED FLUID PULSES PROVIDE A CONTROL INPUT TO A PLURALITY OF PULSE OPERATED FLUIDIC DEVICES WHICH RESPOND TO THE OUTPUTS OF THE TWO GENERATORS IN ACCORDANCE WITH A SYNCHRONIZATION OF THE PULSE OUTPUT OF THE OTHER GENERATOR WITH THE FOUR PHASE PULSE OUTPUT OF THE ONE GENERATOR. THE DIRECTION OF ENGINE SPEED ERROR IS ESTABLISHED BY THE ORDER OF SYNCHRONIZATION OF THE FOUR PHASE PULSE OUTPUT AND THE COMPARED PULSE OUTPUT. THE MAGNITUDE OF THE SPEED ERROR IS ESTABLISHED BY THE FREQUENCY AT WHICH THE PULSES SYNCHRONIZE. A CONTROL FLUID PULSE OUTPUT AT THIS SYNCHRONIZATION OR :BEAT: FREQUENCY IS GENERATED BY EITHER OF TWO FLUIDIC DEVICES ONE OF WHICH IS CONNECTED TO RESPOND TO THE FOUR PULSE OUTPUTS IN A FIRST SEQUENTIAL ORDER REPRESENTING ENGINE OVERSPEED AND THE OTHER OF WHICH IS CONNECTED TO RESPOND TO THE FOUR PULSE OUTPUTS IN A SECOND SEQUENTIAL ORDER REPRESENTING ENGINE UNDERSPEED. THE ENGINE FUEL FLOW RATE IS CAUSED TO STEP UP OR DOWN IN SMALL INCREMENTS WITH THE CONTROL FLUID PULSES. AN ANALOG PROPORTIONAL GOVERNING ACTION IS ADDED TO THIS DIGITAL GOVERNING ACTION

227927 C7104841

## SPACECRAFT CONTROL

REPORT NO.: UNNUMBERED ISSUED BY: CALIFORNIA INST. TECHNOL.,  
PASADENA, USA  
31 DEC. 1969

DESCRIPTORS: AEROSPACE CONTROL, ELECTRIC SENSING DEVICES, ELECTRICAL  
CONTROL EQUIPMENT, STABILITY, SPACE VEHICLE

IDENTIFIERS: SPACECRAFT CONTROL, DIGITAL SUN SENSOR, GRAY CODED  
DIGITAL SIGNAL, THRUST VECTOR CONTROL ANALYSIS, SOLAR ELECTRIC ION  
ENGINE, TORQUE, RATE INFORMATION, POSITION ERROR, FILTERING TECHNIQUES  
INVESTIGATION, ELECTROMAGNETIC ACCELEROMETER, EVALUATION, STABILITY,  
THERMAL STERILIZATION CAPABILITIES

SECTION CLASS CODES: C7576, C7421

AVAILABILITY: CPSTI, SPRINGFIELD, VA. 22151, USA

A DIGITAL SUN SENSOR IS DESCRIBED THAT USES A LINE IMAGE OF THE SUN  
ON A DIGITAL DETECTOR TO PROVIDE THE SUN ANGLE IN TERMS OF A  
GRAY-CODED DIGITAL SIGNAL. A SINGLE-AXIS BREADBOARD DESIGN HAVING A  
5-DEGREE FIELD-OF-VIEW HAD AN OUTPUT OF AN 8-BIT DIGITAL WORD. DYNAMIC  
ANALYSIS OF THRUST VECTOR CONTROL FOR A SOLAR-ELECTRIC NON-ENGINE  
PROPELLED SPACECRAFT REVEALED THAT THE CONTROL TORQUE MUST BE LARGER  
THAN THE TORQUE GENERATED BY THE TRANSLATION OF THE ENGINE ARRAY IN  
ORDER TO INSURE STABILITY. A TECHNIQUE FOR DERIVING RATE INFORMATION  
HAS BEEN DEVELOPED AND APPLIED TO PRODUCE A SIGNAL THAT IS  
PROPORTIONAL TO THE POSITION ERROR. IT WAS DEMONSTRATED THAT  
SEQUENTIAL FILTERING TECHNIQUES MAY BE USED FOR INVESTING OR SELECTING  
CONTROL SYSTEM CONFIGURATIONS THROUGH TRADE-OFF ANALYSES. AN  
ELECTROMAGNETIC ACCELEROMETER WAS EVALUATED FOR STABILITY, THERMAL  
STERILIZATION CAPABILITIES, PERFORMANCE, AND SHOCK RESISTANCE

215920 C713406

BEA ENGINE OVERHAUL REWORK SCHEDULING AT HEATHROW AIRPORT  
PHY, M.

: BRITISH COMPUTER SOC

DATAWARE: DATA CAPTURE TODAY 9 1970

14-15 APR 1970 BRITISH COMPUTER SOC HULL, YORKS, ENGLAND

PUBL: BRITISH COMPUTER SOC. LONDON, ENGLAND

DESCRIPTORS: ADMINISTRATIVE DATA PROCESSING, AIRCRAFT, AEROSPACE  
APPLICATIONS OF COMPUTERS, MAINTENANCE ENGINEERING

SECTION CLASS CODES: C8640

EXTENDED ABSTRACT ONLY GIVEN, SUBSTANTIALLY AS FOLLOWS: THE REWORK  
SCHEDULING SYSTEM IS DESIGNED TO PRODUCE DAILY WORK SCHEDULES AND  
DAILY PROGRESS LISTS WHICH THE MEN ON THE SHOP FLOOR FOLLOW TO REPAIR  
COMPONENTS IN PRIORITY ORDER TO MEET THE TARGET DATES. THIS ENABLES  
BEA'S HOLDINGS OF SPARE ENGINES AND COMPONENTS TO BE CONSIDERABLY  
REDUCED. A DESCRIPTION OF THE ENGINE OVERHAUL REWORK SCHEDULING SYSTEM  
OUTLINE, ITS ADVANTAGES AND WORKING ARE PRESENTED IN THE PAPER



215391 C712833

THE DESIGN OF A DIGITAL THREE-TERM CONTROLLER AS A TURBOJET ENGINE SPEED GOVERNOR USING DIGITAL SIMULATION METHODS. I. DIGITAL SIMULATION OF THE DYNAMIC BEHAVIOUR OF A TWO-SPOOL TURBOJET ENGINE. II. A DIGITAL THREE-TERM CONTROLLER AS A TURBOJET ENGINE SPEED GOVERNOR

COTTINGTON, R.V.

REPORT NO.: ARC-30103 ISSUED BY: NAT. GAS TURBINE ESTAB.,  
FARNBOROUGH, ENGLAND  
1970

DESCRIPTORS: HEAT ENGINES, SPEED CONTROL, AEROSPACE CONTROL,  
SIMULATION, CONTROL SYSTEM SYNTHESIS, THREE-TERM CONTROL, DIGITAL  
CONTROL

SECTION CLASS CODES: C7551, C7575, C6210, C7322, C6120

AVAILABILITY: CFSTI, SPRINGFIELD, VA. 22151, USA

THE DYNAMIC BEHAVIOR OF A TWO-SPOOL TURBOJET ENGINE CAN BE DEFINED MATHEMATICALLY AND THUS SIMULATED IN A GENERAL PURPOSE DIGITAL COMPUTER. THE TECHNIQUE IS DESCRIBED TOGETHER WITH A BRIEF STATEMENT OF THE MATHEMATICAL THEORY. COMPARISON IS MADE BETWEEN THE BEHAVIOR OF A REAL ENGINE AND THAT OBTAINED FROM ITS DIGITAL SIMULATION, AND, IN GENERAL, GOOD AGREEMENT IS FOUND. A BRIEF DISCUSSION OF THE COMPARATIVE MERITS OF DIGITAL AND ANALOG SIMULATION IS ALSO PRESENTED. A DIGITAL THREE-TERM CONTROLLER AS A TURBOJET ENGINE ROTOR SPEED GOVERNOR WAS INVESTIGATED ON A TWO-SHAFT TURBOJET. THE CONTROLLER LOGIC WAS PROGRAMMED INTO A SPECIAL PURPOSE DIGITAL COMPUTER ON-LINE TO THE ENGINE. A NOVEL WAY OF APPLYING THE MODEL REFERENCE ADAPTATION TECHNIQUE WAS USED TO OPTIMIZE CONTROLLER GAIN SETTINGS OFF-LINE USING A DIGITAL SIMULATION FOR STEADY STATE AND TRANSIENT ENGINE BEHAVIOR. THE RESULTS FROM THE ENGINE TEST AND THE DIGITAL SIMULATION ARE PRESENTED

210910 C711133

ENGINE CONTROL BY DIGITAL COMPUTER

INDIAN AND E.ENG. VOL. 112, NO. 4 249 APRIL 1970

DESCRIPTORS: AEROSPACE APPLICATIONS OF COMPUTERS, DIRECT DIGITAL  
CONTROL, ON LINE OPERATION

SECTION CLASS CODES: C7575, C8829

THE OLYMPUS 593 FOR THE CONCORDE SUPERSONIC AIRLINER HAS A FULLY TRANSISTORIZED ANALOGUE CONTROL SYSTEM THAT IS AMONG THE MOST ADVANCED IN THE WORLD. THE NEXT STAGE IN ENGINE CONTROL TECHNOLOGY IS LIKELY TO BE THE INTRODUCTION OF DIGITAL CONTROL SYSTEMS, WHICH DEVELOPMENT IS DISCUSSED

188203 C7018688

MATHEMATICAL MODEL OF AN INTERNAL COMBUSTION ENGINE AND DYNAMOMETER TEST RIG

MONK, J., COMFORT, J. ; UNIV. WARWICK, ENGLAND

MEAS. AND CONTROL (GB) VOL. 3, NO. 6 T93-100 JUNE 1970

DESCRIPTORS: MODELLING, HEAT SYSTEMS, ANALOGUE COMPUTER METHODS, SIMULATION

SECTION CLASS CODES: C6120, C7551

AN ELECTRICAL CIRCUIT MODEL AND AN ANALOG COMPUTER SIMULATION HAVE BEEN DEVELOPED TO REPRESENT THE DYNAMIC BEHAVIOUR OF AN IC ENGINE AND EDDY CURRENT DYNAMOMETER SYSTEM. VARIOUS REFINEMENTS TO THE MODEL ARE INTRODUCED AND ITS PERFORMANCE IS COMPARED WITH THAT OF THE REAL SYSTEM USING PSEUDO-RANDOM BINARY SEQUENCE AND SINEWAVE TESTING TECHNIQUES. A BRIEF DESCRIPTION OF THE NECESSARY INSTRUMENTATION AND INTERFACING IS INCLUDED

175723 B7032322, C7017222

ELECTRONIC COMPUTERS, SIMULATORS AND TRAINING AIDS FOR SHIP-BORNE EQUIPMENT

TRANI, I.

ALTA FREQUENZA (ITALY) VOL.74, NO.SUPP.5 86-91 MAY 1970

DESCRIPTORS: SHIPS, COMPUTER APPLICATION, ENGINEERING APPLICATIONS OF COMPUTERS, SIMULATION, MARINE SYSTEMS

SECTION CLASS CODES: B2740, C7574, B2619, C8829

LANGUAGE: ITALIAN

MODERN ADVANCES IN SHIPBUILDING PRACTICE, PARTICULARLY THE INCREASE IN SIZE AND THE INTRODUCTION OF CONTAINER SHIPS AND BULK CARRIERS, CALL INCREASINGLY FOR AUTOMATION OF ENGINE CONTROL, NAVIGATION, GUIDANCE AND CARGO HANDLING. DIGITAL AND ANALOG COMPUTERS AND DATA PROCESSING FACILITIES ARE UTILIZED, WITH TRANSDUCERS AT THE PHYSICAL INTERFACES. COMPUTERS ARE USED IN SHIP DESIGN, FOR MODELLING AND OPTIMIZATION OF ENGINE OPERATION AND CONTROL. SIMULATORS PLAY AN IMPORTANT PART IN ON-SHORE TRAINING OF CREWS

170777 C7018030

STUDY OF INDUCER LOAD AND STRESS (INTERIM REPORT 15 FEB 1968-15 OCT 1968)

PARTEN, H.J., COONS, L.L., DAVIS, R.F.

REPORT NO.: NASA-CR-72514 ISSUED BY: PRATT AND WHITNEY AIRCRAFT, WEST PALM BEACH, FLA., USA

CONTRACT NO.: NAS3-11216

2 APRIL 1969

DESCRIPTORS: HEAT SYSTEMS, ENGINEERING APPLICATIONS OF COMPUTER, COMPUTER-AIDED DESIGN

SECTION CLASS CODES: C8829

AVAILABILITY: CFSTI, SPRINGFIELD, VA. 22151, USA

A PROGRAM OF ANALYSIS, DESIGN, FABRICATION, AND TESTING IS BEING CONDUCTED TO DEVELOP COMPUTER PROGRAMS FOR PREDICTING ROCKET ENGINE TURBO-PUMP INDUCER HYDRODYNAMIC LOADING STRESS MAGNITUDE AND DISTRIBUTION, AND VIBRATION CHARACTERISTICS. THIS REPORT COVERS THE ANALYSIS AND DESIGN PORTION OF THE PROGRAM. METHODS OF PREDICTING BLADE LOADING STRESS, AND VIBRATION CHARACTERISTICS WERE SELECTED FROM A LITERATURE SEARCH AND USED AS A BASIS FOR THE COMPUTER PROGRAMS. A TEST INDUCER WAS DESIGNED REPRESENTATIVE OF TYPICAL ROCKET ENGINE INDUCERS AND INSTRUMENTATION WAS SELECTED TO PROVIDE MEASUREMENTS OF BLADE SURFACE PRESSURE AND STRESSES FOR CORRELATION WITH THE PREDICTION SYSTEM

161350 C7015407

DIGITAL COMPUTER SIMULATION OF A DIESEL FUEL INJECTION

DUBE, J.P., GOYAL, M.R. : GOVERNMENT ENGG. COLL., REWA, INDIA

J. INSTN. ENGRS. (INDIA) MECH. ENGG. DIV. VOL.50, NO.5, PT. ME3 132-48 JAN. 1970

DESCRIPTORS: MECHANICAL ENGINEERING, ENGINEERING APPLICATIONS OF COMPUTERS, HEAT SYSTEMS, SIMULATION

SECTION CLASS CODES: C8829, C7551

THE PAPER PRESENTS A DETAILED ANALYSIS OF A DIESEL ENGINE FUEL INJECTION SYSTEM WHICH GIVES A PILOT INJECTION AND A MAIN INJECTION, USING A SINGLE PLUNGER HAVING TWO GROOVES TO GIVE STEPPED INJECTION THROUGH A SINGLE MULTI-HOLE, CLOSED NOZZLE. THE CALCULATION FOR SUCH AN INJECTION SYSTEM HAS BEEN PROGRAMMED FOR A DIGITAL COMPUTER. FINITE DIFFERENCE METHOD HAS BEEN USED FOR STEP BY STEP SOLUTION OF THE EQUATIONS AT EACH INTERVAL OF TIME. THE RESULTS PRESENTED WERE OBTAINED FOR A SET OF DATA TO SHOW THE EFFECT OF VARIOUS PUMP PARAMETERS ON THE DISCHARGE CHARACTERISTICS OF THE INJECTION SYSTEM DESIGN DATA (10 REFS)

161327 C7015384

DETERMINATION OF THE COMBUSTION LAW OF AN INTERNAL COMBUSTION ENGINE BY MEANS OF DIGITAL COMPUTERS USING THE INDICATED DIAGRAM

APOSTOLESU, M., GRUNWALD, B., TARAZA, D.

BUL. INST. POLITEH. BUCURESTI (ROMANIA) VOL.31, NO.4 105-14 JULY 1969

DESCRIPTORS: ENGINEERING APPLICATIONS OF COMPUTERS, HEAT SYSTEMS, FLOWCHARTING

SECTION CLASS CODES: C8829

LANGUAGE: ROMANIAN

THE AUTHORS PRESENT A METHOD TAKING INTO CONSIDERATION THE THERMAL DISCONTINUITIES OF THE GAS MIXTURE, THE DISSOCIATION OF GAS, FUEL ATOMIZATION AND HEAT EXCHANGE WITH THE WALLS. IN ORDER TO SOLVE THE EQUATION OBTAINED WHICH SPECIFIES THE LAW OF COMBUSTION THE AUTHORS SUGGEST THE RUNGE-KUTTA SECOND-ORDER METHOD, PRESENTING THE FLOW CHART OF THE CALCULATION PROGRAM ELABORATED FOR A DIGITAL COMPUTER

146232 C0011424

ANALOG COMPUTER CONTROL SYSTEMS FOR THE GROUND TESTING OF NUCLEAR ROCKET ENGINE COMPONENTS

LANGILL, A.W. ; PROCESS SYSTEMS INSTRUMENTATION, SACRAMENTO, CALIF., USA

: INSTRUMENT SOC. AMERICA

PROCEEDINGS OF THE 23RD ANNUAL ISA CONFERENCE, ADVANCES IN INSTRUMENTATION 10PP. 1968

1 28-31 OCT 1968 INSTRUMENT SOC. AMERICA NEW YORK, USA

PUBL: INSTRUMENT SOC. AMERICA PITTSBURGH, PA., USA

DESCRIPTORS: NUCLEAR SYSTEMS, ON-LINE OPERATION, AUTOMATIC TESTING, ANALOGUE COMPUTER METHODS, ENGINEERING APPLICATIONS OF COMPUTERS

SECTION CLASS CODES: C8829

DESCRIBES THE APPLICATION OF THE LARGE-SCALE GENERAL-PURPOSE ANALOG COMPUTER FOR THE DESIGN OF CONTROL SYSTEMS USED IN THE NON-NUCLEAR TESTING OF NUCLEAR ROCKET ENGINE COMPONENTS AND SUB-SYSTEMS. FURTHER, THE APPLICATION OF ON-LINE ANALOG COMPUTER CONTROL OF GROUND TEST FACILITIES IS INDICATED. IN THIS CONTEXT, THE ON-LINE COMPUTER (BAI PC-12) IS EMPLOYED IN CONJUNCTION WITH HIGH-SPEED SERVO SUB-SYSTEMS TO (1) GENERATE ALL REQUIRED FORCING FUNCTIONS, (2) PROVIDE SWITCHING AND MALFUNCTION LOGIC SHUTDOWN COMMANDS, AND (3) PERFORM THE FUNCTIONS OF AN OVERALL SYSTEMS SUPERVISOR

132623 C709787

## DYNAMIC MODELLING OF GAS TURBINE PERFORMANCE

SARAVANAMUTTOO, H.I.H., FAWKE, A.J.

; IEE, CONTROL AND AUTOMATION DIV., INSTITUTE OF MEASUREMENT AND CONTROL

INDUSTRIAL APPLICATIONS OF DYNAMIC MODELLING 133-41 1969

16-18 SEP 1969 IEE, CONTROL AND AUTOMATION DIV., INSTITUTE OF MEASUREMENT AND CONTROL DURHAM, ENGLAND

PUBL: INSTITUTION OF ELECTRICAL ENGINEERS LONDON

DESCRIPTORS: ANALOGUE COMPUTER METHODS, SIMULATION, AEROSPACE APPLICATIONS OF COMPUTERS, HEAT SYSTEMS

SECTION CLASS CODES: C8829

METHODS FOR DYNAMIC MODELLING OF GAS TURBINE PERFORMANCE HAS BEEN DEVELOPPED FOR BOTH ANALOGUE AND DIGITAL COMPUTERS. THE PROBLEM IS APPROACHED FROM THE VIEWPOINT OF THE THERMODYNAMICIST, USING THE BASIC INFORMATION REQUIRED FOR STEADY STATE PERFORMANCE CALCULATIONS. BOTH ANALOGUE AND DIGITAL SIMULATION METHODS HAVE PROVED TO BE SATISFACTORY, AND GOOD AGREEMENT WITH ENGINE TESTS HAS BEEN OBTAINED. THIS PAPER DISCUSSES THE SIMULATION OF THE SIMPLE TURBOJET ENGINE, AND THE METHODS DESCRIBED ARE CURRENTLY BEING USED TO SIMULATE THE PERFORMANCE OF MORE COMPLEX TWO-SPOOL AND THREE-SPOOL UNITS. THE COMPUTER REQUIREMENTS ARE MODEST AND WELL WITHIN THE SCOPE OF REASONABLY EQUIPPED COMPUTER LABORATORIES

114174 C706317

CALCULATION OF DIESEL ENGINES WORKING PROCESSES, AND THE APPLICATION OF DIGITAL COMPUTERS FOR SUCH CALCULATIONS

KALMAR, I.

WISS. Z. TECH. HOCHSCH. OTTO VON GUERICKE MAGDEBURG (GERMANY)  
VOL.12, NO.4 483-91 1968

DESCRIPTORS: HEAT SYST., COMP. AIDED DESIGN, ENG. APPLIC. COMP., DESIGN AND CALC. AIDS

SECTION CLASS CODES: C8829

LANGUAGE: GERMAN

THE NUMBER OF EXPERIMENTS DURING DEVELOPMENT OF AN ENGINE CAN BE REDUCED BY THE STUDY OF DIESEL ENGINE INDICATOR DIAGRAMS. WHEN THE COMPUTATION METHOD IS LAID DOWN, COMPUTATION BY HAND IS COMPARED WITH THAT BY A COMPUTER. THE VIBE COMBUSTION LAW AND THE HEAT TRANSFER EQUATIONS BY PFLAUMF WERE USED WITH THE COMPUTER. THE MATCHING OF THE COMPUTATION RESULT TO AN ENGINE INDICATOR DIAGRAM, AND THE EFFECT OF A SINGLE PARAMETER COMPUTED BY THE PROGRAM SO DETERMINED, ARE GIVEN (11 REFS)

114172 C706315

COMPUTER MODEL FOR CALCULATING THE BURNT CHARGE VOLUME AND THE SURFACE AREA OF THE PROPAGATING FLAME IN A SPARK IGNITION ENGINE

SOMAYAJULU, K.D.S.R., SUBRAMANYAM, J.K.

J. INSTN. ENGRS. (INDIA), MECH. ENGG. DIV. VOL. 49, NO. 11, PT. ME6 298-302 JULY 1969

DESCRIPTORS: ENG. APPLIC. COMP., HEAT SYSTEMS

SECTION CLASS CODES: C8829

IN A COMBUSTION CHAMBER DESIGN, THE VOLUME OF THE CHARGE BURNT AND THE SURFACE AREA OF THE FLAME FRONT AS THE FLAME PROPAGATES ARE IMPORTANT CONSIDERATIONS. A METHOD OF CALCULATION TO BE SOLVED ON A DIGITAL COMPUTER IS DESCRIBED. THE METHOD ENVISAGES DETERMINING THE VOLUME COMMON TO A SPHERE AND THE COMBUSTION CHAMBER. THE POINTS ON THE BOUNDARY OF THE COMBUSTION CHAMBER ARE GIVEN IN CARTESIAN COORDINATES ABOUT A CONVENIENT ORIGIN. THE POINTS ARE CONVERTED INTO SPHERICAL COORDINATES WITH THE SPARK PLUG LOCATION AS THE ORIGIN. A SYSTEMATIC PROCEDURE FINDS THE RADIUS AS THETA AND PHI ARE CHANGED AND COMPUTES BY SUMMATION, THE VOLUME AND SURFACE AREA FOR SEVERAL FLAME RADII. LIMITATIONS AND ADVANTAGES OF THE METHOD ARE DESCRIBED

67901 B6921645, C699490

COMPUTER DATA PROCESSING TO COMPUTE NERVA TRANSFER FUNCTIONS

BENENSON, H.

; ATOMIC ENERGY OF CANADA LTD U.S.A.E.C. NASA

JFER TRANS. NUCLEAR SCI. (USA) VOL. 5-16, NO. 1 207-9 FEB. 1969

CONF: 15TH NUCLEAR SCIENCE SYMPOSIUM 23-25 OCT 1968 ATOMIC ENERGY OF CANADA LTD U.S.A.E.C. NASA MONTREAL, CANADA

DESCRIPTORS: AEROSPACE PROPULSION, COMPUTER APPLICATIONS, NUCLEAR REACTORS, AEROSPACE APPLICATIONS OF COMPUTERS, ENGINEERING APPLICATIONS OF COMPUTERS

SECTION CLASS CODES: B3630, C8829

THIS PAPER DESCRIBES THE COMPUTER DATA-PROCESSING METHODS THAT HAVE BEEN DEVELOPED TO PERMIT TOTAL DATA ANALYSIS COMPLETION WITHIN A 72-HR PERIOD. TO ACHIEVE THIS GOAL, IT WAS NECESSARY TO ESTABLISH EFFICIENT AND FLEXIBLE PROGRAMMING METHODS AND TO ENSURE THAT THE DATA ARE VALID WHEN THE TESTS ARE CONDUCTED. BECAUSE INTERPRETATION IS ESSENTIAL, A WELL PLANNED SYSTEMATIC APPROACH TO VERIFICATION AND SIMULATION WAS INTRODUCED EARLY IN THE PROGRAM TO STUDY AND INTERPRET ANOMALIES THAT COULD OCCUR IN THE DATA

65082 C6911088

SIMPLIFIED SIMULATION OF ENGINE DYNAMICS

STRAUEJINGER, A.

LUFTFAHRTTECHN. RAUMFAHRTTECH. (GERMANY) VOL. 15, NO. 1 1-5 JAN. 1969

DESCRIPTORS: SIMULATION, ANALOGUE COMPUTERS, ENGINEERING APPLICATIONS OF COMPUTERS

SECTION CLASS CODES: C8829, C9950

LANGUAGE: GERMAN

THERE ARE THREE METHODS WHICH CAN BE USED TO SIMULATE ENGINE DYNAMICS ON ANALOG COMPUTERS WITH ADEQUATE ACCURACY. IT DEPENDS ON THE PURPOSE OF THE INVESTIGATION, THE COMPUTER CAPACITY AND THE TYPE OF THE AVAILABLE ENGINE DATA, WHICH OF THE THREE METHODS IS TO BE USED IN A GIVEN CASE

37716 P6912430, C694132

SOME CONSIDERATIONS ON THE POSSIBILITY OF THE ADAPTION OF MARINE ELECTRICAL PROPULSION TO REMOTE CONTROL OR PROGRAMMED SYSTEM CONTROL RAVENNA, I.

MARELLI (ITALY) VOL.42, NO.7-12 7-28 DEC. 1968

DESCRIPTORS: PROPULSION, COMPUTER APPLICATIONS, MOTORS, SHIPS, MARINE SYSTEMS

SECTION CLASS CODES: B4610, C7574

LANGUAGE: ITALIAN

AN HISTORICAL ACCOUNT IS GIVEN OF EARLY SYSTEMS OF DISEL- ELECTRIC PROPULSION, WITH PARTICULAR REFERENCE TO THE (ITALIAN) VESSELS SCILLA AND CARIDDI. THE APPLICATION OF ELECTRIC PROPULSION TO DIFFERENT CLASSES OF VESSEL IS CONSIDERED, TOGETHER WITH A DETAILED INVESTIGATION OF THE ALTERNATIVE FORMS OF PRIME MOVER, ELECTRIC CONVERSION AND PROPULSION MOTOR. INFORMATION ON RELEVANT COSTS IS PRESENTED, AND THE ARTICLE CONCLUDES WITH A DETAILED ACCOUNT OF TWO RECENT MARINE INSTALLATIONS WHICH HAVE INCORPORATED COMPUTER CONTROL FOR SOME OF THE ROUTINE ENGINE ROOM OPERATIONS

User 244 Date:03/25/76 Time:06:51:15 File:14

Set	Items	Description
1	64	VOLTAGE
2	990	SPEED
3	3	RPM
4	1054	1-3/OR
5	35	REGULATOR
6	20	GOVERNOR
7	4182	CONTROL
8	4208	5-7/OR
9	828	ENGINE
10	203	GENERATOR
11	14	ROTATING MACHINERY
12	2	ALTERNATING CURRENT
13	1030	9-12/OR
14	51	SWITCHING
15	0	PROPORTIONAL BAND
16	25	PROPORTIONAL
17	0	BANG BANG
18	2	DANG (W) BANG
19	0	PROPORTIONAL (W) BAND
20	78	14-19/OR
21	1	4 AND 8 AND 13 AND 20
22	11	4 AND 8 AND 13
23	1209	COMPUTER
24	252	DIGITAL
25	0	MICROPROCESSOR
26	0	MICRO PROCESSOR
27	0	MICRO (W) PROCESSOR
28	34	MINICOMPUTER
29	1387	23-28/OR
30	41	13 AND 29

Print 22/5/1-11

Print 30/5/1-41

Search Time: 16.10 Prts.: 52 Descs.: 19




AD-A085 990


NAVAL AIR ENGINEERING CENTER LAKEHURST NJ GROUND SUPP--ETC F/G 10/2  
APPLICATION OF A MICROCOMPUTER TO A MOBILE ELECTRIC POWER PLANT--ETC(U)  
MAY 80 R F O'DONNELL  
NAEC-92-139

UNCLASSIFIED

NL

3 OF 4  
AD-A085 990





MICROCOPY RESOLUTION TEST CHART  
 NATIONAL BUREAU OF STANDARDS-1963-A

36495 D7506320

DESIGN OF DIGITAL ACTUATORS (PNEUMATIC DRIVES EXAMPLES)

USAMOV, KH.G.

VESTN. MASHINOSTR. (USSR) NO.11 29-32 1974 CODEN: VMASAV

TRANS OF: RUSS. ENG. J. (GB) VOL.54, NO.11 32-4 1974 CODEN:

RENJA3

DESCRIPTORS: ACTUATORS, DESIGN, PNEUMATIC CONTROL EQUIPMENT

IDENTIFIERS: SPRING TENSIONING, DESIGN, DIGITAL ACTUATORS, PNEUMATICALLY ACTUATED DRIVES, VARIABLE SPEED REGULATOR, DIESEL ENGINE, CENTRIFUGAL SWITCH, AUTOMATIC SWITCHING SYSTEMS, DIESEL ELECTRIC LOCOMOTIVES, CONTROLLER, POSITIONERS

SECTION CLASS CODES: D2450

(4 REFS)

28761 D7506126

(DIESEL) ENGINE TEST BED MODEL FOR DYNAMIC CONTROL STUDIES

AL-BERHANI, S.A., GRAVESTOCK, R.E. ; QUEEN MARY COLL., LONDON, ENGLAND

J. AUTOMOT. ENG. (GB) VOL.6, NO.1 10-15 FEB. 1975 CODEN: JAUFA9

DESCRIPTORS: DIESEL ENGINES, TEST FACILITIES, DYNAMICS, TORQUE

IDENTIFIERS: DYNAMIC CONTROL, ANALOGUE COMPUTER MODEL, DIESEL ENGINE, FDDY CURRENT DYNAMOMETER TEST BED, STEADY STATE, DYNAMIC TORQUE FUNCTIONS, SPEED CONTROLLER, TRANSFER FUNCTION, THROTTLE ACTUATOR

SECTION CLASS CODES: D5410, D1370

(6 REFS)

25013 D7502378

TORSIONAL STABILITY ANALYSIS OF A GAS-TURBINE POWERED HELICOPTER DRIVE SYSTEM

DARLOW, M.S., VANCE, J.M. ; MECH. TECHNOL. INC., LATHAM, N.Y., USA

TRANS. ASME SPR. A (USA) VOL.96, NO.4 335-41 OCT. 1974

CODEN: JEFOAB

DESCRIPTORS: HELICOPTERS, TORSION, STABILITY, DRIVES, GAS TURBINES

IDENTIFIERS: TORSIONAL STABILITY ANALYSIS, CLOSED LOOP DYNAMIC SYSTEM, TRANSPORT HELICOPTER SPEED GOVERNOR, GAS TURBINE ENGINE, DRIVE TRAIN, NONLINEAR COUPLING, VIBRATIONS, ROTOR, EXCITATION, TIME RESPONSE, FREQUENCY

SECTION CLASS CODES: D6610, D5510, D5420

(9 REFS)

23110 D7500475

WHAT'S NEW IN MOTORCYCLE ENGINEERING

COVINGTON, J.

AUTOMOT. ENG. (USA) VOL.82, NO.9 37-43 SEPT. 1974 CODEN:  
AVEGBIDESCRIPTORS: DESIGN, SAFETY, POLLUTION, INTERNAL COMBUSTION ENGINES,  
MOTOR VEHICLE BRAKES, MOTOR VEHICLE SUSPENSIONIDENTIFIERS: WOBBLE, ANTI LOCK BRAKES, MOTORCYCLE TECHNOLOGY, ENGINE  
EFFICIENCY, OUTPUT, BRAKING, SAFETY FACTORS, SUSPENSION SYSTEMS, NOISE  
, EMISSIONS CONTROL, DESIGN, AUTOMOTIVE APPLICATIONS, COMPUTER,  
PREDICT, SPEED/TORQUE CHARACTERISTICS, AUTOMATED DESIGN

SECTION CLASS CODES: D6290, D5410, D1340

21808 D7406802

IMPROVED WEAR AND DEPOSIT CONTROL IN MEDIUM SPEED MARINE DIESEL  
ENGINES (WITH ENGINE OIL DEVELOPMENT)VAN DER HORST, G.W., POLMAN, J., SUNDERMEIJER, J.J.H. ; CHEVRON  
CENTRAL LAB., ROTTERDAM, NETHERLANDS

STD BOOK NO.: 9 900976 37 3

EUROPORT 73 CONFERENCE PROCEEDINGS: MARINE DIESEL ENGINES 1-12  
1974

15 NOV. 1973 AMSTERDAM, NETHERLANDS

PUBL: INST. MARINE ENGRS. LONDON, ENGLAND

DESCRIPTORS: MARINE ENGINES, DIESEL ENGINES, WEAR, OIL

IDENTIFIERS: WEAR, DEPOSIT CONTROL, MEDIUM SPEED MARINE DIESEL  
ENGINES, ENGINE OILS, LABORATORY BENCH TESTS, OXIDATION, THERMAL  
STABILITY, CORROSION PROTECTION, WATER TOLERANCE

SECTION CLASS CODES: D5410, D3650, D3690

(2 REFS)

21800 D7406794

TURBOCHARGING OF SMALL (DIESEL) ENGINES

GOODLET, I.W. ; HOLSET ENGG. CO. LTD., HUDDERSFIELD, ENGLAND

PROC. INST. MECH. ENG. (GB) VOL. 188 NO.3 77-87 1974 CODEN:  
PIMLAADESCRIPTORS: DIESEL ENGINES, TURBOCHARGERS, INTERNAL COMBUSTION  
ENGINE PERFORMANCEIDENTIFIERS: LOST WAX CAST ROTORS, SMALL DIESEL ENGINES,  
TURBOCHARGING, ADOPTION, RADIAL FLOW TURBINES, COMPONENT EFFICIENCIES,  
BEARING, SEAL DESIGN PROBLEMS, VANE VIBRATION, MANUFACTURING METHODS,  
CONTROL SYSTEMS, DEMANDS, VARIABLE SPEED ENGINES

SECTION CLASS CODES: D5410

(8 REFS)

14190 D7406696  
OPERATION AND CONTROL OF INDUSTRIAL TURBINES (E.G. ELECTRIC GENERATOR DRIVES)  
WILSON, W.B. ; GENERAL ELECTRIC CO., SCHENECTADY, N.Y., USA  
POWER ENG. (USA) VOL.78, NO.2 42-5 FEB. 1974  
DESCRIPTORS: STEAM TURBINES, STEAM-ELECTRIC POWER GENERATION, VELOCITY CONTROL, ELECTRIC VARIABLES CONTROL  
IDENTIFIERS: CONTROL, INDUSTRIAL TURBINES, OPERATION, COSTS, ELECTRIC GENERATOR DRIVES, STEAM TURBINE, STEP LOAD CHANGE, SPEED GOVERNOR REGULATION, CONTROL PERFORMANCE  
SECTION CLASS CODES: D5440, D8210, D2230

12911 D7405417  
PROTOTYPE OF A 100-MW, 3000 RPM GAS TURBINE SERIES FOR POWER GENERATION  
FRIGIERI, G.P. ; FIAT, TORINO, ITALY  
; ASME  
INTERNATIONAL CONFERENCE ON GAS TURBINES (PREPRINTS) 1-9 1974  
31 MARCH - 4 APRIL 1974 ASME ZURICH, SWITZERLAND  
PUBL: ASME NEW YORK, USA  
DESCRIPTORS: GAS TURBINES, POWER PLANTS, CONTROL SYSTEMS  
IDENTIFIERS: PROTOTYPE, GAS TURBINE, POWER GENERATION, LARGE, CHARACTERISTICS, PEAK LOAD, ENGINE, DESIGN, TEST PROGRAM, CONTROL SYSTEM, PACKAGE INSTALLATION, 100 MW, 3000 RPM, BASE LOAD  
SECTION CLASS CODES: D5420, D8250

6680 D7306680  
HYBRID MODEL OF AN AUTOMATED ENGINE TEST BED  
SOLIMAN, J.I.  
J. AUTOMOT. ENG. (GB) VOL.4, NO.5 13-18 OCT. 1973 CODEN: JAUFA9  
DESCRIPTORS: INTERNAL COMBUSTION ENGINES, MODELLING, TEST FACILITIES, CONTROL SYSTEMS  
IDENTIFIERS: CONTROL, HYBRID MODEL, AUTOMATED, TEST BED, SPEED, TORQUE, INTERNAL COMBUSTION ENGINE  
SECTION CLASS CODES: D5410

5471 D7305471  
A PRELIMINARY STUDY OF THE DESIGN OF A CONTROLLER FOR AN AUTOMOTIVE GAS TURBINE (MATHEMATICAL MODELLING)  
WINTERBONE, D.E., MUNRO, N., LOURTIE, P.H.G. ; UNIV. MANCHESTER, ENGLAND  
TRANS. ASME SER. A (USA) VOL.95, NO.3 244-50 JULY 1973  
CODEN: JPPOA8  
DESCRIPTORS: GAS TURBINES, CONTROLLERS  
IDENTIFIERS: DESIGN, CONTROLLER, AUTOMOTIVE GAS TURBINE, FUEL MASS FLOW, TURBINE NOZZLE ANGLE, GAS GENERATOR SPEED, TURBINE INLET TEMPERATURE, CONTROL SYSTEM, MATHEMATICAL MODELS  
SECTION CLASS CODES: D5420, D2470  
(10 REFS)

71 D7300071

DEVELOPMENTS IN HIGH-VOLTAGE GENERATION AND IGNITION CONTROL (FOR COMBUSTION ENGINES)

RITTMANNBERGER, N. ; ROBERT BOSCH GMBH, SCHWIEBERDINGEN, GERMANY  
; INSTN. MECH. ENGRS

STD BOOK NO.: 0 85298 060 4

CONFERENCE ON AUTOMOTIVE ELECTRICAL EQUIPMENT 79-84 1973

13-14 SEPT. 1972 INSTN. MECH. ENGRS BRIGHTON, SUSSEX, ENGLAND

PUBL: INSTN. MECH. ENGRS. LONDON, ENGLAND

DESCRIPTORS: IGNITION SYSTEMS, INTERNAL COMBUSTION ENGINES

IDENTIFIERS: DEVELOPMENTS, IGNITION CONTROL, TRANSISTORIZED METHODS,  
CONTACTLESS TRIGGER SYSTEMS, SPARK IGNITED COMBUSTION ENGINE, HIGH  
VOLTAGE GENERATION, COIL IGNITION

SECTION CLASS CODES: D2450, D5410, D5320

(3 REFS)

39132 D7601423

THE PREDICTION OF JOURNAL LOCT IN DYNAMICALLY LOADED INTERNAL COMBUSTION ENGINE BEARINGS

RITCHIE, G.S. ; HPCCH. PNGNG. LAB., GRC, WHETSTONF, ENGLAND

WEAR (SWITZERLAND) VOL.35, NO.2 291-7 DEC. 1975 CODEN: WEARAH

DESCRIPTORS: DIESEL ENGINES, INTERNAL COMBUSTION ENGINE COMPONENTS, COMPUTER-AIDED DESIGN, JOURNAL BEARINGS, OPTIMISATION

IDENTIFIERS: SEMIANALYTIC METHOD, DYNAMICALLY LOADED BEARINGS, PREDICTION OF JOURNAL LOCT, INTERNAL COMBUSTION ENGINE BEARINGS, DIESEL ENGINE BEARINGS, APPROXIMATE SOLUTION, DYNAMIC REYNOLDS EQUATION, COMPUTER PROGRAM

SECTION CLASS CODES: D3610, D5410

(2 REFS)

38910 D7601201

LATERAL VIBRATION ANALYSIS OF GENERATOR-TURBINE SHAFT SYSTEMS

NAGAPUJI, T. ; TOKYO SHIBAURA ELECTRIC CO. LTD., HEAVY APPARATUS ENGG. LAB., YOKOHAMA, JAPAN

INT. WATER POWER AND DAM CONSTR. (GB) VOL.27, NO.11 418-23 NOV. 1975 CODEN: IWPCDH

DESCRIPTORS: TURBOGENERATORS, SHAFTS, VIBRATIONS

IDENTIFIERS: TRANSIENT RESPONSE, LATERAL VIBRATION ANALYSIS, GENERATOR TURBINE SHAFT, DESIGN, COMPUTER

SECTION CLASS CODES: D8250, D5510, D3220

(4 REFS)

38755 D7601046

HYBRID COMPUTER TREATMENT OF SAMPLED EXPERIMENTAL DATA FROM ROTATING PISTON MOTORS

CAILLIAU, R., SIERENS, R. ; RIJKSUNIV. GENT, GENT, BELGIUM

REV.-M (BELGIUM) VOL.21, NO.3 251-9 SEPT. 1975 CODEN: RMRMAK

DESCRIPTORS: INTERNAL COMBUSTION ENGINE PERFORMANCE, ENGINEERING APPLICATIONS OF COMPUTERS, ROTARY ENGINES

IDENTIFIERS: ENGINE DATA ANALYSIS, HYBRID COMPUTER TREATMENT, SAMPLED EXPERIMENTAL DATA, ROTATING PISTON MOTORS, HYBRID INSTALLATION

SECTION CLASS CODES: D5410

LANGUAGE: FLEMISH

(9 REFS)

38032 D7600323

TPST ENGINES PRODUCED BY DNC (COMPUTER MACHINING CENTRE AND CONVEYOR SYSTEM)

ASHBURN, A.

AM. MACH. (USA) VOL.119, NO.19 114-16 OCT. 1975 CODEN: AMMAAA

DESCRIPTORS: NUMERICAL CONTROL, MACHINING CENTRES, INTERNAL COMBUSTION ENGINES, ENGINEERING APPLICATIONS OF COMPUTERS, CONVEYORS

IDENTIFIERS: MACHINING CENTRES, TOYOTA, DNC, CONVEYORS, COMPUTER CONTROLLED AND MONITORED SYSTEM, ENVIRONMENTAL TESTS, ENGINE PARTS, INTEGRATED PRODUCTION SYSTEM

SECTION CLASS CODES: D4410, D5410, D6720

37557 D7507382

SIMULATION STUDY OF TRANSIENT PERFORMANCE MATCHING OF TURBOPAN ENGINE USING AN ANALOGUE COMPUTER TO EVALUATE ITS USEFULNESS AS DESIGN TOOL

ITOH, H., ISHIGAKI, T., SAGIYA, Y. ; RES. AND DEV. DEPT., AIRCRAFT ENGINE DIV., ISHIKAWAJIMA-HARIMA HEAVY INDUSTRIES CO. LTD., TOKYO, JAPAN

TRANS. ASME SER. A (USA) VOL.97, NO.3 369-74 JULY 1975  
CODEN: JEP0A8DESCRIPTORS: TURBOPAN ENGINES, COMPUTER-AIDED DESIGN, SIMULATION  
IDENTIFIERS: ANALOGUE COMPUTER SIMULATION, TRANSIENT PERFORMANCE MATCHING, TURBOPAN ENGINE, DESIGN TOOL, DYNAMIC RESPONSE, TRANSIENT SPEED CONDITION

SECTION CLASS CODES: D5420

36495 D7506320

DESIGN OF DIGITAL ACTUATORS (PNEUMATIC DRIVES EXAMPLES)

USAMOV, KH.G.

VESTN. MASHINOSTR. (USSR) NO.11 29-32 1974 CODEN: VMASAV

TRANS OF: RUSS. ENG. J. (GB) VOL.54, NO.11 32-4 1974 CODEN: RENJA3

DESCRIPTORS: ACTUATORS, DESIGN, PNEUMATIC CONTROL EQUIPMENT  
IDENTIFIERS: SPRING TENSIONING, DESIGN, DIGITAL ACTUATORS, PNEUMATICALLY ACTUATED DRIVES, VARIABLE SPEED REGULATOR, DIESEL ENGINE, CENTRIFUGAL SWITCH, AUTOMATIC SWITCHING SYSTEMS, DIESEL ELECTRIC LOCOMOTIVES, CONTROLLER, POSITIONERS

SECTION CLASS CODES: D2450

(4 REFS)

36265 D7506090

INDUCTION RAMMING A MOTORED HIGH-SPEED FOUR-STROKE RECIPROCATING ENGINE-INFLUENCE OF INLET PORT PRESSURE WAVES ON VOLUMETRIC EFFICIENCY  
PROSSER, T.G. ; KING'S COLL., UNIV. OF LONDON, LONDON, ENGLANDPROC. INST. MECH. ENG. (GB) VOL.188, NO.49 577-84 1974  
CODEN: PIMLAADESCRIPTORS: INTERNAL COMBUSTION ENGINE PERFORMANCE  
IDENTIFIERS: MOTORED HIGH SPEED FOUR STROKE RECIPROCATING ENGINE, INDUCTION RAMMING, INFLUENCE OF INLET PORT PRESSURE WAVES, VOLUMETRIC EFFICIENCY, PRESSURE FLUCTUATIONS, COMPUTER PROGRAMME, METHOD OF CHARACTERISTICS, AIRFLOW FIGURES

SECTION CLASS CODES: D5410

(20 REFS)

35043 D7504868

CHRYSLER: S : ELECTRONIC: LEAN-BURN ENGINE (WITH SPARK-CONTROL COMPUTER)

MACH. DES. (USA) VOL.47, NO.17 24-6 10 JULY 1975 CODEN: MAGFAP

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: SPARK ADVANCE CONTROL, ELECTRONIC LEAN BURN ENGINE, CHRYSLER, COMPUTER, IGNITION, CIRCUIT BOARDS

SECTION CLASS CODES: D5410



35015 D7504840

A SIMPLE STEAM GENERATOR MODEL (DIGITAL SIMULATION)  
LEITHNER, R., LINZER, V. ; LITERATURWACHWEIS UND BEISPIELE,  
STUTTGART, GERMANY

BRENNST.-WAERME-KRAFT (BWK) (GERMANY) VOL.27, NO.8 334-5 AUG.  
1975 CODEN: BRWKAY

DESCRIPTORS: BOILERS, MODELLING, SIMULATION

IDENTIFIERS: STEAM GENERATOR MODEL, DIGITAL SIMULATION

SECTION CLASS CODES: D5220

34396 D7504221

MEASUREMENT OF AVERAGE INDICATOR DIAGRAMS BY A MINI-COMPUTER AIDED  
DATA ACQUISITION SYSTEM

KONTANI, K.

J. MECH. ENG. LAB. (JAPAN) VOL.29, NO.3 92-108 MAY 1975

CODEN: KGKSBL

DESCRIPTORS: INTERNAL COMBUSTION ENGINE PERFORMANCE

IDENTIFIERS: MEASUREMENT, AVERAGED INDICATOR DIAGRAMS, MINICOMPUTER  
AIDED DATA ACQUISITION SYSTEM, CONTINUOUS ENGINE CYCLES, PRESSURE,  
IGNITION TIMING

SECTION CLASS CODES: D5410

LANGUAGE: JAPANESE

(4 REFS)

30771 D7500596

VIBRATIONS OF ROTORS IN TURBINE UNITS WITH SHORT CIRCUIT OF THE  
GENERATOR (CALCULATION)

KOSINOV, YU.P., FILIPPOV, A.P. ; KHARKOV CENTRAL DESIGN OFFICE  
POWER GENERATION INDUSTRY, ACAD. SCI., UKRAINIAN SSR

TEPLOENERGETIKA (USSR) VOL.21, NO.6 70-3 JUNE 1974 CODEN:  
TPLOAS

TRANS OF: THERM. ENG. (GB) VOL.21, NO.6 97-101 1974 CODEN:  
THENAD

DESCRIPTORS: TURBOGENERATORS, VIBRATIONS, STRESSES

IDENTIFIERS: ROTORS, TURBINE UNITS, SHORT CIRCUIT, GENERATOR,  
CALCULATION, DYNAMIC STRESSES, DIGITAL COMPUTER, TORSIONAL VIBRATIONS

SECTION CLASS CODES: D8210, D5400, D3130

(7 REFS)

30647 D7500472

ENGINE DESIGN SERIES. III. THE CRANKSHAFT

AUTOMOT. DES. ENG. (GB) VOL.14 22-3 APRIL 1975 CODEN: ADRGBS

DESCRIPTORS: CRANKSHAFTS, DESIGN, INTERNAL COMBUSTION ENGINE  
COMPONENTS

IDENTIFIERS: MATERIALS, ENGINE DESIGN, CRANKSHAFT, COMPUTER ANALYSIS  
, STRESSES

SECTION CLASS CODES: D5410, D5510

(25 REFS)

29380 D7506745

CALCULATION PROCEDURES FOR POTENTIAL AND VISCOUS FLOW SOLUTIONS FOR ENGINE INLETS

ALBERS, J.A., STOCKMAN, W.O. ; NASA, CLEVELAND, OHIO, USA

TRANS. ASME SER. A (USA) VOL.97, NO.1 1-10 JAN. 1975 CODEN: JEPOA8

DESCRIPTORS: AIRCRAFT ENGINES, FLOW OF GASES, VISCOUS FLOW

IDENTIFIERS: COMPUTER PROGRAM SYSTEM, POTENTIAL, SOLUTIONS, ENGINE INLETS, CALCULATIONS, SUBSONIC CONVENTIONAL, AIRCRAFT ENGINE NOZZLES, COMPRESSIBLE VISCOUS FLOW, DESIGN, ANALYSIS, VTOL LIFT FANS, ACOUSTIC SPLITTERS, STOL

SECTION CLASS CODES: D5420, D3510

(23 REFS)

29378 D7506743

SIGMA COMPUTER-CONTROLLED MACHINE INSPECTS CYLINDER BLOCKS AT RATE OF 35/H

MACH. AND PROD. ENG. (GB) VOL.126, NO.3254 365-7 16 APRIL 1975

CODEN: MPREAU

DESCRIPTORS: INTERNAL COMBUSTION ENGINE COMPONENTS, INSPECTION, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: SIGMA 3-STATION COMPUTER CONTROLLED INSPECTION MACHINE, CHECKING, CYLINDER BLOCKS, DIESEL ENGINES, GAUGING STATION

SECTION CLASS CODES: D5410, D1370

28761 D7506126

(DIPSEL) ENGINE TEST BED MODEL FOR DYNAMIC CONTROL STUDIES

AL-BYRMANI, S.A., GRAVESTOCK, R.E. ; QUEEN MARY COLL., LONDON, ENGLAND

J. AUTOMOT. ENG. (GB) VOL.6, NO.1 10-15 FEB. 1975 CODEN: JAURA9

DESCRIPTORS: DIESEL ENGINES, TEST FACILITIES, DYNAMICS, TORQUE

IDENTIFIERS: DYNAMIC CONTROL, ANALOGUE COMPUTER MODEL, DIESEL ENGINE, EDDY CURRENT DYNAMOMETER TEST BED, STEADY STATE, DYNAMIC TORQUE FUNCTIONS, SPEED CONTROLLER, TRANSFER FUNCTION, THROTTLE ACTUATOR

SECTION CLASS CODES: D5410, D1370

(6 REFS)

24210 D7501575

NEW APPLICATIONS OF THE SPARK-EROSION TECHNIQUE TO MACHINING  
JANICKE, J. ; CHARHILLES S.A., GENEVA, SWITZERLAND  
; GENERAL DELEGATION TO SCI. AND TECH. RES., ET AL  
4TH JOURNEES DE PRINTEMPS DE LA MECANIQUE INDUSTRIELLE. (4TH SPRING  
CONFERENCE ON INDUSTRIAL MACHINERY) 6PP. 1974  
I 22-24 APRIL 1974 GENERAL DELEGATION TO SCI. AND TECH. RES., ET  
AL PARIS, FRANCE  
PUBL: GROUPEMENT POUR L'AVANCEMENT DE LA MECANIQUE INDUSTRIELLE  
SAINT-OMER, FRANCE  
DESCRIPTORS: ELECTRICAL DISCHARGE MACHINING, MACHINE TOOL CONTROL  
IDENTIFIERS: MINI COMPUTER, NEW APPLICATIONS, MACHINING, FULLY  
AUTOMATED OPERATIONAL CONTROL, OIL, DIELECTRIC, WATER, SHORT PULSE  
SPARK GENERATOR, ELECTRODE SYSTEM, NUMERICAL CONTROL  
SECTION CLASS CODES: D4450  
LANGUAGE: FRENCH

24113 D7501478

SIMILARITY PARAMETER FOR SCALING DYNAMIC (PRESSURE) INLET DISTORTION  
MOORE, M.T., LUEKE, J.E. ; GENERAL ELECTRIC CO., CINCINNATI, OHIO,  
USA  
TRANS. ASME SER. B (USA) VOL.96, NO.3 795-800 AUG. 1974  
CODEN: JEP1A8  
DESCRIPTORS: PRESSURE, AERODYNAMICS  
IDENTIFIERS: ANALOGUE FILTERING, SIMILARITY PARAMETER, SCALING  
DYNAMIC INLET DISTORTION, PRESSURE, DIGITAL AVERAGING, TURBINE ENGINE,  
AIRCRAFT  
SECTION CLASS CODES: D3510  
(4 REFS)

23333 D7500698

DIRECT METHOD FOR ANALYSIS OF BRANCHED TORSIONAL SYSTEMS  
SHAIKH, M. ; MERCURY MARINE, FOND DU LAC, WIS., USA  
TRANS. ASME SER. B (USA) VOL.96, NO.3 1006-9 AUG. 1974  
CODEN: JEP1A8  
DESCRIPTORS: TORSION, ENGINES, NUMERICAL ANALYSIS  
IDENTIFIERS: DIRECT METHOD, ANALYSIS, BRANCHED TORSIONAL SYSTEMS,  
TRANSFER MATRICES, VIBRATIONS, JUNCTION, NATURAL FREQUENCIES, COMPUTER  
SOLUTIONS, COUPLED ENGINE INSTALLATIONS, TURBINES, RECIPROCATING,  
SCREW COMPRESSORS, MARINE, AUTO DIFFERENTIALS, GEARED INSTALLATIONS,  
HOLZER METHOD  
SECTION CLASS CODES: D3110  
(5 REFS)

23110 D7500475

WHAT'S NEW IN MOTORCYCLE ENGINEERING  
COVINGTON, J.AUTOMOT. ENG. (USA) VOL.82, NO.9 37-43 SEPT. 1974 CODEN:  
AVEGBIDESCRIPTORS: DESIGN, SAFETY, POLLUTION, INTERNAL COMBUSTION ENGINES,  
MOTOR VEHICLE BRAKES, MOTOR VEHICLE SUSPENSIONIDENTIFIERS: WOBBLE, ANTI LOCK BRAKES, MOTORCYCLE TECHNOLOGY, ENGINE  
EFFICIENCY, OUTPUT, BRAKING, SAFETY FACTORS, SUSPENSION SYSTEMS, NOISE  
, EMISSIONS CONTROL, DESIGN, AUTOMOTIVE APPLICATIONS, COMPUTER,  
PREDICT, SPEED/TORQUE CHARACTERISTICS, AUTOMATED DESIGN

SECTION CLASS CODES: D6290, D5410, D1340

23055 D7500420

COMPUTER SIMULATION TUNES UP ENGINE (BLOCK MACHINING) LINE (FOR  
HEAVY DUTY TRUCKS)

HAWKINS, W.A.

METALWORK. PROD. (GB) VOL.118, NO.11 91-3 NOV. 1974 CODEN:  
MWPDAWDESCRIPTORS: SIMULATION, TRANSFER LINES, PISTON ENGINES, MACHINING,  
ENGINEERING APPLICATIONS OF COMPUTERSIDENTIFIERS: COMPUTER SIMULATION, ENGINE BLOCK, MACHINING LINE,  
HEAVY DUTY TRUCK, TRANSFER LINE, BALANCING, DESIGN, IN PROCESS GAUGING  
, ADJUSTMENT, AUTOMATIC, DRILLING, TAPPING, V-8 CYLINDER LINE

SECTION CLASS CODES: D5410, D4400, D6720, D1360

23053 D7500418

INTERNAL COMBUSTION ENGINE INSTRUMENTATION FOR ON-LINE COMPUTER  
APPLICATIONS

CONNOR, W.A. ; UNIV. COLL., LONDON, ENGLAND

INT. J. MECH. ENG. EDUC. (GB) VOL.2, NO.4 1-8 OCT. 1974  
CODEN: INEEB3DESCRIPTORS: INTERNAL COMBUSTION ENGINES, INSTRUMENTS, ENGINEERING  
APPLICATIONS OF COMPUTERS, TESTINGIDENTIFIERS: ON LINE COMPUTER APPLICATIONS, INTERNAL COMBUSTION  
ENGINE INSTRUMENTATION, DIGITAL, TEST RIGS, PERFORMANCE DATASECTION CLASS CODES: D5410, D2440, D1370  
(4 REFS)

22227 D7407221

METHOD OF CHARACTERISTIC PERFORMANCE CALCULATION OF JOURNAL BEARINGS  
UNDER DYNAMIC LOADINGNAKAGAWA, E. ; ISHIKAWAJIMA-HARIMA HEAVY INDUSTRIES CO. LTD.,  
TOKYO, JAPANISHIKAWAJIMA-HARIMA ENG. REV. (JAPAN) VOL.14, NO.5 497-506  
SEPT. 1974 CODEN: ISHGAV

DESCRIPTORS: JOURNAL BEARINGS, LOADING

IDENTIFIERS: CHARACTERISTIC PERFORMANCE CALCULATION, JOURNAL  
BEARINGS, DYNAMIC LOADING, DIGITAL COMPUTER METHOD, FLUID FILM  
PRESSURE, PORCE, FRICTION LOSSES, DIESEL ENGINE

SECTION CLASS CODES: D3610

LANGUAGE: JAPANESE

(2 REFS)

21798 D7406792

INTERNAL COMBUSTION ENGINE TESTING BY DIGITAL COMPUTERS

SOLIHAN, J.I. ; QUEEN MARY COLL., UNIV. LONDON, ENGLAND

J. AUTOMOT. ENG. (GB) VOL.5, NO.4 22-6 AUG. 1974 CODEN:

JAUEA9

DESCRIPTORS: INTERNAL COMBUSTION ENGINES, TESTING, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: INTERNAL COMBUSTION ENGINE, TESTING, DIGITAL COMPUTERS

SECTION CLASS CODES: D5410, D1370

21176 D7406170

THE WORLD'S LONGEST CYLINDER BLOCK (MACHINE TOOL TRANSFER) LINE IS ON RUSSIAN FRONT

HOLLINGUM, J.

ENGINEER (GB) VOL.239 NO.6184 40-1, 44 19 SEPT. 1974 CODEN:

ENGIAL

DESCRIPTORS: TRANSFER LINES, MACHINE TOOLS, INTERNAL COMBUSTION ENGINE COMPONENTS

IDENTIFIERS: INGERSOLL CYLINDER BLOCK TRANSFER LINE, RUSSIAN KAMA RIVER TRUCK PLANT, MACHINE TOOL, COMPUTER SIMULATION, REMOTE AUTOMATIC TOOL ADJUSTMENT

SECTION CLASS CODES: D5410, D4400

20082 D7405076

MATCHING ENGINE-GENERATOR SYSTEMS TO NUCLEAR CORE-SPRAY REQUIREMENTS

HARTUNG, E.C. ; GENERAL ELECTRIC CO., SAN JOSE, CALIF., USA

POWER ENG. (USA) VOL.78, NO.7 52-5 JULY 1974

DESCRIPTORS: COMPUTER AIDED DESIGN, NUCLEAR POWER STATIONS, ELECTRIC GENERATORS, DIESEL ENGINES

IDENTIFIERS: MATCH, DESIGN, COMPUTER ANALYSIS PROGRAM, PUMP MOTORS, COMPONENTS, GOVERNOR, EXCITATION SYSTEM, NUCLEAR CORE SPRAY, MOTOR, DIESEL ENGINE GENERATOR SYSTEMS

SECTION CLASS CODES: D8100, D1340

20001 D7404995

USER EXPERIENCE OF A COMPUTER BASED WATCHKEEPING AND CONTROL SYSTEM (IN A TRAWLER)

HATFIELD, M.

; INST. MARINE ENGRS., NAUTICAL INST

STD BOOK NO.: 0 900976 40 3

PRACTICAL EXPERIENCE WITH SHIPBOARD AUTOMATION 12-21 1974

6 MARCH 1974 INST. MARINE ENGRS., NAUTICAL INST ENGLAND

PUBL: MARINE MEDIA MANAGEMENT LONDON, ENGLAND

DESCRIPTORS: CARGO SHIPS, CONTROL SYSTEMS, ENGINEERING APPLICATIONS OF COMPUTERS, RELIABILITY, MONITORING

IDENTIFIERS: EXPERIENCE, COMPUTER BASED WATCHKEEPING, CONTROL SYSTEM, UNMANNED ENGINE ROOM EQUIPMENT, DISTANT WATER FREEZER TRAWLER CLASS, ELECTRONIC, RELIABILITY, FIXED LOGIC RELAY CONTROL CIRCUITS

SECTION CLASS CODES: D6510, D2490

16665 D7404799

EROSIVE PRODUCTION METHODS (WITH SPARK EROSION MACHINES) RATIONALISE PRODUCTION

LEISFDER, L.

MASCHINENMARKT (GERMANY) VOL.80, NO.60 1165-8 26 JULY 1974

CODEN: MAMKAK

DESCRIPTORS: EROSION, ELECTRICAL DISCHARGE MACHINING

IDENTIFIERS: MACHINES, SPARK EROSION, NUMERICALLY CONTROLLED, PRODER, STEEL, DIE, ACCURACY, DIGITAL POSITION INDICATION, PULSE GENERATOR, ADAPTIVE CONTROL SYSTEM, SURFACE ROUGHNESS, PORTAL TYPE, RATES

SECTION CLASS CODES: D4450

LANGUAGE: GERMAN

(2 REFS)

16587 D7403581

TORSIONAL RESPONSE OF INTERNAL COMBUSTION ENGINES

ESHELMAN, R.L. : IIT RES. INST., CHICAGO, ILL., USA

TRANS. ASME SER. F (USA) VOL.96, NO.2 441-9 MAY 1974 CODEN:

JEFIAH

DESCRIPTORS: INTERNAL COMBUSTION ENGINE PERFORMANCE, SIMULATION, VIBRATIONS, TORSION

IDENTIFIERS: TORSIONAL RESPONSE, INTERNAL COMBUSTION ENGINES, DIGITAL SIMULATION TECHNIQUE, REFINED MATHEMATICAL MODEL, END ITEM POWER SHAFTS, NATURAL FREQUENCIES, MODE SHAPES, TORSIONAL MOTIONS, STRESSES, FOURIER SERIES EXPANSION, FORCING FUNCTIONS, GASOLINE ENGINE, DIESEL ENGINE, ENGINE PRESSURE CRANK ANGLE CURVE

SECTION CLASS CODES: D5410

(5 REFS)

17881 D7402875

PRESSURE CHANGES, DUE TO EMERGENCY ARRANGEMENT, IN THE HP-PART AND RE-HEATER OF A STEAM GENERATOR

LEITHNER, R.

BERNNST.-WAERME-KRAFT (BWK) (GERMANY) VOL.26, NO.6 249-57 JUNE 1974 CODEN: BRWKAY

DESCRIPTORS: BOILERS, PRESSURE, FLOW, ENGINEERING APPLICATIONS OF COMPUTERS, MODELLING

IDENTIFIERS: MODEL, STEAM GENERATOR, PRESSURE, CHANGES, ESTIMATE, CALCULATE, ANALOGOUS, DIGITAL, COMPUTER, REHEATER, MASS FLOW, HP PART

SECTION CLASS CODES: D5220

LANGUAGE: GERMAN

(9 REFS)

13567 D7406073

SIMULATION STUDY OF TRANSIENT PERFORMANCE MATCHING OF TURBOPROP ENGINE USING AN ANALOGUE COMPUTER TO EVALUATE ITS USEFULNESS AS DESIGN TOOL

ITOH, M., ISHIGAKI, T., SAGIYA, Y. ; ISHIKAWAJIMA-HARIMA HEAVY INDUSTRIES CO. LTD., TOKYO, JAPAN

; ASME

INTERNATIONAL CONFERENCE ON GAS TURBINES (PREPRINTS) 1-6 1974

31 MARCH - 4 APRIL 1974 ASME ZURICH, SWITZERLAND

PUBL: ASME NEW YORK, USA

DESCRIPTORS: TURBOPROP ENGINES, ENGINEERING APPLICATIONS OF COMPUTERS, PRODUCT DESIGN

IDENTIFIERS: SIMULATION STUDY, TRANSIENT PERFORMANCE MATCHING, TURBOPROP ENGINE, ANALOGUE COMPUTER, DYNAMIC RESPONSE, DESIGN TOOL

SECTION CLASS CODES: D4470, D1340

13459 D7405965

SPINDLE POSITIONING WITH A STEPPING MOTOR IN MULTI-SPINDLE AUTOMATIC LATHES

VAN DE LUG, P.

IND.-ANZ. (GERMANY) VOL.96, NO.25 543-8 22 MARCH 1974

DESCRIPTORS: LATHES, POSITION CONTROL, STEPPING MOTORS

IDENTIFIERS: SPINDLE POSITIONING, STEPPING MOTOR, AUTOMATIC LATHES, DIGITAL CONTROL, HALL EFFECT GENERATOR, ZEROING TRANSMITTER

SECTION CLASS CODES: D4410, D2450, D2210

LANGUAGE: GERMAN

(6 REFS)

12905 D7405411

CALCULATION PROCEDURES FOR POTENTIAL AND VISCOUS FLOW SOLUTIONS FOR (AIRCRAFT) ENGINE INLETS

ALPERS, J.A., STOCKMAN, H.O. ; NASA, CLEVELAND, OHIO, USA

; ASME

INTERNATIONAL CONFERENCE ON GAS TURBINES (PREPRINTS) 1-8 1974

31 MARCH - 4 APRIL 1974 ASME ZURICH, SWITZERLAND

PUBL: ASME NEW YORK, USA

DESCRIPTORS: AIRCRAFT ENGINES, VISCOUS FLOW, ENGINEERING APPLICATIONS OF COMPUTERS, COMPRESSIBLE FLOW

IDENTIFIERS: CALCULATION PROCEDURES, METHOD, BASIC ELEMENTS, COMPUTER SOLUTIONS, POTENTIAL FLOW, ENGINE INLETS, SUBSONIC CONVENTIONAL, CTOL, STOL, VERTICAL TAKEOFF, VTOL, AIRCRAFT, NACELLES, COMPRESSIBLE VISCOUS FLOW, MEASURED SURFACE PRESSURE DISTRIBUTIONS, MODEL INLETS, PROGRAM, DESIGN, ANALYSIS, LIFT FANS, ACOUSTIC SPLITTERS, COMPIN, VISCOUS, SHORT HAUL

SECTION CLASS CODES: D5420, D3510

(23 REFS)

19677 D7403133

AUTOMATING ENGINE AND EMISSION TESTING  
 AUTOMOT. ENG. (USA) VOL. 81, NO. 12 25-33 DEC. 1973 CODEN:  
 AVPGBI

DESCRIPTORS: ENGINES, AUTOMATIC TESTING, ENGINEERING APPLICATIONS OF  
 COMPUTERS, EXHAUST GASES

IDENTIFIERS: COMPUTER CONTROL, ENGINE TESTING, TESTING FLEXIBILITY,  
 REDUCES DOWNTIME, SAVES TECHNICAL MANPOWER, EMISSION TESTING

SECTION CLASS CODES: D5400, D7831

9494 D7402006

COMPUTER-ASSISTED CALCULATION OF STRENGTH (USING FINITE ELEMENT  
 METHOD)

BUCK, F.E., WINKLER, R. ; BROWN ROVERI, HENSEACH, GERMANY

REC NACHR. (GERMANY) VOL. 55, NO. 12 410-17 1973 CODEN: PRCAZ

DESCRIPTORS: COMPUTER-AIDED DESIGN, FINITE ELEMENT METHOD,  
 MECHANICAL STRENGTH

IDENTIFIERS: STRENGTH, FINITE ELEMENTS, STRUCTURES, TILTING ARM,  
 CORELESS INDUCTION FURNACE, GENERATOR, RADIATOR CASING, TURBINE  
 FOUNDATION, COMPUTER ASSISTED CALCULATION

SECTION CLASS CODES: D1340, D3260

(3 REFS)

6683 D7306683

SIMULATION OF THERMODYNAMIC PROCESS OF A DIESEL ENGINE ON A SMALL  
 DIGITAL COMPUTER

GUHA, V.P. ; DIESEL LOCOMOTIVE WORKS, VARANASI, INDIA

J. INST. ENG. (INDIA) MECH. ENG. DIV. VOL. 53, NO. ME 6 292-301  
 JULY 1973 CODEN: JEMDAS

DESCRIPTORS: DIESEL ENGINES, THERMODYNAMICS, ENGINEERING  
 APPLICATIONS OF COMPUTERS

IDENTIFIERS: SIMULATION, SMALL DIGITAL COMPUTER, MATHEMATICAL MODEL,  
 THERMODYNAMIC PROCESS, DIESEL ENGINE

SECTION CLASS CODES: D5410, D5100

(11 REFS)

5472 D7305472

THE USE OF A HYBRID COMPUTER IN THE OPTIMISATION OF GAS TURBINE  
 (TURBOJET ENGINE THRUST RESPONSE) CONTROL PARAMETERS

SARAVANAMUTTOO, H.T.H., MACISAAC, B.D. ; CARLETON UNIV., OTTAWA,  
 CANADA

TRANS. ASME SER. A (USA) VOL. 95, NO. 3 257-64 JULY 1973  
 CODEN: JETDAR

DESCRIPTORS: OPTIMISATION, GAS TURBINES, TURBOJET ENGINES,  
 SIMULATION, COMPUTER APPLICATIONS

IDENTIFIERS: OPTIMISATION, GAS TURBINE, HYBRID COMPUTER, TURBOJET  
 ENGINE, COMPRESSOR, THERMODYNAMICS, SIMULATION, THRUST RESPONSE,  
 CONTROL SYSTEM, ACCELERATION TRAJECTORY

SECTION CLASS CODES: D5420

(6 REFS)



5466 D7305466

GENERAL APPROACH TO THE COMPUTER SOLUTION OF SINGLE- AND TWO-STAGE  
TURBOCHARGED DIESEL ENGINE MATCHING

WALLACE, F.J., CAVE, I.R. ; UNIV. BATH, ENGLAND

PROC. INST. MECH. ENGRS. (GB) VOL.187, NO.48 535-47 1973

CODEN: FIMLAA

DESCRIPTORS: DIESEL ENGINES, ENGINEERING APPLICATIONS OF COMPUTERS

IDENTIFIERS: COMPUTER SOLUTION, TURBOCHARGED DIESEL ENGINE MATCHING

SECTION CLASS CODES: D5410

(28 REFS)

4897 D7304897

:THORSHELM:-FIRST SHIP WITH DATACHIEF (COMPUTER CONTROL ENGINE ROOM)

SHIPBUILT. AND MAR. ENGR. INT. (GB) VOL.96, NO.1169 652-3 AUG.

1973

DESCRIPTORS: MARINE ENGINES, CARGO SHIPS, COMPUTER APPLICATIONS

IDENTIFIERS: 280000 TOW TANKER, MONITORING, ENGINE OPERATION,  
PERFORMANCE, MERCHANT SHIP, COMPUTER CONTROL ENGINE ROOM

SECTION CLASS CODES: D6510, D5410

424 D7300424

DIGITAL SIMULATION OF ROTARY PISTON ENGINES (OR WANKEL ENGINE)

LAWTON, P., MILLAR, D.H., HUTCHINSON, D.P. ; ROYAL MILITARY COLI.

SCI., SWINDON, ENGLAND

; INSTN. MECH. ENGRS. ET. AL

CONFERENCE ON ENGINE PERFORMANCE MODELLING 25-32 1973

22-23 MAY 1973 INSTN. MECH. ENGRS. ET. AL LONDON, ENGLAND

PUBL: INSTN. MECH. ENGRS. LONDON, ENGLAND

DESCRIPTORS: WANKEL ENGINES, ROTARY ENGINES, ENGINEERING

APPLICATIONS OF COMPUTERS, MODELLING

IDENTIFIERS: DIGITAL SIMULATION, ROTARY PISTON ENGINES, WANKEL  
ENGINE, SPARK IGNITION, COMPRESSION IGNITION, MODELLING, THERMODYNAMIC  
CYCLE

SECTION CLASS CODES: D5410

(10 REFS)

421 D7300421

THE COMPUTER MODELLING OF :LARGE: MECHANICAL SYSTEMS-DYNAMIC AND  
KINEMATIC ANALYSIS (OF V-8 ENGINE)TIMM, R.F., LAFSON, C.S., NAGAMATSU, R.P. ; MICHIGAN TECHNOL.  
UNIV., HOUGHTON, USA

; INSTN. MECH. ENGRS

STD LOGE NO.: 0 85298 196 1

MECHANISMS 1972 CONFERENCE 111-16 1973

5-6 SEPT. 1972 INSTN. MECH. ENGRS LONDON, ENGLAND

PUBL: INSTN. MECH. ENGRS. LONDON, ENGLAND

DESCRIPTORS: KINEMATICS, DYNAMICS, MODELLING, INTERNAL COMBUSTION  
ENGINES, COMPUTER-AIDED DESIGNIDENTIFIERS: COMPUTER MODELLING, DYNAMIC AND KINEMATIC ANALYSIS,  
MULTI BODY SYSTEM, INTERNAL COMBUSTION ENGINE

SECTION CLASS CODES: D5410

(17 REFS)

62 D7300062

PULSE-COUNTING SIGNAL SYSTEMS FOR N.C.  
PRISCHANSKII, B.I.

STANKI AND INSTRUM. (USSR) NO.12 11-12 1972 CODEN: STINA4

TRANS OF: MACH. AND TOOL. (GB) NO.12 15-18 1972 CODEN:

MCTOAB

DESCRIPTORS: NUMERICAL CONTROL, DISPLAY INSTRUMENTS

IDENTIFIERS: DIGITAL DISPLAY, PRODUCES, ANALYZES, ALGORITHMS,  
CALCULATING, VARIOUS SYSTEMS, DESIGN, CIRCUIT, START STOP GENERATOR,  
PULSE COUNTING SIGNAL SYSTEMS, NC, MULTI DIGIT COUNTERS, MACHINE TOOLS

SECTION CLASS CODES: D2440, D4400

(2 REFS)

NAEC-92-139

ASSEMBLY LANGUAGE PROGRAM  
TO IMPLEMENT BANG-BANG REGULATION TECHNIQUES

20001:

\* AP23,24,25 JUNE 15,1976

20002:

\* START FROM ZERO

NAEC- 92-139

20003:	20000	00000	REL	0
20004:	00000	00001	UP	BSS
20005:	00001	XXXXX	ADJOR	ADR
20006:	00002	00000	LIN	BSS
20007:	00003	XXXXX	ADLP3	ADR
20008:	00004	XXXXX	ADLP1	ADR
20009:	00005	XXXXX	ADLP2	ADR
00010:	00006	00001	DGTL	BSS
00011:	00007	00001	ONE	BSS
20012:	00010	26740	CLR	
00013:	00011	161771	STA	LIN
00014:	00012	55222	LPI	L,I
20015:	00013	65132		L,I
20016:	00014	61136		L
00017:	00015	65764		L,I
20018:	00016	141762	LA	UP
00019:	00017	20200	OCA	
20020:	00020	24100	SAE	
20021:	00021	45127	J,I	ADWN
20022:	00022	141154	LA	REF
00023:	00023	175124	S,I	ADBP
00024:	00024	121151	C	VO
00025:	00025	27414	SLE	
00026:	00026	41764	J	LPI
20027:	00027	141147	LA	REF
00028:	00030	121145	C	VO
20029:	00031	27412	SGE	
20030:	00032	45116	J,I	ADWN
20031:	00033	141751	LA	ADLP1
00032:	00034	161177	STA	POINT
20033:	00035	141112	LA	ADBP
20034:	00036	20040	AOA	
20035:	00037	121165	C	ADDUM
20036:	00040	27404	SL	
20037:	00041	55125	L,I	ADLCN
20038:	00042	71105	ADM	ACBP
20039:	00043	71105	ADM	ADGCN
00040:	00044	65101	L,I	CONR
00041:	00045	26740	CLR	
20042:	00046	161734	STA	LIN
00043:	00047	41743	J	LPI
00044:	00050	26740	DWN	CLR
00045:	00051	161727	STA	UP
20046:	00052	141124	LA	REF
20047:	00053	155074	A,I	ADBP
20048:	00054	121121	C	VO
20049:	00055	27404	SL	
20050:	00056	41004	J	**4
20051:	00057	26740	CLR	
20052:	00060	161722	STA	LIN
20053:	00061	41012	J	LP2
20054:	00062	141722	LA	ADLP1
20055:	00063	161150	STA	POINT
20056:	00064	141063	LA	ADBP
20057:	00065	20040	AOA	
20058:	00066	121135	C	ADDUM

00059: 00057	27404		SL	
00060: 00070	65055	00146	L.I	ADLCN
00061: 00071	26740		CLR	
00062: 00072	161710	00002	STA	LIN
00063: 00073	141056	00151	LA	ADCON
00064: 00074	171713	00007	S	ONE
00065: 00075	121127	00224	C	ADDUM
00066: 00076	27402		SG	
00067: 00077	41012	00111	J	XX
00068: 00100	161051	00151	STA	ADCON
00069: 00101	141046	00147	LA	ADBP
00070: 00102	171705	00007	S	ONE
00071: 00103	161044	00147	STA	ADBP
00072: 00104	145043	00147	LA.I	ADEF
00073: 00105	151071	00176	A	REF
00074: 00106	121067	00175	C	VO
00075: 00107	27412		SGE	
00076: 00110	41763	00073	J	LP2
00077: 00111	61142	00253	L	CONO
00078: 00112	61040	00152	L	REFRD
00079: 00113	61122	00235	L	VORD
00080: 00114	141062	00176	LA	REF
00081: 00115	155032	00147	A.I	ADBP
00082: 00116	125054	00172	C.I	ADVO
00083: 00117	27402		SG	
00084: 00120	41772	00112	J	LP3
00085: 00121	141055	00176	LA	REF
00086: 00122	121053	00175	C	VO
00087: 00123	27402		SG	
00088: 00124	41004	00130	J	**4
00089: 00125	20000		CAO	
00090: 00126	161052	00000	STA	UP
00091: 00127	41223	00352	J	LP4
00092: 00130	141653	00003	LA	ADLP3
00093: 00131	161102	00233	STA	POINT
00094: 00132	141015	00147	LA	ADBP
00095: 00133	20040		AOA	
00096: 00134	121070	00224	C	ADDUM
00097: 00135	27404		SL	
00098: 00136	65010	00146	L.I	ADLCN
00099: 00137	26740		CLR	
00100: 00140	161642	00002	STA	LIN
00101: 00141	71206	00147	AOM	ADBP
00102: 00142	71207	00151	AOM	ADCON
00103: 00143	61110	00253	L	CONO
00104: 00144	41746	00112	J	LP3
00105: 00145	XXXXX	00253	CONR	ADR
00106: 00146	XXXXX	00406	ADLCN	ADR
00107: 00147	XXXXX	00177	ADBP	ADR
00108: 00150	XXXXX	00050	ADWN	ADR
00109: 00151	XXXXX	00212	ADCON	ADR
00110: 00152	00000	00000	* READ REFERENCE VOLTAGE	
00111: 00153	141020	00173	REFRD	ADR
00112: 00154	05270	00070	LA	GAIN
00113: 00155	24070	00070	DR	'70
00114: 00156	131013	00171	SI	'70
00115: 00157	27427		AND	MASK
			SNZ	

00117:	00150	41775	00155	J	+-3
00118:	00151	00070	00070	DI	'70
00119:	00152	00250	00210	LRS	'10
00120:	00153	00121		TCA	
00121:	00154	00210	00310	LLS	'10
00122:	00155	00250	00010	LRS	'10
00123:	00156	161010	00175	STA	REF
00124:	00157	45763	00152	J.I	REFD
00125:	00170	00000		REFVOL	BSS
00126:	00171	40000	40000	MASK	BSS
00127:	00172	XXXXX	00175	ADVS	ADR
00128:	00173	00000	00000	GAIN	BSS
00129:	00174			UNDER	DEC
00130:	00175	00000	00000	VO	BSS
00131:	00176			REF	ADR
00132:	00177			BREAK	BSS
00133:	00201	00000	00000	EUM	ADR
00134:	00202			REF	ADR
00135:	00224	XXXXX	00011	ADDUM	ADR
00136:	00225	XXXXX	00012	AUP	ADR
00137:	00226	XXXXX	00012	ALPI	ADR
00138:	00227	XXXXX	00002	ALIN	ADR
00139:	00230	XXXXX	00233	APNT	ADR
00140:	00231	XXXXX	00176	AREF	ADR
00141:	00232	XXXXX	00006	ADGTL	ADR
00142:	00233	00000	00000	POINT	ADR
00143:	00234	XXXXX	00372	ADONI	ADR
00144:				* READ OUTPUT VOLTAGE + COMPARE	
00145:	00235	00000	00000	VORD	ADR
00146:	00236	141014	00252	LA	VOGN
00147:	00237	05070	00070	DF	'70
00148:	00240	04070	00070	SI	'70
00149:	00241	131730	00171	AND	MASK
00150:	00242	27407		SNZ	
00151:	00243	41775	00240	J	+-3
00152:	00244	00070	00070	DI	'70
00153:	00245	00250	00010	LRS	'10
00154:	00246	00100		TCA	
00155:	00247	00210	00010	LLS	'10
00156:	00250	161725	00175	STA	VO
00157:	00251	45764	00235	J.I	VORD
00158:	00252	00001	00001	VOGN	BSS
00159:				* OUTPUT CONTROL WORD	
00160:	00253	00000	00000	CONO	ADR
00161:	00254	141046	00322	LA	CHAN
00162:	00255	05076	00076	DF	'76
00163:	00256	145754	00232	LA-I	ADGTL
00164:	00257	121530	00007	C	ONE
00165:	00260	27406		SNE	
00166:	00261	41003	00264	J	+-3
00167:	00262	141122	00404	LA	ANA
00168:	00263	41013	00276	J	OUT
00169:	00264	141514	00000	LA	UP
00170:	00265	121520	00007	C	ONE
00171:	00266	27410		SE	
00172:	00267	41004	00273	J	+-4
00173:	00270	145651	00151	LA.I	ADCON
00174:	00271	00210	00010	LLS	'10

00208:	00332	155615	00147
00209:	00333	121642	00175
00210:	00334	27402	
00211:	00335	41002	00337
00212:	00336	41004	00342
00213:	00337	20000	
00214:	00340	161446	00006
00215:	00341	41507	00050
00216:	00342	141634	00176
00217:	00343	175604	00147
00218:	00344	121631	00175
00219:	00345	27402	
00220:	00346	41756	00324
00221:	00347	20000	
00222:	00350	161436	00006
00223:	00351	165654	00225
00224:	00352	141577	00151
00225:	00353	175750	00323
00226:	00354	121550	00224
00227:	00355	27402	
00228:	00356	41012	00370
00229:	00357	161572	00151
00230:	00360	141567	00147
00231:	00361	175742	00323

[illegible]

203: 00363 141613 00176  
 00234: 00364 175563 00147

LA  
 S, I REF  
 ADBP

NAEC-92-139

0035: 00365 121610 00175  
 00235: 00365 27404  
 00237: 00367 41763 00352  
 00238: 00370 45636 00226  
 00239: 00371 XXXXX 00175

C  
 SL  
 J  
 YY J, I  
 AVO ADR  
 V0

00240: \* READ IN LINEAR CONTROL  
 00241: 00372 00000 00000  
 00242: 00373 141012 00405  
 00243: 00374 05070 00070  
 00244: 00375 04070 00070  
 00245: 00376 131573 00171  
 00246: 00377 27407  
 00247: 00400 41775 00375  
 00248: 00401 00070 00070  
 00249: 00402 161002 00404  
 00250: 00403 45767 00372  
 00251: 00404 00000 00000  
 00252: 00405 00002 00002  
 00253:

CONI ADR  
 LA  
 DF  
 SI  
 AND  
 SNZ  
 J  
 DI  
 STA  
 J, I  
 ANA BSS  
 LNGN BSS  
 0  
 LNGN  
 '70  
 '70  
 MASK  
 \*-3  
 '70  
 ANA  
 CONI  
 1,0  
 1,2

\* DETERMINES IF SYSTEM READY FOR LINEAR CONTROL

00254: 00406 00000 00000  
 00255: 00407 75620 00227  
 00256: 00410 145617 00227  
 00257: 00411 121036 00417  
 00258: 00412 27412  
 00259: 00413 45520 00233  
 00260: 00414 26740  
 00261: 00415 165615 00232  
 00262: 00416 41706 00324  
 00263: 00417 00005  
 00264: 00000

LCNT ADR  
 AOM, I  
 LA, I  
 C  
 SGE  
 J, I  
 CLR  
 STA, I  
 J  
 GOLN DEC  
 END  
 0  
 ALIN  
 ALIN  
 GOLN  
 POINT  
 ADGTL  
 IDLE  
 5  
 0



NAEC-92-139

STUDY OF EFFECT OF LOWER MAIN FIELD TIME CONSTANTS

210(A-199 of A-203)

The time constant of the main field and the exciter field are associated with the lowest frequency band of the alternator control spectrum. In view of this the main field time constant was changed from 0.133 seconds to 0.364 seconds to determine the effect on control stability. The gain was adjusted to provide the same bandwidth of 20 Hz as shown in the curve of  $M_1$  in Figure 4-12.

The results of the change in time constant are noted in the curve of  $M_1$  where the peak at 11 Hz is slightly higher when no compensation issued. Using the same compensation (lead at 3.3 Hz and lag at 13.3 Hz) as used for  $M_2$  of Figure 4-12, we find that the characteristic of  $M_2$  in D-1 is flat within 0.5 db out to 20 Hz. Optimization of the compensation could improve this characteristic.

Figure D-2 shows the transfer of open loop to closed loop for the main field time constant of .364 and an open loop gain of 57 db/S as plotted on a Nichols Chart. This gain would provide about an 11 Hz bandwidth for the uncompensated case. Increase of gain to 64 db/S provides the closed loop characteristic recorded in  $M_1$  of Figure D-1. The compensated case has the desired gain (57 db/S) as shown and produces the closed loop characteristic shown as  $M_2$  in Figure D-2.







Figure D-1. Alternator Voltage Control  
Closed Loop Frequency Response  
 $M_1$  - Without Compensation  
 $M_2$  - With Compensation











NAEC-92-139



REV NO	DATE	DESCRIPTION	REV'D BY	CHECK'D BY
 <b>THE FRANKLIN INSTITUTE RESEARCH LABORATORIES</b> THE BENJAMIN FRANKLIN PARKWAY • PHILADELPHIA, PENNSYLVANIA 19103				
<b>TITLE</b> AC-APU ANALOG COMPUTER PROGRAM				
<b>TOLERANCES</b> UNLESS OTHERWISE NOTED RES. 0.005% ± 0.01 CAP. 0.005% ± 0.005 FRACTIONAL RES. 0.01% ± 0.005 ANALOG 0.01% ± 0.005 REMOVE PUNCH, SHARP EDGES		<b>DRAWN</b> J.D.	<b>DATE</b> 3/24/66	<b>SCALE</b> 1/2" = 1"
<b>CHECKED</b> J.D.		<b>DATE</b> 3/24/66	<b>APPROV'D</b> J.D.	<b>REFERENCE</b> C4258-06

2



APPENDIX B

MICROCOMPUTER CONTROL SYSTEM SOFTWARE

**B-1. BRIEF DISCUSSION ON TYPES OF CONTROL**

Three types of control are ordinarily considered:

1. Proportional

$$K_p e$$

where  $e$  = desired value - actual value

2. Integral

$$K_I \int_0^t e \, dt$$

3. Derivative

$$K_D \frac{de}{dt}$$

Proportional control is always desirable. Integral control is used when the steady state error must be small since the integral control signal will grow indefinitely for any error however small. However, too much integral control may lead to instability especially if there are large time delays in the response of the system. Derivative control tends to stabilize the system and to offset time delays.

In the voltage control system, the specifications require a small steady state error, therefore integral control is necessary. The time delays mainly in the exciter and generator field circuits are relatively small and it was possible to stabilize the system without derivative control. Therefore, in the voltage control system, the control function consists of integral plus proportional control. The control signal =  $K_p e + K_I \int_0^t e \, dt$ .

The specifications for speed control do not require as small a steady error as in voltage control. Therefore, integral control isn't necessary. The system time delays mainly due to the generator and engine inertias are large and derivative control helps to stabilize the system. Therefore, the speed (frequency) control system consists of proportional plus derivative control. The control signal =  $K_p e + K_D \frac{de}{dt}$ . Integral control was tried in the frequency control system. However, even a small amount of integral control tended to make the system oscillate, so the best performance was obtained with no integral control.

B-2. EQUATIONS RELATING TO DEVELOPMENT OF VOLTAGE CONTROL ALGORITHM

$V_g$  = Generator voltage in RMS volts

$K_1 V_g$  = d-c voltage after rectification where  $K_1$  is dependent on potentiometer R30 (Three Phase Voltage to Analog Switch Circuit)

$I_f$  = field current

$K_1 V_{des}$  = d-c reference voltage (created by -12 V through circuitry consisting of R4, D1, D2, R3, and potentiometer R1 in Three Phase Voltage to Analog Switch Circuit)

$V_g = K_g I_f$  Generator Equation (1)  
where:  $K_g$  = slope of generator air gap line

$E_{ex} = R_f I_f + L_f \frac{dI_f}{dt}$  Main Field Equation (2)

$V_c = R_{ex} I_{ex} + L_{ex} \frac{dI_{ex}}{dt}$  Rotary Exciter Equation (3)

$E_{ex} = K_{ex} I_{ex}$  = Voltage applied to main field by rotary exciter (4)  
where:  $K_{ex}$  = slope of exciter saturation curve

$R_f$  = Main field resistance

$L_f$  = Main field inductance

$V_c$  = Voltage from computer

$I_{ex}$  = Rotary Exciter field current

$R_{ex}$  = Rotary Exciter field resistance

$L_{ex}$  = Rotary Exciter Field inductance

$K(V_{des} - V_g)$  = voltage to A to D converter

$V_c = K_p K_1 (V_{des} - V_g) + K_I \int_0^t K_1 (V_{des} - V_g) dt =$  (5)  
Control equation (Proportional & Integral) where:  $K_p$  &  $K_I$  are parameters set in computer program.

Taking Laplace transforms of equations (1), (2), (3) & (4)

$$\underline{V_g} = K_g \underline{I_f} \quad (6)$$

$$\underline{E_{ex}} = (R_f + sL_f) \underline{I_f} = R_f \underline{I_f} (1 + sT_f) \quad (7)$$

$$\underline{V_c} = (R_{ex} + sL_{ex}) \underline{I_{ex}} = R_{ex} \underline{I_{ex}} (1 + sT_{ex}) \quad (8)$$

$$\underline{V_c} = K_1 \left( \frac{\underline{V_{des}}}{s} - \underline{V_g} \right) \left[ K_p + \frac{K_I}{s} \right] \quad (9)$$

$$\underline{E_{ex}} = K_{ex} \underline{I_{ex}}$$

NOTE: The underscore under a quantity indicates Laplace transform

$$T_f = \frac{L_f}{R_f}$$

$$T_{ex} = \frac{L_{ex}}{R_{ex}}$$

$$\underline{V_g} = K_g \underline{i_f} = \frac{K_g E_{ex}}{R_f (1+sT_f)} = \frac{K_g K_{ex} \underline{V_c}}{R_{ex} R_f (1+sT_f)(1+sT_{ex})}$$

$$\underline{V_g} = \frac{K_g K_{ex} K_I K_I \left[ 1 + \frac{K_p}{K_I} s \right]}{R_f R_{ex} s (1+sT_f)(1+sT_{ex})} \left( \frac{V_{des}}{s} - \underline{V_g} \right)$$

$$\underline{V_g} = \frac{K \left( 1 + \frac{K_p}{K_I} s \right)}{s (1+sT_f)(1+sT_{ex})} \left( \frac{V_{des}}{s} - \underline{V_g} \right)$$

$$\underline{V_g} = \frac{K \left( 1 + \frac{K_p}{K_I} s \right)}{s (1+sT_f)(1+sT_{ex}) + K \left( 1 + \frac{K_p}{K_I} s \right)} \frac{V_{des}}{s} \quad (10)$$

$$\text{Where: } K = \frac{K_g K_{ex} K_I K_I}{R_f R_{ex}}$$

To get steady state value of  $V_g$  apply final value theorem

$$V_g \text{ steady state} = \lim_{s \rightarrow 0} s \underline{V_g}$$

$$V_g \text{ steady state} = V_{des} \quad \text{as it should}$$

If  $K_p$  &  $K_I$  are chosen such that

$$\frac{K_p}{K_I} = T_f$$

$$\underline{V_g} = \frac{K}{s(1+sT_{ex}) + K} \frac{V_{des}}{s} \quad (11)$$

Equation (11) is equivalent to the differential equation

$$T_{ex} \frac{d^2 V_g}{dt^2} + \frac{dV_g}{dt} + K V_g = K V_{des} \quad (12)$$

To model the effect of applying or removing load assume the machine is running in steady state with  $V_g = V_{des}$  and  $V_{des}$  is suddenly changed from  $V_{des}$  to  $V_{des} + \Delta V$ .

Solving equation (12) with initial conditions:

$$t = 0, V_g = V_{des} + \Delta V$$

$$\frac{dV_g}{dt} = 0$$

Which gives rise to:

$$V_g = \frac{V_{des} + \Delta V}{s} - \frac{K}{s(Tex s + 1) + K} \frac{\Delta V}{s}$$

This corresponds to a sudden jump from  $V_{des}$  to  $V_{des} + \Delta V$  followed by a decrease to  $V_{des}$  governed by the time function corresponding to:

$$\frac{K}{s(Tex s + 1) + K} \frac{\Delta V}{s}$$

The time function is:


$$V_g = V_{des} + \left( \frac{1-A}{2A} e^{-\alpha_1 t} - \frac{1+A}{2A} e^{-\alpha_2 t} \right) \Delta V$$

$$\text{Where: } A = \frac{1}{Tex} \sqrt{1 - 4KTex}$$

$$\alpha_1 = \frac{1}{2Tex} (1+A)$$

$$\alpha_2 = \frac{1}{2Tex} (1-A)$$


A sketch of  $V_g$  is:




$\Delta V$  is positive for removal of load and negative for application of load

This is qualitatively the same as oscillograms taken on the real system (see Appendix D).

A simple block diagram of the entire system is illustrated below.



B-3. VOLTAGE CONTROL ALGORITHM



**B-4. EQUATIONS RELATING TO DEVELOPMENT OF FREQUENCY REGULATION ALGORITHM**

For Generator:

$$f = \frac{W_g P \pi}{3600}$$

Where:  $f$  = Frequency of generator voltage in Hz $W_g$  = Speed of engine in radians/second $p$  = Number of poles in generator = 24

$$f = \frac{\frac{60000}{\pi} (24) \pi}{3600} = 400 \quad \left( \frac{60000}{\pi} \frac{\text{rad}}{\text{sec}} = 2000 \text{ RPM} \right)$$

For Diesel Engine:

$$J \frac{dW_g}{dt} + K_f W_g = \gamma_e - \gamma_g$$

$$\text{Where: } \gamma_g = \frac{P_e}{W_g} = \frac{\sqrt{3} V_g I_a \cos \theta}{W_g}$$

$$\gamma_e = K_e X \quad (X = K_a V_c)$$

 $J$  = Moment of inertia of engine and generator in watt-sec<sup>3</sup> $W_g$  = Speed of engine in rad/sec $K_f$  = Damping coefficient in watt-secs<sup>2</sup> $\gamma_e$  = Engine torque in watt-secs $\gamma_g$  = Generator torque in watt-secs $X$  = Fuel pump position in radians $K_e$  = Engine gain in watt-secs/radian $K_a$  = Woodward actuator gain

$$J \frac{dW_g}{dt} + K_f W_g = K_e K_a V_c - \gamma_g$$

$$V_c = K_p (f_{des} - f) + K_d \frac{d(f_{des} - f)}{dt}$$

$$f_{des} - f = \frac{P \pi}{3600} (W_{g \text{ des}} - W_g)$$



Taking Laplace transforms for no load ( $\gamma_g = 0$ )

$$(J_s + K_f) \underline{W_g} = K_e K_a \frac{P \pi}{3600} [K_p + s K_d] \left( \frac{W_{g \text{ des}}}{s} - \underline{W_g} \right)$$

$$\text{Where: } K = \frac{K_e K_a p \pi K_p}{3600}$$

Note: Underscore indicates Laplace transform

$$\left[ J_s + K_f + K \left( s \frac{K_d}{K_p} + 1 \right) \right] \underline{W_g} = K \left( s \frac{K_d}{K_p} + 1 \right) \frac{W_{g \text{ des}}}{s}$$

$$\underline{W_g} = \frac{K \left( 1 + s \frac{K_d}{K_p} \right)}{\left( J + K \frac{K_d}{K_p} \right) s + K_f + K} \frac{W_{g \text{ des}}}{s}$$

$$W_{g \text{ steady state}} = \lim_{s \rightarrow 0} s \underline{W_g}$$

$$W_{g \text{ steady state}} = \frac{K}{K_f + K} W_{g \text{ des}}$$

Therefore if  $K \gg K_f$  the steady state speed will have the desired value.

$$\Delta W_g = \frac{K K_L}{(K_f + K)(K_f + K_L + K)} W_{g \text{ des}}$$

for  $K_f = 0$

$$\Delta W_g = \frac{K_L}{K_L + K} W_{g \text{ des}}$$

$$\text{If } \frac{\Delta W_g}{W_{g \text{ des}}} = \frac{5}{400} \text{ \& } K_L = .01 \text{ watt-sec}^2$$

$$\Delta W_g = \frac{.01}{.01 + K} = \frac{5}{400}$$

$$4 = .05 + 5K$$

$$K = \frac{3.95}{5} = 7.9 \text{ watt-sec}^2$$

A K of 7.9 will be enough to hold frequency within 4 Hertz.

For load on generator proportional to  $W_g$ ;  $\mathcal{F}_g = K_L W_g$

$$\begin{aligned} \left[ J s + K_f + K \left( s \frac{K_d}{K_p} + 1 \right) \right] \underline{W_g} &= K \left( s \frac{K_d}{K_p} + 1 \right) \frac{W_{g \text{ des}}}{s} - K_L \underline{W_g} \\ \left[ J s + K_f + K_L + K \left( s \frac{K_d}{K_p} + 1 \right) \right] \underline{W_g} &= K \left( s \frac{K_d}{K_p} + 1 \right) \frac{W_{g \text{ des}}}{s} \end{aligned}$$


$$\underline{W_g} = \frac{K \left( s \frac{K_d}{K_p} + 1 \right)}{\left( J + K \frac{K_d}{K_p} \right) s + K_f + K_L + K} \frac{W_{g \text{ des}}}{s}$$

In Steady State:


$$W_g = \frac{K}{K_f + K_L + K} W_{g \text{ des}} \quad \text{under load}$$

$$\Delta W_g = \left( \frac{K}{K_f + K} - \frac{K}{K_f + K_L + K} \right) W_{g \text{ des}} \quad \begin{array}{l} \text{Change from no load} \\ \text{to full load} \end{array}$$


A simple block diagram of the frequency control scheme is illustrated below:



B-5. FREQUENCY CONTROL ALGORITHM



## B-6. CONTROL SYSTEM FLOWCHART



## B-7. CONTROL SYSTEM PROGRAM LISTING

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0038		0	ORG 38H
0038	3EB0	1	MVI A,0B0H
003A	D3E6	2	OUT 0E6H
003C	3EF0	3	MVI A,0F0H
003E	D3E6	4	OUT 0E6H
0040	3EE0	5	MVI A,0E0H
0042	D3E6	6	OUT 0E6H
0044	3EF0	7	MVI A,0F0H
		8	
0046	D3E6	9	OUT 0E6H
0048	3EEF	10	MVI A,0EFH
004A	D3C0	11	OUT 0C0H
004C	78	12	MOV A,B
004D	D3C3	13	OUT 0C3H
004F	3E6F	14	MVI A,6FH
0051	D3C0	15	OUT 0C0H
0053	7C	16	MOV A,H
0054	D3C1	17	OUT 0C1H
0056	DBE6	18	IN 0E6H
0058	E602	19	ANI 02H
005A	DBE5	20	IN 0E5H
005C	EB	21	XCHG

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
005D	CABD01	22	JZ SUB1
0060	C680	23	ADI 80H
0062	4F	24	MOV C,A
0063	7D	25	MOV A,L
0064	F27600	26	JP P80
0067	A7	27	ANA A
0068	F29D00	28	JP P81
006B	CDDA01	29	CALL MMULT
006E	FAA000	30	JM P83
0071	0600	31	MVI B,0
0073	C3A900	32	JMP TTMR
0076	A7	33	P80: ANA A
0077	FA8500	34	JM P881
007A	CDE901	35	CALL PMULT
007D	F2A000	36	JP P83
0080	06FE	37	MVI B,0FEH
0082	C3A900	38	JMP TTMR
0085	CDE901	39	P881: CALL PMULT
0088	C680	40	ADI 80H
008A	FEFF	41	CPI OFFH
008C	C2A800	42	JNZ TMR
008F	3D	43	DCR A
0090	47	44	MOV B,A
0091	EB	45	XCHG

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0092	DBE6	46	IN 0E6H
0094	E604	47	ANI 4H
0096	C2B900	48	JNZ CHECK
0099	57	49	MOV D,A
009A	C37E01	50	JMP INT
009D	CDDA01	51	P81: CALL MMULT
00A0	C680	52	P83: ADI 80H
00A2	FEFF	53	NZI: CPI OFFH
00A4	C2A800	54	JNZ TMR
00A7	3D	55	DCR A
00A8	47	56	TMR: MOV B,A
00A9	EB	57	TTMR: XCHG
00AA	DBE6	58	IN 0E6H
00AC	E60H	59	ANI 4H
00AE	C2B900	60	JNZ CHECK
00B1	57	61	MOV D,A
00B2	3E40	62	MVI A,40H
00B4	D3EA	63	OUT 0EAH
00B6	C37E01	64	JMP INT
00B9	7A	65	CHECK: MOV A,D
00BA	A7	66	ANA A
00BB	C27E01	67	JNZ INT
00BE	14	68	INR D
00BF	DBC2	69	IN 0C2H



<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
00C1	4F	70	MOV C,A
00C2	DBC2	71	IN OC2H
00C4	FEFB	72	CPI OFBH
00C6	CADD00	73	JZ F1
00C9	D2D400	74	JNC F2
00CC	3E45	75	MVI A,45H
00CE	D3EA	76	OUT OEAH
00D0	AF	77	XRA A
00D1	C37101	78	JMP TMR2
00D4	3E46	79	F2: MVI A,46H
00D6	D3EA	80	OUT OEAH
00D8	3EFE	81	MVI A,0FEH
00DA	C37101	82	JMP TMR2
00DD	3E80	83	F1: MVI A,80H
00DF	81	84	ADD C
00E0	4F	85	MOV C,A
00E1	F25101	86	JP F3
00E4	95	87	SUB L
00E5	F20301	88	JP F72
00E8	69	89	F91: MOV L,C
00E9	FEFO	90	CPI OFOH
00EB	DA1801	91	JC FTEST1
00EE	17	92	RAL
00EF	3F	93	CMC

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
00F0	17	94	RAL
00F1	3F	95	CMC
00F2	17	96	RAL
00F3	67	97	F93: MOV H,A
00F4	79	98	F993: MOV A,C
00F5	FECO	99	CPI OCOH
00F7	DA1801	100	JC FTEST1
00FA	17	101	RAL
00FB	84	102	ADD H
00FC	FA6901	103	JM F52
00FF	AF	104	XRA A
0100	C37101	105	JMP TMR2
0103	69	106	F72: MOV L,C
0104	FE10	107	CPI 10H
0106	D23201	108	JNC FT22
0109	07	109	RLC
010A	17	110	RAL
010B	17	111	RAL
010C	67	112	MOV H,A
010D	79	113	F772: MOV A,C
010E	FECO	114	CPI OCOH
0110	DA2101	115	JC FTST1
0113	17	116	RAL
0114	84	117	ADD H

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0115	C36901	118	JMP F52
0118	AF	119 FTEST1:	XRA A
0119	C37101	120	JMP TMR2
011C	3EFE	121 FTEST2:	MVI A,0FEH
011E	C37101	122	JMP TMR2
0121	3E80	123 FTST1:	MVI A,80H
0123	84	124	ADD H
0124	C36901	125	JMP F52
0127	3E7F	126 FTST2:	MVI A,7FH
0129	84	127	ADD H
012A	C36901	128	JMP F52
012D	2680	129 FT11:	MVI H,80H
012F	C36101	130	JMP F33
0132	267F	131 FT22:	MVI H,7FH
0134	C30D01	132	JMP F772
0137	69	133 F9:	MOV L,C
0138	FE10	134	CPI 10H
013A	D21C01	135	JNC FTEST2
013D	07	136	RLC
013E	17	137	RAL
013F	17	138	RAL
0140	67	139	MOV H,A
0141	79	140 F99:	MOV A,C
0142	FE40	141	CPI 40H

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0144	D21C01	142	JNC FTEST2
0147	07	143	RLC
0148	84	144	ADD H
0149	F26901	145	JP F52
014C	3EFE	146	MVI A,0FEH
014E	C37101	147	JMP TMR2
0151	95	148 F3:	SUB L
0152	F23701	149	JP F9
0155	69	150	MOV L,C
0156	FEFO	151	CPI 0FOH
0158	DA2D01	152	JC FT11
015B	17	153	RAL
015C	3F	154	CMC
015D	17	155	RAL
015E	3F	156	CMC
015F	17	157	RAL
0160	67	158	MOV H,A
0161	79	159 F33:	MOV A,C
0162	FE40	160	CPI 40H
0164	D22701	161	JNC FTST2
0167	07	162	RLC
0168	84	163	ADD H
0169	C680	164 F52:	ADI 80H
016B	FEFF	165 D1:	CPI OFFH

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
016D	C27101	166	JNZ TMR2
0170	3D	167	DCR A
0171	67	168 TMR2:	MOV H,A
0172	3E8F	169	MVI A,8FH
0174	D3C0	170	OUT OCOH
0176	3EA0	171	MVI A,0A0H
0178	D3C2	172	OUT OC2H
017A	3EF6	173	MVI A,OF6H
017C	D3C2	174	OUT OC2H
		175	
017E	FB	176 INT:	EI
017F	F1	177	POP PSW
0180	76	178	HLT
0181	210040	179 BEGIN:	LXI H,4000H; START
		180	
0184	F9	181	SPHL
0185	F5	182	PUSH PSW
0186	3EFE	183	MVI A,OFEH
0188	67	184	MOV H,A
0189	57	185	MOV D,A
018A	C37F01	186	JMP INT
018D	C680	187 SUB1:	ADI 80H
018F	4F	188	MOV C,A
0190	7D	189	MOV A,L

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0191	F2BE01	190	JP P3
0194	A7	191	ANA A
0195	F2A301	192	JP P92
0198	81	193	ADD C
0199	FAA701	194	JM P91
019C	2E80	195	MVI L,80H
019E	0600	196	MVI B,0
01A0	C3A900	197	JMP TTMR
01A3	81	198 P92:	ADD C
01A4	F2D601	199	JP P95
01A7	6F	200 P91:	MOV L,A
01A8	CDDA01	201	CALL MMULT
01AB	FAA000	202	JM P83
01AE	0600	203	MVI B,0
01B0	C3A900	204	JMP TTMR
01B3	81	205 P32:	ADD C
01B4	F2C601	206	JP P9
		207	
01B7	2E7F	208	MVI L,7FH
01B9	06FE	209	MVI B,0FEH
01BB	C3A900	210	JMP TTMR
01BE	A7	211 P3:	ANA A
01BF	F2B301	212	JP P32
01C2	81	213	ADD C

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
01C3	FAD201	214	JM P995
01C6	6F	215 P9:	MOV L,A
01C7	CDE901	216	CALL PMULT
01CA	F2A000	217	JP P83
01CD	06FE	218	MVI B,0FEH
01CF	C3A900	219	JMP TTMR
01D2	6F	220 P995:	MOV L,A
01D3	C38500	221	JMP P881
01D6	6F	222 P95:	MOV L,A
01D7	C39D00	223	JMP P81
01DA	79	224 MMULT:	MOV A,C
01DB	FEFB	225	CPI 0FBH
01DD	DAFB01	226	JC TEST1
01E0	17	227	RAL
01E1	3F	228	CMC
01E2	17	229	RAL
01E3	3F	230	CMC
01E4	17	231	RAL
01E5	3F	232	CMC
01E6	C3F201	233	JMP M4
01E9	79	234 PMULT:	MOV A,C
01EA	FE06	235	CPI 6H
01EC	D2F701	236	JNC TEST2
01EF	07	237	RLC

All mnemonics copyright Intel Corporation 1980.

NARC-92-139

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
01F0	17	238	RAL
01F1	17	239	RAL
01F2	4F	240 M4:	MOV C,A
01F3	17	241	RAL
01F4	81	242	ADD C
01F5	85	243	ADD L
01F6	C9	244	RET
01F7	3E7F	245 TEST2:	MVI A,7FH
01F9	85	246	ADD L
01FA	C9	247	RET
01FB	3E80	248 TEST1:	MVI A,80H
01FD	85	249	ADD L
01FE	C9	250	RET
01FF	3E80	251 LED:	MVI A,80H
0201	D3EB	252	OUT OEBH
0203	3E40	253	MVI A,40H
0205	210040	254 L1:	LXI H,4000H
0208	F9	255	SPHL
0209	D3EA	256	OUT OEAH
020B	0E04	257	MVI C,4H
020D	CDD902	258	CALL DELAY
0210	DBEA	259	IN OEAH
0212	3C	260	INR A
0213	FE48	261	CPI 48H

All mnemonics copyright Intel Corporation 1980.



<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0215	C20502	262	JNZ L1
0218	3E83	263	MVI A,83H
021A	D3E7	264	OUT 0E7H
021C	3E80	265	MVI A,80H
021E	D3EB	266	OUT 0EBH
0220	3E55	267 L2:	MVI A,55H
0222	D3E4	268 P2:	OUT 0E4H
0224	D3E8	269	OUT 0E8H
0226	D3E9	270	OUT 0E9H
0228	D3EA	271	OUT 0EAH
022A	5F	272	MOV E,A
022B	DBE4	273	IN 0E4H
022D	BB	274	CMP E
022E	C24D02	275	JNZ P8
0231	DBE8	276	IN 0E8H
0233	BB	277	CMP E
0234	C24D02	278	JNZ P8
0237	DBE9	279	IN 0E9H
0239	BB	280	CMP E
023A	C24D02	281	JNZ P8
023D	DBEA	282	IN 0EAH
023F	BB	283	CMP E
0240	C24D02	284	JNZ P8
0243	FEAA	285	CPI 0AAH

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0245	CA6502	286	JZ P1
0248	3EAA	287	MVI A,0AAH
024A	C32202	288	JMP P2
024D	3E41	289 P8:	MVI A,41H
024F	D3EA	290	OUT 0EAH
0251	0E03	291	MVI C,3H
0253	CDD902	292	CALL DELAY
0256	C36502	293	JMP P1
0259	3E43	294 T8:	MVI A,43H
025B	D3EA	295	OUT 0EAH
025D	0E03	296	MVI C,3H
025F	CDD902	297	CALL DELAY
0262	C37902	298	JMP P4
0265	3EEF	299 P1:	MVI A,0EFH
0267	D3C0	300	OUT 0C0H
0269	D3C3	301	OUT 0C3H
026B	DBC3	302	IN 0C3H
026D	FE6F	303	CPI 0EFH
026F	3E6F	304	MVI A,6FH
0271	D3C0	305	OUT 0C0H
0273	D3C1	306	OUT 0C1H
0275	DBC1	307	IN 0C1H
0277	FE6F	308	CPI 6FH
0279	21FF3B	309 P4:	LXI H,3BFH

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
027C	23	310 R1:	INX H
027D	4E	311	MOV C,M
027E	79	312	MOV A,C
027F	2F	313	CMA
0280	77	314	MOV M,A
0281	7E	315	MOV A,M
0282	2F	316	CMA
0283	91	317	SUB C
0284	C2B602	318	JNZ R8
0287	71	319	MOV M,C
0288	7C	320	MOV A,H
0289	DE3F	321	SBI 3FH
028B	C27C02	322	JNZ R1
028E	7D	323	MOV A,L
028F	DEFF	324	SBI OFFH
0291	C27C02	325	JNZ R1
0294	3EF0	326	MVI A,0F0H
0296	D3E6	327	OUT 0E6H
0298	3EE0	328	MVI A,0E0H
029A	D3E6	329	OUT 0E6H
		330	
029C	3EFC	331	MVI A,0F0H
029E	D3E6	332	OUT 0E6H
02A0	DBE6	333	IN 0E6H

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
02A2	E601	334	ANI 1H
02A4	C2C202	335	JNZ AD8
02A7	0E01	336	MVI C,1H
02A9	CDD902	337	CALL DELAY
02AC	DBE6	338	IN OE6H
02AE	E601	339	ANI 1H
02B0	CAC202	340	JZ AD8
02B3	C3CB02	341	JMP READY
02B6	3E42	342 R8:	MVI A,42H
02B8	D3EA	343	OUT OEAH
02BA	0E03	344	MVI C,3H
02BC	CDD902	345	CALL DELAY
02BF	C3CB02	346	JMP READY
02C2	3E44	347 AD8:	MVI A,44H
02C4	D3EA	348	OUT OEAH
02C6	0E03	349	MVI C,3H
02C8	CDD902	350	CALL DELAY
02CB	DBEA	351 READY:	IN OEAH
02CD	E655	352	ANI 55H
02CF	C22002	353	JNZ L2
02D2	3E40	354	MVI A,40H
02D4	D3EA	355	OUT OEAH
02D6	C38101	356	JMP BEGIN
02D9	21003F	357 DELAY:	LXI H,3F00H

All mnemonics copyright Intel Corporation 1980.

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
02DC	71	358	MOV M,C
02DD	2C	359	INR L
02DE	3601	360	MVI M,1H
02E0	21003F	361 D5:	LXI H,3F00H
02E3	7E	362	MOV A,M
02E4	2C	363	INR L
02E5	96	364	SUB M
02E6	DA0B03	365	JC D8
02E9	2C	366	INR L
02EA	3601	367	MVI M,1H
02EC	3E04	368 D4:	MVI A,4H
02EE	21023F	369	LXI H,3F02H
		370	
02F1	96	371	SUB M
02F2	DA0603	372	JC D6
02F5	3EFA	373	MVI A,0FAH
02F7	060C	374	MVI B,0CH
		375	
02F9	48	376 D3:	MOV C,B
02FA	0D	377 D2:	DCR C
02FB	C2FA02	378	JNZ D2
02FE	3D	379	DCR A
02FF	C2F902	380	JNZ D3
0302	34	381	INR M

All mnemonics copyright Intel Corporation 1980.

NAEC-92-139

<u>LOCATION</u>	<u>OP CODE</u>	<u>LINE NUMBER</u>	<u>SOURCE STATEMENT</u>
0303	C2EC02	382	JNZ D4
0306	2D	383 D6:	DCR L
		384	
0307	34	385	INR M
0308	C2E002	386	JNZ D5
030B	C9	387 D8:	RET
		388	
0038		389	END 38H

All mnemonics copyright Intel Corporation 1980.

NAEC-92-139

APPENDIX C

MICROCOMPUTER CONTROL SYSTEM HARDWARE

C-1. MICROCOMPUTER CONTROL BOARD

COMPONENT LIST

A1 - header	C5 - header
A2 - header	C6 - 54192
A3 - 741CJ	C7 - 54192
A4 - 7402	C8 - 54192
A5 - AH0126	D1 - header
A6 - header	D2 - 3205
A7 - 7400	D3 - 74LS192
A8 - 7400	D4 - 74123
A9 - MM5357	
B1 - 1K resistor network chip	
B2 - empty	
B3 - empty	
B4 - 7476	
B5 - 7476	
B6 - header	
B7 - 54S04	
B8 - 74S00	
B9 - 8253	
C1 - header	
C2 - header	
C3 - empty	
C4 - MC1711	



## PIN ASSIGNMENTS

T1 - edge connector on microcomputer control board

J1, P1, P2 - connectors on Intel SBC 80/10 board

T1-1	+5V	T1-2	GND	T1-41	J-31	T1-42	P1-68
3	+12V	4	-	43	-	44	P1-67
5	-12V	6	-	45	-	46	P1-70
7	-5V	8	-	47	-	48	P1-69
9	-	10	frequency com- parator circuit input	49	-	50	P1-72
11	J1-1	12	GND	51	-	52	P1-71
13	J1-3	14	A10-1 on 80/10 board	53	-	54	P1-74
15	J1-5	16	A10-4 " " "	55	-	56	P1-73
17	J1-7	18	A10-13 " " "	57	-	58	P1-22
19	J1-9	20	A9-4 " " "	59	J1-49	60	P1-21
21	J1-11	22	Ready/Run Led	61	-	62	P1-58
23	J1-13	24	I/O LED	63	-	64	P1-57
25	J1-15	26	RAM LED	65	-	66	P1-23
27	-	28	TIMER LED	67	-	68	-
29	A4-12 on 80/10 Board	30	A/D LED	69	-	70	Voltage Input
31	J1-21	32	Overspeed LED	71	-	72	-
33	J1-23	34	Underfrequency LED	73	-	74	Woodward Driver Circuit Input
35	J1-25	36	Program not running LED	75	-	76	-
37	-	38	P2-28	77	-	78	Field Driver Circuit Input
39	J1-29	40	A14-15 on 80/10 board	79	+5V	80	GND

## PARTS LIST

R1	5K $\Omega$ pot, 1/4 Watt	R23	120 $\Omega$	C2	.01 $\mu$ f
R2	2.5 K $\Omega$	R24	120 $\Omega$	C3	180nf
R3	15.2 K $\Omega$	R25	120 $\Omega$	C4	.33 $\mu$ f, 1000V
R4	183 $\Omega$	R26	120 $\Omega$	C5	.0028 $\mu$ f
R5	2.0 K $\Omega$	R27	120 $\Omega$	D1	1N4001
R6	10 K $\Omega$ pot, 1/4 Watt	R28	120 $\Omega$	D2	1N754
R7	10 K $\Omega$	R29	160.75 K $\Omega$	D3	1N4001
R8	1 K $\Omega$	R30	1.5 K $\Omega$ pot, 1/4 Watt	D4	1N4001
R9	1 K $\Omega$	R31	1 K $\Omega$	D5	1N750
R10	1 K $\Omega$	R32	1 K $\Omega$	D6	1N750
R11	1 K $\Omega$	R33	1 K $\Omega$	D7	1N4001
R12	1 K $\Omega$	R34	50 $\Omega$ pot, 10 Watt	D8	1N4005
R13	1 K $\Omega$	R35	47 K $\Omega$	D9	1N4005
R14	1 K $\Omega$	R36	1 K $\Omega$	D10	1N4005
R15	220 K $\Omega$	R37	1 K $\Omega$	D11	1N4001
R16	47 K $\Omega$	R38	10 K $\Omega$	D12	1N4001
R17	2.2 K $\Omega$	R39	10 K $\Omega$	D13	1N249B
R18	2.2 K $\Omega$	R40	3.3 K $\Omega$	Q1	2N2222
R19	1 K $\Omega$ pot, 1/4 Watt	R41	688 $\Omega$ , 2 Watt	Q2	2N2222
R20	1 K $\Omega$	R42	1 K $\Omega$	Q3	2N2222
R21	120 $\Omega$	R43	1.5 $\Omega$ , 150 Watt	Q4	2N3055
R22	120 $\Omega$	C1	.1 $\mu$ f	Q5	2N2222
				Q6	2N3741
				Q7	2N6282

Various bypass capacitors of .1 $\mu$ f were used between +5V and GND.

## WIRE LIST










FROM	TO	FROM	TO	FROM	TO
A1-4	A1-5	A4-10	B5-16	A7-8	T1-13
5	A1-9	11	A4-12,A5-13	9	A7-10
6	A1-7	13	A5-9	A7-11	T1-11
8	GND	14	+5V	12	A7-13
9	A2-4	A5-1	A5-7,A6-12	14	+5V
A2-2	A3-4,A2-5	10	GND	A8-1	A8-2
5	A2-3	11	+12V	3	T1-19
10	A3-10	12	-12V	4	A8-5
11	-12V	A6-1	B6-7	6	T1-21
12	A1-10	2	GND	7	GND
13	T1-70	3	T1-33	8	T1-23
A3-4	A2-5	4	+12V	9	A8-10
5	GND	6	B6-14,A6-10	11	T1-25
6	-12V	8	GND	12	A8-13
10	A5-8	12	A6-7	14	+5V
11	+12V	13	-12V	A9-1	A8-1
A4-1	A9-6	14	A9-12	2	A8-4
4	A4-11	A7-1	A7-2	3	A8-9
5	T1-41,A4-6	3	T1-17	4	A8-12
7	GND	4	A7-5	5	A6-9
8	A4-9,B5-4	6	T1-15	8	-12V
9	T1-31	7	GND	9	T1-35


## NAEC-92-139

<u>FROM</u>	<u>TO</u>	<u>FROM</u>	<u>TO</u>	<u>FROM</u>	<u>TO</u>
A9-10	+5V	B5-13	GND	B9-2	T1-44
13	A7-1	14	B5-12,A4-3	3	T1-46
14	A7-4	15	B5-9	4	T1-48
15	+5V	B6-1	B6-13	5	T1-50
16	A7-9	2	B6-3	6	T1-52
17	A7-12	6	-12V	7	T1-54
18	GND	8	GND	8	T1-56
B1-5	B7-2	11	+5V	10	C1-14
10	+5V	12	B6-4	11	B7-4
11	+5V	14	B6-9	12	GND
12	+5V	B7-1	GND	14	B7-11
13	T1-78	3	GND	15	A9-11
14	GND	4	B1-1	16	B7-8
15	+5V	6	B8-5,B1-2	17	T1-74
16	+5V	7	GND	18	B9-9
B4-1	T1-38	8	B1-6	19	T1-64
4	B4-16,C2-5	9	GND	20	T1-62
5	+5V	10	B1-7,T1-29	21	T1-40,B7-5
11	B9-9	11	C5-13	22	T1-60,B8-1
12	B4-9	14	+5V	23	T1-58,B8-2
13	GND	B8-3	B8-4	24	+5V
15	B4-6,A9-11	6	T1-66	C1-1	B1-3,B1-4
B5-1	B5-6,B4-15	7	GND	2	+5V
5	+5V	14	+5V	3	C1-4
11	A4-2	B9-1	T1-42	C2-7	+5V


<u>FROM</u>	<u>TO</u>	<u>FROM</u>	<u>TO</u>	<u>FROM</u>	<u>TO</u>
C2-8	B4-9	C7-8	GND	D2-1	T1-14
10	+5V	12	C8-5	2	T1-16
C4-2	GND	14	GND	3	T1-18
4	T1-7	16	+5V	4	GND
5	T1-10	C8-5	C7-12	5	GND
6	T1-12	8	GND	6	T1-20
9	B7-2	12	T1-59	8	GND
10	C5-1	14	GND	16	+5V
11	+12V	16	+5V	D3-5	C8-12
12	GND	D1-1	D2-15	8	GND
C5-3	C5-5	2	D2-14	12	D4-1
4	GND	3	D2-13	14	GND
6	T1-7	4	D2-12	16	+5V
7	GND	5	D2-11	D4-4	T1-39
8	C5-9,B9-14	6	D2-10	8	GND
9	C5-10	7	D2-9	14	C1-12
10	C5-13	8	D2-7	15	C1-4
11	+5V	9	T1-36	16	+5V,C1-11
14	+5V	10	T1-34		
C6-5	T1-38	11	T1-32		
8	GND	12	T1-30		
12	C7-5	13	T1-28		
14	GND	14	T1-26		
16	+5V	15	T1-24		
C7-5	C6-12	16	T1-22		

## HEADER ASSEMBLIES






THREE PHASE VOLTAGE TO ANALOG SWITCH CIRCUIT





FREQUENCY COMPARATOR CIRCUIT







ANALOG SWITCH-SAMPLE AND HOLD CIRCUIT






CONVERT SIGNAL CIRCUIT FOR A/D







CLOCK SOURCE CIRCUIT



CLOCK FREQUENCY DIVIDER CIRCUIT




1 OF 8 DECODER CIRCUIT FOR L E D DISPLAY





FIELD DRIVER CIRCUIT






WOODWARD ACTUATOR DRIVER CIRCUIT






MICROCOMPUTER CONTROL BOARD




3

NOTES:  
1. UNLESS OTHERWISE SPECIFIED  
2. RESISTOR VALUES ARE IN OHMS, 1/4 W, ±5%  
3. CAPACITOR VALUES ARE IN MICROFARADS, 25V, ±20%  
4. ON J1 AND J2 EVEN PINS ARE GROUND.  
5. AS THE 1, 2, 3 THRU 20 ARE SHOWN FOR CLARITY,  
ACTUAL COMPONENTS ARE CUSTOMER INSTALLED.  
6. A41, 42 & 44 MAY BE SUBSTITUTED WITH A 74LS13B.




- NOTES: UNLESS OTHERWISE SPECIFIC
1. REMOVED
  2. RESISTOR VALUES ARE IN OHMS, 1/4 W, ±5%.
  3. CAPACITOR VALUES ARE IN MICROFARADS, 25V, ±20%.
  4. ON J1 AND J2 EVEN PINS ARE GROUND.
  5. AS THE 1, 2, 3 THRU 20 ARE SHOWN FOR CLARITY, ACTUAL COMPONENTS ARE CUSTOMER INSTALLED.
  6. A41, 42 & 44 MAY BE SUBSTITUTED WITH A 74LS13B.






REPRINTED BY PERMISSION OF INTEL CORPORATION, COPYRIGHT 1980.



REVISIONS			
DATE	DESCRIPTION	BY	CHK
SEP 1981	SHEET 1		

SCALE	1:1	DATE	2000951
SHEET	2 of 5	BY	D S






JUMPER TABLE				
2716	50-67	69-70	74-75	77-78
2708	55-66	68-69	73-74	76-78

	A23	A24	A25	A26
2716	0-7FF	800-FFF	800-FFF	800-FFF
2708	0-3FF	400-7FF	800-FFF	800-FFF


REPRINTED BY PERMISSION OF INTEL CORPORATION



REVISIONS				
REV	DESCRIPTION	DATE	BY	CHKD
1	SEE SHEET 1.			

ORATION, COPYRIGHT 1980.


SCALE	DATE	REV	APP'D BY	CHK'D BY
1:1	10/3/83	D		




REVISIONS				
LTN	DESCRIPTION	BY	CHK	DATE
✓	SEE SHEET 1			2000

IO RDY IN/ T7CB

CS 1/ 57DB  
CS 2/ 52DB



SCALE	DATE	BY	CHK	DATE
1:1	10/1/80	D		2000



REPRINTED BY PERMISSION OF INTEL CORPORATION, COPYRIGHT 1980.




NAEC-92-139


This page left blank  
intentionally.

APPENDIX D

VOLTAGE AND FREQUENCY REGULATION RESULTS







FREQUENCY REGULATION RESULTS

AD-A085 990

NAVAL AIR ENGINEERING CENTER LAKEHURST NJ GROUND SUPP--ETC F/6 10/2  
APPLICATION OF A MICROCOMPUTER TO A MOBILE ELECTRIC POWER PLANT--ETC(U)  
MAY 80 R F O'DONNELL

UNCLASSIFIED

NAEC-92-139

NL

4 of 4

001  
001-0000




END

DATE  
FILMED

8-80

DTIC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

NAEC-92-139

This page left blank  
intentionally.

1944-1945

**NAVAIRSYCON**

AIR-5402 (3)  
 AIR-55232 (5)  
 AIR-4500 (2)

DDC - 12

[illegible]

DATE  
FILMED  
— 8